



# Notebook - Competitive Programming

Anões do TLE

Contents		
<b>1 Data structures</b>	<b>2</b>	
1.1 Matrix	2	
1.2 Minimal Excluded With Updates (MEX-U)	3	
1.3 Minimal Excluded (MEX)	4	
1.4 Segment Tree (Parameterized OP)	4	
1.5 Segment Tree 2D	4	
1.6 Union Find Disjoint Set (UFDS)	5	
<b>2 Dynamic programming</b>	<b>5</b>	
2.1 Kadane	5	
2.2 Longest Increasing Subsequence (LIS)	5	
<b>3 Geometry</b>	<b>5</b>	
3.1 Convex Hull	5	
3.2 Point To Segment	6	
<b>4 Graphs</b>	<b>6</b>	
4.1 Articulation Points	6	
4.2 Bellman Ford	6	
4.3 BFS 0/1	6	
4.4 Bridges	7	
4.5 Negative Cycle Bellman Ford	7	
4.6 Negative Cycle Floyd Warshall	7	
4.7 Dijkstra	7	
4.8 Floyd Warshall	8	
4.9 Graph	8	
4.10 TopSort - Kahn	8	
4.11 Kruskal	8	
4.12 Minimax	9	
4.13 MSF	9	
4.14 Minimum Spanning Graph (MSG)	9	
4.15 Prim	9	
4.16 Retrieve Path 2d	10	
4.17 Retrieve Path	10	
4.18 Second Best MST	10	
4.19 TopSort - Tarjan	10	
<b>5 Math</b>	<b>11</b>	
5.1 Binomial	11	
5.2 Count Divisors Range	11	
5.3 Count Divisors	11	
5.4 Factorization With Sieve	11	
5.5 Factorization	11	
5.6 Fast Exp Iterative	11	
5.7 Fast Exp	11	
5.8 GCD	12	
5.9 Integer Mod	12	
5.10 Is prime	12	
5.11 LCM	12	
5.12 Euler phi $\varphi(n)$	12	
5.13 Sieve	13	
5.14 Sum Divisors	13	
5.15 Sum of difference	13	
<b>6 Problems</b>	<b>13</b>	
6.1 Kth Digit String (CSES)	13	
<b>7 Strings</b>	<b>13</b>	
7.1 Edit Distance	13	
7.2 Manacher	14	
<b>8 Trees</b>	<b>14</b>	
8.1 LCA Binary Lifting (CP Algo)	14	
8.2 LCA SegTree (CP Algo)	14	
8.3 LCA Sparse Table	15	
8.4 Tree Isomorph	15	
<b>9 Settings and macros</b>	<b>16</b>	
9.1 macro.cpp	16	
9.2 short-macro.cpp	16	
<b>10 Theoretical guide</b>	<b>17</b>	
10.1 Notable Series	17	
10.2 Modular Multiplicative Inverse	17	

# 1 Data structures

## 1.1 Matrix

```
template <typename T>
struct Matrix {
    vector<vector<T>> d;

    Matrix() : Matrix(0) {}
    Matrix(int n) : Matrix(n, n) {}
    Matrix(int n, int m) : Matrix(vector<vector<T>>(n, vector<T>(m))) {}
    Matrix(const vector<vector<T>> &v) : d(v) {}

    constexpr int n() const { return (int)d.size(); }
    constexpr int m() const { return n() ? (int)d[0].size() : 0; }

    void rotate() { *this = rotated(); }

    Matrix<T> rotated() const {
        Matrix<T> res(m(), n());
        for (int i = 0; i < m(); i++) {
            for (int j = 0; j < n(); j++) {
                res[i][j] = d[n() - j - 1][i];
            }
        }
        return res;
    }

    Matrix<T> pow(int power) const {
        assert(n() == m());

        auto res = Matrix<T>::identity(n());
        auto b = *this;
        while (power) {
            if (power & 1) res *= b;
            b *= b;
            power >>= 1;
        }
        return res;
    }

    Matrix<T> submatrix(int start_i, int start_j, int rows = INT_MAX,
                       int cols = INT_MAX) const {
        rows = min(rows, n() - start_i);
        cols = min(cols, m() - start_j);
        if (rows <= 0 or cols <= 0) return {};

        Matrix<T> res(rows, cols);
        for (int i = 0; i < rows; i++)
            for (int j = 0; j < cols; j++) res[i][j] = d[i + start_i][j + start_j];
        return res;
    }

    Matrix<T> translated(int x, int y) const {
        Matrix<T> res(n(), m());
        for (int i = 0; i < n(); i++) {
            for (int j = 0; j < m(); j++) {
                if (i + x < 0 or i + x >= n() or j + y < 0 or j + y >= m()) continue;

```

```
                res[i + x][j + y] = d[i][j];
            }
        }
        return res;
    }

    static Matrix<T> identity(int n) {
        Matrix<T> res(n);
        for (int i = 0; i < n; i++) res[i][i] = 1;
        return res;
    }

    vector<T> &operator[](int i) { return d[i]; }
    const vector<T> &operator[](int i) const { return d[i]; }
    Matrix<T> &operator+=(T value) {
        for (auto &row : d) {
            for (auto &x : row) x += value;
        }
        return *this;
    }
    Matrix<T> operator+(T value) const {
        auto res = *this;
        for (auto &row : res) {
            for (auto &x : row) x = x + value;
        }
        return res;
    }
    Matrix<T> &operator-=(T value) {
        for (auto &row : d) {
            for (auto &x : row) x -= value;
        }
        return *this;
    }
    Matrix<T> operator-(T value) const {
        auto res = *this;
        for (auto &row : res) {
            for (auto &x : row) x = x - value;
        }
        return res;
    }
    Matrix<T> &operator*=(T value) {
        for (auto &row : d) {
            for (auto &x : row) x *= value;
        }
        return *this;
    }
    Matrix<T> operator*(T value) const {
        auto res = *this;
        for (auto &row : res) {
            for (auto &x : row) x = x * value;
        }
        return res;
    }
    Matrix<T> &operator/=(T value) {
        for (auto &row : d) {
            for (auto &x : row) x /= value;
        }
        return *this;
    }
}
```

```

}
Matrix<T> operator/(T value) const {
    auto res = *this;
    for (auto &row : res) {
        for (auto &x : row) x = x / value;
    }
    return res;
}
Matrix<T> &operator+=(const Matrix<T> &o) {
    assert(n() == o.n() and m() == o.m());
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            d[i][j] += o[i][j];
        }
    }
    return *this;
}
Matrix<T> operator+(const Matrix<T> &o) const {
    assert(n() == o.n() and m() == o.m());
    auto res = *this;
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            res[i][j] = res[i][j] + o[i][j];
        }
    }
    return res;
}
Matrix<T> &operator-=(const Matrix<T> &o) {
    assert(n() == o.n() and m() == o.m());
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            d[i][j] -= o[i][j];
        }
    }
    return *this;
}
Matrix<T> operator-(const Matrix<T> &o) const {
    assert(n() == o.n() and m() == o.m());
    auto res = *this;
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            res[i][j] = res[i][j] - o[i][j];
        }
    }
    return res;
}
Matrix<T> &operator*=(const Matrix<T> &o) {
    *this = *this * o;
    return *this;
}
Matrix<T> operator*(const Matrix<T> &o) const {
    assert(m() == o.n());
    Matrix<T> res(n(), o.m());
    for (int i = 0; i < res.n(); i++) {
        for (int j = 0; j < res.m(); j++) {
            auto &x = res[i][j];
            for (int k = 0; k < m(); k++) {
                x += (d[i][k] * o[k][j]);
            }
        }
    }
}

```

```

    }
}
return res;
}

friend istream &operator>>(istream &is, Matrix<T> &mat) {
    for (auto &row : mat)
        for (auto &x : row) is >> x;
    return is;
}

friend ostream &operator<<(ostream &os, const Matrix<T> &mat) {
    bool frow = 1;
    for (auto &row : mat) {
        if (not frow) os << '\n';
        bool first = 1;
        for (auto &x : row) {
            if (not first) os << ' ';
            os << x;
            first = 0;
        }

        frow = 0;
    }
    return os;
}

auto begin() { return d.begin(); }
auto end() { return d.end(); }
auto rbegin() { return d.rbegin(); }
auto rend() { return d.rend(); }

auto begin() const { return d.begin(); }
auto end() const { return d.end(); }
auto rbegin() const { return d.rbegin(); }
auto rend() const { return d.rend(); }
};

```

## 1.2 Minimal Excluded With Updates (MEX-U)

In the problem you need to change individual numbers in the array, and compute the new MEX of the array after each such update.

Pre-compute:  $O(N \log N)$

Update:  $O(\log N)$

Query:  $O(1)$

```

class Mex {
private:
    map<ll, ll> frequency;
    set<ll> missing_numbers;
    vl A;

public:
    Mex(vl const& A) : A(A) {
        for (ll i = 0; i <= A.size(); i++) missing_numbers.insert(i);

        for (ll x : A) {
            ++frequency[x];
            missing_numbers.erase(x);
        }
    }
}

```

```

    }
}

ll mex() { return *missing_numbers.begin(); }

void update(ll idx, ll new_value) {
    if (--frequency[A[idx]] == 0) missing_numbers.insert(A[idx]);
    A[idx] = new_value;
    ++frequency[new_value];
    missing_numbers.erase(new_value);
}
};

```

### 1.3 Minimal Excluded (MEX)

Given an array  $A$  of size  $N$ . You have to find the minimal non-negative element that is not present in the array. That number is commonly called the MEX (minimal excluded).

Time:  $O(N)$

```

ll mex(vl const& A) {
    static bool used[MAX + 111] = {0};

    for (ll x : A) {
        if (x <= MAX) used[x] = true;
    }

    ll result = 0;
    while (used[result]) ++result;

    for (ll x : A) {
        if (x <= MAX) used[x] = false;
    }

    return result;
}

```

### 1.4 Segment Tree (Parameterized OP)

Query:  $O(\log N)$

Update:  $O(\log N)$

```

template <typename T, auto op>
class SegTree {
private:
    T e;
    ll N;
    vector<T> seg;

public:
    SegTree(ll N, T e) : e(e), N(N), seg(N + N, e) {}

    void assign(ll i, T v) {
        i += N;
        seg[i] = v;
        for (i >= 1; i; i >>= 1) seg[i] = op(seg[2 * i], seg[2 * i + 1]);
    }
}

```

```

T query(ll l, ll r) {
    T la = e, ra = e;
    l += N;
    r += N;

    while (l <= r) {
        if (l & 1) la = op(la, seg[l++]);
        if (~r & 1) ra = op(seg[r--], ra);
        l >>= 1;
        r >>= 1;
    }

    return op(la, ra);
}
};

```

### 1.5 Segment Tree 2D

Query:  $O(\log N \cdot \log M)$   
Update:  $O(\log N \cdot \log M)$

```

template <typename T, auto op>
class SegTree {
private:
    T e;
    ll n, m;
    vector<vector<T>> seg;

public:
    SegTree(ll n, ll m, T e)
        : e(e), n(n), m(m), seg(2 * n, vector<T>(2 * m, e)) {}

    void assign(ll x, ll y, T v) {
        ll ny = y += m;
        for (x += n; x; x >>= 1, y = ny) {
            if (x >= n)
                seg[x][y] = v;
            else
                seg[x][y] = op(seg[2 * x][y], seg[2 * x + 1][y]);

            while (y >>= 1) seg[x][y] = op(seg[x][2 * y], seg[x][2 * y + 1]);
        }
    }

    T query(ll lx, ll rx, ll ly, ll ry) {
        ll ans = e, nx = rx + n, my = ry + m;

        for (lx += n, ly += m; lx <= ry; ++lx >>= 1, --ly >>= 1) {
            for (rx = nx, ry = my; rx <= ry; ++rx >>= 1, --ry >>= 1) {
                if (lx & 1 and rx & 1) ans = op(ans, seg[lx][rx]);
                if (lx & 1 and !(ry & 1)) ans = op(ans, seg[lx][ry]);
                if (!(ly & 1) and rx & 1) ans = op(ans, seg[ly][rx]);
                if (!(ly & 1) and !(ry & 1)) ans = op(ans, seg[ly][ry]);
            }

            return ans;
        }
    }
};

```

## 1.6 Union Find Disjoint Set (UFDS)

Uncomment the lines to recover which element belong to each set.

Time:  $\approx O(1)$  for everything.

```
class UFDS {
public:
    vi ps, size;
    // vector<unordered_set<int>> sts;

    UFDS(int N) : size(N + 1, 1), ps(N + 1), sts(N) {
        iota(ps.begin(), ps.end(), 0);
        // for (int i = 0; i < N; i++) sts[i].insert(i);
    }

    int find_set(int x) { return x == ps[x] ? x : (ps[x] = find_set(ps[x])); }

    bool same_set(int x, int y) { return find_set(x) == find_set(y); }

    void union_set(int x, int y) {
        if (same_set(x, y)) return;

        int px = find_set(x);
        int py = find_set(y);

        if (size[px] < size[py]) swap(px, py);

        ps[py] = px;
        size[px] += size[py];
        // sts[px].merge(sts[py]);
    }
};
```

## 2 Dynamic programming

### 2.1 Kadane

```
int kadane(const vi& xs) {
    vi s(xs.size());
    s[0] = xs[0];

    for (size_t i = 1; i < xs.size(); ++i) s[i] = max(xs[i], s[i - 1] + xs[i]);

    return *max_element(all(s));
}
```

### 2.2 Longest Increasing Subsequence (LIS)

Time:  $O(N \cdot \log N)$ .

```
int lis(vi const& a) {
    int n = a.size();
    const int INF = 1e9;
    vi d(n + 1, INF);
    d[0] = -INF;

    for (int i = 0; i < n; i++) {
```

```
        int l = upper_bound(d.begin(), d.end(), a[i]) - d.begin();
        if (d[l - 1] < a[i] && a[i] < d[l]) d[l] = a[i];
    }

    int ans = 0;
    for (int l = 0; l <= n; l++) {
        if (d[l] < INF) ans = l;
    }

    return ans;
}
```

## 3 Geometry

### 3.1 Convex Hull

Given a set of points find the smallest convex polygon that contains all the given points.

Time:  $O(N \cdot \log N)$

By default it removes the collinear points, set the boolean to true if you don't want that

```
struct pt {
    double x, y;
};

int orientation(pt a, pt b, pt c) {
    double v = a.x * (b.y - c.y) + b.x * (c.y - a.y) + c.x * (a.y - b.y);
    if (v < 0) return -1; // clockwise
    if (v > 0) return +1; // counter-clockwise
    return 0;
}

bool cw(pt a, pt b, pt c, bool include_collinear) {
    int o = orientation(a, b, c);
    return o < 0 || (include_collinear && o == 0);
}

bool collinear(pt a, pt b, pt c) { return orientation(a, b, c) == 0; }

void convex_hull(vector<pt>& a, bool include_collinear = false) {
    pt p0 = *min_element(a.begin(), a.end(), [](pt a, pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    });
    sort(a.begin(), a.end(), [p0](const pt& a, const pt& b) {
        int o = orientation(p0, a, b);
        if (o == 0)
            return (p0.x - a.x) * (p0.x - a.x) + (p0.y - a.y) * (p0.y - a.y) <
                (p0.x - b.x) * (p0.x - b.x) + (p0.y - b.y) * (p0.y - b.y);
        return o < 0;
    });
    if (include_collinear) {
        int i = (int)a.size() - 1;
        while (i >= 0 && collinear(p0, a[i], a.back())) i--;
        reverse(a.begin() + i + 1, a.end());
    }

    vector<pt> st;
    for (int i = 0; i < (int)a.size(); i++) {
        while (st.size() > 1 &&
```

```

        !cw(st.size() - 2), st.back(), a[i], include_collinear))
    st.pop_back();
    st.push_back(a[i]);
}

a = st;
}

```

## 3.2 Point To Segment

```

typedef pair<double, double> pdb;

double pt2segment(pdb A, pdb B, pdb E) {
    pdb AB = {B.fst - A.fst, B.snd - A.snd};
    pdb BE = {E.fst - B.fst, E.snd - B.snd};
    pdb AE = {E.fst - A.fst, E.snd - A.snd};

    double AB_BE = AB.fst * BE.fst + AB.snd * BE.snd;
    double AB_AE = AB.fst * AE.fst + AB.snd * AE.snd;

    double ans;
    if (AB_BE > 0) {
        double y = E.snd - B.snd;
        double x = E.fst - B.fst;
        ans = hypot(x, y);
    } else if (AB_AE < 0) {
        double y = E.snd - A.snd;
        double x = E.fst - A.fst;
        ans = hypot(x, y);
    } else {
        auto [x1, y1] = AB;
        auto [x2, y2] = AE;
        double mod = hypot(x1, y1);
        ans = abs(x1 * y2 - y1 * x2) / mod;
    }

    return ans;
}

```

## 4 Graphs

### 4.1 Articulation Points

```

int dfs_num[MAX], dfs_low[MAX];
vi adj[MAX];

int dfs_articulation_points(int u, int p, int& next, set<int>& points) {
    int children = 0;
    dfs_low[u] = dfs_num[u] = next++;

    for (auto v : adj[u])
        if (not dfs_num[v]) {
            ++children;

            dfs_articulation_points(v, u, next, points);
        }
}

```

```

        if (dfs_low[v] >= dfs_num[u]) points.insert(u);

        dfs_low[u] = min(dfs_low[u], dfs_low[v]);
    } else if (v != p)
        dfs_low[u] = min(dfs_low[u], dfs_num[v]);

    return children;
}

set<int> articulation_points(int N) {
    memset(dfs_num, 0, (N + 1) * sizeof(int));
    memset(dfs_low, 0, (N + 1) * sizeof(int));

    set<int> points;

    for (int u = 1, next = 1; u <= N; ++u)
        if (not dfs_num[u]) {
            auto children = dfs_articulation_points(u, u, next, points);

            if (children == 1) points.erase(u);
        }

    return points;
}

```

### 4.2 Bellman Ford

Time:  $O(V \cdot E)$ . Returns the shortest path from  $s$  to all other nodes.

```

using edge = tuple<int, int, int>;

pair<vi, vi> bellman_ford(int s, int N, const vector<edge>& edges) {
    vi dist(N + 1, oo), pred(N + 1, oo);

    dist[s] = 0;
    pred[s] = s;

    for (int i = 1; i <= N - 1; i++)
        for (auto [u, v, w] : edges)
            if (dist[u] < oo and dist[v] > dist[u] + w) {
                dist[v] = dist[u] + w;
                pred[v] = u;
            }

    return {dist, pred};
}

```

### 4.3 BFS 0/1

Time:  $O(V + E)$ .

```

vii adj[MAX];

vi bfs_01(int s, int N) {
    vi dist(N + 1, oo);
    dist[s] = 0;

    deque<int> q;
}

```

```

q.emplace_back(s);

while (not q.empty()) {
    auto u = q.front();
    q.pop_front();

    for (auto [v, w] : adj[u])
        if (dist[v] > dist[u] + w) {
            dist[v] = dist[u] + w;
            w == 0 ? q.emplace_front(v) : q.emplace_back(v);
        }
}

return dist;
}

```

## 4.4 Bridges

```

int dfs_num[MAX], dfs_low[MAX];
vi adj[MAX];

void dfs_bridge(int u, int p, int& next, vii& bridges) {
    dfs_low[u] = dfs_num[u] = next++;

    for (auto v : adj[u])
        if (not dfs_num[v]) {
            dfs_bridge(v, u, next, bridges);

            if (dfs_low[v] > dfs_num[u]) bridges.emplace_back(u, v);

            dfs_low[u] = min(dfs_low[u], dfs_low[v]);
        } else if (v != p)
            dfs_low[u] = min(dfs_low[u], dfs_num[v]);
}

vii bridges(int N) {
    memset(dfs_num, 0, (N + 1) * sizeof(int));
    memset(dfs_low, 0, (N + 1) * sizeof(int));

    vii bridges;

    for (int u = 1, next = 1; u <= N; ++u)
        if (not dfs_num[u]) dfs_bridge(u, u, next, bridges);

    return bridges;
}

```

## 4.5 Negative Cycle Bellman Ford

Time:  $O(V \cdot E)$ . Detects whether there is a negative cycle in the graph using Bellman Ford.

```

using edge = tuple<int, int, int>;

bool has_negative_cycle(int s, int N, const vector<edge>& edges) {
    vi dist(N + 1, oo);
    dist[s] = 0;

```

```

    for (int i = 1; i <= N - 1; i++)
        for (auto [u, v, w] : edges)
            if (dist[u] < oo and dist[v] > dist[u] + w) dist[v] = dist[u] + w;

    for (auto [u, v, w] : edges)
        if (dist[u] < oo and dist[v] > dist[u] + w) return true;

    return false;
}

```

## 4.6 Negative Cycle Floyd Warshall

Time:  $O(n^3)$ . Detects whether there is a negative cycle in the graph using Floyd Warshall.

```

int dist[MAX][MAX];
vii adj[MAX];

bool has_negative_cycle(int N) {
    for (int u = 1; u <= N; ++u)
        for (int v = 1; v <= N; ++v) dist[u][v] = u == v ? 0 : oo;

    for (int u = 1; u <= N; ++u)
        for (auto [v, w] : adj[u]) dist[u][v] = w;

    for (int k = 1; k <= N; ++k)
        for (int u = 1; u <= N; ++u)
            for (int v = 1; v <= N; ++v)
                if (dist[u][k] < oo and dist[k][v] < oo)
                    dist[u][v] = min(dist[u][v], dist[u][k] + dist[k][v]);

    for (int i = 1; i <= N; ++i)
        if (dist[i][i] < 0) return true;

    return false;
}

```

## 4.7 Dijkstra

```

pair<vl, vl> Graph::dijkstra(ll src) {
    vl pd(this->N, LLONG_MAX), ds(this->N, LLONG_MAX);
    pd[src] = src;
    ds[src] = 0;

    set<pll> st;
    st.emplace(0, src);

    while (!st.empty()) {
        ll u = st.begin()->snd;
        ll wu = st.begin()->fst;
        st.erase(st.begin());

        if (wu != ds[u]) continue;
        for (auto& [v, w] : adj[u]) {
            if (ds[v] > ds[u] + w) {
                ds[v] = ds[u] + w;
                pd[v] = u;

```

```

        st.emplace(ds[v], v);
    }
}

return {ds, pd};
}

```

## 4.8 Floyd Warshall

```

vii adj[MAX];

pair<vector<vi>, vector<vi>> floyd_warshall(int N) {
    vector<vi> dist(N + 1, vi(N + 1, oo));
    vector<vi> pred(N + 1, vi(N + 1, oo));

    for (int u = 1; u <= N; ++u) {
        dist[u][u] = 0;
        pred[u][u] = u;
    }

    for (int u = 1; u <= N; ++u)
        for (auto [v, w] : adj[u]) {
            dist[u][v] = w;
            pred[u][v] = u;
        }

    for (int k = 1; k <= N; ++k) {
        for (int u = 1; u <= N; ++u) {
            for (int v = 1; v <= N; ++v) {
                if (dist[u][k] < oo and dist[k][v] < oo and
                    dist[u][v] > dist[u][k] + dist[k][v]) {
                    dist[u][v] = dist[u][k] + dist[k][v];
                    pred[u][v] = pred[k][v];
                }
            }
        }
    }

    return {dist, pred};
}

```

## 4.9 Graph

```

class Graph {
private:
    ll N;
    bool undirected;
    vector<vll> adj;

public:
    Graph(ll N, bool is_undirected = true) {
        this->N = N;
        adj.resize(N);
        undirected = is_undirected;
    }

    void add(ll u, ll v, ll w) {

```

```

        adj[u].emplace_back(v, w);
        if (undirected) adj[v].emplace_back(u, w);
    }
};

```

## 4.10 TopSort - Kahn

Works only on Directed Acyclic Graphs (DAGs). For each edge (u,v), u comes before v in the ordering. If the task A is a prerequisite for task B, then A comes before B in the ordering. Time:  $O(E \cdot \log(v))$

```

unordered_set<int> in[MAX], out[MAX];

vi topological_sort(int N) {
    vi o;
    queue<int> q;

    for (int u = 1; u <= N; ++u)
        if (in[u].empty()) q.push(u);

    while (not q.empty()) {
        auto u = q.front();
        q.pop();

        o.emplace_back(u);

        for (auto v : out[u]) {
            in[v].erase(u);

            if (in[v].empty()) q.push(v);
        }
    }

    return (int)o.size() == N ? o : vi{};
}

```

## 4.11 Kruskal

Time:  $O(e \cdot \log(v))$

```

using edge = tuple<int, int, int>;

int kruskal(int N, vector<edge>& es) {
    sort(es.begin(), es.end());

    int cost = 0;
    UnionFind udfs(N);

    for (auto [w, u, v] : es) {
        if (not udfs.same_set(u, v)) {
            cost += w;
            udfs.union_set(u, v);
        }
    }

    return cost;
}

```



## 4.12 Minimax

A MST minimizes the maximum weight between the edges in any spanning tree. Time:  $O(e \cdot \log(v))$

```
vii adj[MAX];

int minimax(int u, int N) {
    set<int> C;
    C.insert(u);

    priority_queue<ii, vii, greater<ii>> pq;

    for (auto [v, w] : adj[u]) pq.push(ii(w, v));

    int minmax = -oo;

    while ((int)C.size() < N) {
        int v, w;

        do {
            w = pq.top().first, v = pq.top().second;
            pq.pop();
        } while (C.count(v));

        minmax = max(minmax, w);
        C.insert(v);

        for (auto [s, p] : adj[v]) pq.push(ii(p, s));
    }

    return minmax;
}
```

## 4.13 MSF

Minimum Spanning Forest - a forest of trees of length  $k$  that connects all vertices in a graph with minimum total weight. Time:  $O(e \cdot \log(v))$

```
using edge = tuple<int, int, int>;

int msf(int k, int N, vector<edge>& es) {
    sort(es.begin(), es.end());

    int cost = 0, cc = N;
    UnionFind udfs(N);

    for (auto [w, u, v] : es) {
        if (not udfs.same_set(u, v)) {
            cost += w;
            udfs.union_set(u, v);

            if (--cc == k) return cost;
        }
    }

    return cost;
}
```

## 4.14 Minimum Spanning Graph (MSG)

Given some obligatory edges  $es$ , find a minimum spanning graph that contains them. Time:  $O(e \cdot \log(v))$

```
using edge = tuple<int, int, int>;

const int MAX{100010};

vector<ii> adj[MAX];

int msg(int N, const vector<edge>& es) {
    set<int> C;
    priority_queue<ii, vii, greater<ii>> pq;
    int cost = 0;

    for (auto [u, v, w] : es) {
        cost += w;

        C.insert(u);
        C.insert(v);

        for (auto [r, s] : adj[u]) pq.push(ii(s, r));
        for (auto [r, s] : adj[v]) pq.push(ii(s, r));
    }

    while ((int)C.size() < N) {
        int v, w;

        do {
            w = pq.top().first, v = pq.top().second;
            pq.pop();
        } while (C.count(v));

        cost += w;
        C.insert(v);

        for (auto [s, p] : adj[v]) pq.push(ii(p, s));
    }

    return cost;
}
```

## 4.15 Prim

A node  $u$  is chosen to start a connected component. Time:  $O(e \cdot \log(v))$

```
const int MAX{100010};

vector<ii> adj[MAX];

int prim(int u, int N) {
    set<int> C;
    C.insert(u);

    priority_queue<ii, vector<ii>, greater<ii>> pq;

    for (auto [v, w] : adj[u]) pq.push(ii(w, v));
```

```

int mst = 0;

while ((int)C.size() < N) {
    int v, w;

    do {
        w = pq.top().first, v = pq.top().second;
        pq.pop();
    } while (C.count(v));

    mst += w;
    C.insert(v);

    for (auto [s, p] : adj[v]) pq.push(ii(p, s));
}

return mst;
}

```

## 4.16 Retrieve Path 2d

```

vll Graph::retrieve_path_2d(ll src, ll trg, const vector<vl>& pred) {
    vll p;

    do {
        p.emplace_back(pred[src][trg], trg);
        trg = pred[src][trg];
    } while (trg != src);

    reverse(all(p));

    return p;
}

```

## 4.17 Retrieve Path

```

vll Graph::retrieve_path(ll src, ll trg, const vl& pred) {
    vll p;

    do {
        p.emplace_back(pred[trg], trg);
        trg = pred[trg];
    } while (trg != src);

    reverse(all(p));

    return p;
}

```

## 4.18 Second Best MST

Time:  $O(v \cdot e)$

```
using edge = tuple<int, int, int>;
```

```

pair<int, vi> kruskal(int N, vector<edge>& es, int blocked = -1) {
    vi mst;

```

```

    UnionFind udfs(N);
    int cost = 0;

    for (int i = 0; i < (int)es.size(); ++i) {
        auto [w, u, v] = es[i];

        if (i != blocked and not udfs.same_set(u, v)) {
            cost += w;
            udfs.union_set(u, v);
            mst.emplace_back(i);
        }
    }

    return {(int)mst.size() == N - 1 ? cost : oo, mst};
}

int second_best(int N, vector<edge>& es) {
    sort(es.begin(), es.end());

    auto [_, mst] = kruskal(N, es);
    int best = oo;

    for (auto blocked : mst) {
        auto [cost, __] = kruskal(N, es, blocked);
        best = min(best, cost);
    }

    return best;
}

```

## 4.19 TopSort - Tarjan

Works only on Directed Acyclic Graphs (DAGs). For each edge (u,v), u comes before v in the ordering. If the task A is a prerequisite for task B, then A comes before B in the ordering. Time:  $O(V + E)$

```

enum State { NOT_FOUND, FOUND, PROCESSED };

vi adj[MAX];

bool dfs(int u, vi& o, vi& state) {
    if (state[u] == PROCESSED) return true;

    if (state[u] == FOUND) return false;

    state[u] = FOUND;

    for (auto v : adj[u])
        if (not dfs(v, o, state)) return false;

    state[u] = PROCESSED;
    o.emplace_back(u);

    return true;
}

```

```

vi topological_sort(int N) {
    vi o, state(N + 1, NOT_FOUND);

```

```

for (int u = 1; u <= N; ++u)
    if (state[u] == NOT_FOUND and not dfs(u, o, state)) return {};

reverse(o.begin(), o.end());

return o;
}

```

## 5 Math

### 5.1 Binomial

```

ll binom(ll n, ll k) {
    if (k > n) return 0;
    vll dp(k + 1, 0);
    dp[0] = 1;
    for (ll i = 1; i <= n; i++)
        for (ll j = k; j > 0; j--) dp[j] = dp[j] + dp[j - 1];
    return dp[k];
}

```

### 5.2 Count Divisors Range

```

vl divisors(MAX, 0);
void count_divisors_range() {
    for (ll i = 1; i <= MAX; i++) {
        for (ll j = 1; j * i <= MAX; j++) divisors[i * j]++;
    }
}

```

### 5.3 Count Divisors

```

ll count_divisors(ll num) {
    ll count = 1;
    for (int i = 2; (ll)i * i <= num; i++) {
        if (num % i == 0) {
            int e = 0;
            do {
                e++;
                num /= i;
            } while (num % i == 0);
            count *= e + 1;
        }
    }
    if (num > 1) {
        count *= 2;
    }
    return count;
}

```

### 5.4 Factorization With Sieve

```

map<ll, ll> factorization_with_sieve(ll n, const vl& primes) {
    map<ll, ll> fact;

```

```

for (ll d : primes) {
    if (d * d > n) break;

    ll k = 0;
    while (n % d == 0) {
        k++;
        n /= d;
    }

    if (k) fact[d] = k;
}

if (n > 1) fact[n] = 1;
return fact;
}

```

### 5.5 Factorization

```

map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
        if (count) ans[i] = count;
    }
    if (n > 1) ans[n]++;
    return ans;
}

```

### 5.6 Fast Exp Iterative

```

ll fast_exp_it(ll a, ll n, ll mod = LLONG_MAX) {
    a %= mod;
    ll res = 1;

    while (n) {
        if (n & 1) (res *= a) %= mod;

        (a *= a) %= mod;
        n >>= 1;
    }

    return res;
}

```

### 5.7 Fast Exp

```

ll fast_exp(ll a, ll n, ll mod = LLONG_MAX) {
    if (n == 0) return 1;
    if (n == 1) return a;

    ll x = fast_exp(a, n / 2, mod) % mod;

    return ((x * x) % mod * (n & 1 ? a : 1)) % mod;
}

```

## 5.8 GCD

The Euclidean algorithm allows to find the greatest common divisor of two numbers  $a$  and  $b$  in  $O(\log \cdot \min(a, b))$ .

```
11 gcd(11 a, 11 b) { return b ? gcd(b, a % b) : a; }
```

## 5.9 Integer Mod

```
const 11 INF = 1e18;
const 11 mod = 998244353;
template <11 MOD = mod>
```

```
struct Modular {
    11 value;
    static const 11 MOD_value = MOD;
```

```
Modular(11 v = 0) {
    value = v % MOD;
    if (value < 0) value += MOD;
}
```

```
Modular(11 a, 11 b) : value(0) {
    *this += a;
    *this /= b;
}
```

```
Modular& operator+=(Modular const& b) {
    value += b.value;
    if (value >= MOD) value -= MOD;
    return *this;
}
```

```
Modular& operator--(Modular const& b) {
    value -= b.value;
    if (value < 0) value += MOD;
    return *this;
}
```

```
Modular& operator*=(Modular const& b) {
    value = (11)value * b.value % MOD;
    return *this;
}
```

```
friend Modular mexp(Modular a, 11 e) {
    Modular res = 1;
    while (e) {
        if (e & 1) res *= a;
        a *= a;
        e >>= 1;
    }
    return res;
}
```

```
friend Modular inverse(Modular a) { return mexp(a, MOD - 2); }
```

```
Modular& operator/=(Modular const& b) { return *this *= inverse(b); }
friend Modular operator+(Modular a, Modular const b) { return a += b; }
Modular operator++(int) { return this->value = (this->value + 1) % MOD; }
Modular operator++() { return this->value = (this->value + 1) % MOD; }
friend Modular operator-(Modular a, Modular const b) { return a -= b; }
friend Modular operator-(Modular const a) { return 0 - a; }
```

```
Modular operator--(int) {
    return this->value = (this->value - 1 + MOD) % MOD;
}
```

```
Modular operator--() { return this->value = (this->value - 1 + MOD) % MOD; }
friend Modular operator*(Modular a, Modular const b) { return a *= b; }
friend Modular operator/(Modular a, Modular const b) { return a /= b; }
friend std::ostream& operator<<(std::ostream& os, Modular const& a) {
    return os << a.value;
}
friend bool operator==(Modular const& a, Modular const& b) {
    return a.value == b.value;
}
friend bool operator!=(Modular const& a, Modular const& b) {
    return a.value != b.value;
}
};
```

## 5.10 Is prime

$O(\sqrt{N})$

```
bool isprime(11 n) {
    if (n < 2) return false;
    if (n == 2) return true;
    if (n % 2 == 0) return false;
    for (11 i = 3; i * i < n; i += 2)
        if (n % i == 0) return false;
    return true;
}
```

## 5.11 LCM

Calculating the least common multiple (commonly denoted LCM) can be reduced to calculating the GCD with the following simple formula:  $\text{lcm}(a, b) = (a \cdot b) / \text{gcd}(a, b)$

Thus, LCM can be calculated using the Euclidean algorithm with the same time complexity:

```
11 lcm(11 a, 11 b) { return a / gcd(a, b) * b; }
```

## 5.12 Euler phi $\varphi(n)$

Computes the number of positive integers less than  $n$  that are co-primes with  $n$ , in  $O(\sqrt{N})$ .

```
11 phi(11 n) {
    if (n == 1) return 1;

    auto fs = factorization(n);
    auto res = n;

    for (auto [p, k] : fs) {
        res /= p;
        res *= (p - 1);
    }

    return res;
}
```

## 5.13 Sieve

```
vl sieve(ll N) {
    bitset<MAX + 1> sieve;
    vl ps{2, 3};
    sieve.set();

    for (ll i = 5, step = 2; i <= N; i += step, step = 6 - step) {
        if (sieve[i]) {
            ps.push_back(i);

            for (ll j = i * i; j <= N; j += 2 * i) sieve[j] = false;
        }
    }
    return ps;
}
```

## 5.14 Sum Divisors

```
ll sum_divisors(ll num) {
    ll result = 1;

    for (int i = 2; (ll)i * i <= num; i++) {
        if (num % i == 0) {
            int e = 0;
            do {
                e++;
                num /= i;
            } while (num % i == 0);

            ll sum = 0, pow = 1;
            do {
                sum += pow;
                pow *= i;
            } while (e-- > 0);
            result *= sum;
        }
    }
    if (num > 1) {
        result *= (1 + num);
    }
    return result;
}
```

## 5.15 Sum of difference

Function to calculate sum of absolute difference of all pairs in array:  $\frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N |A_i - A_j|$

```
ll sum_of_difference(vl& arr, ll n) {
    sort(all(arr));

    ll sum = 0;
    for (ll i = 0; i < n; i++) {
        sum += i * arr[i] - (n - 1 - i) * arr[i];
    }

    return sum;
}
```

# 6 Problems

## 6.1 Kth Digit String (CSES)

Time:  $O(\log_{10} K)$ .

Space:  $O(1)$ .

```
ll kth_digit_string(ll k) {
    if (k < 10) return k;

    ll c = 180, i = 2, u = 10, r = 0, ans = -1, m;
    for (k -= 9; k > c; i++, u *= 10) {
        k -= c;
        c /= i;
        c *= 10 * (i + 1);
    }

    if ((m = k % i))
        r++;
    else
        m = i;

    ll tmp = (k / i) + r + u - 1;
    for (m = i + 1 - m; m--; tmp /= 10) ans = tmp % 10;

    return ans;
}
```

# 7 Strings

## 7.1 Edit Distance

Returns the minimum number of operations (insert, delete, replace) to transform string  $a$  into string  $b$ .

Time:  $O(M * N)$

```
int min_value(int x, int y, int z) { return min(min(x, y), z); }

int edit_distance(string str1, string str2) {
    int n = (int)str1.size(), m = (int)str2.size();
    int dp[m + 1][n + 1];

    for (int i = 0; i <= m; i++)
        for (int j = 0; j <= n; j++)
            if (i == 0)
                dp[i][j] = j;
            else if (j == 0)
                dp[i][j] = i;
            else if (str1[i - 1] == str2[j - 1])
                dp[i][j] = dp[i - 1][j - 1];
            else
                dp[i][j] = 1 + min_value(dp[i][j - 1], dp[i - 1][j], dp[i - 1][j - 1]);

    return dp[m][n];
}
```

## 7.2 Manacher

Given string  $s$  with length  $n$ . Find all the pairs  $(i, j)$  such that substring  $s[i \dots j]$  is a palindrome. String  $t$  is a palindrome when  $t = t_{rev}$  ( $t_{rev}$  is a reversed string for  $t$ ).

Time:  $O(N)$

```
vi manacher(string s) {
    string t;
    for (auto c : s) t += string("#") + c;
    t = t + '?#?';

    int n = t.size();
    t = "$" + t + "~";

    vi p(n + 2);
    int l = 1, r = 1;
    for (int i = 1; i <= n; i++) {
        p[i] = max(0, min(r - i, p[l + (r - i)]));
        while (t[i - p[i]] == t[i + p[i]]) p[i]++;
        if (i + p[i] > r) {
            l = i - p[i], r = i + p[i];
        }
        p[i]--;
    }

    return vi(begin(p) + 1, end(p) - 1);
}
```

## 8 Trees

### 8.1 LCA Binary Lifting (CP Algo)

The algorithm described will need  $O(N \cdot \log N)$  for preprocessing the tree, and then  $O(\log N)$  for each LCA query.

```
ll n, l;
vector<ll> adj[MAX];

ll timer;
vector<ll> tin, tout;
vector<vector<ll>> up;

void dfs(ll v, ll p) {
    tin[v] = ++timer;
    up[v][0] = p;
    for (ll i = 1; i <= l; ++i) up[v][i] = up[up[v][i - 1]][i - 1];

    for (ll u : adj[v]) {
        if (u != p) dfs(u, v);
    }

    tout[v] = ++timer;
}

bool is_ancestor(ll u, ll v) { return tin[u] <= tin[v] && tout[u] >= tout[v]; }

ll lca(ll u, ll v) {
```

```
    if (is_ancestor(u, v)) return u;
    if (is_ancestor(v, u)) return v;
    for (ll i = l; i >= 0; --i) {
        if (!is_ancestor(up[u][i], v)) u = up[u][i];
    }
    return up[u][0];
}

void preprocess(ll root) {
    tin.resize(n);
    tout.resize(n);
    timer = 0;
    l = ceil(log2(n));
    up.assign(n, vector<ll>(l + 1));
    dfs(root, root);
}
```

### 8.2 LCA SegTree (CP Algo)

The algorithm can answer each query in  $O(\log N)$  with preprocessing in  $O(N)$  time.

```
struct LCA {
    vector<ll> height, euler, first, segtree;
    vector<bool> visited;
    ll n;

    LCA(vector<vector<ll>>& adj, ll root = 0) {
        n = adj.size();
        height.resize(n);
        first.resize(n);
        euler.reserve(n * 2);
        visited.assign(n, false);
        dfs(adj, root);
        ll m = euler.size();
        segtree.resize(m * 4);
        build(1, 0, m - 1);
    }

    void dfs(vector<vector<ll>>& adj, ll node, ll h = 0) {
        visited[node] = true;
        height[node] = h;
        first[node] = euler.size();
        euler.push_back(node);
        for (auto to : adj[node]) {
            if (!visited[to]) {
                dfs(adj, to, h + 1);
                euler.push_back(node);
            }
        }
    }

    void build(ll node, ll b, ll e) {
        if (b == e) {
            segtree[node] = euler[b];
        } else {
            ll mid = (b + e) / 2;
            build(node << 1, b, mid);
            build(node << 1 | 1, mid + 1, e);
        }
    }
}
```

```

    ll l = segtree[node << 1], r = segtree[node << 1 | 1];
    segtree[node] = (height[l] < height[r]) ? l : r;
}
}

ll query(ll node, ll b, ll e, ll L, ll R) {
    if (b > R || e < L) return -1;
    if (b >= L && e <= R) return segtree[node];
    ll mid = (b + e) >> 1;

    ll left = query(node << 1, b, mid, L, R);
    ll right = query(node << 1 | 1, mid + 1, e, L, R);
    if (left == -1) return right;
    if (right == -1) return left;
    return height[left] < height[right] ? left : right;
}

ll lca(ll u, ll v) {
    ll left = first[u], right = first[v];
    if (left > right) swap(left, right);
    return query(1, 0, euler.size() - 1, left, right);
}
};

```

### 8.3 LCA Sparse Table

The algorithm described will need  $O(N)$  for preprocessing, and then  $O(1)$  for each LCA query.  
0 indexed!

```

typedef vector<vl> vl2d;
#define all(a) a.begin(), a.end()
#define len(x) (int)x.size()

template <typename T>
struct SparseTable {
    vector<T> v;
    ll n;
    static const ll b = 30;
    vl mask, t;

    ll op(ll x, ll y) { return v[x] < v[y] ? x : y; }
    ll msb(ll x) { return __builtin_clz(1) - __builtin_clz(x); }
    SparseTable() {}
    SparseTable(const vector<T>& v_) : v(v_), n(v.size()), mask(n), t(n) {
        for (ll i = 0, at = 0; i < n; mask[i++] = at |= 1) {
            at = (at << 1) & ((1 << b) - 1);
            while (at and op(i, i - msb(at & -at)) == i) at ^= at & -at;
        }
        for (ll i = 0; i < n / b; i++)
            t[i] = b * i + b - 1 - msb(mask[b * i + b - 1]);
        for (ll j = 1; (1 << j) <= n / b; j++)
            for (ll i = 0; i + (1 << j) <= n / b; i++)
                t[n / b * j + i] =
                    op(t[n / b * (j - 1) + i], t[n / b * (j - 1) + i + (1 << (j - 1))]);
    }
    ll small(ll r, ll sz = b) { return r - msb(mask[r] & ((1 << sz) - 1)); }
    T query(ll l, ll r) {
        if (r - l + 1 <= b) return small(r, r - l + 1);
    }
};

```

```

    ll ans = op(small(l + b - 1), small(r));
    ll x = l / b + 1, y = r / b - 1;
    if (x <= y) {
        ll j = msb(y - x + 1);
        ans = op(ans, op(t[n / b * j + x], t[n / b * j + y - (1 << j) + 1]));
    }
    return ans;
}
};

struct LCA {
    SparseTable<ll> st;
    ll n;
    vl v, pos, dep;

    LCA(const vl2d& g, ll root) : n(len(g)), pos(n) {
        dfs(root, 0, -1, g);
        st = SparseTable<ll>(vector<ll>(all(dep)));
    }

    void dfs(ll i, ll d, ll p, const vl2d& g) {
        v.emplace_back(len(dep)) = i, pos[i] = len(dep), dep.emplace_back(d);
        for (auto j : g[i])
            if (j != p) {
                dfs(j, d + 1, i, g);
                v.emplace_back(len(dep)) = i, dep.emplace_back(d);
            }
    }

    ll lca(ll a, ll b) {
        ll l = min(pos[a], pos[b]);
        ll r = max(pos[a], pos[b]);
        return v[st.query(l, r)];
    }
    ll dist(ll a, ll b) {
        return dep[pos[a]] + dep[pos[b]] - 2 * dep[pos[lca(a, b)]];
    }
};

```

### 8.4 Tree Isomorph

Checks whether two tree are isomorph. The function *thash()* returns the hash of the tree (using centroids as special vertices). Two trees are isomorph if their hash are the same.

map<vector<int>, int> mhash;

```

struct tree {
    int n;
    vector<vector<int>> g;
    vector<int> sz, cs;

    tree(int n_) : n(n_), g(n_), sz(n_) {}

    void dfs_centroid(int v, int p) {
        sz[v] = 1;
        bool cent = true;
        for (int u : g[v])
            if (u != p) {

```

```

        dfs_centroid(u, v), sz[v] += sz[u];
        if (sz[u] > n / 2) cent = false;
    }
    if (cent and n - sz[v] <= n / 2) cs.push_back(v);
}
int fhash(int v, int p) {
    vector<int> h;
    for (int u : g[v])
        if (u != p) h.push_back(fhash(u, v));
    sort(h.begin(), h.end());
    if (!mphash.count(h)) mphash[h] = mphash.size();
    return mphash[h];
}
ll thash() {
    cs.clear();
    dfs_centroid(0, -1);
    if (cs.size() == 1) return fhash(cs[0], -1);
    ll h1 = fhash(cs[0], cs[1]), h2 = fhash(cs[1], cs[0]);
    return (min(h1, h2) << 30) + max(h1, h2);
}
void add(int a, int b) {
    g[a].emplace_back(b);
    g[b].emplace_back(a);
}
};

```

## 9 Settings and macros

### 9.1 macro.cpp

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

using namespace __gnu_pbds;
#define ordered_set tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update>

using namespace std;

#ifdef DEBUG
#include "../settings-and-macros/debug.cpp"
#else
#define dbg(...)
#endif

typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef vector<int> vi;
typedef vector<ll> vl;
typedef vector<pii> vii;
typedef vector<pll> vll;

#define fst first
#define snd second

```

```

#define all(x) x.begin(), x.end()
#define vin(vt) for (auto &e : vt) cin >> e
#define LSONe(S) ((S) & ~(S))
#define MSOne(S) (1ull << (63 - __builtin_clzll(S)))
#define fastio ios_base::sync_with_stdio(0); \
    cin.tie(0); \
    cout.tie(0)

const vii dir4 {{1,0},{-1,0},{0,1},{0,-1}};

auto solve() { }

int main() {
    fastio;

    ll t = 1;
    //cin >> t;

    while (t--) solve();

    return 0;
}

```

### 9.2 short-macro.cpp

```

#include <bits/stdc++.h>

using namespace std;

#ifdef DEBUG
#include "../settings-and-macros/debug.cpp"
#else
#define dbg(...)
#endif

typedef long long ll;
typedef pair<int, int> ii;

#define all(x) x.begin(), x.end()
#define vin(vt) for (auto &e : vt) cin >> e

auto solve() { }

int main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll t = 1;
    //cin >> t;

    while (t--) solve();

    return 0;
}

```



## 10 Theoretical guide

### 10.1 Notable Series

1. Sum of the first  $n$  naturals:

$$S_n = \sum_{i=1}^n i = 1 + 2 + 3 + \cdots + n = \frac{n(n+1)}{2}$$

2. Sum of the squares of the first  $n$  naturals:

$$S_n = \sum_{i=1}^n i^2 = 1^2 + 2^2 + 3^2 + \cdots + n^2 = \frac{n(n+1)(2n+1)}{6}$$

3. Sum of the cubes of the first natural  $n$ :

$$S_n = \sum_{i=1}^n i^3 = 1^3 + 2^3 + 3^3 + \cdots + n^3 = \left[ \frac{n(n+1)}{2} \right]^2$$

4. Sum of the first  $n$  odd numbers:

$$S_n = \sum_{i=1}^n 2i - 1 = 1 + 3 + 5 + \cdots + (2n - 1) = n^2$$

### 10.2 Modular Multiplicative Inverse

A modular multiplicative inverse of an integer  $a$  is an integer  $x$  such that  $a \cdot x$  is congruent to 1 modular some modulus  $m$ . To write it in a formal way:

$$a \cdot x \equiv 1 \pmod{m}.$$

Euler's theorem, which states that the following congruence is true if  $a$  and  $m$  are co-primes:

$$a^{\phi(m)} \equiv 1 \pmod{m}$$

Multiply both sides of the above equations by  $a^{-1}$ , and we get:

- For an arbitrary (but coprime) modulus  $m$ :  $a^{\phi(m)-1} \equiv a^{-1} \pmod{m}$
- For a prime modulus  $m$ :  $a^{m-2} \equiv a^{-1} \pmod{m}$

From these results, we can easily find the modular inverse using the binary exponentiation algorithm, which works in  $O(\log m)$  time.