

Snake Wrangling For Kids

Learning to Program with Python

Mac Edition



Written by Jason R. Briggs

Snake Wrangling for Kids, Learning to Program with Python
by Jason R. Briggs

Version 0.7.7

Copyright ©2007.

Published by... ah, no one actually.

Cover art and illustrations by Nuthapitol C.

Website:

<http://www.briggs.net.nz/log/writing/snake-wrangling-for-kids>

Thanks To:

Guido van Rossum (for benevolent dictatorship of the Python language), the members of the [Edu-Sig](#) mailing list (for helpful advice and commentary), author [David Brin](#) (the original [instigator](#) of this book), Michel Weinachter (for providing better quality versions of the illustrations), and various people for providing feedback and errata, including: Paulo J. S. Silva, Tom Pohl, Janet Lathan, Martin Schimmels, and Mike Cariaso (among others). Anyone left off this list, who shouldn't have been, is entirely due to premature senility on the part of the author.

License:



This work is licensed under the Creative Commons Attribution-Noncommercial-Share Alike 3.0 New Zealand License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-sa/3.0/nz/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

Below is a summary of the license.

You are free:

- **to Share** — to copy, distribute and transmit the work
- **to Remix** — to adapt the work

Under the following conditions:

Attribution. You must attribute the work in the manner specified by the author or licensor (but not in any way that suggests that they endorse you or your use of the work).

Noncommercial. You may not use this work for commercial purposes.

Share Alike. If you alter, transform, or build upon this work, you may distribute the resulting work only under the same or similar license to this one.

For any reuse or distribution, you must make clear to others the license terms of this work.

Any of the above conditions can be waived if you get permission from the copyright holder.

Nothing in this license impairs or restricts the author's moral rights.



Conteúdo

Preface	v
1 Nem todas cobras te morderão	1
1.1 Um pouco sobre linguagens	2
1.2 A Ordem das Não-venenosas Serpentes Constritoras	3
1.3 Seu primeiro programa em Python	4
1.4 Seu segundo programa em Python...o mesmo?	5
2 8 multiplicado por 3.57 é...	9
2.1 Uso de parênteses e “Prioridade de Operações”	11
2.2 Não há nada possa mudar tanto como uma variável	13
2.3 Usando uma variável	15
2.4 Um pedaço de ‘string’?	17
2.5 Truques com Strings	18
2.6 Não é igual a uma lista de compras	19
2.7 Tuples and Lists	23
2.8 Things to try	23
3 Turtles, and other slow moving creatures	25
3.1 Things to try	31
4 How to ask a question	33
4.1 Do this... or ELSE!!!	34

4.2	Do this... or do this... or do this... or ELSE!!!	35
4.3	Combining conditions	36
4.4	Emptiness	36
4.5	What's the difference...?	38
5	Again and again	41
5.1	When is a block not square?	44
5.2	While we're talking about looping...	50
5.3	Things to try	52
6	Sort of like recycling...	53
6.1	Bits and Pieces	57
6.2	Modules	59
6.3	Things to try	61
7	A short chapter about Files	63
8	Turtles galore	65
8.1	Colouring in	69
8.2	Darkness	72
8.3	Filling things	72
8.4	Things to try	78
9	A bit graphic	81
9.1	Quick Draw	83
9.2	Simple Drawing	85
9.3	Drawing Boxes	87
9.4	Drawing Arcs	91
9.5	Drawing Ovals	92
9.6	Drawing Polygons	95
9.7	Drawing Images	96
9.8	Basic Animation	98

9.9	Reacting to events...	99
10	Where to go from here	103
A	Python Keywords	105
B	Built-in Functions	119
C	A Few Python Modules	129
D	Answers to “Things to try”	139

Introdução

Um recado aos Pais...

Prezado(a) Pai, Mãe ou Responsável,

Para que seu filho inicie as atividades de programação, você terá que instalar o Python em seu computador. Este livro foi recentemente atualizado para utilizar o Python 3.2, que é a última versão do Python. Caso você possua uma versão antiga do Python instalada, você precisará utilizar uma versão antiga do livro.

Instalar o Python é uma tarefa muito simples, porém, dependendo do Sistema Operacional que você estiver utilizando, talvez precise passar por alguns obstáculos. Se você apenas comprou um novo computador, não tem ideia do que fazer com ele, e a última frase te deu até calafrios, você provavelmente precisará de alguém para realizar tal trabalho. Dependendo do seu computador, e da velocidade da sua conexão com a internet, essa tarefa pode levar de 10 minutos a algumas horas.

Primeiramente, vá até www.python.org e baixe a última versão do instalador do Python 3.2 para Mac. No momento em que estou escrevendo, é esse:

<http://python.org/ftp/python/3.2/python-3.2-macosx10.6.dmg>

Clique duas vezes sobre o ícone do instalador para Mac (provavelmente na pasta Downloads do seu usuário), e siga as instruções para completar a instalação.

Após a instalação...

... Você pode precisar sentar ao lado de seu filho em alguns dos primeiros capítulos, mas nós esperamos que após alguns exemplos, eles tirem o teclado das suas mãos e façam eles mesmos. Eles devem pelo menos saber como utilizar algum tipo de editor de texto (não um editor como o Microsoft Word, mas um editor de texto comum, apenas para texto). Eles devem saber como abrir e fechar arquivos, criar novos arquivos de texto e salvar o que estiverem fazendo. Fora isso, o livro tentará ensinar a partir do mais básico.

Obrigado pela sua atenção, meus cumprimentos,
O LIVRO

Capítulo 1

Nem todas cobras te morderão


Há possibilidade de que este livro tenha sido lhe dado em seu aniversário, ou possivelmente no Natal. Tia Amélia lhe daria um par de meias duas vezes maior que o seu pé (e que mesmo se servisse, você não gostaria de usar). Mas ao invés disso, ela ouviu alguém falando sobre a versão impressa deste livro e logo lembrou que você tinha um daqueles compu-alguma-coisa, que inclusive tentou ensiná-la a usar uma vez, no último Natal (até que ela começasse a tentar falar com o mouse), e pediu-lhe para que imprimisse mais uma cópia. Seja grato por não ter ganho aquele velho par de meias.

Espero que você não esteja tão decepcionado, por eu surgir de um papel de presentes reciclado, ao invés disso. Um não-tão-falante (ok, um nada-falante) livro, com um título aparentemente ameaçador na capa “Aprendendo...”. Mas espere um momento para pensar em como eu me sinto. Se você fosse o personagem daquela novela sobre magos que estão na prateleira de livros do seu quarto, eu possivelmente teria dentes... ou até olhos. Eu poderia mover figuras dentro de mim, ou ser capaz de fazer sons fantasmagóricos enquanto você folheia minhas páginas. Mas pelo contrário, eu sou impresso em folhas de papel A4 com algumas orelhas, ou quem sabe grampeados, dentro de uma pasta. Como eu saberia—Eu não tenho olhos.

Eu daria qualquer coisa por alguns belos e afiados dentes...

Porém isso não é tão ruim quanto parece. Mesmo que eu não possa falar... ou morder os seus dedos enquanto não está olhando... Eu posso lhe dizer um pouquinho como os computadores funcionam. Nada da parte física, com fios, chips, cabos e outros dispositivos que, mais do que provável, lhe dariam choque antes mesmo que o tocassem (então, não!!)—mas as coisas escondidas que rodam entre esses fios, chips de computador, cabos e bits, que fazem o seu computador ter alguma utilidade.

É um pouco como os pensamentos rodando dentro da sua cabeça. Se você não tivesse pensamentos, você estaria sentado no chão do seu quarto, olhando vagarosamente para a porta e babando sobre a sua camiseta. Sem os *programas*, os computadores serviriam apenas para apoiar portas—e mesmo assim ainda não seriam muito úteis, pois você ainda tropeçaria sobre eles durante a noite. E convenhamos que, não há nada pior que tropeçar no escuro e bater o dedinho do pé.



Eu sou apenas um livro e eu sei disso.

Sua família pode ter um Playstation, Xbox ou Wii na sala—eles não teriam muito uso sem os programas (jogos) para fazê-los funcionar. Seu aparelho de DVD, possivelmente sua geladeira e seu carro, todos usam programas de computador que os tornam mais prestativos do que seriam. Seu aparelho de DVD tem programas que ajudam-o a escolher o que quer assistir no DVD; sua geladeira pode ter um simples programa que o ajuda a economizar energia elétrica, e mesmo assim mantém a comida conservada; seu carro pode ter um computador, que possui um programa, que alerta o motorista sobre uma possível colisão.

Se você souber como escrever programas de computador, você pode fazer todos tipos de coisas úteis. Quem sabe escrever seus próprios jogos. Criar web sites que realmente façam algo, não apenas deixá-los com um visual colorido. Ser capaz de programar o ajudaria até com o seu dever de casa.

Como dito, vamos para algo um pouco mais interessante.

1.1 Um pouco sobre linguagens

Assim como os humanos, certamente as baleias, possivelmente os golfinhos, e talvez alguns pais (embora isso seja discutível), computadores tem sua própria linguagem. Atualmente, como os humanos, eles tem até mais de uma linguagem. Praticamente há uma linguagem para cada letra do alfabeto. A, B, C, D e E não são apenas letras, mas também linguagens de programação (que provam que adultos não tem imaginação, e deveriam ter lido um dicionário, ou ao menos uma enciclopédia, antes

de nomear algo).

Há linguagens de programação com nomes de pessoas, nomeadas usando simples acrônimos (a primeira letra de uma série de palavras), e apenas algumas nomeadas após um programa de TV. Ah, e se você adicionar alguns sinais de adição, ou sustentados (+, #) após algumas das letras que mencionei—você terá mais algumas linguagens de programação. Tornando as coisas piores, algumas linguagens de programação são praticamente a mesma coisa, diferenciando-se levemente.

O que eu te disse? Sem imaginação!

Felizmente, muitas dessas linguagens caíram em desuso, ou sumiram completamente; mas a lista de diferentes formas que você pode ‘falar’ com o computador continua preocupantemente grande. Irei discutir apenas uma delas—caso contrário nem mesmo teríamos começado.

Seria mais produtivo sentar-se em seu quarto e babar sobre a sua camiseta...

1.2 A Ordem das Não-venenosas Serpentes Constritoras...

...ou Pythons (Pítons em português), mais especificamente.

Além de ser uma cobra, Python também é uma linguagem de programação. Porém, não foi nomeada com o nome de um réptil sem patas; mas é uma das linguagens de programação nomeadas após um programa de TV. Monty Python foi um popular programa humorístico de TV britânico, durante a década de 70 (e continua popular até hoje), que você deve ter uma certa idade para achar engraçado. Qualquer um abaixo dessa idade... digamos 12... ficará se perguntando do que se trata¹.

Existe uma série de coisas sobre Python (a linguagem de programação, não a cobra, nem o programa de TV) que a fazem extremamente útil quando você está aprendendo a programar. Para nós, no momento, o motivo mais importante é que você pode começar a fazer as coisas muito mais rapidamente.

Esta é a parte em que você espera que a sua Mãe, Pai (ou quem estiver responsável pelo computador), tenha lido o começo do livro, rotulado “Um recado aos Pais”.

Existe um bom modo de saber se eles realmente leram:

¹Exceto a dança-do-peixe-na-cara. Que é engraçado independente da sua idade.




Figure 1.1: Interpretador Python no Mac OSX.

Na barra lateral do Finder, você deve ver um grupo chamado ‘Aplicativos’. Clique sobre ele, e então procure pelo programa chamado ‘Terminal’ (provavelmente estará dentro da pasta ‘Utilitários’). Clique em ‘Terminal’, e quando abrir, digite python e pressione enter. Esperamos que você veja uma tela parecida com a Figura 1.1.

Se você descobrir que eles não leram o começo do livro...

...porque está faltando algo quando você tenta seguir essas instruções—então vire a página até o começo do livro e coloque-o sobre o jornal que eles estão tentando ler, olhando-os com confiança. Dizendo, “por favor, por favor” de novo e de novo, até que se torne chato o bastante, deve funcionar bem, caso você esteja tendo problemas para tirá-los do sofá. E claro, uma outra alternativa, é você tentar seguir as instruções da ‘Introdução’, de como instalar o Python, você mesmo.

1.3 Seu primeiro programa em Python

Com sorte, se você chegou até aqui, você já deve ter iniciado o Interpretador Python, que é uma das formas de executar comandos e programas em Python. Quando você o inicia pela primeira vez (ou após executar algum comando), você verá o que chamamos de ‘prompt’. No Interpretador Python, o ‘prompt’ é indicado por três sinais de ‘maior que’ (>):

```
>>>
```

Se você juntar alguns comandos Python necessários, você terá um programa que poderá rodar não apenas no interpretador... mas no momento, nós queremos deixar as coisas simples, digitando nossos comandos diretamente no interpretador, no ‘prompt’ (>>>). Então, por que não começamos digitando o seguinte:

```
print("Olá mundo")
```

Certifique-se de colocar as aspas (que são essas: ””), e pressionar a tecla ‘enter’ no final da linha. Esperando que você veja algo parecido com isso:

```
>>> print("Olá mundo")
Olá mundo
```

O ‘prompt’ reaparece, informando-o que o Interpretador Python já está pronto para outros comandos.

Parabéns! Você acaba de criar seu primeiro programa em Python. `print` é a função que escreve no interpretador, o que estiver entre os parênteses—em breve, nós o utilizaremos novamente.

1.4 Seu segundo programa em Python...o mesmo?

Os programas em Python não seriam tão úteis assim, caso você tivesse que digitar cada comando, toda hora que quisesse fazer algo—ou se você escrevesse um programa para alguém, e ele tivesse que digitar tudo de novo, antes de usá-lo.

O editor de texto que você utiliza para fazer seus trabalhos de escola, deve ter em torno de 10 a 100 milhões de linhas de código. Dependendo do número de linhas que você imprimir por página (imprimindo ou não em frente e verso), isso daria por volta de 400,000 páginas... ou uma pilha de papel de mais de 40 metros. Imagine que, quando você levasse esse programa da loja para a sua casa, você teria que fazer várias viagens de ida e volta, para carregar tanto papel...

...e ainda teria que torcer para não ocorresse nenhuma rajada de vento, enquanto carregava os papéis. Felizmente, há uma alternativa para tudo que foi dito aqui—ou ninguém faria nada disso.



Abra o seu Editor de Texto clicando sobre o seu ícone. Pode estar no Dock, na



parte inferior da tela , ou procure pelo ícone  **TextEdit** na lista de Aplicativos, no Finder. Digite o comando `print` exatamente como você digitou anteriormente no interpretador:

```
print("Ola mundo")
```

Clique no menu Arquivo e salve-o no seu diretório (barra lateral esquerda do Finder, em Locais—pergunte a sua Mãe ou Pai caso não ache) com o nome *ola.py*.

Abra o ‘Terminal’ novamente—ele abrirá automaticamente no seu diretório—e siga as instruções:

```
python ola.py
```

Você deverá ver a frase ‘Ola mundo’ exatamente como você digitou no Interpretador Python.

Agora você pode ver que as boas pessoas que criaram o Python, amavelmente, salvaram-o de ter que digitar a mesma coisa repetidas e repetidas vezes. Como fizeram alguns lá nos anos 80. É sério—eles fizeram. Vá e pergunte ao seu pai, se ele já não teve um *ZX81* quando era criança.

Se já teve, você pode apontar para ele e começar a rir.

Acredite em mim. Você não vai entender isso, mas ele vai.²

Porém esteja preparado para correr.

O fim do começo

Bem-vindo ao maravilhoso mundo da Programação. Nós começamos com um simples programa de “Olá mundo”—todo mundo começa assim quando estão aprendendo a programar. No próximo capítulo, nós começaremos a fazer coisas mais úteis com o Interpretador Python, e veremos como são feitos os programas.

²O Sinclair ZX81, lançado nos anos 80, foi um dos primeiros computadores pessoais acessíveis. Uma série de jovens, garotos e garotas, ficaram enlouquecidos, digitando o código de alguns jogos que vinham nas populares revistas sobre o ZX81—descobrindo somente após horas de digitação, que aquelas maluquices jamais funcionaram como deveriam.

Capítulo 2

8 multiplicado por 3.57 é...

Quanto é 8 multiplicado por 3.57? Você teria que usar uma calculadora, certo? Bom, a não ser que você seja extremamente esperto e consiga fazer mutiplicações de frações, de cabeça — mas isso não vem ao caso. Você pode fazer isso no terminal do Python. Inicie o terminal novamente (veja o Capítulo 1 para mais informações, caso você tenha pulado uma parte por algum motivo estranho), e assim que ele iniciar, digite `8*3.57` e pressione a tecla Enter:

```
Python 3.0 (r30:67503, Dec  6 2008, 23:22:48)
Type "help", "copyright", "credits" or "license" for more information.
>>> 8 * 3.57
28.559999999999999
```

A tecla estrela (*), ou asterisco (shift 8, em alguns teclados), é usada para multiplicação, ao invés do sinal de vezes (X) que você usa na escola (usar o asterisco é necessário, pois caso contrário, como o computador entenderia quando você quisesse usar a letra *x* ou o símbolo de multiplicação X ?). Que tal uma equação, que é um pouco mais interessante?

Suponhamos que você faça algumas pequenas tarefas, ao menos uma vez por semana e ganhe R\$5 para isso. E que você também entregue alguns jornais, pelo menos 5 vezes na semana e ganhe R\$30 para isso — quanto você ganharia em um ano?

Se estivessemos escrevendo isso em um papel, escreveríamos algo assim:

$$(5 + 30) \times 52$$

O Python é defeituoso!?!?

Se você pegar uma calculadora e digitar 8×3.57 , a resposta exibida será:

28.56

Mas porque no Python é diferente? É um defeito?

Na verdade não. O motivo é a forma com que os pontos flutuantes (frações de números com casas decimais) números são manuseados pelo computador. É um problema complicado e um pouco confuso para iniciantes, então o melhor coisa a se fazer é sempre que estiver trabalhando com frações (ex.: com números com casas decimais), se lembrar que *algumas* vezes o resultado pode ser diferente do esperado. Isso é fato para multiplicação, divisão, adição ou subtração.

Que é R\$5 + R\$30 multiplicado por 52 semanas em um ano. Claro, você é esperto e nós sabemos que $5 + 30$ é 35, então a equação seria:

35×52

Que é bastante fácil de se fazer com uma calculadora, ou até mesmo no papel. Mas nós podemos fazer todos esses cálculos no terminal também:

```
>>> (5 + 30) * 52
1820
>>> 35 * 52
1820
```

Mas e se você gastasse R\$10 toda semana? Quanto lhe sobraria no final do ano? Nós poderíamos escrever essa equação no papel de diversas maneiras, mas vamos fazer isso no terminal:

```
>>> (5 + 30 - 10) * 52
1300
```

Isso seria R\$5 mais R\$30, menos R\$10, multiplicado pelas 52 semanas no ano. E lhe sobraria R\$1300 no final do ano. Certo, mas isso não está parecendo muito

útil. Nós poderíamos fazer tudo isso com uma calculadora. Mas nós voltaremos mais tarde nesse assunto e demonstraremos como tornar isso muito mais útil.

Você pode multiplicar, somar (obviamente), subtrair e dividir, usando o terminal do Python, junto à diversas outras operações matemáticas que não nos aprofundaremos no momento. Para agora, os símbolos matemáticos mais básicos (chamados operadores) em Python, são:

+	Adição
-	Subtração
*	Multiplicação
/	Divisão

O motivo da barra (/) ser utilizada para divisão, é que seria muito difícil desenhar a linha de divisão (além disso, o teclado dos computadores não contempla o símbolo de divisão \div) que você está acostumado a usar nas equações. Por exemplo, se você tem 100 ovos e 20 caixas e gostaria de saber quantos ovos deveriam ir em cada caixa, você dividiria 100 por 20, escrevendo a seguinte equação:

$$\begin{array}{r} 100 \\ \hline 20 \end{array}$$

Ou se você usa o método de Divisão Longa, você escreveria dessa forma:

$$\begin{array}{r} 5 \\ 20) 100 \\ \hline 100 \\ \hline 0 \end{array}$$

Ou ainda, você poderia escrever assim:

$$100 \div 20$$

Porém, em Python você apenas digitaria “100 / 20”.

Que eu acho muito mais simples. Porém eu sou apenas um livro — do que eu sei?

2.1 Uso de parênteses e “Prioridade de Operações”

Nós usamos parênteses em uma linguagem de programação para controlar o que chamamos de “Prioridade de Operações”. Uma operação é a utilização de um operador (algum daqueles símbolos da tabela acima). Existem outros operadores além

dos símbolos matemáticos básicos, mas para estes operadores (adição, subtração, multiplicação e divisão), é o suficiente saber que a multiplicação e a divisão tem mais prioridade que a adição e a subtração. Que significa que você faz a multiplicação e a divisão em uma equação, antes da adição e da subtração. Na equação abaixo, onde todos os operadores são de adição (+), os números são adicionados em ordem:

```
>>> print(5 + 30 + 20)
55
```

Da mesma forma, nesta equação, existem somente operadores de adição e subtração, por isso o Python considera cada número na ordem em que ele aparece.

```
>>> print(5 + 30 - 20)
15
```

Mas na equação abaixo, existe um operador de multiplicação, então os números 30 e 20 são considerados primeiro. Esta equação é outro jeito de se dizer, “multiplique 30 por 20 e então adicione 5 ao resultado” (multiplicação primeiro, pois ela tem mais prioridade que a adição):

```
>>> print(5 + 30 * 20)
605
```

Então o que acontece se nós usarmos parênteses? A seguinte equação nos mostrará o resultado:

```
>>> print((5 + 30) * 20)
700
```

Por que o resultado é diferente? Porque os parênteses controlam a ordem das operações. Com os parênteses, o Python sabe que deve realizar as operações entre parênteses primeiro, e depois as que estiverem fora. Então, essa equação é outra maneira de dizer, “adicione 5 e 30, então multiplique o resultado por 20”.

O uso dos parênteses pode se tornar complicado. Podem existir parênteses dentro de parênteses:

```
>>> print(((5 + 30) * 20) / 10)
70
```

Neste caso, o Python calculará o que estiver **dentro** dos parênteses primeiro, depois o que estiver fora, e assim por diante. Então essa equação é outra maneira de se dizer, “adicione 5 e 30, então multiplique o resultado por 20, finalmente divida o resultado por 10”. O resultado, sem parênteses, é novamente um pouco diferente:


```
>>> 5 + 30 * 20 / 10
65
```

Neste caso, o 30 é multiplicado por 20 primeiro, então o resultado é dividido por 10 e finalmente o 5 é adicionado ao resultado.

Lembre-se de que a multiplicação e a divisão são sempre realizadas antes da adição e da subtração, a não ser que os parênteses estejam sendo utilizados para controlar a ordem das operações.

2.2 Não há nada possa mudar tanto como uma variável

Uma ‘variável’, em termos de programação, é usada para descrever um lugar onde se possa armazenar coisas. Essas ”coisas” podem ser números, textos, listas de números e textos — e todos os outros tipos de itens, que seria impossível de descrever aqui. Para agora, vamos apenas imaginar as variáveis como uma caixa de correios.



Você pode colocar coisas (como uma carta ou um pacote) na caixa de correios, assim como você pode colocar coisas (números, textos, listas de números e textos, etc) em uma variável. A ideia da caixa de correios, é um modo que muitas linguagens de programação funcionam. Mas não todas.

Em Python, as variáveis são um pouco diferentes. Ao invés de uma caixa de correios com coisas dentro, uma variável lembra mais um selo que é colado do lado

de fora de uma caixa de correios. Nós podemos descolar esse selo e colá-lo em outra coisa, ou até mesmo amarrá-lo em mais de uma coisa (talvez usando uma corda). Nós criamos uma variável dando à ela um nome, usando o sinal de igual (=) e então dizendo ao Python o que nós queremos apontar para aquele nome.

```
>>> fred = 100
```

Nós apenas criamos uma variável chamada ‘fred’ e dissemos para que ela apontasse para o número 100. É quase o mesmo que dizer ao Python para se lembrar daquele número porque nós vamos querer usá-lo posteriormente. Para descobrir para onde uma variável está apontando, nós apenas digitamos ‘print’ no terminal, seguido do nome da variável e então pressionamos o Enter, por exemplo:

```
>>> fred = 100
>>> print(fred)
100
```

Nós também podemos dizer ao Python, que nós queremos que a variável fred aponte para outra coisa:

```
>>> fred = 200
>>> print(fred)
200
```

Na primeira linha, nós dizemos que agora nós queremos que o fred aponte para o número 200. Depois, na segunda linha, nós perguntamos para onde o fred está apontando, apenas para provar que mudou. Nós podemos também apontar mais de um nome para a mesma coisa:

```
>>> fred = 200
>>> john = fred
>>> print(john)
200
```

No código acima, nós estavamos dizendo que nós queríamos que o nome (ou etiqueta) john apontasse para a mesma coisa que fred estava apontando. Claro que, ‘fred’ não é um nome muito útil para uma variável. Ele não nos diz nada a respeito da sua utilidade. Uma caixa de correios é fácil — você usa uma caixa de correios para enviar cartas. Mas uma variável pode ter diversas utilidades e pode apontar para um monte de coisas diferentes, então nós precisamos de um nome mais informativo.

Suponha que você tenha iniciado o terminal do Python, digitado ‘fred = 200’ e então tenha saído — passou 10 anos escalando o Monte Everest, atravessando o Deserto do Saara, pulando de uma ponte na Nova Zelândia e finalmente, passeou por todo o rio Amazonas — quando você voltou para o seu computador, como você se lembraria o que o número 200 significa (e para que ele seria usado)?

Eu acho que eu não lembraria.

Eu só fiz isso até agora e não tenho ideia do que ‘fred = 200’ significa (a não ser um *nome* apontando para o número *200*). Então após 10 anos, você não teria nenhuma chance de se lembrar.

Ahá! Mas se nós chamassemos nossa variável de: *numero_de_estudantes*.

```
>>> numero_de_estudantes = 200
```

Nós podemos fazer isso, pois o nome das variáveis podem conter letras, números e (_) sublinhados — embora elas não possam começar com um número. Se você voltar após 10 anos, ‘numero_de_estudantes’ ainda vai fazer sentido. Você pode digitar:

```
>>> print(numero_de_estudantes)
200
```

E você vai imediatamente se lembrar que estamos falando de 200 estudantes. Nem sempre é importante usar nomes significativos para variáveis. Você pode usar qualquer coisa, desde uma única letra (como o ‘a’) até grandes sentenças. E de vez em quando, se estiver fazendo algo rápido, um nome de variável simples e curto também será útil. Depende muito do que você vai querer pensar posteriormente, ao olhar para o nome dessa variável.

```
este_nome_de_variavel_tambem_eh_valido_porem_nao_eh_muito_util
```

2.3 Usando uma variável

Agora que nós sabemos como criar uma variável, como nós a usamos? Lembra da equação que nós vimos lá atrás? Aquela para saber quanto você teria em dinheiro no final do ano, caso ganhasse R\$5 por semana fazendo alguns pequenos trabalhos, R\$30 por semana entregando jornais e gastasse R\$10 por semana. Até agora, o que temos é:

```
>>> print((5 + 30 - 10) * 52)
1300
```

Que tal se transformarmos os 3 primeiros números em variáveis? Tente digitar o seguinte:

```
>>> trabalhos = 5
>>> entregas_de_jornal = 30
>>> gastos = 10
```

Nós apenas criamos as variáveis ‘trabalhos’, ‘entregas_de_jornal’ e ‘gastos’. Nós podemos redigir a equação para ver:

```
>>> print((trabalhos + entregas_de_jornal - gastos) * 52)
1300
```

Que dará exatamente o mesmo resultado. E se você ganhasse mais R\$2 por semana, fazendo alguns trabalhos extras? Mude a variável ‘trabalhos’ para 7, então aperte a tecla para cima (\uparrow) até que a equação apareça novamente e aperte Enter:

```
>>> trabalhos = 7
>>> print((trabalhos + entregas_de_jornal - gastos) * 52)
1404
```

Assim é muito mais fácil descobrir que você ficou com R\$1404 no final do ano. Você pode tentar alterar outras variáveis e apertar a seta para cima para realizar a conta novamente e você verá o efeito que terá.

Se você gastar o dobro do dinheiro por semana:

```
>>> gastos = 20
>>> print((trabalhos + entregas_de_jornal - gastos) * 52)
884
```

Você terá pouparado apenas R\$884 no final do ano. Isso ainda é bem pouco útil. Nós ainda não chegamos em algo realmente útil. Mas para o momento, é o bastante para entender que variáveis são usadas para armazenar coisas.

Pense em uma caixa de correios com uma etiqueta colada!

2.4 Um pedaço de ‘string’?

Se você está prestando atenção, não apenas folheando as páginas olhando as partes boas, você deve se lembrar que eu mencionei que variáveis podem ser usadas para tudo — não somente números. Em programação, na maior parte do tempo nós chamamos um texto de ‘string’ (corda). Que pode parecer um pouco estranho; mas se você pensar que um texto é apenas um punhado de letras ‘amarradas’ umas as outras, talvez faça um pouco mais sentido.

E novamente, caso não faça.

Neste caso, tudo que você deve saber é que uma string é apenas um punhado de letras, números e outros símbolos juntos, formando algo mais significativo. Todas as letras, números e símbolos neste livro poderiam formar uma string. O seu nome pode ser uma string. Assim como o endereço da sua casa. Nossa primeiro programa em Python, no capítulo 1, usou uma string: ‘Olá mundo’.

Em Python, nós criamos uma string colocando aspas ao redor do texto. Então nós podemos pegar a nossa variável de pouca utilidade ‘fred’ e colocar uma string dentro:

```
>>> fred = "esta é uma string"
```

E nós podemos ver o que está dentro da variável fred, digitando `print(fred)`:

```
>>> print(fred)
esta é uma string
```

Nós também podemos usar aspas simples para criar uma string:

```
>>> fred = 'esta também é uma string'
>>> print(fred)
esta também é uma string
```

Porém, se você tentar digitar mais de uma linha de texto na sua string, usando aspas simples (‘) ou duplas (“”), você receberá uma mensagem de erro. Por exemplo, digite a seguinte linha e aperte Enter. Você verá uma mensagem de erro assustadora, parecida com a seguinte:

```
>>> fred = "estas são duas
      File "<stdin>", line 1
          fred = "estas são duas
          ^
SyntaxError: EOL while scanning string literal
```

Nós falaremos sobre errors mais tarde, mas por agora, se você quiser mais de uma linha de texto, você pode usar 3 aspas simples:

```
>>> fred = '''estas são duas  
... linhas de texto em uma única string'''
```

Imprima o conteúdo para ver se funcionou:

```
>>> print(fred)
estas são duas
linhas de texto em uma única string
```

A propósito, você verá esses 3 pontinhos (...) sempre que estiver digitando algo que continue na próxima linha (como as strings de várias linhas). Na verdade, você ainda verá muitos destes conforme continuamos.

2.5 Truques com Strings

Aqui está uma questão interessante: quanto é $10 * 5$ (10 vezes 5)? A resposta é 50, claro.

Ok, essa não é uma questão das mais interessantes.

Mas quanto é $10 * 'a'$ (10 vezes a letra a)? Isso pode parecer uma questão sem sentido, mas aqui está a resposta diretamente do Mundo do Python:

```
>>> print(10 * 'a')
aaaaaaaaaa
```

Isso funciona ainda com mais caracteres:

Outro truque com uma string é embutir valores. Você pode fazer isso usando o sinalizador %s, que será substituído pelo valor que você quer incluir na string. É mais fácil de explicar com um exemplo:

```
>>> meutexto = 'Eu tenho %s anos de idade'  
>>> print(meutexto % 12)  
Eu tenho 12 anos de idade
```

Na primeira linha, a variável ‘meutexto’ foi criada contendo uma string com algumas palavras e o sinalizador (%s). O %s está dizendo “substitua-me com

algo” para o terminal do Python. Então na linha seguinte, quando nós chamamos `print(meutexto)`, nós usamos o símbolo %, que diz ao Python para substituir o sinalizador pelo número 12. Nós podemos reutilizar a string e passar diferentes valores:

```
>>> meutexto = 'Olá %s, como vai você hoje?'
>>> nome1 = 'Joe'
>>> nome2 = 'Jane'
>>> print(meutexto % nome1)
Olá Joe, como vai você hoje?
>>> print(meutexto % nome2)
Olá Jane, como vai você hoje?
```

No exemplo acima, 3 variáveis (`meutexto`, `nome1` e `nome2`) foram criadas — o primeiro inclui a string com o sinalizador. Em seguida nós imprimimos a variável ‘`meutexto`’ e usamos novamente o operador % para passar as variáveis ‘`nome1`’ e ‘`nome2`’. E você pode usar mais de um sinalizador:

```
>>> meutexto = 'Olá %s e %s, como vocês estão hoje?'
>>> print(meutexto % (nome1, nome2))
Olá Joe e Jane, como vocês estão hoje?
```

Quando utilizar mais de um sinalizador, você precisa envolver os valores entre parênteses — então, `(nome1, nome2)` é a forma apropriada de se passar 2 variáveis. Uma série de valores entre parênteses é chamado de *tupla* e é bem parecido com uma lista, que nós abordaremos depois.

2.6 Não é igual a uma lista de compras

Ovos, leite, queijo, salsinha e margarina. Que não é uma lista de compras completa, mas serve para o que precisamos. Se você quiser armazenar isso em uma variável, você pode criar uma string:

```
>>> lista_de_compras = 'ovos, leite, queijo, salsinha, margarina'
>>> print(lista_de_compras)
ovos, leite, queijo, salsinha, margarina
```

Uma outra forma, seria criar uma ‘lista’, que é um tipo de objeto especial em Python:

```
>>> lista_de_compras = ['ovos', 'leite', 'queijo', 'salsinha'
... 'margarina']
>>> print(lista_de_compras)
['ovos', 'leite', 'queijo', 'salsinha', 'margarina']
```

É um pouco mais de digitação, porém mais útil. Nós poderíamos imprimir o terceiro item da lista, usando a sua posição (chamado de índice), usando colchetes []:

```
>>> print(lista_de_compras[2])
queijo
```

Listas iniciam no índice 0 — então o primeiro item da lista é 0, o segundo é 1 e o terceiro é 2. Isso não faz muito sentido para a maioria das pessoas, mas faz para os programadores. Um pouco a frente, quando você subir mais alguns degraus você vai começar a contar a partir do zero, ao invés do um. Isso deve confundir um pouco o seu irmão ou irmã.

Nós podemos exibir todos os itens, do 3º ao 5º da lista, usando o dois pontos dentro do colchetes:

```
>>> print(lista_de_compras[2:5])
['queijo', 'salsinha', 'margarina']
```

[2:5] é o mesmo que dizer que nós estamos interessados nos itens do índice 2 ao 5 (mas não o incluindo). E por começarmos a contar do 0, o 3º item da lista é o número 2 e o 5º item é o número 4. Listas podem ser usadas para armazenar qualquer tipo de item. Elas podem armazenar números:

```
>>> minhalista = [1, 2, 5, 10, 20]
```

E strings:

```
>>> minhalista = ['a', 'bbb', 'ccccccc', 'ddddddddd']
```

E misturar números e strings:

```
>>> minhalista = [1, 2, 'a', 'bbb']
>>> print(minhalista)
[1, 2, 'a', 'bbb']
```

E até listas de listas:

```
>>> lista1 = ['a', 'b', 'c']
>>> lista2 = [1, 2, 3]
>>> minhalista = [lista1, lista2]
>>> print(minhalista)
[['a', 'b', 'c'], [1, 2, 3]]
```

No exemplo acima, uma variável chamada ‘lista’ é criada contendo 3 letras, ‘lista2’ é criada contendo 3 números e ‘minhalista’ é criada contendo a ‘lista1’ e a ‘lista2’. As coisas podem ficar um pouco confusas, rapidamente, se você começar a criar listas de listas de listas... mas felizmente não há muita necessidade de se fazer coisas desse tipo em Python. Ainda assim, é útil para você saber que pode armazenar quaisquer tipos de itens em uma lista em Python.

E não somente a sua lista de compras.

Substituindo itens

Nós podemos substituir um item em uma lista, apenas trocando o seu valor, da mesma forma que é trocado o valor de uma variável. Por exemplo, nós podemos trocar a salsinha por alface, trocando o valor do índice 3:

```
>>> lista_de_compras[3] = 'alface'
>>> print(lista_de_compras)
['ovos', 'leite', 'queijo', 'alface', 'margarina']
```

Adicionando itens...

Nós podemos adicionar itens à uma lista, usando o método ‘append’. Um método é uma ação ou comando que diz ao Python que nós queremos fazer algo. Nós falaremos mais adiante sobre métodos, por agora, para adicionar um item à nossa lista de compras, nós fazemos:

```
>>> lista_de_compras.append('barra de chocolate')
>>> print(lista_de_compras)
['ovos', 'leite', 'queijo', 'alface', 'margarina', 'barra de chocolate']
```

Que certamente torna a lista de compras muito melhor.

...and removing items

We can remove items from a list by using the command ‘del’ (short for delete). For example, to remove the 6th item in the list (baking soda):

```
>>> del shopping_list[5]
>>> print(shopping_list)
['eggs', 'milk', 'cheese', 'lettuce', 'peanut butter', 'chocolate bar']
```

Remember that positions start at zero, so `shopping_list[5]` actually refers to the 6th item.

2 lists are better than 1

We can join lists together by adding them, as if we were adding two numbers:

```
>>> list1 = [ 1, 2, 3 ]
>>> list2 = [ 4, 5, 6 ]
>>> print(list1 + list2)
[1, 2, 3, 4, 5, 6]
```

We can also add the two lists and set the result to another variable:

```
>>> list1 = [ 1, 2, 3 ]
>>> list2 = [ 4, 5, 6 ]
>>> list3 = list1 + list2
>>> print(list3)
[1, 2, 3, 4, 5, 6]
```

And you can multiply a list in the same way we multiplied a string:

```
>>> list1 = [ 1, 2 ]
>>> print(list1 * 5)
[1, 2, 1, 2, 1, 2, 1, 2, 1, 2]
```

In the above example, multiplying `list1` by five is another way of saying “repeat `list1` five times”. However, division (/) and subtraction (-) don’t make sense when working with lists, so you’ll get errors when trying the following examples:

```
>>> list1 / 20
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: unsupported operand type(s) for /: 'list' and 'int'
```

or:

```
>>> list1 - 20
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: unsupported operand type(s) for -: 'list' and 'int'
```

You’ll get a rather nasty error message.

2.7 Tuples and Lists

A tuple (mentioned earlier) is a little bit like a list, but rather than using square brackets, you use round brackets—e.g. ‘(’ and ‘)’. You can use tuples in a similar way to a list:

```
>>> t = (1, 2, 3)
>>> print(t[1])
2
```

The main difference is that, unlike lists, tuples can’t change, once you’ve created them. So if you try to replace a value like we did earlier with the list, you’ll get another error message:

```
>>> t[0] = 4
Traceback (most recent call last):
  File "<stdin>", line 1, in ?
TypeError: 'tuple' object does not support item assignment
```

That doesn’t mean you can’t change the variable containing the tuple to something else. For example, this code will work fine:

```
>>> myvar = (1, 2, 3)
>>> myvar = [ 'a', 'list', 'of', 'strings' ]
```

First we create the variable `myvar` pointing to a tuple of 3 numbers. Then we change `myvar` to point at a list of strings. This might be a bit confusing at first. But think of it like lockers in a school. Each locker has a name tag on it. You put something in the locker, close the door, lock it, then throw away the key. You then peel the name tag off, wander over to another empty locker, and stick something else in that (but this time you keep the key). A tuple is like the locked locker. You can’t change what’s inside it. But you can take the label off and stick it on an unlocked locker, and then put stuff inside that locker and take stuff out—that’s the list.

2.8 Things to try

In this chapter we saw how to calculate simple mathematical equations using the Python console. We also saw how brackets can change the result of an equation, by controlling the order that operators are used. We found out how to tell Python to remember values for later use—using variables—plus how Python uses ‘strings’ for storing text, and lists and tuples, for handling more than one item.

Exercise 1

Make a list of your favourite toys and name it toys. Make a list of your favourite foods and name it foods. Join these two lists and name the result favourites. Finally print the variable favourites.

Exercise 2

If you have 3 boxes containing 25 chocolates, and 10 bags containing 32 sweets, how many sweets and chocolates do you have in total? (Note: you can do this with one equation with the Python console)

Exercise 3

Create variables for your first and last name. Now create a string and use placeholders to add your name.

Capítulo 3

Turtles, and other slow moving creatures

There are certain similarities between turtles in the real world and a Python turtle. In the real world, a turtle is a (sometimes) green reptile that moves around very slowly and carries its house on its back. In the world of Python, a turtle is a small black arrow that moves very slowly around the screen. No mention of house-carrying though.

In fact, considering that a Python turtle leaves a trail as it moves around the screen, this makes it less like a real turtle, and more like a snail or a slug. However, I suppose that a module called ‘slug’ wouldn’t be particularly attractive, so it makes sense to stick with turtles. Just imagine the turtle is carrying a couple of marker pens with it, and drawing as it goes.

In the deep, dark, and distant past, there was a simple programming language called Logo. Logo was used to control a robot turtle (called Irving). Over time, the turtle evolved from a robot that could move around the floor, to a small arrow moving around a screen.

Which just goes to show, things don’t always improve as technology advances—a little robot turtle would be a lot more fun.

Python’s turtle module (we’ll come to modules a bit later, but for now just just think of a module as something we can use inside a program) is a little bit like the Logo programming language, but while Logo was (is) fairly limited, Python has many more capabilities. The turtle module itself, is a useful way to learn how computers draw pictures on your computer screen.

Let’s get started and see just how it works. The first step is to tell Python we want to use turtle, by importing the module:




Figure 3.1: An arrow representing the turtle.

```
>>> import turtle
```

Then we need to display a canvas to draw on. A canvas is just like the material an artist might use for painting; in this case it's a blank space for drawing on:

```
>>> t = turtle.Pen()
```

In this code, we call a special function (`Pen`) on the module `turtle`, which automatically creates a canvas we can draw on. A function is a re-useable piece of code (again we'll come to functions later) that does something useful—in this case, an object which represents the turtle is returned by the `Pen` function—we set that object to the variable '`t`' (in effect we're giving our turtle canvas the name '`t`'). When you type the code into the Python console, you'll see a blank box (the canvas) appear, looking something like figure 3.1.

Yes, that little arrow in the middle of the screen really is the turtle. And, no, it's not very turtle-like.

You can send instructions to the turtle, by using functions on the object that was created (by calling `turtle.Pen`)—since we assigned that object to the variable `t`, we use `t` to send the instructions. One turtle instruction is `forward`. `Forward` tells the turtle to move forward in whatever direction she is facing (I have no idea whether it's a boy or a girl turtle, but let's just assume it's a girl-turtle for the




Figure 3.2: The turtle draws a line.

moment). Let's tell the turtle to move forward 50 pixels (we'll talk about pixels in a minute):

```
>>> t.forward(50)
```

You should see something like figure 3.2.

From the turtle's point-of-view, she has moved forward 50 steps. From our point-of-view, she has moved 50 pixels.

So, what's a pixel?

A pixel is a dot on the screen. When you look at your computer, everything is made up of tiny (square) dots. The programs you use and the games you play on the computer, or with a Playstation, or an Xbox, or a Wii; are all made up of a whole bunch of different coloured dots, arranged on the screen. In fact, if you look at your computer screen with a magnifying glass, you might just be able to make out some of those dots. So if we zoom in on the canvas and the line that was just drawn by the turtle, we can see the arrow representing the turtle, is also just a bunch of square dots, as you can see in figure 3.3.

We'll talk more about these dots, or pixels, in a later chapter.

Next, we can tell the turtle to turn left or right:




Figure 3.3: Zooming in on the line and the arrow.




Figure 3.4: The ‘divisions’ on a clock.

```
>>> t.left(90)
```

This tells the turtle to turn left, 90 degrees. You may not have learned about degrees in school so far, but the easiest way to think about them, is that they are like the divisions on the face of a clock as seen in figure 3.4.

The difference to a clock, is that rather than 12 divisions (or 60, if you’re counting minutes rather than hours), there are 360 divisions. So, if you count 360 divisions around the face of a clock, you get 90 where there’s normally a 3, 180 where there’s normally a 6, and 270 where there’s normally a 9; and 0 would be at the top (at the start), where you normally see a 12. Figure 3.5 shows you the degree divisions.

So, what does it actually mean when you call `left(90)`?

If you stand and face one direction, point your arm out directly away from your shoulder, THAT is 90 degrees. If you point your left arm, that’s 90 degrees left. If you point your right arm, that’s 90 degrees right. When Python’s turtle turns left, she plants her nose in one spot then swivels her body around the face the new direction (same as if you turned your body to face where your arm is pointing).




Figure 3.5: Degrees.

So, `t.left(90)` results in the arrow now pointing upwards, as shown in figure 3.6.

Let's try the same commands again a few times:

```
>>> t.forward(50)
>>> t.left(90)
>>> t.forward(50)
>>> t.left(90)
>>> t.forward(50)
>>> t.left(90)
```

Our turtle has drawn a square and is left facing the same direction as she started (see figure 3.7).

We can erase what's on the canvas by using `clear`:

```
>>> t.clear()
```

Some of the other basic functions you can use with your turtle are: `reset`, which also clears the screen, but puts the turtle automatically back into her starting position; `backward`, which moves the turtle backwards; `right`, which turns the turtle to the right; `up` which tells the turtle to stop drawing as she moves (in other words pick her pen up off the canvas); and finally `down` which tells the turtle to start drawing again. You call these functions in the same way we've used the others:




Figure 3.6: The turtle after turning left.




Figure 3.7: Drawing a square.

```
>>> t.reset()
>>> t.backward(100)
>>> t.right(90)
>>> t.up()
>>> t.down()
```

We'll come back to the turtle module shortly.

3.1 Things to try

In this chapter we saw how to use turtle to draw simple lines, using left and right turns. We saw that turtle uses degrees to turn, a bit like the minute divisions on a clock face.

Exercise 1

Create a canvas using turtle's Pen function, and draw a rectangle.

Exercise 2

Create another canvas using turtles Pen function, and draw a triangle.

Capítulo 4

How to ask a question

In programming terms, a question usually means we want to do either one thing, or another, depending upon the answer to the question. This is called an **if-statement**. For example:

How old are you? If you're older than 20, you're too old!

This might be written in Python as the following if-statement:

```
if age > 20:  
    print('you are too old!')
```

An if-statement is made up of an ‘if’ followed by what is called a ‘condition’ (more on that in a second), followed by a colon (:). The lines following the if must be in a block—and if the answer to the question is ‘yes’ (or True, as we call it in programming terms) the commands in the block will be run.

A condition is a programming statement that returns ‘yes’ (True) or ‘no’ (False). There are certain symbols (or operators) used to create conditions, such as:

==	equals
!=	not equals
>	greater than
<	less than
>=	greater than or equal to
<=	less than or equal to

For example, if you are 10 years old, then the condition `your_age == 10` would return True (yes), but if you are not 10, it would return False. Remember: don’t

mix up the **two** equals symbols used in a condition (`==`), with the equals used in assigning values (`=`)—if you use a single `=` symbol in a *condition*, you’ll get an error message.

Assuming you set the variable `age` to your age, then if you are 12 years old, the condition . . .

```
age > 10
```

. . . would again return True. If you are 8 years old, it would return False. If you are 10 years old, it would also return False—because the condition is checking for greater than (`>`) 10, and not greater than or equal (`>=`) to 10.

Let’s try a few examples:

```
>>> age = 10
>>> if age > 10:
...     print('got here')
```

If you enter the above example into the console, what might happen?

Nothing.

Because the value of the variable `age` is not greater than 10, the `print` command in the block will not be run. How about:

```
>>> age = 10
>>> if age >= 10:
...     print('got here')
```

If you try this example, then you should see the message `got here` printed to the console. The same will happen for the next example:

```
>>> age = 10
>>> if age == 10:
...     print('got here')
got here
```

4.1 Do this. . . or ELSE!!!

We can also extend an if-statement, so that it does something when a condition is not true. For example, print the word ‘Hello’ out to the console if your age is 12, but print ‘Goodbye’ if it’s not. To do this, we use an if-then-else-statement (this is another way of saying “*if something is true, then do this, otherwise do that*”):

```
>>> age = 12
>>> if age == 12:
...     print('Hello')
... else:
...     print('Goodbye')
Hello
```

Type in the above example and you should see ‘Hello’ printed to the console. Change the value of the variable age to another number, and ‘Goodbye’ will be printed:

```
>>> age = 8
>>> if age == 12:
...     print('Hello')
... else:
...     print('Goodbye')

Goodbye
```

4.2 Do this... or do this... or do this... or ELSE!!!

We can extend an if-statement even further using elif (short for else-if). For example, we can check if your age is 10, or if it’s 11, or if it’s 12 and so on:

```
1. >>> age = 12
2. >>> if age == 10:
3. ...     print('you are 10')
4. ... elif age == 11:
5. ...     print('you are 11')
6. ... elif age == 12:
7. ...     print('you are 12')
8. ... elif age == 13:
9. ...     print('you are 13')
10. ... else:
11. ...     print('huh?')
12. ...
13. you are 12
```

In the code above, line 2 checks whether the value of the age variable is equal to 10. It’s not, so it then jumps to line 4 to check whether the value of the age variable is equal to 11. Again, it’s not, so it jumps to line 6 to check whether the variable is equal to 12. In this case it is, so Python moves to the block in line 7, and runs the print command. (Hopefully you’ve also noticed that there are 5 groups in this code—lines 3, 5, 7, 9 and line 11)

4.3 Combining conditions

You can combine conditions together using the keywords ‘and’ and ‘or’. We can shrink the example above, a little, by using ‘or’ to join the conditions together:

```
1. >>> if age == 10 or age == 11 or age == 12 or age == 13:
2. ....     print('you are %s' % age)
3. .... else:
4. ....     print('huh?')
```

If any of the conditions in line 1 are true (i.e. if age is 10 **or** age is 11 **or** age is 12 **or** age is 13), then the block of code in line 2 is run, otherwise Python moves to line 4. We could shrink the example a little bit more by using the ‘and’, \geq and \leq symbols:

```
1. >>> if age >= 10 and age <= 13:
2. ....     print('you are %s' % age)
3. .... else:
4. ....     print('huh?')
```

Hopefully, you’ve figured out that if **both** the conditions on line 1 are true then the block of code in line 2 is run (if age is greater than or equal to 10 **and** age is less than or equal to 13). So if the value of the variable age is 12, then ‘you are 12’ would be printed to the console: because 12 is greater than 10 and it is also less than 13.

4.4 Emptiness

There is another sort of value, that can be assigned to a variable, that we didn’t talk about in the previous chapter: **Nothing**.

In the same way that numbers, strings and lists are all values that can be assigned to a variable, ‘nothing’ is also a kind of value that can be assigned. In Python, an empty value is referred to as `None` (in other programming languages, it is sometimes called `null`) and you can use it in the same way as other values:

```
>>> myval = None
>>> print(myval)
None
```

`None` is a way to reset a variable back to being un-used, or can be a way to create a variable without setting its value before it is used.

For example, if your football team were raising funds for new uniforms, and you were adding up how much money had been raised, you might want to wait until all the team had returned with the money before you started adding it all up. In programming terms, we might have a variable for each member of the team, and then set all the variables to None:

```
>>> player1 = None
>>> player2 = None
>>> player3 = None
```

We could then use an if-statement, to check these variables, to determine if all the members of the team had returned with the money they'd raised:

```
>>> if player1 is None or player2 is None or player3 is None:
...     print('Please wait until all players have returned')
... else:
...     print('You have raised %s' % (player1 + player2 + player3))
```

The if-statement checks whether any of the variables have a value of None, and prints the first message if they do. If each variable has a real value, then the second message is printed with the total money raised. If you try this code out with all variables set to None, you'll see the first message (don't forget to create the variables first or you'll get an error message):

```
>>> if player1 is None or player2 is None or player3 is None:
...     print('Please wait until all players have returned')
... else:
...     print('You have raised %s' % (player1 + player2 + player3))
Please wait until all players have returned
```

Even if we set one or two of the variables, we'll still get the message:

```
>>> player1 = 100
>>> player3 = 300
>>> if player1 is None or player2 is None or player3 is None:
...     print('Please wait until all players have returned')
... else:
...     print('You have raised %s' % (player1 + player2 + player3))
Please wait until all players have returned
```

Finally, once all variables are set, you'll see the message in the second block:

```
>>> player1 = 100
>>> player3 = 300
>>> player2 = 500
>>> if player1 is None or player2 is None or player3 is None:
...     print('Please wait until all players have returned')
... else:
...     print('You have raised %s' % (player1 + player2 + player3))
You have raised 900
```

4.5 What's the difference...?

What's the difference between 10 and '10'?

Not much apart from the quotes, you might be thinking. Well, from reading the earlier chapters, you know that the first is a number and the second is a string. This makes them differ more than you might expect. Earlier we compared the value of a variable (age) to a number in an if-statement:

```
>>> if age == 10:
...     print('you are 10')
```

If you set variable age to 10, the print statement will be called:

```
>>> age = 10
>>> if age == 10:
...     print('you are 10')
...
you are 10
```

However, if age is set to '10' (note the quotes), then it won't:

```
>>> age = '10'
>>> if age == 10:
...     print('you are 10')
...
```

Why is the code in the block not run? Because a string is different from a number, even if they look the same:

```
>>> age1 = 10
>>> age2 = '10'
>>> print(age1)
10
>>> print(age2)
10
```

See! They look exactly the same. Yet, because one is a string, and the other is a number, they are different values. Therefore `age == 10` (age equals 10) will never be true, if the value of the variable is a string.

Probably the best way to think about it, is to consider 10 books and 10 bricks. The number of items might be the same, but you couldn't say that 10 books are exactly the same as 10 bricks, could you? Luckily in Python we have magic functions which can turn strings into numbers and numbers into strings (even if they won't quite turn bricks into books). For example, to convert the string '10' into a number you would use the function `int`:

```
>>> age = '10'
>>> converted_age = int(age)
```

The variable `converted_age` now holds the number 10, and not a string. To convert a number into a string, you would use the function `str`:

```
>>> age = 10
>>> converted_age = str(age)
```

`converted_age` now holds the string 10, and not a number. Back to that if-statement which prints nothing:

```
>>> age = '10'
>>> if age == 10:
...     print('you are 10')
...
```

If we convert the variable *before* we check, then we'll get a different result:

```
>>> age = '10'
>>> converted_age = int(age)
>>> if converted_age == 10:
...     print('you are 10')
...
you are 10
```


Capítulo 5

Again and again

There's nothing worse than having to do the same thing over and over and over again. There's a reason your parents tell you to count sheep to try to go to sleep, and it has got nothing to do with the amazing sleep-inducing powers of woolly mammals. It's all to do with the fact that endlessly repeating something is boring, and your mind should drop off to sleep more easily, if it's not focussing on something interesting.

Programmers don't particularly like repeating themselves either. It puts them to sleep as well. Which is a good reason why all programming languages have what is called a **for-loop**. For example, to print hello 5 times in Python, you *could* do the following:

```
>>> print("hello")
hello
```

Which is... rather tedious.

Or you could use a for-loop (note: there's 4 spaces on the second line before the print statement—I've highlighted them using @ so that you can see where they are):

```
>>> for x in range(0, 5):
...     @@@@print('hello')
...
hello
hello
hello
hello
hello
```

range is a function and is a quick and easy way to create a list of numbers ranging between a start and end number. For example:

```
>>> print(list(range(10, 20)))
[10, 11, 12, 13, 14, 15, 16, 17, 18, 19]
```

So in the case of the for-loop, what the code ‘for x in range(0, 5)’ is actually telling Python, is to create a list of numbers (0, 1, 2, 3, 4) and then for each number, store the value in the variable x. We can then use the x in our print statement if we want to:

```
>>> for x in range(0, 5):
...     print('hello %s' % x)
hello 0
hello 1
hello 2
hello 3
hello 4
```

If we get rid of the for-loop again, it might look something like this:

```
x = 0
print('hello %s' % x)
x = 1
print('hello %s' % x)
x = 2
print('hello %s' % x)
x = 3
print('hello %s' % x)
x = 4
print('hello %s' % x)
```

So the loop has actually saved us from writing an extra 8 lines of code. This is extremely useful, since the average programmer is more lazy than a hippopotamus on a hot day, when it comes to typing. Good programmers hate doing things more

than once, so the for-loop is one of the more useful statements in a programming language.

WARNING!!!

If you've been trying out the examples as you go along, you might have got a funny error message when typing in the code for that for-loop. If you did, it might have looked something like this:

```
IndentationError: expected an indented block
```

If you see an error like this, then you missed typing the spaces on the second line. Spaces in Python (either a normal space or a tab) are extremely important. We'll talk more about this shortly...

We don't have to stick to using range, we can also use lists we've already created. Such as the shopping list we created in the last chapter:

```
>>> shopping_list = [ 'eggs', 'milk', 'cheese', 'celery', 'peanut butter',
... 'baking soda' ]
>>> for i in shopping_list:
...     print(i)
eggs
milk
cheese
celery
peanut butter
baking soda
```

The above code is a way of saying, "for each item in the list, store the value in the variable 'i' and then print the contents of that variable". Again, if we got rid of the for-loop, we'd have to do something like this:

```
>>> shopping_list = [ 'eggs', 'milk', 'cheese', 'celery', 'peanut butter',
... 'baking soda' ]
>>> print(shopping_list[0])
eggs
>>> print(shopping_list[1])
milk
>>> print(shopping_list[2])
cheese
>>> print(shopping_list[3])
celery
>>> print(shopping_list[4])
peanut butter
>>> print(shopping_list[5])
baking soda
```

So once again, the loop has saved us from a lot of typing.

5.1 When is a block not square?

When it's a block of code.

So what's a 'block of code' then?

A block of code is a set of programming statements you want to group together. For example, in the for-loop example above, you might want to do more than just print out the items. Perhaps you'd want to buy each item and then print out what it was. Supposing we had a function called 'buy', you might write code like this:

```
>>> for i in shopping_list:
...     buy(i)
...     print(i)
```

Don't bother typing that example into the Python console—because we don't have a buy function and you'll get an error message if you do try to run it—but it does demonstrate a simple Python block made up of 2 commands:

```
buy(i)
print(i)
```

In Python, white space such as tab (when you press the tab key) and space (when you press the space bar) is *very* important. Code that is at the same position is grouped together into blocks.

```

this would be block 1
this would be block 1
this would be block 1
    this would be block 2
        this would be block 2
            this would be block 2
this would still be block 1
this would still be block 1
    this would be block 3
        this would be block 3
            this would be block 4
                this would be block 4
                    this would be block 4

```

But you must be consistent with your spacing. For example:

```

>>> for i in shopping_list:
...     buy(i)
...     print(i)

```

The second line (function `buy(i)`) starts with **4** spaces. The third line (`print(i)`) starts with **6** spaces. Let's take another look at that code with visible spaces (using @ again):

```

>>> for i in shopping_list:
... @@@@buy(i)
... @@@@@@print(i)

```

This would cause an error. Once you start using 4 spaces, you need to continue using 4 spaces. And if you want to put a block *inside* another block, you'll need 8 spaces (2×4) at the beginning of the lines for that inner block.

So the first block has 4 spaces (I'll highlight them again so you can see them):

```

@@@here's my first block
@@@here's my first block

```

And then the second block (which is ‘inside’ the first) needs 8 spaces:

```

@@@here's my first block
@@@here's my first block
@@@@@@here's my second block
@@@@@@here's my second block

```

Why do we want to put one block ‘inside’ another? Usually we do this when the second block relies on the first in some way. Such as our for-loop. If the line

with the for-loop is the first block, then the statements we want to run over and over again are in the second block—in a way they rely on the first block to work properly.

In the Python console, once you start typing code in a block, Python continues that block until you press the Enter key on a blank line (you’ll see the 3 dots at the beginning of the line showing that you’re still inside a block).

Let’s try some real examples. Open the console and type the following (remember that you need to press the space bar 4 times at the beginning of the print lines):

```
>>> mylist = [ 'a', 'b', 'c' ]
>>> for i in mylist:
...     print(i)
...     print(i)
...
a
a
b
b
c
c
```

After the second print, press the Enter key on the blank line—which tells the console you want to end the block. It will then print each item in the list twice.

The next example will cause an error message to be displayed:

```
>>> mylist = [ 'a', 'b', 'c' ]
>>> for i in mylist:
...     print(i)
...     print(i)
...
File <stdin>, line 3
    print(i)
    ^
IndentationError: unexpected indent
```

The second print line has 6 spaces, not 4, which Python doesn’t like because it wants spacing to stay the same.

REMEMBER

If you start your blocks of code with 4 spaces you must continue using 4 spaces. If you start blocks with 2 spaces, you must continue with 2 spaces. Stick to 4 spaces, because that's what most people use.

Here's a more complicated example with 2 blocks of code:

```
>>> mylist = [ 'a', 'b', 'c' ]
>>> for i in mylist:
...     print(i)
...     for j in mylist:
...         print(j)
...
```

Where are the blocks in this code and what is it going to do...?

There are **two** blocks—number one is part of the first for-loop:

```
>>> mylist = [ 'a', 'b', 'c' ]
>>> for i in mylist:
...     print(i)                      #
...     for j in mylist:              #-- these lines are the FIRST block
...         print(j)                  #
...
```

Block number two is the single print line in the second for-loop:

```
>>> mylist = [ 'a', 'b', 'c' ]
>>> for i in mylist:
...     print(i)
...     for j in mylist:
...         print(j)                  # this line is the SECOND block
...
```

Can you figure out what this little bit of code is going to do?

It's going to print out the 3 letters from 'mylist', but how many times? If we look at each line, we can probably figure out the number. We know that the first loop statement will go through each of the items in the list, and then run the commands in block number 1. So it will print out a letter, then start the next loop. This loop will also go through each of the items in the list and then run the command in block number 2. So what we should get when this code runs, is 'a' followed by 'a', 'b', 'c', then 'b' followed by 'a', 'b', 'c' and so on. Enter the code into the Python console and see for yourself:

```
>>> mylist = [ 'a', 'b', 'c' ]
>>> for i in mylist:
...     print(i)
...     for j in mylist:
...         print(j)
...
a
a
b
c
b
a
b
c
c
a
b
c
```

How about something more useful than just printing letters? Remember that calculation we came up with at the beginning of this book to work out how much you might have saved at the end of the year, if you earned \$5 doing chores, \$30 doing a paper route and spent \$10 a week?

It looked like this:

```
>>> (5 + 30 - 10) * 52
```

(That's $\$5 + \$30 - \$10$ multiplied by 52 weeks in the year).

It might be useful to see how much your savings are increasing during the year, rather than working out what they will be at the very end. We can do this with another for-loop. But first of all, we need to load those numbers into variables:

```
>>> chores = 5
>>> paper = 30
>>> spending = 10
```

We can perform the original calculation using the variables:

```
>>> (chores + paper - spending) * 52
1300
```

Or we can see the savings increase over the year, by creating another variable called `savings`, and then using a loop:

```

1. >>> savings = 0
2. >>> for week in range(1, 53):
3. ...     savings = savings + chores + paper - spending
4. ...     print('Week %s = %s' % (week, savings))
5. ...

```

On line 1 the variable ‘savings’ is loaded with 0 (because we haven’t saved anything yet).

Line 2 sets up the for-loop, which will run the commands in the block (the block is made up of lines 3 and 4). Each time it loops, the variable week is loaded with the next number in the range 1-52.

Line 3 is a bit more complicated. Basically, each week we want to add what we’ve saved to our total savings. Think of the variable ‘savings’ as something like a bank. We add up the money we earn doing odd jobs and the paper route, subtract our spending money and then take the rest to the bank. So in computer-speak, line 3 really means, “replace the contents of the variable savings with my current savings, plus what I’ve earned this week”. Basically, the equals symbol (=) is a bossy piece of code that is a way of saying, “work out some stuff on the right first and then save it for later, using the name on the left”.

Line 4 is a slightly more complicated print statement, which prints the week number and the total amount saved (for that week) to the screen. Check the section *Tricks with Strings* on page 18, if this line doesn’t make a lot of sense to you. So, if you run this program, you’ll see something like the following...

```

Week 1 = 25
Week 2 = 50
Week 3 = 75
Week 4 = 100
Week 5 = 125
Week 6 = 150
Week 7 = 175
Week 8 = 200
Week 9 = 225
Week 10 = 250
Week 11 = 275
Week 12 = 300
Week 13 = 325
Week 14 = 350
Week 15 = 375

```

...going all the way up to week 52.

5.2 While we're talking about looping...

A for-loop isn't the only kind of looping you can do in Python. There's also the while-loop. If a for-loop is a loop where you know exactly when you'll stop running, a while-loop is a loop where you don't necessarily know ahead of time when you'll stop. Imagine a staircase with 20 steps. You know you can easily climb 20 steps. That's a for-loop.

```
>>> for step in range(0,20):
...     print(step)
```

Now imagine a staircase going up a mountainside. You might run out of energy before you reach the top. Or the weather might turn bad forcing you to stop climbing. This is a while-loop.

```
>>> step = 0
>>> while step < 10000:
...     print(step)
...     if tired == True:
...         break
...     elif badweather == True:
...         break
...     else:
...         step = step + 1
```

Don't bother running the code sample above, because we haven't bothered to create the variables `tired` and `badweather`. But it demonstrates the basics of a while-loop. *While* the value of variable `step` is less than 10000 (`step < 10000`) the code in the block is executed. In the block, we print the value of `step`, then check whether `tired` or `badweather` is true. If `tired` is true, then the `break` statement stops the code in the loop executing (basically we jump out of the loop to the next line of code immediately following the block). If `badweather` is true, we also break out of the loop. If not, then **1** is added to the value of `step`, and the condition of the while loop (`step < 10000`) is checked again.

So the steps of a while loop are basically:

- ▷ check the condition,
- ▷ execute the code in the block,
- ▷ repeat

More commonly, a while-loop might be created with a couple of conditions:

```
>>> x = 45
>>> y = 80
>>> while x < 50 and y < 100:
...     x = x + 1
...     y = y + 1
...     print(x, y)
```

In this loop, we create a variable `x` with the value 45, and a variable `y` with the value 80. There are two conditions that are checked by the loop: whether `x` is less than 50 and whether `y` is less than 100. While both conditions are true, the block of code is executed, adding 1 to both variables and then printing them. The output of this code is just:

```
46 81
47 82
48 83
49 84
50 85
```

Maybe you can figure out why these numbers are printed?¹

Another common usage of a while-loop, is to create a semi-eternal loop. This is a loop that basically goes forever, or at least until something happens in the code to break out of it. For example:

```
>>> while True:
...     lots of code here
...     lots of code here
...     lots of code here
...     if some_condition == True:
...         break
```

The condition for the while loop is just ‘True’. So it will always run the code in the block (thus the loop is eternal or infinite). Only if the variable `some_condition` is true will the code break out of the loop. You can see a better example of this in Appendix C (the section about the random module), but you might want to wait until you’ve read the next chapter before taking a look at it.

¹We start counting at 45 in the variable `x` and at 80 in the variable `y`, and then increment (add one) to each variable every time the code in the loop is run. The conditions check that `x` must be less than 50 and `y` must be less than 100. After looping five times (adding 1 to each variable) the value in `x` reaches 50. Now the first condition (`x < 50`) is no longer true, so Python knows to stop looping.

5.3 Things to try

In this chapter we saw how to use loops to perform repetitive tasks. We used blocks of code inside the loops for the tasks to be repeated.

Exercise 1

What do you think will happen with the following code?

```
>>> for x in range(0, 20):
...     print('hello %s' % x)
...     if x < 9:
...         break
```

Exercise 2


When you save money in a bank, you earn interest. ‘Interest’ is the money the bank pays you for letting them use your money—each year you are paid a small amount of money depending upon how much you’ve saved. This payment is usually added back to your savings account at the bank, and it also makes you money... which is a bit confusing, so you might have to ask Mum or Dad to explain. Interest is calculated using percentages. If you don’t know what a percentage is, don’t worry, it’s enough to know that if the bank is paying you 1% (1 percent) interest, you can multiply the monetary amount by the number 0.01 (if your amount is \$1000, then you will do: $1000 * 0.01$). If they’re paying you 2% interest, you can use the number 0.02, and so on. If you have \$100 saved in a bank account, and they pay you 3% interest every year, how much money do you think you will have each year, up to 10 years? You can write a program using a for-loop to figure it out (Hint: remember to add the interest to the total).

Capítulo 6

Sort of like recycling...

Think about how much rubbish you create each day. Bottled water or bottles of soft drink, packets of crisps, plastic sandwich wrappers, bags of vegetables, meat on plastic trays, plastic shopping bags, newspapers, magazines, and so on and so on and so on...

Now just think about what would happen if all of that trash just got dumped in a pile at the end of your driveway.



Of course, you probably recycle as much as possible. Which is fortunate, because no one likes having to climb over a rubbish heap, on the way to school. So, those glass bottles in the recycle bin are hopefully melted down, and then turned into new jars and bottles; paper is pulped into recycled paper; plastic turned into heavier plastic goods—so your front lawn doesn’t disappear under tonnes of garbage. We get to reuse some of the goods we create, rather than eating a gaping hole in the side of the world to manufacture the same things over and over again.

Recycling or reuse, in the programming world, is just as important. Not because your program will disappear under a pile of garbage—but if you don’t re-use some of what you’re doing, you’ll eventually wear your fingers down to painful stubs through over-typing.

There are a number of different ways to reuse code in Python (and in programming languages in general), but we’ve seen one of the ways already, back in Chapter 3, with the function range. Functions are one way to reuse code—so you can write the code once, then use it in your programs again and again. Let’s first try a simple example of a function:

```
>>> def myfunction(myname):
...     print('hello %s' % myname)
...
```

The above function has a name ‘myfunction’ and has a parameter ‘myname’. A *parameter* is a variable which is only available within the ‘body’ of the function (which is the block of code immediately after the line starting with `def`—in case you’re wondering, `def` is short for `define`). You can run the function by calling its name with brackets surrounding the parameter value:

```
>>> myfunction('Mary')
hello Mary
```

We could change the function to take 2 parameters:

```
>>> def myfunction(firstname, lastname):
...     print('Hello %s %s' % (firstname, lastname))
...
```

And then call it in a similar fashion to the first:

```
>>> myfunction('Mary', 'Smith')
Hello Mary Smith
```

Or we could create some variables and call the function with the variables:

```
>>> fn = 'Joe'
>>> ln = 'Robertson'
>>> myfunction(fn, ln)
Hello Joe Robertson
```

We can return values from a function using the return statement:

```
>>> def savings(chores, paper, spending):
...     return chores + paper - spending
...
>>> print(savings(10, 10, 5))
15
```

This function takes 3 parameters, and then adds the first two (chores and paper) before subtracting the last one (spending). The result is then returned—this result can be used as the value of a variable (the same way we set other values to variables):

```
>>> my_savings = savings(20, 10, 5)
>>> print(my_savings)
25
```

However, a variable that we use inside the body of a function will not be accessible (usable), when the function has finished:

```
>>> def variable_test():
...     a = 10
...     b = 20
...     return a * b
...
>>> print(variable_test())
200
>>> print(a)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'a' is not defined
```

In the above example we create a function variable_test, which multiplies two variables (a and b) and returns the result. If we call this function using print, we get the answer: 200. However if we try to print the contents of a (or b for that matter), we get the error message ““a’ is not defined”. This is something called ‘scope’, in the world of programming.

Think of a function as a little island floating in the ocean—and it’s too far to swim from the island to anywhere else. Occasionally, a plane flies over and drops

bits of paper on the island (those are parameters coming into a function) which the inhabitants then stick together into a message, put the message into a bottle and then toss the bottle into the sea (this is the return value). What the islanders do on the island, and how many of them it took to make the message, makes no difference to the person picking up the bottle and reading the message inside. This is probably the easiest way to think about scope—but there is one small problem with that idea. One of the islanders has a large pair of binoculars and can see all the way to the mainland. He can see what other people are doing there, and that can affect the message that they’re creating:

```
>>> x = 100
>>> def variable_test2():
...     a = 10
...     b = 20
...     return a * b * x
...
>>> print(variable_test2())
20000
```

So, even though variables `a` and `b` aren’t able to be used outside of the function, the variable `x` (which was created outside the function) is usable inside. Just think about the islander with the binoculars, and hopefully it might help that idea to make a little bit of sense.



The for-loop we created earlier to display savings over a year, could easily be added to a function:

```
>>> def yearly_savings(chores, paper, spending):
...     savings = 0
...     for week in range(1, 53):
...         savings = savings + chores + paper - spending
...         print('Week %s = %s' % (week, savings))
...
```

Try entering that function in the console, and call it with different values for chores, paper and spending:

```
>>> yearly_savings(10, 10, 5)
Week 1 = 15
Week 2 = 30
Week 3 = 45
Week 4 = 60
Week 5 = 75
Week 6 = 90
Week 7 = 105
Week 8 = 120
Week 9 = 135
Week 10 = 150
```

(continues on...)

```
>>> yearly_savings(25, 15, 10)
Week 1 = 30
Week 2 = 60
Week 3 = 90
Week 4 = 120
Week 5 = 150
```

(continues on...)

This is a bit more useful than re-typing the for-loop every time you want to try it with a different value. Functions can also be grouped together into something called ‘modules’, which is where Python becomes really useful... as opposed to just mildly useful.

More about modules shortly.

6.1 Bits and Pieces

When Python is installed on your computer, a whole pile of functions and modules are also installed. Some functions are available by default. `range` is a function we’ve already seen. `file` is another function we haven’t use yet.




Figure 6.1: The save dialog from Mac OS X Text Editor.

To see how file is used, open up the Text Editor, by clicking on the editor icon . Type a few words then save the file to the Desktop by clicking File, then Save, and entering the name ‘text.txt’ in the entry box next to ‘Save As’.

Open the Python console again, and try the following:

```
>>> f = open('Desktop/test.txt')
>>> print(f.read())
```

The contents of the file you just created should be printed to the console. You can now jump ahead to the bit that says: “Continuing from here...”.

So what does that little bit of code do? The first line calls the function `open`, passing the name of the file you just created, as a parameter. The function returns a special type of value (called an object) which represents that file. It’s not the file itself; rather it’s a bit like a big finger pointing at the file going “HERE IT IS!!!!” The file object is stored in the variable `f`.

The next line calls a special function (`read`) on the file object, to read in the contents of the file, and print the result to the console. Because the variable `f` contains an object, this means we need to call the `read` function using the dot symbol `(.)`.

Appendix B (at the back of this book) has more information about the functions that are built into Python.

6.2 Modules

We've actually seen a couple of different ways to reuse code already. One is a standard function, which we can create ourselves, or use the functions built into Python (like range and file and int and str). Another is a special kind of function on objects—which we can call using the dot symbol—and the next are modules; which are a way of grouping lots of functions and objects together in useful ways. An example of this is the module ‘time’:

```
>>> import time
```

The import command is used to tell Python we want to access a module. In the above example, we’re saying we want to use the ‘time’ module. We can then call functions and objects that are available in this module, using the dot symbol yet again:

```
>>> print(time.localtime())
(2006, 11, 10, 23, 49, 1, 4, 314, 1)
```

localtime is a function *inside* the module time, that returns the current date and time, broken up into individual parts—year, month, day, hour, minute, second, day of the week, day of the year, and whether or not it’s daylight savings (1 if it is, 0 if it isn’t). The individual parts are stored in a tuple (see *Tuples and Lists* on page 23). You can use another function in the time module to convert the datetime returned by localtime, into something a bit more understandable:

```
>>> t = time.localtime()
>>> print(time.asctime(t))
Sat Nov 18 22:37:15 2006
```

We can do that all in a single line if we wanted to:

```
>>> print(time.asctime(time.localtime()))
Sat Nov 18 22:37:15 2006
```

Suppose you want to ask for someone to enter a value. You can do this using a print statement and the module ‘sys’—imported the same way we imported the time module:

```
import sys
```

Inside the `sys` module is an object called ‘`stdin`’ (short for standard input). `stdin` has a rather useful method (or function) called `readline`—which is used to read a line of text someone types on the keyboard (up until the point when they press the Enter key). You can test `readline`, by entering the following command in the Python console:

```
>>> print(sys.stdin.readline())
```

If you then type some words, and press the Enter key, what you’ve typed will be printed to the console. Think back, for a moment, to the code we wrote earlier, using an if-statement:

```
if age >= 10 and age <= 13:
    print('you are %s' % age)
else:
    print('huh?')
```

Rather than creating the variable `age` beforehand, we can now ask someone to enter the value instead. How about first turning the code into a function...

```
>>> def your_age(age):
...     if age >= 10 and age <= 13:
...         print('you are %s' % age)
...     else:
...         print('huh?')
... 
```

Which can be called, by passing a number as the parameter value. We’ll test that it works properly, first:

```
>>> your_age(9)
huh?
>>> your_age(10)
you are 10
```

Now we know there are no problems with our function, we can change the function to ask for a person’s age instead:

```
>>> def your_age():
...     print('Please enter your age')
...     age = int(sys.stdin.readline())
...     if age >= 10 and age <= 13:
...         print('you are %s' % age)
...     else:
...         print('huh?')
...
```

Because readline() returns what a person typed as text (in other words, a string), we need to use the function int to convert it to a number (this so it will work correctly in the if-statement—check *What's the difference* on page 38 for more information about this). To try it for yourself, call the your_age function without any parameters, then type some text when ‘Please enter your age’ appears:

```
>>> your_age()
Please enter your age
10
you are 10
>>> your_age()
Please enter your age
15
huh?
```

The important thing to note here is that even though you’re typing in a number (in the above case 10 or 15), readline always returns a string.

sys and time are just two of the many modules that are included with Python. For more information on some (but not all) Python modules, see Appendix C.

6.3 Things to try

In this chapter we saw how to do recycling in Python; through the use of functions and modules. We saw a little bit about the ‘scope’ of variable, how variables outside of functions can be ‘seen’ inside, whereas variables inside cannot be seen outside, and learned how to create our own functions using def

Exercise 1

In exercise 2 in Chapter 5, we created a for-loop to work out the interest we might earn from \$100 over a period of 10 years. That for-loop could easily be turned into

a function. Try creating a function which takes a starting amount, and a rate of interest. You could call the function using code like:

```
calculate_interest(100, 0.03)
```

Exercise 2

Take the function you've just created, and make it calculate interest for different periods—such as 5 years or 15 years. Perhaps you could call it using code like:

```
calculate_interest(100, 0.03, 5)
```

Exercise 3

Perhaps rather than a simple function, where we pass in the values as parameters, we can make a mini-program which asks someone for the values (using the `sys.stdin.readline()` function). In this case, we'll call the function without any parameters at all:

```
calculate_interest()
```

To create this mini-program requires a function that we haven't talked about yet: `float`. The `float` function is a bit like the `int` function, except it converts strings into what is called floating point numbers (which we discussed briefly in Chapter 2). Floating point numbers are numbers with a decimal place (.), such as 20.3 or 2541.933.

Capítulo 7

A short chapter about Files

You probably know what a file is already.

If your parents have a home office, chances are they've got a file cabinet of some sort. Various important papers (mostly boring adult stuff) are stored in those cabinets, usually in cardboard folders labelled with letters of the alphabet, or months of the year. Files on a computer are rather similar to those cardboard folders. They have labels (the name of the file), and are used to store important information. The drawers on a file cabinet, which might be used to organise paperwork so they are easier to find, are similar to directories (or folders) on a computer.

We've already created a file object, using Python, in the previous chapter. The example looked like this:

```
>>> f = open('Desktop/test.txt')
>>> print(f.read())
```

A file object doesn't just have the function `read`. After all, file cabinets wouldn't be very useful if you could only open a drawer and take papers out, but could never put them back in. We can create a new, empty file, by passing another parameter when we call the `file` function:

```
>>> f = open('myfile.txt', 'w')
```

`'w'` is the way we tell Python we want to write to the file object, and not read from it. We can now add information to the file using the function `write`.

```
>>> f = open('myfile.txt', 'w')
>>> f.write('this is a test file')
```

Then we need to tell Python when we're finished with the file, and don't want to write to it any more—we use the function `close` to do this.

```
>>> f = open('myfile.txt', 'w')
>>> f.write('this is a test file')
>>> f.close()
```

If you open the file using your favourite editor, you will see it contains the text: “this is a test file”. Or better yet, we can use Python to read it in again:

```
>>> f = open('myfile.txt')
>>> print(f.read())
this is a test file
```

Capítulo 8

Turtles galore

Let's get back to the turtle module we started looking at in Chapter 3. Remember that to setup the canvas for the turtle to draw on, we need to import the module and the create the 'Pen' object:

```
>>> import turtle  
>>> t = turtle.Pen()
```

We can now use basic functions to move the turtle around the canvas and draw simple shapes, but it's more interesting to use some of what we've already covered in the previous chapters. For example, the code we used to create a square earlier was:

```
>>> t.forward(50)  
>>> t.left(90)  
>>> t.forward(50)  
>>> t.left(90)  
>>> t.forward(50)  
>>> t.left(90)
```

We can rewrite this using a for-loop:

```
>>> t.reset()  
>>> for x in range(1,5):  
...     t.forward(50)  
...     t.left(90)  
...
```

This is certainly less typing, but for something a bit more interesting, try the following:




Figure 8.1: The turtle drawing an 8-point star.

```
>>> t.reset()
>>> for x in range(1,9):
...     t.forward(100)
...     t.left(225)
...
...
```

This code produces the 8-point star shown in figure 8.1 (the turtle turns 225 degrees, each time it goes forward 100 pixels).

With a different angle (175 degrees), and a longer loop (37 times), we can make a star with even more points (shown in figure 8.2):

```
>>> t.reset()
>>> for x in range(1,38):
...     t.forward(100)
...     t.left(175)
...
...
```

Or how about the following code, which produces the spiral-like star figure 8.3.

```
>>> for x in range(1,20):
...     t.forward(100)
...     t.left(95)
...
...
```




Figure 8.2: A star with a lot more points.




Figure 8.3: A star with a lot more points.




Figure 8.4: A 9-point star.

Here's something a bit more complicated:

```
>>> t.reset()
>>> for x in range(1,19):
...     t.forward(100)
...     if x % 2 == 0:
...         t.left(175)
...     else:
...         t.left(225)
...
...
```

In the above code, we check to see if the variable x contains an even number. To do this we use what is called a modulo operator ($\%$), in the expression: $x \% 2 == 0$.

$x \% 2$ is equal to zero, if the number in variable x can be divided by two, with nothing left over (no remainder)—if this doesn't make much sense, don't worry too much about it, just remember you can use ' $x \% 2 == 0$ ' to check if a number in a variable is an even number. The result of running this code is the 9-point star in figure 8.4.

You don't have to just draw stars and simple geometric shapes, using a combination of the functions calls, your turtle can draw many different things. For example:

```
t.color(1,0,0)
t.begin_fill()
t.forward(100)
t.left(90)
t.forward(20)
t.left(90)
t.forward(20)
t.right(90)
t.forward(20)
t.left(90)
t.forward(60)
t.left(90)
t.forward(20)
t.right(90)
t.forward(20)
t.left(90)
t.forward(20)
t.end_fill()
t.color(0,0,0)
t.up()
t.forward(10)
t.down()
t.begin_fill()
t.circle(10)
t.end_fill()
t.setheading(0)
t.up()
t.forward(90)
t.right(90)
t.forward(10)
t.setheading(0)
t.begin_fill()
t.down()
t.circle(10)
t.end_fill()
```

Which is a long, long, long, drawn-out way to draw the rather ugly and primitive-looking car in figure 8.5. But it does demonstrate a couple of other turtle functions: color, to change the colour of the pen being used by the turtle; fill, which fills in an area of the canvas; and circle, to draw a circle of a particular size.

8.1 Colouring in

The color function takes 3 parameters. The first parameter is a value for red, the second is a value for green, and the last is a value for blue.




Figure 8.5: The turtle is terrible at drawing cars!

Why red, green and blue?

If you've ever played around with different colours of paint, you'll already know part of the answer to that question. When you mix two different paint colours, you get another colour¹. When you mix blue and red together, you get purple... and when you mix too many colours together, you usually get a muddy brown. On a computer you can mix colours together in a similar fashion—put red and green together to get yellow—except with a computer, we are combining colours of light, not colours of paint.

Even though we're not using paint, for a moment, think about 3 large pots of paint. One red, one green, and one blue. Each pot is full, so we'll say that a full pot of paint has a value of 1 (or 100%). We then pour all of the red paint (100%) into a vat, followed by all of the green paint (again 100%). After a bit of mixing, we get a yellow colour. Let's draw a yellow circle using turtle:

```
>>> t.color(1,1,0)
>>> t.begin_fill()
>>> t.circle(50)
>>> t.end_fill()
```

So in the above example, we call the color function with 100% for red, 100%

¹Actually, the three **primary** paint colours are red, yellow and blue, and not the red/green/blue (RGB) on a computer.

green and 0% for blue (in other words, 1, 1, and 0). To make it easier to experiment with different colours, let's turn that into a function:

```
>>> def mycircle(red, green, blue):
...     t.color(red, green, blue)
...     t.begin_fill()
...     t.circle(50)
...     t.end_fill()
...
```

We can draw a bright green circle, by using all of the green paint (1 or 100%):

```
>>> mycircle(0, 1, 0)
```

And we can draw a darker green circle, by using only half the green paint (0.5 or 50%):

```
>>> mycircle(0, 0.5, 0)
```

Here's where thinking about paint doesn't make much sense any more. In the real world, if you've got a pot of green paint, it doesn't matter how much you use, it's still going to look the same. With colours on a computer, because we're playing with light, using less of that colour generally results in a darker shade. It's the same as if you shine a torch at night, you get a yellowish light—when the batteries start to run out and the light begins to fade, the yellow colour gets darker and darker. Just to see for yourself, try drawing a circle with full red and half red (1 and 0.5), and full blue and half blue.

```
>>> mycircle(1, 0, 0)
>>> mycircle(0.5, 0, 0)

>>> mycircle(0, 0, 1)
>>> mycircle(0, 0, 0.5)
```

Different combinations of red, green and blue will produce a huge variety of colours. You can get a gold colour by using 100% of red, 85% of green and no blue:

```
>>> mycircle(1, 0.85, 0)
```

A light pink colour can be achieved by combining 100% red, 70% green and 75% blue:

```
>>> mycircle(1, 0.70, 0.75)
```

And you get orange by combining 100% red and 65% green; and brown by combining 60% red, 30% green and 15% blue:

```
>>> mycircle(1, 0.65, 0)
>>> mycircle(0.6, 0.3, 0.15)
```

Don't forget, you can clear the canvas by using `t.clear()`.

8.2 Darkness

Here's a question for you: What happens when you turn all the lights off at night? Everything goes black.

The same thing happens with colours on a computer. No light equals no colour. So a circle with 0 for red, 0 for green and 0 for blue:

```
>>> mycircle(0, 0, 0)
```

Produces the black spot in figure 8.6.

The opposite is true; if you use 100% red, 100% green and 100% blue, you get white. Use the following code and the black circle will be wiped out again:

```
>>> mycircle(1,1,1)
```

8.3 Filling things

You've probably figured out by now that the fill function is switched on by passing the parameter '1', then switched off again with '0'. When you switch it off, the function actually fills in the area you've drawn—assuming you've drawn at least part of a shape. So we can easily draw a filled in square by using code we created earlier. First, let's turn it into a function. To draw a square with turtle we do:




Figure 8.6: A black hole!

```
>>> t.forward(50)
>>> t.left(90)
>>> t.forward(50)
>>> t.left(90)
>>> t.forward(50)
>>> t.left(90)
>>> t.forward(50)
>>> t.left(90)
```

So as a function, we might want to pass the size of the square as a parameter. This makes the function a little more flexible:

```
>>> def mysquare(size):
...     t.forward(size)
...     t.left(90)
...     t.forward(size)
...     t.left(90)
...     t.forward(size)
...     t.left(90)
...     t.forward(size)
...     t.left(90)
```

We can test our function by calling:

```
>>> mysquare(50)
```

That's a start, but it's not quite perfect. If you look at the code above, you'll see a pattern. We repeat: `forward(size)` and `left(90)` four times. That's a waste of typing. So we can use a for-loop to do it for us (pretty much the same as we did earlier):

```
>>> def mysquare(size):
...     for x in range(0,4):
...         t.forward(size)
...         t.left(90)
```

That's a big improvement on the previous version. You can test the function with different sizes:

```
>>> t.reset()
>>> mysquare(25)
>>> mysquare(50)
>>> mysquare(75)
>>> mysquare(100)
>>> mysquare(125)
```

And the turtle should draw something like figure 8.7.

Now we can try a filled square. First of all, reset the canvas once again:

```
>>> t.reset()
```

Then, turn on filling, and call the square function again:

```
>>> t.begin_fill()
>>> mysquare(50)
```

You'll still see an empty square until you turn filling off:

```
>>> t.end_fill()
```

Which produces something like the square in figure 8.8.

How about changing the function so that we can either draw a filled or an unfilled square? We need another parameter, and slightly more complicated code, to do this:




Figure 8.7: Lots of squares.




Figure 8.8: A black square.

```
>>> def mysquare(size, filled):
...     if filled == True:
...         t.begin_fill()
...         for x in range(0,4):
...             t.forward(size)
...             t.left(90)
...         if filled == True:
...             t.end_fill()
...
...
```

The first two lines check to see if the value of parameter ‘filled’ is set to True. If it is, then filling is turned on. We then loop four times to draw the four sides of the rectangle, before checking a second time whether the parameter ‘filled’ is True, and if so, turn filling off once again. You can now draw a filled square by calling:

```
>>> mysquare(50, True)
```

And an unfilled square by calling:

```
>>> mysquare(150, False)
```

Which causes our turtle to draw the image in figure 8.9. which, now that I think about it, looks like a weird square eye.

You can draw all sorts of shapes and fill them with colour. Let’s turn the star, we drew earlier, into a function. The original code looked like this:

```
>>> for x in range(1,19):
...     t.forward(100)
...     if x % 2 == 0:
...         t.left(175)
...     else:
...         t.left(225)
...
...
```

We can use the same if-statements from the mysquare function, and use the size parameter in the forward function.




Figure 8.9: A square eye.

```

1. >>> def mystar(size, filled):
2. ...     if filled:
3. ...         t.begin_fill()
4. ...     for x in range(1,19):
5. ...         t.forward(size)
6. ...         if x % 2 == 0:
7. ...             t.left(175)
8. ...         else:
9. ...             t.left(225)
10. ...     if filled:
11. ...         t.end_fill()

```

In lines 2 and 3, we switch filling on, depending upon the value of the parameter filled (turn filling on, if the parameter is set to True, turn it off, if the parameter is set to False). We do the reverse in lines 10 and 11 (switch filling back off again). The other difference about this function is that we pass the size of the star in the parameter size, and use this value in line 5.

Now let's set the colour to gold (you might remember that gold can be made by using 100% of red, 85% of green and no blue), and then call the function:




Figure 8.10: A gold star.

```
>>> t.color(1, 0.85, 0)
>>> mystar(120, True)
```

The turtle should draw the gold star in figure 8.10. We can add an outline for the star, by changing the colour again (this time to black) and redrawing the star with filling turned off

```
>>> t.color(0,0,0)
>>> mystar(120, False)
```

Thus the star now looks like figure 8.11.

8.4 Things to try

In this chapter we learned about the turtle module, using it to draw a few basic geometric shapes. We used functions in order to re-use some of our code, to make it easier to draw shapes with different colours.




Figure 8.11: A star with an outline.

Exercise 1

We've drawn stars, squares and rectangles. How about an octagon? An octagon is an 8 sided shape. (Hint: try turning 45 degrees).

Exercise 2

Now convert the octagon drawing code into a function which will fill it with a colour.

Capítulo 9

A bit graphic


The problem with using a turtle to draw, is... that..... turtles..... are..... really..... slow.

Even when a turtle is going at top speed, it's still not going that fast. For turtles, this is not really a problem—they've got time to waste—but when you're talking about computer graphics, it is. If you've got a Nintendo DS, a Gameboy Advance, or play games on your computer, think for a moment about the graphics (what you see displayed on the screen). There are a number of different ways that graphics are presented in games: there are 2d (or two-dimensional) games, where the images are flat and the characters generally only move up and down, and left and right—quite common in hand-held devices like the Gameboy, Nintendo DS, or mobile phones. There are pseudo-3d (almost three-dimensional) games, where the images look a little more real, but still the characters generally only move up and down, left and right—again quite common in hand-held devices—and finally there are 3d games, where the pictures drawn on the screen attempt to mimic reality.

All these kinds of graphic displays have one thing in common—the need to draw on the computer screen very quickly. Have you ever tried your own animation? Where you get a blank pad of paper, and in the corner of the first page you draw something (perhaps a stick figure), on the bottom corner of the next page you draw the same stick figure but you move its leg slightly. Then on the next page you draw the figure again with the leg moved a little more. Gradually you go through each page drawing on the bottom corner. When you've finished, you flick through the pages, and if you flick through fast enough it appears as if the stick figure is moving. This is the basics of how all animation is done—whether it's the cartoons you're watching on TV or the games that you play on your games console or computer. You draw something, then you draw it again but slightly changed to give the illusion of movement. Which is why a turtle is no good for doing most graphics. In order to

make an image look like it is moving, you have to draw each ‘frame’ of the animation very quickly.

Three-dimensional graphics is done in a considerably different manner to two-dimensional graphics, but still, the basic idea is the same. By the time your turtle has finished drawing even a small portion of the picture it would be time to turn the page and start drawing the next one...



9.1 Quick Draw

Each programming language has a different method to draw on the screen. Some methods are fast and some are slow, which means that programmers who develop games for a living have to be very careful about the language they choose to work in.

Python has a number of different ways to do graphics as well (including turtle, which we've already used), but the best methods (from a graphics point of view) are usually modules and libraries of code that are not included with Python itself. You will probably have to be programming for a few years before you'll be able to figure out how to install and use one of those complex libraries.

Luckily, there is a module, which comes with Python, that we can use to do basic graphics (at a slightly faster speed than a turtle). Perhaps even fast enough to be called the Quick Draw Turtle.



The module is called `tkinter` (a strange name, which stands for ‘Tk interface’) and it can be used to create full applications (you could even create a simple Word Processor program if you wanted to) as well as simple drawing. We could create a simple application with a button using the following code:

```

1. >>> from tkinter import *
2. >>> tk = Tk()
3. >>> btn = Button(tk, text="click me")
4. >>> btn.pack()

```

In line 1, we import the contents of the Tk module, so we can use them—the most useful of these is Tk, which creates a basic window to which we can then add things. After you type in line 2, that window will suddenly appear on the screen. In line 3, we create a new Button and assign it to the variable btn. The button is created by passing the tk object as a parameter, along with a named parameter with the words ‘click me’.

Named Parameters

This is the first time we’ve used ‘named parameters’. These work just like normal parameters, except they can appear in any order, so we need to provide a name.

For example, suppose we had a function rectangle which took two parameters width and height. Normally we might call this function using something like rectangle(200, 100), meaning we want to draw a rectangle 200 pixels wide by 100 pixels high. But what if the parameters could appear in any order? How do we know which is the width and which is the height?

In this case, it’s better to say exactly which is which, for example: rectangle(height=100, width=200). In actual fact, the whole idea of named parameters is a bit more complicated than this, and can be used in a number of different ways to make functions a lot more flexible—but that’s the subject of a more advanced book than this introduction to programming.

The final line (4) is an instruction to tell the button to draw itself. At which point, the window that was created in line 2 will shrink to the size of a small button containing the words ‘click me’. It will look something like this:



The button doesn’t do much but you can, at least, click it. We can make it

do something by changing the previous example a little (make sure you close the window we created earlier). First we can create a function to print out some text:

```
>>> def hello():
...     print('hello there')
```

Then modify the example to use this function:

```
>>> from tkinter import *
>>> tk = Tk()
>>> btn = Button(tk, text="click me", command=hello)
>>> btn.pack()
```

The named parameter ‘command’ says that we want to use the hello function, when the button is clicked. If you now click the button, you’ll see “hello there” written out to the console—printed once each time the button is clicked.

9.2 Simple Drawing

Buttons aren’t very useful when you want to draw things on the screen—so we need to create and add a different sort of component: a Canvas. When creating a canvas, unlike a button (which takes text and command parameters), we need to pass the width and height (in pixels) of the canvas. Apart from that, the code is similar to the button code:

```
>>> from tkinter import *
>>> tk = Tk()
>>> canvas = Canvas(tk, width=500, height=500)
>>> canvas.pack()
```

Similar to the button example, a window will appear when you type line 2. When you ‘pack’ the canvas on line 4, it will suddenly increase in size. We can draw a line onto the canvas using pixel coordinates. Coordinates are the positions of pixels on a canvas. On a Tk canvas, coordinates describe how far across the canvas (from left to right) and how far down the canvas (top to bottom) to move. The ‘left-right part’ is called the x-axis. The ‘top-bottom part’ is called the y-axis.

Since the canvas is 500 pixels wide, and 500 pixels high, the coordinates of the bottom-right corner of the screen are 500,500. So the line in figure 9.1 can be drawn by using start coordinates of 0,0 and end coordinates of 500,500:




Figure 9.1: Canvas x and y axis.

```
>>> from tkinter import *
>>> tk = Tk()
>>> canvas = Canvas(tk, width=500, height=500)
>>> canvas.pack()
>>> canvas.create_line(0, 0, 500, 500)
```

Now, to do the same thing with turtle, would have required the following code:

```
>>> import turtle
>>> turtle.setup(width=500, height=500)
>>> t = turtle.Pen()
>>> t.up()
>>> t.goto(-250,250)
>>> t.down()
>>> t.goto(500,-500)
```

So the tkinter code is already an improvement, being shorter and less complicated. There are a large number of methods available on the canvas object, some of which aren't very useful to us, but let's take a look at some examples of the interesting functions.

9.3 Drawing Boxes

In turtle, we drew a box by moving forward, turning, moving forward, turning again and so on. Eventually you can draw a rectangular or square box, just by changing how far you move forward. With tkinter, drawing a square or rectangle is considerably easier—you just need to know the coordinates for the corners.

```
>>> from tkinter import *
>>> tk = Tk()
>>> canvas = Canvas(tk, width=400,height=400)
>>> canvas.pack()
>>> canvas.create_rectangle(10, 10, 50, 50)
1
```

In the above example, we create a canvas that is 400 pixels wide, and 400 pixels high, and then we draw a square in the top left corner (the top left corner is 10 pixels in from the top left, and the bottom right corner is 50 pixels in from the bottom right). You might be wondering what the number is that appeared when you typed `create_rectangle` and earlier when calling `create_line`? That's an identifying number for the shape you've just drawn (whether a line or a square or a circle). We'll come back to that number later.

The parameters that are passed to `create_rectangle` are therefore: top left x position, top left y position, bottom right x position and bottom right y position. To save all that typing, we'll just refer to those as `x1, y1` and `x2, y2`. We can draw a rectangle by making `x2` a larger number:

```
>>> canvas.create_rectangle(100, 100, 300, 50)
```

Or by making `y2` a bit larger:

```
>>> canvas.create_rectangle(100, 200, 150, 350)
```

That last rectangle is basically saying: go 100 pixels across the canvas (from the top left), and 200 pixels down, then draw a box across to 150 pixels and down to 350 pixels. At the moment you should have something like figure 9.2 on your canvas.

Let's try filling the canvas with different sized rectangles. We can do this using a module called `random`. First import the `random` module:

```
>>> import random
```

Then we can create a function using a random number for the coordinates at the top and bottom corners. The function to use is called `randrange`:




Figure 9.2: tkinter boxes.

```
>>> def random_rectangle(width, height):
...     x1 = random.randrange(width)
...     y1 = random.randrange(height)
...     x2 = random.randrange(x1 + random.randrange(width))
...     y2 = random.randrange(y1 + random.randrange(height))
...     canvas.create_rectangle(x1, y1, x2, y2)
```

In the first two lines we create variables for the top left corner of the rectangle using `randrange`, passing the width and the height. The `randrange` function takes a number as an argument (actually, see Appendix C for more uses of `randrange`)—so `randrange(10)` gives you a number between 0 and 9, `randrange(100)` gives you a number between 0 and 99, and so on. The next two lines create variables for the bottom right corner of the rectangle (or square!)—we use the top left coordinate (`x1` or `y1`) and add a random number to that variable. Finally we call the `create_rectangle` function using those variables. You can try out the `random_rectangle` function by passing the width and height of the canvas you created:

```
>>> random_rectangle(400, 400)
```

Or to fill the screen, how about creating a loop to call it a number of times:




Figure 9.3: A mess of rectangles.

```
>>> for x in range(0, 100):
...     random_rectangle(400, 400)
```

Which produces a bit of a mess (figure 9.3, but is interesting nonetheless).

Remember, back in the last chapter, we set the colour the turtle drew with using percentages of the 3 colours: red, green and blue? With tkinter you can set the colour using similar ideas, but unfortunately, it's slightly more complicated than with turtle. First of all, let's change the random rectangle function to pass in a colour to fill the rectangle with:

```
>>> def random_rectangle(width, height, fill_colour):
...     x1 = random.randrange(width)
...     y1 = random.randrange(height)
...     x2 = random.randrange(x1 + random.randrange(width))
...     y2 = random.randrange(y1 + random.randrange(height))
...     canvas.create_rectangle(x1, y1, x2, y2, fill=fill_colour)
```

The canvas `create_rectangle` function can take a parameter ‘`fill`’ which specifies the fill colour. We can now pass this into the function. Try the following:

```
>>> random_rectangle(400, 400, 'green')
>>> random_rectangle(400, 400, 'red')
>>> random_rectangle(400, 400, 'blue')
>>> random_rectangle(400, 400, 'orange')
>>> random_rectangle(400, 400, 'yellow')
>>> random_rectangle(400, 400, 'pink')
>>> random_rectangle(400, 400, 'purple')
>>> random_rectangle(400, 400, 'violet')
>>> random_rectangle(400, 400, 'magenta')
>>> random_rectangle(400, 400, 'cyan')
```

Some, and maybe all, of those named colours will work. But some of them might result in an error message (it depends on whether you're using Windows, Mac OS X or Linux). So far, that's pretty easy. But what about a colour like gold? In the turtle module, we created gold using 100% of red, 85% of green and no blue. In tkinter we can create gold using:

```
>>> random_rectangle(400, 400, '#ffd800')
```

Which, all in all, is a pretty strange way to create a colour. 'ffd800' is called hexadecimal, and is another way to represent numbers. Explaining how hexadecimal numbers work would take a few more pages than we have to spare for this book, so for the moment, you can use the following function to create a hexadecimal colour:

```
>>> def hexcolor(red, green, blue):
...     red = 255*(red/100.0)
...     green = 255*(green/100.0)
...     blue = 255*(blue/100.0)
...     return '#%02x%02x%02x' % (red, green, blue)
```

Calling hexcolor with 100% for red, 85% for green and 0% for blue, results in the hexadecimal for a gold colour we just used:

```
>>> print(hexcolor(100, 85, 0))
#ffd800
```

You can create a bright purple colour using 98% of red, 1% of green, and 77% of blue:

```
>>> print(hexcolor(98, 1, 77))
#f902c4
```

You can use that with the random_rectangle function we created earlier:

```
>>> random_rectangle(400, 400, hexcolor(98, 1, 77))
```




Figure 9.4: A purple rectangle.

9.4 Drawing Arcs

An arc is a part of a circle, but to draw one with tkinter you need to draw a rectangle. Which doesn't make a lot of sense until you try to draw a rectangle and then draw an arc inside it (see figure 9.5). The code to draw this arc might look something like this:

```
canvas.create_arc(10, 10, 200, 100, extent=180, style=ARC)
```

This places the top left corner of the rectangle at the coordinates 10, 10 (that's 10 pixels across, 10 pixels down), and the bottom right corner of the rectangle at the coordinates 200, 100 (200 pixels across, 100 pixels down). The next parameter (a **named** parameter) 'extent' is used to specify the degrees of the angle of the arc. If you don't know anything about degrees in a circle (or arc), then just remember that if you think about a circle, 180 degrees would be half of the circle (or half the arc), 359 degrees would be a full circle, 90 degrees is a quarter of a circle and 0 degrees is... well, nothing at all. Here's some code that draws a bunch of different arcs down the page so you can see the basic differences when we use different degrees (you can see the examples in figure 9.6):



Figure 9.5: An arc fitting inside a rectangle.

```
>>> canvas.create_arc(10, 10, 200, 80, extent=45, style=ARC)
>>> canvas.create_arc(10, 80, 200, 160, extent=90, style=ARC)
>>> canvas.create_arc(10, 160, 200, 240, extent=135, style=ARC)
>>> canvas.create_arc(10, 240, 200, 320, extent=180, style=ARC)
>>> canvas.create_arc(10, 320, 200, 400, extent=359, style=ARC)
```

9.5 Drawing Ovals

While the last statement in the above example draws an oval, you can also draw ovals using the `create_oval` function. Similar to drawing arcs, an oval is drawn inside the boundaries of a rectangle. For example, the following code:

```
>>> tk = Tk()
>>> canvas = Canvas(tk, width=400,height=400)
>>> canvas.pack()
>>> canvas.create_oval(1, 1, 300, 200)
```

This example draws an oval in the (imaginary) square drawn from pixel positions 1,1 to 300,200. If we draw a red rectangle with the same coordinates, you can properly see how the oval is drawn inside (figure 9.7):

```
>>> canvas.create_rectangle(1, 1, 300, 200, outline="#ff0000")
```

To draw a circle, rather than an elliptical oval, the imaginary rectangle should be a square (which produces the circle in figure 9.9):

```
>>> tk = Tk()
>>> canvas = Canvas(tk, width=400,height=400)
>>> canvas.pack()
>>> canvas.create_oval(1, 1, 300, 300)
```




Figure 9.6: Differing degrees of arcs.




Figure 9.7: The outline of an oval.




Figure 9.8: The outline of an oval inside a rectangle.




Figure 9.9: A simple circle.




Figure 9.10: A simple triangle.

9.6 Drawing Polygons

A polygon is any shape with 3 or more sides. Triangles, squares, rectangles, pentagons, hexagons, and so on are all examples of polygons. As well as these more regular shapes, you can also create irregular shaped polygons. For example, to draw a triangle, you need to provide 3 sets of coordinates (that's a position across plus a position down) for each point of the triangle (creating the triangle in figure 9.10):

```
>>> from tkinter import *
>>> tk = Tk()
>>> canvas = Canvas(tk, width=400,height=400)
>>> canvas.pack()
>>> canvas.create_polygon(10, 10, 100, 10, 100, 50, fill="", outline="black")
```

We can add an irregular polygon using the following code. Figure 9.11 shows both the triangle and the oddly shaped polygon.

```
>>> canvas.create_polygon(200, 10, 240, 30, 120, 100, 140, 120, fill="", outline="black")
```




Figure 9.11: A simple triangle.

9.7 Drawing Images

You can draw an image on a canvas using tkinter by first loading the image, then using the `create_image` function on the canvas object. This sounds a bit illogical, but it works as follows:

```
1. >>> from tkinter import *
2. >>> tk = Tk()
3. >>> canvas = Canvas(tk, width=400, height=400)
4. >>> canvas.pack()
5. >>> myimage = PhotoImage(file='test.gif')
6. >>> canvas.create_image(0, 0, image=myimage, anchor=NW)
```

In lines 1 to 4 we set up the canvas the same as we have in previous examples. In line 5, the image is loaded into the variable `myimage`. It's important that the image you want to load is in a directory that's accessible to Python. This is usually the directory that the Python console is running from. You can find out the name of this directory by importing the `os` module and using the `getcwd()` function:




Figure 9.12: A photo image.

```
>>> import os  
>>> print(os.getcwd())
```

This will probably print out something like '/Users/yourname'..., so if your name is Jane Matthews, getcwd() might return '/Users/janematthews'.

Copy your image into that directory and then load it using the PhotoImage function (same as line 5). You then use the create_image function on the canvas to display your image (line 6). If you've done all this correctly, you'll see something like figure 9.12.

PhotoImage can load image files with the extensions .gif, .ppm and .pgm. If you want to load other types of images (there are lots of different ways you can create image files—for example, digital cameras usually store images with the extension .jpg), then you'll need to use an extension which adds that capability to Python. The Python Imaging Library (PIL)¹ adds the ability to load all kinds of images, as well as do things like expand and shrink, change image colours, reverse images and so on. However, installing and using the Python Imaging Library, is a bit beyond the scope of this book.

¹The Python Imaging Library can be found at <http://www.pythonware.com/products/pil/index.htm>




Figure 9.13: The triangle moving across the screen.

9.8 Basic Animation

So far, we've seen how to do static drawing—that's pictures that don't move. What about animation? Animation is not necessarily Tk's strong suit, but you can do the basics. For example, we can create a filled triangle and then make it move across the screen using the following code:

```
1. >>> import time
2. >>> from tkinter import *
3. >>> tk = Tk()
4. >>> canvas = Canvas(tk, width=400, height=400)
5. >>> canvas.pack()
6. >>> canvas.create_polygon(10, 10, 10, 60, 50, 35)
7. 1
8. >>> for x in range(0, 60):
9. ...     canvas.move(1, 5, 0)
10. ...     tk.update()
11. ...     time.sleep(0.05)
```

The moment you press the Enter key after typing the last line, the triangle will start moving across the screen (you can see it half-way across in figure 9.13).

How does it work?

Lines 1 to 5 we've seen before—it's just the basic setup to display a canvas—and in line 6, we create the triangle (using the `create_polygon` function), and in line 7 you can see the identifier (the number 1) that is returned by this function. In line 8, we setup a simple for-loop to count from 0 to 59.

The block of lines (9 to 11) is the code to move the triangle. The `move` function on the `canvas` object will move any drawn object by adding values to the object's x and y coordinates. For example, in line 9 we move the object with id 1 (the identifier for the triangle) 5 pixels across and 0 pixels down. If we wanted to move the back again we might use `canvas.move(1, -5, 0)`.

The function `update` on the `tk` object forces it to update (if we didn't use `update`, `tkinter` would wait until the loop had finished before moving the triangle, which means you wouldn't see it move). Finally line 11 tells Python to sleep for 1/20th of a second (0.05), before continuing. We can change this code, so the triangle moves diagonally down the screen, by calling `move(1, 5, 5)`. First, close the canvas (by clicking on the X button on the window), then try this code:

```
>>> import time
>>> tk = Tk()
>>> canvas = Canvas(tk, width=400, height=400)
>>> canvas.pack()
>>> canvas.create_polygon(10, 10, 10, 60, 50, 35)
1
>>> for x in range(0, 60):
...     canvas.move(1, 5, 5)
...     tk.update()
...     time.sleep(0.05)
...
...
```

Figure 9.14 shows the triangle part way down the screen. Move the triangle diagonally back up the screen to its starting position, by using `-5, -5`:

```
>>> import time
>>> for x in range(0, 60):
...     canvas.move(1, -5, -5)
...     tk.update()
...     time.sleep(0.05)
```

9.9 Reacting to events...

We can also make the triangle react when someone hits a key, by using what are called *event bindings*. Events are things that occur while a program is running,




Figure 9.14: The triangle moving down the screen.

such as someone moving the mouse, hitting a key, or even closing a window. You can setup Tk to look out for these events, and then do something in response. To begin handling events we need to start by creating a function. Suppose we want the triangle to move when the enter key is pressed? We can define a function to move the triangle:

```
>>> def movetriangle(event):
...     canvas.move(1, 5, 0)
```

The function needs to have a single parameter (`event`), which is used by Tk to send information to the function about what has happened. We then tell Tk that this function should be used for a particular event, using the `bind_all` function on the canvas. The full code looks like this:

```
>>> from tkinter import *
>>> tk = Tk()
>>> canvas = Canvas(tk, width=400, height=400)
>>> canvas.pack()
>>> canvas.create_polygon(10, 10, 10, 60, 50, 35)
>>> def movetriangle(event):
...     canvas.move(1, 5, 0)
...
>>> canvas.bind_all('<KeyPress-Return>', movetriangle)
```

The first parameter in the bind_all function describes the event which we want Tk to look out for. In this case, it's the event `<KeyPress-Return>` (which is a press of the enter key). We tell Tk that the movetriangle function should be called when this key-press event occurs. If you run this code, click on the Tk canvas with your mouse, and then try hitting the Enter (or Return) key on your keyboard.

How about changing the direction of the triangle depending upon different key presses, such as the arrow keys? First of all we change the move triangle function to the following:

```
>>> def movetriangle(event):
...     if event.keysym == 'Up':
...         canvas.move(1, 0, -3)
...     elif event.keysym == 'Down':
...         canvas.move(1, 0, 3)
...     elif event.keysym == 'Left':
...         canvas.move(1, -3, 0)
...     else:
...         canvas.move(1, 3, 0)
```

The event object that is passed to movetriangle, contains a number of *properties*². One of these properties is `keysym`, which is a string holding the value of the actual key pressed. If `keysym` contains the string ‘Up’, we call `canvas.move` with the parameters `(1, 0, -3)`; if it contains down we call with the parameters `(1, 0, 3)`, and so on. Remember that the first parameter is the identifying number for the shape drawn on the canvas, the second parameter is the value to add to the x (horizontal) coordinate, and the last parameter is the value to add to the y (vertical) coordinate. We then tell Tk that the movetriangle function should be used to handle events from 4 different keys (up, down, left and right). So, the code now looks like this:

²Properties are named values, which describe something—for example, a property of the sky is that it's blue (sometimes), a property of a car is that it has wheels. In programming terms, a property has a name and a value.

```
>>> from tkinter import *
>>> tk = Tk()
>>> canvas = Canvas(tk, width=400, height=400)
>>> canvas.pack()
>>> canvas.create_polygon(10, 10, 10, 60, 50, 35)
1
>>> def movetriangle(event):
...     if event.keysym == 'Up':
...         canvas.move(1, 0, -3)
...     elif event.keysym == 'Down':
...         canvas.move(1, 0, 3)
...     elif event.keysym == 'Left':
...         canvas.move(1, -3, 0)
...     else:
...         canvas.move(1, 3, 0)
...
>>> canvas.bind_all('<KeyPress-Up>', movetriangle)
>>> canvas.bind_all('<KeyPress-Down>', movetriangle)
>>> canvas.bind_all('<KeyPress-Left>', movetriangle)
>>> canvas.bind_all('<KeyPress-Right>', movetriangle)
```

With this example, the triangle now moves in the direction of the arrow key that you press.

Capítulo 10

Where to go from here

Congratulations! You've made it to the end.

What you've hopefully learned from this book, are basic concepts that will make learning other programming languages much simpler. While Python is a brilliant programming language, one language is not *always* the best tool for every task. So don't be afraid of looking at other ways to program your computer, if it interests you.

For example, if you're interested in games programming, you can perhaps look at something like BlitzBasic (www.blitzbasic.com), which uses the Basic programming language. Or perhaps Flash (which is used by many websites for animation and games—for example, the Nickelodeon website, www.nick.com, uses a lot of Flash).

If you're interested in programming Flash games, possibly a good place to start would be 'Beginning Flash Games Programming for Dummies', a book written by Andy Harris, or a more advanced reference such as 'The Flash 8 Game Developing Handbook' by Serge Melnikov. Searching for 'flash games' on www.amazon.com will find a number of books on this subject.

Some other games programming books are: 'Beginner's Guide to DarkBASIC Game Programming' by Jonathon S Harbour (also using the Basic programming language), and 'Game Programming for Teens' by Maneesh Sethi (using BlitzBasic). Be aware that BlitzBasic, DarkBasic and Flash (at least the development tools) all cost money (unlike Python), so Mum or Dad will have to get involved before you can even get started.

If you want to stick to Python for games programming, a couple of places to look are: www.pygame.org, and the book 'Game Programming With Python' by Sean Riley.

If you're not specifically interested in games programming, but do want to

learn more about Python (more advanced programming topics), then take a look at ‘Dive into Python’ by Mark Pilgrim (www.diveintopython.org). There’s also a free tutorial for Python available at: <http://docs.python.org/tut/tut.html>. There’s a whole pile of topics we haven’t covered in this basic introduction so, at least from the Python perspective, there’s still a lot for you to learn and play with.

Good luck and enjoy your programming efforts.

Appendix A

Python Keywords

Keywords in Python (indeed, in most programming languages) are important words that are used by the language itself. If you try to use these special words as variables, or use them in the wrong way, you will get strange (sometimes funny, sometimes confusing) error messages from the Python console. Each of the Python keywords, and a basic description is given below.

and

The keyword **and** is used to join two expressions together in a statement (like an if-statement), to say that both expressions must be true. For example:

```
if age > 10 and age < 20
```

This means that age must be greater than 10 and less than 20.

as

The keyword **as** is used to give another name to an imported module. For example, if you had a module with a name like:

```
i_am_a_python_module_that_is_not_very_useful
```

It would be enormously annoying to have to type that module name every time you want to use it:

```
>>> import i_am_a_python_module_that_is_not_very_useful
>>>
>>> i_am_a_python_module_that_is_not_very_useful.do_something()
I have done something
>>> i_am_a_python_module_that_is_not_very_useful.do_something_else()
I have done something else!
```

Instead you can give it a new name when you import it, then just use that new name (kind of like a nickname):

```
>>> import i_am_a_python_module_that_is_not_very_useful as notuseful
>>>
>>> notuseful.do_something()
I have done something

>>> notuseful.do_something_else()
I have done something else!
```

You probably won't use the keyword 'as' that much, though.

assert

Assert is an advanced keyword that is used by programmers to say that some code must be true. It's another way of catching errors and problems in code—and usually used by more advanced programs.

break

The **break** keyword is used to stop some code from running. You might use a break inside a for-loop such as:

```
>>> age = 25
>>> for x in range(1, 100):
...     print('counting %s' % x)
...     if x == age:
...         print('end counting')
...         break
```

If the variable 'age' was set to 10, this would print out:

```

counting 1
counting 2
counting 3
counting 4
counting 5
counting 6
counting 7
counting 8
counting 9
counting 10
end counting

```

Take a look at Chapter 5 to find out more information about for-loops.

class

The **class** keyword is used to define a type of object. This is a feature provided in many programming languages, and is very useful when developing more complicated programs, but is a little too advanced for this book.

del

Del is a special function used to get rid of something. For example, if you had a list of things you wanted for your birthday in your diary, but then changed your mind about one, you would cross it off the list, and add the new one:

remote controlled car
 new bike
~~computer game~~
 roboreptile

If we had the same list in python:

```
>>> what_i_want = ['remote controlled car', 'new bike', 'computer game']
```

We could remove the computer game by using del, and add the new item by using the function append:

```
>>> del what_i_want[2]
>>> what_i_want.append('roboreptile')
```

And then to see the new list:

```
>>> print(what_i_want)
['remote controlled car', 'new bike', 'roboreptile']
```

See Chapter 2 for more information about lists.

elif

The keyword **elif** is used as part of an if-statement. See **if** below...

else

The keyword **else** is also used as part of an if-statement. See **if** below...

except

Another keyword used for catching problems in code. Again this is used in more complicated programs, but too advanced for this book.

exec

exec is a special function used to look at a string as though it was a piece of Python code. For example, you can create a variable with a string value as follows:

```
>>> myvar = 'hello there'
```

Then print the contents:

```
>>> print(myvar)
hello there
```

But you could also put some Python code in that string instead:

```
>>> myvar = 'print("hello there")'
```

And then you could use exec to turn that string into a mini Python program and run it:

```
>>> exec(myvar)
hello there
```

It's a bit of a weird idea, and something that might not make sense to you until you needed it. Like assert it's one of those advanced keywords that is used in more sophisticated programs.

finally

This is another advanced keyword, used to make sure that if an error occurs, some special code runs (usually to tidy up any 'mess' that a piece of code has left behind).

for

The **for** keyword is used to create a for-loop of some kind. For example:

```
for x in range(0,5):
    print('x is %s' % x)
```

The above for-loop executes the block of code (the print statement) 5 times, creating the output:

```
x is 0
x is 1
x is 2
x is 3
x is 4
```

from

When importing a module, you can just import the part of it you need, using the **from** keyword. For example, the turtle module has a function Pen(), which is used to create a Pen object (basically a canvas on which the turtle moves)—you can import the entire turtle module and then use the Pen function, as follows:

```
>>> import turtle  
>>> t = turtle.Pen()
```

Or, you can just import the Pen function on its own, and then use it directly (without needing to refer to the turtle module at all):

```
>>> from turtle import Pen  
>>> t = Pen()
```

Of course, this does mean that you can't use the parts of the module you haven't imported. For example, the time module has a functions called localtime and gmtime. If we import localtime, then try to use gmtime, we'll get an error:

```
>>> from time import localtime  
>>> print(localtime())  
(2007, 1, 30, 20, 53, 42, 1, 30, 0)
```

This works fine, but:

```
>>> print(gmtime())  
Traceback (most recent call last):  
  File "<stdin>", line 1, in <module>  
NameError: name 'gmtime' is not defined
```

By saying ““gmtime’ is not defined” Python is telling us that it doesn’t know about the function gmtime... yet. If there are a bunch of functions in a particular module that you want to use, and you don’t want to refer to them by using the module name (i.e. time.localtime, or time.something-else) you can import everything in the module using an asterisk (*):

```
>>> from time import *  
>>> print(localtime())  
(2007, 1, 30, 20, 57, 7, 1, 30, 0)  
>>> print(gmtime())  
(2007, 1, 30, 13, 57, 9, 1, 30, 0)
```

In this case, we import everything from the time module, and can refer to the individual functions by name.

global

In Chapter 6, we talked about *scope*. Scope is the ‘visibility’ of a variable. If a variable is defined outside of a function, usually it can be seen inside the function. If defined inside a function, usually it can’t be seen **outside** of that function.

The global keyword is one exception to this rule. A variable that is defined as global, can be seen everywhere. The definition of the word global is world-wide or universal, so if you think of your Python console as like a mini-world, then global truly means world-wide. For example:

```
>>> def test():
...     global a
...     a = 1
...     b = 2
```

What do you think happens when you call `print(a)`, and then `print(b)`, after running the function `test`? The first will work, and then second will cause an error message to be displayed:

```
>>> test()
>>> print(a)
1
>>> print(b)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'b' is not defined
```

The variable `a` is now global (visible across the ‘world’), but `b` is still only visible inside the function. Note that you must call `global` before saving a value using in your global variable.

if

A statement making a decision about something—which is sometimes used with the additional keywords `else` and `elif` (else if). An if-statement is a way of saying, “if something is true, then perform an action of some kind”. For example:

```

if toy_price > 1000:
    print('That toy is over-priced')
elif toy_price > 100:
    print('That toy is expensive')
else:
    print('I would like that toy')

```

This if-statement says that if a toy price is over \$1000, it is over-priced; if the toy price is over \$100, then it's expensive.... otherwise it says (prints) "I would like that toy". Chapter 4 has more information about if-statements.

import

The **import** keyword is to tell Python to load a module so it can be used. For example:

```
>>> import sys
```

This code tells Python you want to use the module sys.

in

The **in** keyword is used in expressions, to find if an item is within a collection of items. For example, can the number 1 be found in a list (a collection) of numbers:

```

>>> if 1 in [1,2,3,4]:
...     print('number is in list')
number is in list

```

Or can lettuce be found in a shopping list:

```

>>> shopping_list = [ 'eggs', 'milk', 'cheese' ]
>>> if 'lettuce' in shopping_list:
...     print('lettuce is in the shopping list')
... else:
...     print('lettuce is not in the shopping list')
...
lettuce is not in the shopping list

```

is

The keyword **is**, is sort of like the equals operator (==) which is used to tell if two things are equal (for example 10 == 10 is true, 10 == 11 is false). However, there is a fundamental difference between **is** and ==. If you are comparing two things, == may return true, where is may not (even if you think the things are the same).

This is one of those extremely advanced programming concepts, that tends to be enormously confusing, so for the moment just stick with using ==.

lambda

Another advanced keyword. In fact lambda is so complicated, even to write an explanation about it would cause this book to burst into flames.

So best not to talk about it.

not

If something is true, the **not** keyword makes it false. For example, if we create a variable x and set it to the value True...

```
>>> x = True
```

...and then print the value of x using **not**, we get:

```
>>> print(not x)
False
```

Which doesn't seem very useful, until you start using **not** in if-statements. For example, if you are 12 years old, and the most important age for you is 12, you don't particular want to refer to all other years by saying:

“1 is not an important age” “2 is not an important age” “3 is not an important age” “4 is not an important age” “50 is not an important age”

And so on.

In terms of an if-statement, we could write that as...

```
if age == 1:
    print("1 is not an important age")
elif age == 2:
    print("2 is not an important age")
elif age == 3:
    print("3 is not an important age")
elif age == 4:
    print("4 is not an important age")
```

...continuing on forever. A simpler way to write the statement would be:

```
if age < 10 or age > 10:
    print("%s is not an important age" % age)
```

But one of the most simple ways to write that if-statement is by using **not**:

```
if not age == 10:
    print("%s is not an important age" % age)
```

Which, you've probably already realised, is just another way of saying, "if age is not 10".

or

The **or** keyword is used to join two expressions together in a statement (such as an if-statement), to say that at least one of the expressions should be true. For example:

```
>>> if friend == 'Rachel' or friend == 'Rob':
...     print('The Robinsons')
... elif friend == 'Bill' or friend == 'Bob':
...     print('The Baxters')
```

In this case, if the variable friend contains 'Rachel' or 'Rob' then it prints 'The Robinsons'. If the variable friend contains 'Bill' or 'Bob' then it prints 'The Baxters'.

pass

Sometimes when you're writing a program you only want to write bits of it, to try things out. The problem with this is that you can't have an if-statement without

the block of code that should be run if the expression in the if-statement is true. You also can't have a for-loop without the block of code that should be run in the loop. For example:

```
>>> if age > 10:  
...     print('older than 10')
```

The above code will work, but if you type:

```
>>> if age > 10:  
...
```

You'll get an error message in the console that looks something like this:

```
File "<stdin>", line 2  
  
    ^  
IndentationError: expected an indented block
```

This is the error message Python displays, when you should have a block of code after a statement of some kind.

The **pass** keyword can be used in these cases, so you can write a statement, but not provide the block of code that goes with it. For example, you might want to write a for-loop, with an if-statement inside it. Perhaps you haven't decided what to put in the if-statement yet. Maybe you'll put a print, maybe you'll put a break, maybe something else. In which case, you can use **pass** and the code will still work (even if it doesn't do exactly what you want yet). The code:

```
>>> for x in range(1,7):  
...     print('x is %s' % x)  
...     if x == 5:  
...         pass
```

will print out the following:

```
x is 1  
x is 2  
x is 3  
x is 4  
x is 5  
x is 6
```

Later on you can add the code in the block for the if-statement (replacing the **pass** keyword).

print

The **print** keyword, writes something to the Python console; such as a string, a number or a variable:

```
print('hello there')
print(10)
print(x)
```

raise

Another advanced keyword. In this case, **raise** is used to cause an error to happen—which might seem like a strange thing to do but, in advanced programs, is actually quite useful.

return

The **return** keyword is used to return a value from a function. For example, you might create a function to return the amount of money you've saved:

```
>>> def mymoney():
...     return money_amount
```

When you call this function, the value returned can be assigned to another variable:

```
>>> money = mymoney()
```

or printed:

```
>>> print(mymoney())
```

try

The **try** keyword is the beginning of a block of code that ends with the **except** and/or **finally** keywords. All together, these **try/except/finally** blocks of code are used to handle errors in a program—for example, to make sure that the program displays a useful message to the user, rather than an ugly Python error.

while

A bit like a for-loop, **while** is another way of looping code. Where a for-loop counts through a range (of numbers), a while loop keeps running while an expression is True. You have to be rather careful with while loops, because if the expression is always True, the loop will never end (this is called an infinite loop). For example:

```
>>> x = 1
>>> while x == 1:
...     print('hello')
```

If you run the above code, it will loop forever. Well, at least until you either close the Python console, or hit **CTRL+C** (the control key and the C key together) to interrupt it. However the following code:

```
>>> x = 1
>>> while x < 10:
...     print('hello')
...     x = x + 1
```

Will print ‘hello’ 9 times (each time adding 1 to the variable x, until x is no longer less than 10). This is obviously a bit like a for-loop, but does have its uses in certain situations.

with

With is a very advanced keyword.

yield

Yield is another very advanced keyword.

Appendix B

Built-in Functions

Python has a number of built-in functions—functions that can be used without needing to **import** them first. Some of the available built-in functions are listed below.

abs

The **abs** function returns the absolute value of a number. An absolute value is a number that is not negative. So the absolute value of 10 is 10, and the absolute value of -20.5 is 20.5. For example:

```
>>> print(abs(10))
10
>>> print(abs(-20.5))
20.5
```

bool

The **bool** function returns either True or False based on the value passed as its parameter. For numbers, 0 returns False, while any other number returns True:

```
>>> print(bool(0))
False
>>> print(bool(1))
True
>>> print(bool(1123.23))
True
>>> print(bool(-500))
True
```

For other values, `None` returns `False` while anything else returns `True`:

```
>>> print(bool(None))
False
>>> print(bool('a'))
True
```

cmp

The `cmp` function compares two values and returns a negative number if the first value is less than the second; returns 0 if the first value is equal to the second; and returns a positive number if the first value is greater than the second. For example, 1 is less than 2:

```
>>> print(cmp(1,2))
-1
```

And 2 is equal to 2:

```
>>> print(cmp(2,2))
0
```

But 2 is greater than 1:

```
>>> print(cmp(2,1))
1
```

Compare doesn't only work with numbers. You can use other values, such as strings:

```
>>> print(cmp('a','b'))
-1
>>> print(cmp('a','a'))
0
>>> print(cmp('b','a'))
1
```

But do be careful with strings; the return value may not be exactly what you expect...

```
>>> print(cmp('a','A'))
1
>>> print(cmp('A','a'))
-1
```

A lower-case 'a' is actually greater than an upper-case 'A'. Of course...

```
>>> print(cmp('aaa','aaaa'))
-1
>>> print(cmp('aaaa','aaa'))
1
```

...3 letter a's (aaa) are less than 4 letter a's (aaaa).

dir

The **dir** function returns a list of information about a value. You can use dir on strings, numbers, functions, modules, objects, classes—pretty much anything. On some values, the information might not be all that useful (in fact it might not make a huge amount of sense at all). For example, calling dir on the number 1 results in...

```
>>> dir(1)
['__abs__', '__add__', '__and__', '__class__', '__cmp__', '__coerce__', '__delattr__',
 '__div__', '__divmod__', '__doc__', '__float__', '__floordiv__', '__getattribute__',
 '__getnewargs__', '__hash__', '__hex__', '__index__', '__init__', '__int__', '__invert__',
 '__long__', '__lshift__', '__mod__', '__mul__', '__neg__', '__new__', '__nonzero__',
 '__oct__', '__or__', '__pos__', '__pow__', '__radd__', '__rand__', '__rdiv__',
 '__rdivmod__', '__reduce__', '__reduce_ex__', '__repr__', '__rfloordiv__',
 '__rlshift__', '__rmod__', '__rmul__', '__ror__', '__rpow__', '__rrshift__', '__rshift__',
 '__rsub__', '__rtruediv__', '__rxor__', '__setattr__', '__str__', '__sub__', '__truediv__',
 '__xor__']
```

...quite a large number of special functions. Whereas calling dir on the string 'a' results in...

```
>>> dir('a')
['__add__', '__class__', '__contains__', '__delattr__', '__doc__', '__eq__', '__ge__', '__getattribute__', '__getitem__', '__getnewargs__', '__getslice__', '__gt__', '__hash__', '__init__', '__le__', '__len__', '__lt__', '__mod__', '__mul__', '__ne__', '__new__', '__reduce__', '__reduce_ex__', '__repr__', '__rmod__', '__rmul__', '__setattr__', '__str__', 'capitalize', 'center', 'count', 'decode', 'encode', 'endswith', 'expandtabs', 'find', 'index', 'isalnum', 'isalpha', 'isdigit', 'islower', 'isspace', 'istitle', 'isupper', 'join', 'ljust', 'lower', 'lstrip', 'partition', 'replace', 'rfind', 'rindex', 'rjust', 'rpartition', 'rsplit', 'rstrip', 'split', 'splitlines', 'startswith', 'strip', 'swapcase', 'title', 'translate', 'upper', 'zfill']
```

Which shows you there are functions such as `capitalize` (change the first letter in a string to a capital)...

```
>>> print('aaaaa'.capitalize())
Aaaaa
```

`...isalnum` (which returns True if a string is alphanumeric—contains only letters and numbers), `isalpha` (which returns True if a string contains only letters), and so on. `Dir` can be useful when you have a variable and quickly want to find out what you can do with it.

eval

The `eval` function takes a string as a parameter and runs it as though it were a Python expression. This is similar to the `exec` keyword, but works a little differently. With `exec` you can create mini Python programs in your string, but `eval` only allows simple expressions, such as:

```
>>> eval('10*5')
50
```

file

A function to open a file and return a file object with functions that can access information in the file (the contents of the file, its size and so on). You can find more information about file and file objects in Chapter 7.

float

The `float` function converts a string or a number into a floating point number. A floating point number is a number with a decimal place (also called a real number).

For example, the number 10 is an ‘integer’ (also called a whole number), but 10.0, 10.1, 10.253, and so on, are all ‘floats’. You can convert a string to a float by calling:

```
>>> float('12')
12.0
```

You can use a decimal place in the string as well:

```
>>> float('123.456789')
123.456789
```

A number can be converted to a float by calling:

```
>>> float(200)
200.0
```

Of course, converting a floating point number just returns another floating point number:

```
>>> float(100.123)
100.123
```

Calling float with no arguments, returns 0.0.

int

The **int** function converts a string or a number into a whole number (or integer). For example:

```
>>> int(123.456)
123
>>> int('123')
123
```

This function works a little differently from the **float** function. If you try to convert a floating point number in a string, you will get an error message:

```
>>> int('123.456')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
ValueError: invalid literal for int() with base 10: '123.456'
```

However, if you call int with no argument, then 0 is returned.

len

The **len** function returns the length of an object. In this case of a string, it returns the number of characters in the string:

```
>>> len('this is a test string')
21
```

For a list or a tuple, it returns the number of items:

```
>>> mylist = [ 'a', 'b', 'c', 'd' ]
>>> print(len(mylist))
4
>>> mytuple = (1,2,3,4,5,6)
>>> print(len(mytuple))
6
```

For a map, it also returns the number of items:

```
>>> mymap = { 'a' : 100, 'b' : 200, 'c' : 300 }
>>> print(len(mymap))
3
```

You might find the **len** function useful with loops, if you want to count through the elements in a list. You could do this using the following code:

```
>>> mylist = [ 'a', 'b', 'c', 'd' ]
>>> for item in mylist:
...     print(item)
```

Which would print out all the items in the list (a,b,c,d)—but what if you wanted to print the index position of each item in the list? In this case we could find the length of the list, then count through the items as follows:

```
>>> mylist = [ 'a', 'b', 'c', 'd' ]
>>> length = len(mylist)
>>> for x in range(0, length):
...     print('the item at index %s is %s' % (x, mylist[x]))
...
the item at index 0 is a
the item at index 1 is b
the item at index 2 is c
the item at index 3 is d
```

We store the length of the list in the variable ‘length’, and then use that variable in the range function to create our loop.

max

The **max** function returns the largest item in a list, tuple or even a string. For example:

```
>>> mylist = [ 5, 4, 10, 30, 22 ]
>>> print(max(mylist))
30
```

A string with the items are separated by commas or spaces will also work:

```
>>> s = 'a,b,d,h,g'
>>> print(max(s))
h
```

And you don't have to use lists, or tuples or strings. You can also call the max function directly with a number of arguments:

```
>>> print(max(10, 300, 450, 50, 90))
450
```

min

The **min** function works in the same way as max, except it returns the smallest item in the list/tuple/string:

```
>>> mylist = [ 5, 4, 10, 30, 22 ]
>>> print(min(mylist))
4
```

range

The **range** function is mainly used in for-loops, when you want to loop through some code a number of times. We first saw range in Chapter 5, so we've seen how to use it with two arguments, but it can also be used with three arguments. Here's another example of range with two arguments:

```
>>> for x in range(0, 5):
...     print(x)
...
0
1
2
3
4
```

What you might not have realised, is that the range function actually just returns a special object (called an iterator) which the for-loop then works through. You can convert the iterator into a list (oddly enough, using the function list), so if you print the return value when calling range, you'll see the numbers it contains:

```
>>> print(list(range(0, 5)))
[0, 1, 2, 3, 4]
```

You get a list of numbers that can be assigned to variables and used elsewhere in your program:

```
>>> my_list_of_numbers = list(range(0, 30))
>>> print(my_list_of_numbers)
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29]
```

Range also takes a third argument, called a ‘step’ (the first two arguments are called the ‘start’ and the ‘stop’). If the step value is not passed into the function (in other words, when you call it with only the start and stop values), by default the number 1 is used. But what happens when we pass the number 2 as the step? You can see the result in the following example:

```
>>> my_list_of_numbers = list(range(0, 30, 2))
>>> print(my_list_of_numbers)
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28]
```

Each number in the list increases by 2 from the previous number. We can use larger steps:

```
>>> mylist = list(range(0, 500, 50))
>>> print(mylist)
[0, 50, 100, 150, 200, 250, 300, 350, 400, 450]
```

This creates a list from 0 to 500 (but not including 500, of course), incrementing the numbers by 50.

sum

The **sum** function adds up items in a list and returns the total number. For example:

```
>>> mylist = list(range(0, 500, 50))
>>> print(mylist)
[0, 50, 100, 150, 200, 250, 300, 350, 400, 450]

>>> print(sum(mylist))
2250
```


Appendix C

A Few Python Modules

Python has a large number of modules available for doing all sorts of things. If you want to read about them, you can look at the Python documentation at the following address: docs.python.org/modindex.html, however, a few of the more useful modules are explained below. A warning if you do decide to look at the Python documentation—the list of modules is very long, and some of them are quite complicated.

The ‘random’ module

If you’ve ever played the game where you ask someone to guess a number between 1 and 100, you’ll know what to do with the random module. Random contains a number of functions useful for coming up with... random numbers. It’s kind of like asking the computer to pick a number. The random module contains a number of functions, but the most useful are randint, choice and shuffle. The first function, random, picks a random number between a start and end number (in other words, between 1 and 100, or between 100 and 1000, or between 1000 and 5000, and so on). For example:

```
>>> import random
>>> print(random.randint(1, 100))
58
>>> print(random.randint(100, 1000))
861
>>> print(random.randint(1000, 5000))
3795
```

We could use this to create a simple (and annoying) guessing game, using a while loop:

```

import random
import sys
num = random.randint(1, 100)
while True:
    print('Guess a number between 1 and 100')
    chk = sys.stdin.readline()
    i = int(chk)
    if i == num:
        print('You guessed right')
        break
    elif i < num:
        print('Try higher')
    elif i > num:
        print('Try lower')

```

Use choice, if you have a list and want to pick a random item from that list. For example:

```

>>> import random
>>> list1 = [ 'a', 'b', 'c', 'd', 'e', 'f', 'g', 'h' ]
>>> print(random.choice(list1))
c
>>> list2 = [ 'ice cream', 'pancakes', 'trifle', 'pavlova', 'sponge' ]
>>> print(random.choice(list2))
trifle

```

And finally, use shuffle if you want to mix up a list (like shuffling cards):

```

>>> import random
>>> list1 = [ 'a', 'b', 'c', 'd', 'e', 'f', 'g', 'h' ]
>>> list2 = [ 'ice cream', 'pancakes', 'trifle', 'pavlova', 'sponge' ]
>>> random.shuffle(list1)
>>> print(list1)
['h', 'e', 'a', 'b', 'c', 'g', 'f', 'd']
>>> random.shuffle(list2)
>>> print(list2)
['pancakes', 'ice cream', 'sponge', 'trifle', 'pavlova']

```

The ‘sys’ module

The sys module contains useful ‘system’ functions. This is just an odd way of saying that they are very important within Python. Some of the most useful functions and values available in sys are: exit, stdin, stdout, and version.

The exit function is another way of stopping the Python console. For example if you type:

```
>>> import sys
>>> sys.exit()
```

The Python console will stop. Depending upon whether you’re using Windows, Mac or Linux, a number of different things might happen—but the end result is that the Python console stops running.

Stdin has been used elsewhere in this book (see Chapter 6), to prompt someone using a program to enter some values. For example:

```
>>> import sys
>>> myvar = sys.stdin.readline()
this is a test value
>>> print(myvar)
this is a test value
```

Stdout is the opposite—used to write messages to the console. In some ways, it’s the same as print, but works more like a file, so sometimes it’s more useful to use stdout than print:

```
>>> import sys
>>> l = sys.stdout.write('this is a test')
this is a test>>>
```

Notice where the prompt (>>>) reappears? It’s not an error, that it’s at the end of the message. That’s because, unlike print, when you call write, it doesn’t automatically move to the next line. To do the same with write we can do the following:

```
>>> import sys
>>> l = sys.stdout.write('this is a test\n')
this is a test
>>>
```

(Note that stdout.write returns the number of characters written—try print(l) to see the result).

\n is the *escape* character for a newline (what you get when you hit the enter key). An escape character is a special character that you use in strings when you can’t type it directly. For example, if you want to create a string with a newline in the middle, but try to use the enter key, you’ll get an error:

```
>>> s = 'test test
File "<stdin>", line 1
    s = 'test test
^
SyntaxError: EOL while scanning single-quoted string
```

Instead you can use the newline escape character:

```
>>> s = 'test test\ntest'
```

Finally, version is just a way of displaying the version of Python you are running:

```
>>> import sys
>>> print(sys.version)
2.5.1c1 (release25-maint, Apr 12 2007, 21:00:25)
[GCC 4.1.2 (Ubuntu 4.1.2-0ubuntu4)]
```

The ‘time’ module

Python’s time module contains functions for displaying... well, the time, obviously. However, if you try to call the most obvious function (time), the result won’t quite be what you were expecting:

```
>>> import time
>>> print(time.time())
1179918604.34
```

The number returned by time() is actually the number of seconds since the 1st of January, 1970 (at 00:00:00am to be exact). You might not think this is enormously useful, however it does, occasionally, have its purpose. For example, if you create a program and want to know how fast bits of it run, you can record the time at the beginning, the time at the end, and then compare the values. For example, how long would it take to print all the numbers from 0 to 100,000? We can easily create a function to print them out:

```
>>> def lots_of_numbers(max):
...     for x in range(0, max):
...         print(x)
```

Then call the function:

```
>>> lots_of_numbers(100000)
```

But if we want to know how long it took, we can modify the function and use the time module:

```
>>> def lots_of_number(max):
...     t1 = time.time()
...     for x in range(0, max):
...         print(x)
...     t2 = time.time()
...     print('it took %s seconds' % (t2-t1))
```

If we call it again:

```
>>> lots_of_numbers(100000)
0
1
2
3
.
.
.
99997
99998
99999
it took 6.92557406425 seconds
```

How does it work? The first time we call the time() function, we assign the value to the variable t1. We then loop and print out all the numbers. Again we call the time() function and this time assign the value to the variable t2. Since it took a few seconds for the loop to complete, the value in t2 will be higher (or later to be exact) than t1 (the number of seconds since 1st of Jan, 1970 will have increased). So if you subtract t2 from t1, you have the number of seconds it took to print all those numbers.

Other functions available on the time module include: asctime, ctime, localtime, sleep, strftime, and strftime.

The function asctime takes a date as a tuple (remember: a tuple is a list of values that cannot be changed) and converts it into a readable form. You can also call it without any argument and it will display the current date and time in a readable form:

```
>>> import time
>>> print(time.asctime())
Sun May 27 20:11:12 2007
```

To call it with an argument, we first need to make a tuple with the correct values for date and time. Let's assign the tuple to the variable t:

```
>>> t = (2007, 5, 27, 10, 30, 48, 6, 0, 0)
```

The values in the sequence are year, month, day, hours, minutes, seconds, day of the week (0 is Monday, 1 is Tuesday, and so on, up till Sunday which is 6) and finally the day of the year and whether or not it is daylight savings (0 is isn't, 1 it is). Calling asctime with the above tuple, we get:

```
>>> import time
>>> t = (2007, 5, 27, 10, 30, 48, 6, 0, 0)
>>> print(time.asctime(t))
Sun May 27 10:30:48 2007
```

But be careful with the values you put in a tuple. You can end up with a nonsensical date if you put in the wrong values:

```
>>> import time
>>> t = (2007, 5, 27, 10, 30, 48, 0, 0, 0)
>>> print(time.asctime(t))
Mon May 27 10:30:48 2007
```

Because the value for 'day of the week' was set to 0 (rather than 6), asctime now thinks that May the 27th is a Monday, rather than what it actually is—a Sunday.

The function ctime is used to convert a number of seconds into a readable form. For example, we can use the time() function explained in the beginning of this section:

```
>>> import time
>>> t = time.time()
>>> print(t)
1180264952.57
>>> print(time.ctime(t))
Sun May 27 23:22:32 2007
```

The function localtime returns the current date and time as a tuple in the same sequence of values we've just used:

```
>>> import time
>>> print(time.localtime())
(2007, 5, 27, 23, 25, 47, 6, 147, 0)
```

This value we can also pass into asctime:

```
>>> import time
>>> t = time.localtime()
>>> print(time.asctime(t))
Sun May 27 23:27:22 2007
```

The function sleep is quite useful when you want to delay your program for a certain period of time. For example, if you wanted to print out one number every second, the following loop wouldn't be very successful:

```
>>> for x in range(1, 61):
...     print(x)
...
1
2
3
4
```

It would instantly print out all the numbers from 1 to 60. However if you tell Python to go to sleep for a second between each print statement:

```
>>> for x in range(1, 61):
...     print(x)
...     time.sleep(1)
...
```

There will be a short (1 second) delay between the display of each number. Telling a computer to sleep might not seem all that useful, but there are times when it can be. Think about your alarm clock that wakes you up in the morning. When you hit the sleep button, it stops buzzing for a few minutes, giving you an extra few moments of sleep (at least until someone calls you for breakfast). The sleep function is just as useful in certain situations.

The function strftime is used to change the way a date and time value is displayed, and strptime is used to take a string and convert it into a date/time tuple. Let's look at strftime first. Just before we saw how to change a tuple into a string using asctime:

```
>>> t = (2007, 5, 27, 10, 30, 48, 6, 0, 0)
>>> print(time.asctime(t))
Sun May 27 10:30:48 2007
```

That works fine for most situations, but what if you don't like the way that string is displayed—what if you only want to display the date and not the time? We can do that with strftime:

```
>>> print(time.strftime('%d %b %Y', t))
27 May 2007
```

As you can see, strftime takes 2 arguments: the first is a date/time format (which describes how the date/time should be displayed), and the second is the tuple containing the time values. The format, %d %b %Y is another way of saying: 'show the day, the month and then the year'. We could also display the month as a number, for example:

```
>>> print(time.strftime('%d/%m/%Y', t))
27/05/2007
```

This format is a way of saying, 'display the day, then a forward-slash, then display the month as a number, then a forward-slash, then display the year'. There are a number of different values you can use in a format:

%a	a shortened version of a week day (for example, Mon, Tues, Wed, Thurs, Fri, Sat, and Sun)
%A	the full weekday name (Monday, Tuesday, Wednesday, Thursday, Friday, Saturday, Sunday)
%b	a shortened version of a month name (Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct , Nov, Dec)
%B	the full version of a month name (January, February, March, April, May, and so on)
%c	the full date and time, in the same format the asctime uses
%d	the day of the month as a number (from 01 to 31)
%H	the hour of the day, in 24 hour format (from 00 to 23)
%I	the hour of the day, in 12 hour format (from 01 to 12)
%j	the day of the year as a number (from 001 to 366)
%m	the month as a number (from 01 to 12)
%M	the minute as a number (from 00 to 59)
%p	morning or afternoon as either AM or PM
%S	the seconds as a number
%U	the week number of the year as a number (from 00 to 53)
%w	the day of the week as a number. Sunday is 0, Monday is 1, up to Saturday, which is 6
%x	a simple date format (usually month/day/year—for example, 03/25/07)
%X	a simple time format (usually hour:minutes:seconds—for example 10:30:53)
%y	the year in 2 digits (for example, 2007 would be 07)
%Y	the year in 4 digits (e.g. 2007)

The function `strptime` is almost the reverse of `strftime`—it takes a string and converts it into a tuple containing the date and time values. It also takes the same values in the format string. An example of using this function is:

```
>>> import time
>>> t = time.strptime('05 Jun 2007', '%d %b %Y')
>>> print(t)
(2007, 6, 5, 0, 0, 0, 1, 156, -1)
```

If the date in our string is day/month/year (for example, 01/02/2007), we might use:

```
>>> import time
>>> t = time.strptime('01/02/2007', '%d/%m/%Y')
>>> print(t)
(2007, 2, 1, 0, 0, 0, 3, 32, -1)
```

Or if the date is month/day/year, we might use:

```
>>> import time
>>> t = time.strptime('03/05/2007', '%m/%d/%Y')
>>> print(t)
(2007, 3, 5, 0, 0, 0, 0, 64, -1)
```

We can combine the 2 functions to convert a string in one format to another. Let's do it in a function:

```
>>> import time
>>> def convert_date(datestring, format1, format2):
...     t = time.strptime(datestring, format1)
...     return time.strftime(format2, t)
...
```

We can use this function by passing in the date string, the format of that string, and then the format that we want the returned date in:

```
>>> print(convert_date('03/05/2007', '%m/%d/%Y', '%d %B %Y'))
05 March 2007
```

Appendix D

Answers to “Things to try”

Here is where you can find the answers to the questions asked in each chapter in the section “Things to try”.

Chapter 2

1. The answer to **Exercise 1** might be something like the following:

```
>>> toys = [ 'car', 'Nintendo Wii', 'computer', 'bike' ]
>>> foods = [ 'pancakes', 'chocolate', 'ice cream' ]
>>> favourites = toys + foods
>>> print(favourites)
['car', 'Nintendo Wii', 'computer', 'bike', 'pancakes', 'chocolate', 'ice cream']
```

2. The answer to **Exercise 2** is simply adding the result of multiplying 3 by 25 and the result of multiplying 10 by 32. The following equations shows the result of this equation:

```
>>> print(3 * 25 + 10 * 32)
395
```

However, given that we looked at the use of brackets in Chapter 2, you might have decided that you needed to put brackets around some parts of this equation. You might've done something like this:

```
>>> print((3 * 25) + (10 * 32))
395
```

The answer is the same, because multiplication is done before addition. In either equation, the two multiplication operations are performed first, and the results are

added. However, the second equation is possibly slightly better than the first—because it’s immediately obvious to the reader which operations are performed first. A less knowledgeable programmer (who doesn’t know as much about the order of operations) might think that, in the first equation, you multiply 3 by 25, then add 10, then multiply the result by 32 (the answer to that is 2720—completely wrong). With the brackets, it’s a bit more obvious what gets calculated first.

3. The answer to **Exercise 3** will be something like the following:

```
>>> first_name = 'Mary'
>>> second_name = 'Wilson'
>>> print('My name is %s %s' % (first_name, second_name))
My name is Mary Wilson
```

Chapter 3

1. A rectangle is like a square, except two of its sides are longer than the other two. By telling the turtle to do the following operations, you can easily draw a rectangle:

- move forward a certain number of pixels
- turn left
- move forward a shorter number of pixels
- turn left
- move forward, the number of pixels in the first movement
- turn left
- move forward the shorter number of pixels in the second movement

For example, the following code will drawing the rectangle in figureD.1.

```
>>> import turtle
>>> t = turtle.Pen()
>>> t.forward(150)
>>> t.left(90)
>>> t.forward(50)
>>> t.left(90)
>>> t.forward(150)
>>> t.left(90)
>>> t.forward(50)
```




Figure D.1: Turtle drawing a rectangle.

2. A triangle is a bit more complicated to draw, because you need to know more about angles and line lengths. If you haven't studied angles in school then this may be a bit harder to do than you expect. You can draw a basic triangle (see figure D.2) using the following code:

```
>>> import turtle  
>>> t = turtle.Pen()  
>>> t.forward(100)  
>>> t.left(135)  
>>> t.forward(70)  
>>> t.left(90)  
>>> t.forward(70)
```

Chapter 5

1. The loop stops after the first print. So when you run the code in the Python console you get:




Figure D.2: Turtle drawing a triangle.

```
>>> for x in range(0, 20):
...     print('hello %s' % x)
...     if x < 9:
...         break
hello 0
```

The reason it stops after the first print is that during the first run of the loop, the value of the variable `x` is zero. Since zero is less than nine, the `break` statement stops the loop from running any further.

2. To figure out how much money you get when you are paid 3% interest, you need to multiply the number by 0.03. To begin with we should create a variable and point it at the amount of our savings:

```
>>> amount = 100
```

To the amount of interest paid for 1 year would be that amount multiplied by 0.03:

```
>>> amount = 100
>>> print(amount * 0.03)
3.0
```

That's \$3! Not bad since we didn't need to do anything to get it. We need to print out this value and then add it to the total, and do it 10 times to work out the interest that we are paid for 10 years:

```
>>> amount = 100
>>> for year in range(1, 11):
...     interest = amount * 0.03
...     print('interest earned for year %s is %s' % (year, interest))
...     amount = amount + interest
...
interest earned for year 1 is 3.0
interest earned for year 2 is 3.09
interest earned for year 3 is 3.1827
interest earned for year 4 is 3.278181
interest earned for year 5 is 3.37652643
interest earned for year 6 is 3.4778222229
interest earned for year 7 is 3.58215688959
interest earned for year 8 is 3.68962159627
interest earned for year 9 is 3.80031024416
interest earned for year 10 is 3.91431955149
```

In the first line we create a for-loop using the variable year and the function range to count from 1 to 10. The second line calculates the interest, multiplying the value in variable amount by 0.03. The next line is the print statement—which uses place holders (%s) to include the values for year and interest. Finally in the last line, we add the interest back into the amount. All the decimal places—the numbers after the period (.) in the print lines—are a bit confusing, but you can tell that the amount of interest each year increases a little bit as you add the interest. The code might be a bit more helpful if we also add the total saved each year:

```
>>> amount = 100
>>> for year in range(1, 11):
...     interest = amount * 0.03
...     print('interest earned for savings %s for year %s is %s' %
...           (amount, year, interest))
...     amount = amount + interest
...
interest earned for savings 100 for year 1 is 3.0
interest earned for savings 103.0 for year 2 is 3.09
interest earned for savings 106.09 for year 3 is 3.1827
interest earned for savings 109.2727 for year 4 is 3.278181
interest earned for savings 112.550881 for year 5 is 3.37652643
interest earned for savings 115.92740743 for year 6 is 3.4778222229
interest earned for savings 119.405229653 for year 7 is 3.58215688959
interest earned for savings 122.987386542 for year 8 is 3.68962159627
interest earned for savings 126.677008139 for year 9 is 3.80031024416
interest earned for savings 130.477318383 for year 10 is 3.91431955149
```

Chapter 6

1. Turning the for-loop into a function is actually quite easy. The function will look something like this:

```
>>> def calculate_interest(amount, rate):
...     for year in range(1, 11):
...         interest = amount * rate
...         print('interest earned for savings %s for year %s is %s' %
...               (amount, year, interest))
...         amount = amount + interest
```

If you compare the function with the code above, you might notice that, apart from the first line, there's only one change to the original code (0.03 is now the parameter rate). Because amount was already a variable, there's no change required when it becomes a parameter. You'll find the output is also the same when you run the function:

```
>>> calculate_interest(100, 0.03)
interest earned for savings 100 for year 1 is 3.0
interest earned for savings 103.0 for year 2 is 3.09
interest earned for savings 106.09 for year 3 is 3.1827
interest earned for savings 109.2727 for year 4 is 3.278181
interest earned for savings 112.550881 for year 5 is 3.37652643
interest earned for savings 115.92740743 for year 6 is 3.4778222229
interest earned for savings 119.405229653 for year 7 is 3.58215688959
interest earned for savings 122.987386542 for year 8 is 3.68962159627
interest earned for savings 126.677008139 for year 9 is 3.80031024416
interest earned for savings 130.477318383 for year 10 is 3.91431955149
```

2. Changing the function to pass in the year as a parameter also involves only minor changes:

```
>>> def calculate_interest(amount, rate, years):
...     for year in range(1, years):
...         interest = amount * rate
...         print('interest earned for savings %s for year %s is %s' %
...               (amount, year, interest))
...         amount = amount + interest
```

- We can now easily change the starting amount, the rate of interest and the number of years:

```
>>> calculate_interest(1000, 0.05, 6)
interest earned for savings 1000 for year 1 is 50.0
interest earned for savings 1050.0 for year 2 is 52.5
interest earned for savings 1102.5 for year 3 is 55.125
interest earned for savings 1157.625 for year 4 is 57.88125
interest earned for savings 1215.50625 for year 5 is 60.7753125
```

3. The mini-program is a bit more complicated than the functions we've already created. First we need to import the sys module so we can ask for input. Then we need to prompt the user of our program for each of the values. Apart from that, the function stays roughly the same:

```
>>> import sys
>>> def calculate_interest():
...     print('Enter the amount you have to save')
...     amount = float(sys.stdin.readline())
...     print('Enter the interest rate')
...     rate = float(sys.stdin.readline())
...     print('Enter the number of years')
...     years = int(sys.stdin.readline())
...     for year in range(1, years):
...         interest = amount * rate
...         print('interest earned for savings %s for year %s is %s' %
...               (amount, year, interest))
...         amount = amount + interest
```

When we run the function, we'll see something like the following:

```
>>> calculate_interest()
Enter the amount you have to save
500
Enter the interest rate
0.06
Enter the number of years
12
interest earned for savings 500.0 for year 1 is 30.0
interest earned for savings 530.0 for year 2 is 31.8
interest earned for savings 561.8 for year 3 is 33.708
interest earned for savings 595.508 for year 4 is 35.73048
interest earned for savings 631.23848 for year 5 is 37.8743088
interest earned for savings 669.1127888 for year 6 is 40.146767328
interest earned for savings 709.259556128 for year 7 is 42.5555733677
interest earned for savings 751.815129496 for year 8 is 45.1089077697
interest earned for savings 796.924037265 for year 9 is 47.8154422359
interest earned for savings 844.739479501 for year 10 is 50.6843687701
interest earned for savings 895.423848271 for year 11 is 53.7254308963
```

Chapter 8

1. There's a hard way to draw an octagon, and an easy way. The hard way, isn't hard because it's complicated. It's hard because it requires more typing:

```
import turtle
t = turtle.Pen()
>>> t.forward(50)
>>> t.right(45)
>>> t.forward(50)
```

You can see from that code that we tell the turtle to move forward 50 pixels, then turn right 45 degrees. We do this 8 times. Which is a lot of time. The easier way to draw an octagon is the following code (which produces the octagon in figure D.3):

```
>>> for x in range(0,8):
...     t.forward(50)
...     t.right(45)
```

2. If you take another look at the other functions in Chapter 8, you'll already see how to create a filled shape. We can convert the octagon code into a function that takes a colour, but we'll also want to reuse the hexcolour function

```
>>> def octagon(red, green, blue):
...     t.color(red, green, blue)
...     t.begin_fill()
...     for x in range(0,8):
...         t.forward(50)
...         t.right(45)
...     t.end_fill()
```

We set the colour, then turn filling on. Then we run the for loop to draw the octagon, finally we switch filling back off again to fill in the shape. How about a blue octagon (see figure D.4):

```
>>> octagon(0, 0, 1)
```




Figure D.3: Turtle drawing an octagon.




Figure D.4: Turtle drawing a blue octagon.

Index

- addition, 11
- blocks of code, 44
- conditions, 33
 - combining, 36
- date/time formats, 136
- degrees, 28
- equality, 38
- escape characters, 131
- floatingpoint, 10
- for-loop, 41
- functions, 54
 - abs, 119
 - bool, 119
 - cmp, 120
 - dir, 121
 - eval, 122
 - file, 57, 63, 122
 - close, 63
 - read, 63
 - write, 63
 - float, 122
 - int, 123
 - len, 124
 - max, 125
 - min, 125
 - range, 42, 125
 - sum, 127
- hexadecimal colors, 90
- if-statement, 33
- if-then-else-statement, 34
- Interpretador Python, 4
- keywords
 - and, 105
 - as, 105
 - assert, 106
 - break, 106
 - class, 107
 - del, 107
 - elif, 108
 - else, 108
 - except, 108
 - exec, 108
 - finally, 109
 - for, 109
 - from, 109
 - global, 111
 - if, 111
 - import, 112
 - in, 112
 - is, 113
 - lambda, 113
 - not, 113
 - or, 114
 - pass, 114
 - print, 116
 - raise, 116
 - return, 116
 - try, 116
 - while, 117
 - with, 117
 - yield, 117
- lists, 19

appending, 21
 joining, 22
 removing, 21
 replacing, 21
 modules, 59, 129
 os, 96
 random, 87, 129
 choice, 130
 randint, 129
 randrange, 87
 shuffle, 130
 sys, 59, 130
 exit, 130
 stdin, 60, 131
 stdout, 131
 version, 132
 time, 59, 132
 asctime, 133
 ctime, 134
 localtime, 59, 134
 sleep, 135
 strftime, 135
 strptime, 137
 time (function), 132
 tkinter, 83
 basic animation, 98
 bind_all, 100
 Canvas, 85
 create_arc, 91
 create_image, 96
 create_line, 85
 create_oval, 92
 create_polygon, 95
 create_rectange, 87
 events, 99
 move, 99
 modulo operator, 68
 multi-line string, 17
 multiplication, 9, 11
 named parameters, 84
 None, 36
 operators, 11
 order of operations, 11
 Pen, 26
 pixels, 27
 Python, 3
 return, 55
 scope, 55
 strings, 17
 subtraction, 11
 tuples, 23
 turtle, 25
 advanced, 65
 backward, 29
 clear, 29
 color, 69
 black, 72
 down (start drawing), 29
 fill, 72
 forward, 26
 reset, 29
 turning left, 27
 turning right, 27
 up (stop drawing), 29
 Variáveis, 15
 variable, 13
 while-loop, 50
 white space, 44