



FindMyFlick ZAP Report2

Sites: <https://nav-edge.smartscreen.microsoft.com> <https://findmyflick.com> <https://www.bing.com> <http://findmyflick.com>

ZAP Version: 2.17.0

ZAP by [Checkmarx](#)

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	4
Low	9
Informational	4

Alerts

Name	Risk Level	Number of Instances
Content Security Policy (CSP) Header Not Set	Medium	2
HTTP to HTTPS Insecure Transition in Form Post	Medium	2
Missing Anti-clickjacking Header	Medium	2
Sub Resource Integrity Attribute Missing	Medium	2
Big Redirect Detected (Potential Sensitive Information Leak)	Low	1
Cookie No HttpOnly Flag	Low	Systemic
Cookie with SameSite Attribute None	Low	5
Cookie without SameSite Attribute	Low	5
Cross-Domain JavaScript Source File Inclusion	Low	2
Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	Low	2
Strict-Transport-Security Header Not Set	Low	4
Timestamp Disclosure - Unix	Low	1
X-Content-Type-Options Header Missing	Low	7
Modern Web Application	Informational	1
Re-examine Cache-control Directives	Informational	1
Session Management Response Identified	Informational	3
User Agent Fuzzer	Informational	Systemic

Alert Detail

Medium	Content Security Policy (CSP) Header Not Set
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks, including Cross Site Scripting (XSS) and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	
Other Info	
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	
Other Info	
Instances	2
Solution	Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Guides/CSP https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html https://www.w3.org/TR/CSP/ https://w3c.github.io/webappsec-csp/ https://web.dev/articles/csp https://caniuse.com/#feat=contentsecuritypolicy https://content-security-policy.com/
CWE Id	693
WASC Id	15
Plugin Id	10038

Medium	HTTP to HTTPS Insecure Transition in Form Post
Description	This check looks for insecure HTTP pages that host HTTPS forms. The issue is that an insecure HTTP page can easily be hijacked through MITM and the secure HTTPS form can be replaced or spoofed.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	https://porkbun.com/checkout/search
	The response to the following request over HTTP included an HTTPS form tag action

Other Info	attribute value: http://findmyflick.com The context was: <form method="GET" action="https://porkbun.com/checkout/search"> <div class="form-group"> <label for="q">Find your own great domain:</label> <input class="form-control" type="text" id="q" name="q" placeholder="find your domain..."> </div> <button type="submit" class="btn btn-porkbun">Submit</button> </form>
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	https://porkbun.com/checkout/search
Other Info	The response to the following request over HTTP included an HTTPS form tag action attribute value: http://findmyflick.com/ The context was: <form method="GET" action="https://porkbun.com/checkout/search"> <div class="form-group"> <label for="q">Find your own great domain:</label> <input class="form-control" type="text" id="q" name="q" placeholder="find your domain..."> </div> <button type="submit" class="btn btn-porkbun">Submit</button> </form>
Instances	2
Solution	Use HTTPS for landing pages that host secure forms.
Reference	
CWE Id	319
WASC Id	15
Plugin Id	10041

Medium	Missing Anti-clickjacking Header
Description	The response does not protect against 'ClickJacking' attacks. It should include either Content-Security-Policy with 'frame-ancestors' directive or X-Frame-Options.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	
Other Info	
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	
Other Info	
Instances	2
Solution	Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers. Ensure one of them is set on all web pages returned by your site/app. If you expect the page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should use DENY. Alternatively consider implementing Content Security Policy's "frame-ancestors" directive.

Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/X-Frame-Options
CWE Id	1021
WASC Id	15
Plugin Id	10020

Medium	Sub Resource Integrity Attribute Missing
Description	The integrity attribute is missing on a script or link tag served by an external server. The integrity tag prevents an attacker who have gained access to this server from injecting a malicious content.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	<script async src="https://www.googletagmanager.com/gtag/js?id=UA-59154711-35"></script>
Other Info	
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	<script async src="https://www.googletagmanager.com/gtag/js?id=UA-59154711-35"></script>
Other Info	
Instances	2
Solution	Provide a valid integrity attribute to the tag.
Reference	https://developer.mozilla.org/en-US/docs/Web/Security/Subresource_Integrity
CWE Id	345
WASC Id	15
Plugin Id	90003

Low	Big Redirect Detected (Potential Sensitive Information Leak)
Description	The server has responded with a redirect that seems to provide a large response. This may indicate that although the server sent a redirect it also responded with body content (which may include sensitive details, PII, etc.).
URL	http://findmyflick.com/sitemap.xml
Node Name	http://findmyflick.com/sitemap.xml
Method	GET
Attack	
Evidence	
Other Info	Location header URI length: 23 [http://findmyflick.com/]. Predicted response size: 323. Response Body Length: 668.
Instances	1

Solution	Ensure that no sensitive information is leaked via redirect responses. Redirect responses should have almost no content.
Reference	
CWE Id	201
WASC Id	13
Plugin Id	10044

Low	Cookie No HttpOnly Flag
Description	A cookie has been set without the HttpOnly flag, which means that the cookie can be accessed by JavaScript. If a malicious script can be run on this page then the cookie will be accessible and can be transmitted to another site. If this is a session cookie then session hijacking may be possible.
URL	http://findmyflick.com/css/all.css
Node Name	http://findmyflick.com/css/all.css
Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	
URL	http://findmyflick.com/css/all.css
Node Name	http://findmyflick.com/css/all.css
Method	GET
Attack	
Evidence	Set-Cookie: AWSALBCORS
Other Info	
URL	http://findmyflick.com/images/parked-on-the-bun.png
Node Name	http://findmyflick.com/images/parked-on-the-bun.png
Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	
URL	http://findmyflick.com/images/parked-on-the-bun.png
Node Name	http://findmyflick.com/images/parked-on-the-bun.png
Method	GET
Attack	
Evidence	Set-Cookie: AWSALBCORS
Other Info	
URL	http://findmyflick.com/sitemap.xml
Node Name	http://findmyflick.com/sitemap.xml

Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	
Instances	Systemic
Solution	Ensure that the HttpOnly flag is set for all cookies.
Reference	https://owasp.org/www-community/HttpOnly
CWE Id	1004
WASC Id	13
Plugin Id	10010

Low	Cookie with SameSite Attribute None
Description	A cookie has been set with its SameSite attribute set to "none", which means that the cookie can be sent as a result of a 'cross-site' request. The SameSite attribute is an effective counter measure to cross-site request forgery, cross-site script inclusion, and timing attacks.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	Set-Cookie: AWSALBCORS
Other Info	
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	Set-Cookie: AWSALBCORS
Other Info	
URL	http://findmyflick.com/css/all.css
Node Name	http://findmyflick.com/css/all.css
Method	GET
Attack	
Evidence	Set-Cookie: AWSALBCORS
Other Info	
URL	http://findmyflick.com/images/parked-on-the-bun.png
Node Name	http://findmyflick.com/images/parked-on-the-bun.png
Method	GET
Attack	

Evidence	Set-Cookie: AWSALBCORS
Other Info	
URL	http://findmyflick.com/sitemap.xml
Node Name	http://findmyflick.com/sitemap.xml
Method	GET
Attack	
Evidence	Set-Cookie: AWSALBCORS
Other Info	
Instances	5
Solution	Ensure that the SameSite attribute is set to either 'lax' or ideally 'strict' for all cookies.
Reference	https://datatracker.ietf.org/doc/html/draft-ietf-httpbis-cookie-same-site
CWE Id	1275
WASC Id	13
Plugin Id	10054

Low	Cookie without SameSite Attribute
Description	A cookie has been set without the SameSite attribute, which means that the cookie can be sent as a result of a 'cross-site' request. The SameSite attribute is an effective counter measure to cross-site request forgery, cross-site script inclusion, and timing attacks.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	
URL	http://findmyflick.com/css/all.css
Node Name	http://findmyflick.com/css/all.css
Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	

URL	http://findmyflick.com/images/parked-on-the-bun.png
Node Name	http://findmyflick.com/images/parked-on-the-bun.png
Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	
URL	http://findmyflick.com/sitemap.xml
Node Name	http://findmyflick.com/sitemap.xml
Method	GET
Attack	
Evidence	Set-Cookie: AWSALB
Other Info	
Instances	5
Solution	Ensure that the SameSite attribute is set to either 'lax' or ideally 'strict' for all cookies.
Reference	https://datatracker.ietf.org/doc/html/draft-ietf-httpbis-cookie-same-site
CWE Id	1275
WASC Id	13
Plugin Id	10054

Low	Cross-Domain JavaScript Source File Inclusion
Description	The page includes one or more script files from a third-party domain.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	<script async src="https://www.googletagmanager.com/gtag/js?id=UA-59154711-35"></script>
Other Info	
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	<script async src="https://www.googletagmanager.com/gtag/js?id=UA-59154711-35"></script>
Other Info	
Instances	2
Solution	Ensure JavaScript source files are loaded from only trusted sources, and the sources can't be controlled by end users of the application.
Reference	

CWE Id	829
WASC Id	15
Plugin Id	10017

Low	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)
------------	--

Description	The web/application server is leaking information via one or more "X-Powered-By" HTTP response headers. Access to such information may facilitate attackers identifying other frameworks/components your web application is reliant upon and the vulnerabilities such components may be subject to.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	X-Powered-By: PHP/8.0.25
Other Info	
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	X-Powered-By: PHP/8.0.25
Other Info	
Instances	2
Solution	Ensure that your web server, application server, load balancer, etc. is configured to suppress "X-Powered-By" headers.
Reference	https://owasp.org/www-project-web-security-testing-guide/v42/4-Web_Application_Security_Testing/01-Information_Gathering/08-Fingerprint_Web_Application_Framework https://www.troyhunt.com/shhh-dont-let-your-response-headers/
CWE Id	497
WASC Id	13
Plugin Id	10037

Low	Strict-Transport-Security Header Not Set
------------	---

Description	HTTP Strict Transport Security (HSTS) is a web security policy mechanism whereby a web server declares that complying user agents (such as a web browser) are to interact with it using only secure HTTPS connections (i.e. HTTP layered over TLS/SSL). HSTS is an IETF standards track protocol and is specified in RFC 6797.
URL	https://findmyflick.com/
Node Name	https://findmyflick.com/
Method	GET
Attack	
Evidence	
Other Info	

URL	https://findmyflick.com/favicon.ico
Node Name	https://findmyflick.com/favicon.ico
Method	GET
Attack	
Evidence	
Other Info	
URL	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Node Name	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Method	GET
Attack	
Evidence	
Other Info	
URL	https://nav-edge.smartscreen.microsoft.com/api/browser/edge/navigate/3
Node Name	https://nav-edge.smartscreen.microsoft.com/api/browser/edge/navigate/3 ()({userAgent, redirectChain:[],enhancedRedirectChain:{redirectSource,referrerChain:[]},identity:{user:{locale},device:{id,customId,onlineIdTicket,family,locale,osVersion,browser:{internetExplorer},netJoinStatus,enterprise:{},cloudSku,architecture},caller:{locale,name,version},client:{version,data:{topTraffic,customSynchronousLookupUris,edgeSettings,customSettings}}},config:{user:{uriReputation:{enforcedByPolicy,level}},device:{appControl:{level},appReputation:{enforcedByPolicy,level}}},destination:{uri,ip},...)
Method	POST
Attack	
Evidence	
Other Info	
Instances	4
Solution	Ensure that your web server, application server, load balancer, etc. is configured to enforce Strict-Transport-Security.
Reference	https://cheatsheetseries.owasp.org/cheatsheets/HTTP_Strict_Transport_Security_Cheat_Sheet.html https://owasp.org/www-community/Security-Headers https://en.wikipedia.org/wiki/HTTP_Strict_Transport_Security https://caniuse.com/stricttransportsecurity https://datatracker.ietf.org/doc/html/rfc6797
CWE Id	319
WASC Id	15
Plugin Id	10035

Low	Timestamp Disclosure - Unix
Description	A timestamp was disclosed by the application/web server. - Unix
URL	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Node Name	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Method	GET
Attack	

Evidence	1776704674
Other Info	1776704674, which evaluates to: 2026-04-20 13:04:34.
Instances	1
Solution	Manually confirm that the timestamp data is not sensitive, and that the data cannot be aggregated to disclose exploitable patterns.
Reference	https://cwe.mitre.org/data/definitions/200.html
CWE Id	497
WASC Id	13
Plugin Id	10096

Low	X-Content-Type-Options Header Missing
Description	The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://findmyflick.com/css/all.css
Node Name	http://findmyflick.com/css/all.css
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://findmyflick.com/images/parked-on-the-bun.png
Node	

Name	http://findmyflick.com/images/parked-on-the-bun.png
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://findmyflick.com/robots.txt
Node Name	http://findmyflick.com/robots.txt
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Node Name	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	https://nav-edge.smartscreen.microsoft.com/api/browser/edge/navigate/3
Node Name	https://nav-edge.smartscreen.microsoft.com/api/browser/edge/navigate/3 ()({userAgent, redirectChain:[],enhancedRedirectChain:{redirectSource,referrerChain:[]},identity:{user:{locale},device:{id,customId,onlineIdTicket,family,locale,osVersion,browser:{internetExplorer},netJoinStatus,enterprise:{},cloudSku,architecture},caller:{locale,name,version},client:{version,data:{topTraffic,customSynchronousLookupUri,edgeSettings,customSettings}}},config:{user:{uriReputation:{enforcedByPolicy,level}},device:{appControl:{level},appReputation:{enforcedByPolicy,level}}},destination:{uri,ip},...)
Method	POST
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
Instances	7
Solution	Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages. If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application /web server to not perform MIME-sniffing.
Reference	https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85)

	https://owasp.org/www-community/Security-Headers
CWE Id	693
WASC Id	15
Plugin Id	10021

Informational	Modern Web Application
Description	The application appears to be a modern web application. If you need to explore it automatically Spider may well be more effective than the standard one.
URL	http://findmyflick.com/sitemap.xml
Node Name	http://findmyflick.com/sitemap.xml
Method	GET
Attack	
Evidence	<script defer src="https://static.cloudflareinsights.com/beacon.min.js/v8c78df7c7c0f484497ecbca7046644da1771523124516" integrity="sha512-8DS7rglrAmghBFwoOTujcf6D9rXvH8xm8JQ1Ja01h9QX8EzXldiszufYa4IFfKdLUKTTnSFXLDk data-cf-beacon="{\"version\":\"2024.11.0\",\"token\":\"e0d901cd96904b31889fe26f9eddc7ac\",\"r\":1,\"s\":{\"name\":{\"cfCacheStatus\":true,\"cfEdge\":true,\"cfExtPri\":true,\"cfL4\":true,\"cfOrigin\":true,\"cfSpeedB location_startswith\":\"null\"}}\" crossorigin=\"anonymous\"></script>
Other Info	No links have been found while there are scripts, which is an indication that this is a modern we
Instances	1
Solution	This is an informational alert and so no changes are required.
Reference	
CWE Id	
WASC Id	
Plugin Id	10109

Informational	Re-examine Cache-control Directives
Description	The cache-control header has not been set properly or is missing, allowing the browser and proxies to cache content. For static assets like css, js, or image files this might be intended, however, the resources should be reviewed to ensure that no sensitive content will be cached.
URL	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Node Name	https://www.bing.com/bloomfilterfiles/ExpandedDomainsFilterGlobal.json
Method	GET
Attack	
Evidence	
Other Info	
Instances	1
Solution	For secure content, ensure the cache-control HTTP header is set with "no-cache, no-store, must-revalidate". If an asset should be cached consider setting the directives "public, max-age, immutable".
Reference	https://cheatsheetseries.owasp.org/cheatsheets/Session_Management_Cheat_Sheet.html#web-content-caching https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/Cache-Control https://grayduck.mn/2021/09/13/cache-control-recommendations/
CWE Id	525

WASC Id	13
Plugin Id	10015

Informational	Session Management Response Identified
---------------	--

Description	The given response has been identified as containing a session management token. The 'Other Info' field contains a set of header tokens that can be used in the Header Based Session Management Method. If the request is in a context which has a Session Management Method set to "Auto-Detect" then this rule will change the session management to use the tokens identified.
URL	http://findmyflick.com
Node Name	http://findmyflick.com
Method	GET
Attack	
Evidence	AWSALBCORS
Other Info	cookie:AWSALBCORS cookie:AWSALB
URL	http://findmyflick.com/
Node Name	http://findmyflick.com/
Method	GET
Attack	
Evidence	AWSALBCORS
Other Info	cookie:AWSALBCORS cookie:AWSALB
URL	http://findmyflick.com/sitemap.xml
Node Name	http://findmyflick.com/sitemap.xml
Method	GET
Attack	
Evidence	AWSALBCORS
Other Info	cookie:AWSALBCORS cookie:AWSALB
Instances	3
Solution	This is an informational alert rather than a vulnerability and so there is nothing to fix.
Reference	https://www.zaproxy.org/docs/desktop/addons/authentication-helper/session-mgmt-id/
CWE Id	
WASC Id	
Plugin Id	10112

Informational	User Agent Fuzzer
---------------	-------------------

Description	Check for differences in response based on fuzzed User Agent (eg. mobile sites, access as a Search Engine Crawler). Compares the response statuscode and the hashcode of the response body with the original response.
URL	http://findmyflick.com/css
Node Name	http://findmyflick.com/css
Method	GET

Attack	Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 6.0)
Evidence	
Other Info	
URL	http://findmyflick.com/css
Node Name	http://findmyflick.com/css
Method	GET
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
URL	http://findmyflick.com/images
Node Name	http://findmyflick.com/images
Method	GET
Attack	Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 6.0)
Evidence	
Other Info	
URL	http://findmyflick.com/images
Node Name	http://findmyflick.com/images
Method	GET
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
URL	http://findmyflick.com/sitemap.xml
Node Name	http://findmyflick.com/sitemap.xml
Method	GET
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
Instances	Systemic
Solution	
Reference	https://owasp.org/wstg
CWE Id	
WASC Id	
Plugin Id	10104