

# Quarto template

## Table of contents

|  |          |
|--|----------|
| <b>Quarto vs Rmarkdown</b>                         | <b>1</b> |
| A more comprehensive list of differences . . . . . | 2        |
| An example . . . . .                               | 2        |

## Quarto vs Rmarkdown

Note **Quarto** (.qmd file) is just a “new”, more flexible **Rmarkdown** (.rmd file).

The only difference I’ve noticed for our purposes, when including R code, is:

- instead of including code chunk options between the code chunk opening’s curly braces “{...}”,
- the options are specified in the lines below starting the line with “#|”

So in Rmarkdown you might do the following (ignore the first comment character “#” on each line in the below code chunk):

```
# <!-- Rmarkdown version -->
# ```${r, some_option = "option value", some_other_option = FALSE}
# ... some code ...
# ````
```

You equivalently do (ignore the first comment character “#” on each line in the below code chunk):

```
# <!-- Quarto version -->
# ```${r}
# #| some_option: "option value"
# #| some_other_option: false
```

```
# ... some code ...  
# ``
```

## A more comprehensive list of differences

[This FAQ page](#)

## An example

If reading this from the pdf output - please see the `.qmd` code chunk to see what generates this code/output.

```
x <- 10  
x
```

```
[1] 10
```