



Lehrstuhl für
Eingebettete Systeme
der Informationstechnik



Design and Implementation of an LDPC-based FEC encoder/decoder suitable for Storage devices

Schriftliche Prüfungsarbeit für die Bachelorprüfung der Fakultät für Elektrotechnik und Informationstechnik an der Ruhr-Universität Bochum (Bachelor-Prüfungsordnung für den Studiengang „Elektrotechnik und Informationstechnik“ an der Ruhr-Universität Bochum vom 12. August 2013)

vorgelegt von:

Henry Bathke

Datum: September 18, 2018

| | |
|-------------------|------------------------------|
| erster Betreuer: | Prof. Dr.-Ing Michael Hübner |
| zweiter Betreuer: | M. Sc. Keyvan Shahin |

Eidesstattliche Erklärung

Ich erkläre, dass ich keine Arbeit in gleicher oder ähnlicher Fassung bereits für eine andere Prüfung an der Ruhr-Universität Bochum oder einer anderen Hochschule eingereicht habe.

Ich versichere, dass ich diese Arbeit selbstständig verfasst und keine anderen als die angegebenen Quellen benutzt habe. Die Stellen, die anderen Quellen dem Wortlaut oder dem Sinn nach entnommen sind, habe ich unter Angabe der Quellen kenntlich gemacht. Dies gilt sinngemäß auch für verwendete Zeichnungen, Skizzen, bildliche Darstellungen und dergleichen.

Ich versichere auch, dass die von mir eingereichte schriftliche Version mit der digitalen Version übereinstimmt. Ich erkläre mich damit einverstanden, dass die digitale Version dieser Arbeit zwecks Plagiatsprüfung verwendet wird.

Official Declaration

Hereby I declare, that I have not submitted this thesis in this or similar form to any other examination at the Ruhr-Universität Bochum or any other Institution of University.

I officially ensure, that this paper has been written solely on my own. I herewith officially ensure, that I have not used any other sources but those stated by me. Any and every parts of the text which constitute quotes in original wording or in its essence have been explicitly referred by me by using official marking and proper quotation. This is also valid for used drafts, pictures and similar formats.

I also officially ensure, that the printed version as submitted by me fully confirms with my digital version. I agree that the digital version will be used to subject the paper to plagiarism examination.

Not this English translation, but only the official version in German is legally binding.

Datum / Date

Unterschrift / Signature

1. Abstract

Contents

| | |
|--|-----------|
| 1. Abstract | 3 |
| 2. Motivation | 7 |
| 3. Error Correcting Codes | 8 |
| 3.1. Low-Density Parity-Check (LDPC) Codes | 8 |
| 3.1.1. Encoding | 9 |
| 4. Field Programmable Gate Array (FPGA) | 10 |
| 5. Approach | 11 |
| 6. Implementation | 12 |
| 7. Results | 13 |
| A. Appendix | 14 |

List of Figures

| | |
|---------------------------------------|---|
| 3.1. An example Tanner graph. | 8 |
|---------------------------------------|---|

List of Tables

2. Motivation

3. Error Correcting Codes

For modern communications systems reliable data transmission and storage is required. To achieve this goal usually error correcting codes are used. There are different possible codes available for error correction, but I will restrain myself to LDPC[1] codes in this thesis. As these codes can archive good performance and can be used at large block lengths[4]. This is especially useful for use with NAND based solid state drives.

When describing a block code there are important parameters as the message length k . The message is what is given into the encoder and the result from the decoder. The block length n is the length of the encoded message which is transmitted over the channel. And the rate $R = k/n$.

3.1. Low-Density Parity-Check (LDPC) Codes

The following section will describe LDPC codes invented by Robert Gallager[1]. Starting with a graph representation I will describe the LDPC code and then continue with a matrix representation. LDPC codes can be shown as a bipartite graph also called Tanner graph[5] based on their inventor. figure 3.1 shows an example of one, where the check and parity nodes are connected by edges. This is an effective representation, moreover it will also help understanding the decoding algorithm later.

Instead of using the Tanner graph one can also use a matrix representation. In this matrix the ones represent the edges of the graph. Usually for a LDPC code the matrix is sparse or




Figure 3.1.: An example Tanner graph.

low density as the name implies. In equation (3.1) a matrix representing the same code as in the graph in figure 3.1 is shown. The \mathbf{H} matrix is of size $(n - k) \times n$. And the possible code words are given by the null space of \mathbf{H} , so in other words c is a code word if and only if $c\mathbf{H}^T = \mathbf{0}$ [3].

$$\mathbf{H} = \begin{bmatrix} 0 & 1 & 0 & 1 & 1 & 0 & 0 & 1 \\ 1 & 1 & 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 & 1 & 1 \\ 1 & 0 & 0 & 1 & 1 & 0 & 1 & 0 \end{bmatrix} \quad (3.1)$$

3.1.1. Encoding

Generator Matrix

For encoding the probably simplest algorithm is transforming the parity check matrix into systematic form $\mathbf{H} = [-\mathbf{A}^T \quad \mathbf{I}_{n-k}]$. Where \mathbf{I}_{n-k} is a $n - k \times n - k$ identity matrix and \mathbf{A} has $k \times n - k$ elements. To archive this form one could for example use gaussian elimination. With \mathbf{A} known I can construct the generator matrix $\mathbf{G} = [\mathbf{I}_k \quad \mathbf{A}]$. Now encoding can be done with a simple matrix multiplication. With u the information word and v the code word is given by $v = u\mathbf{G}$.

The main disadvantage of this strategy is the high computational complexity. When transforming the parity check matrix into systematic form we have a complexity of $\mathcal{O}(n^3)$. This is not too bad as it will mostly be done offline and only the \mathbf{G} matrix stored in the encoder, but the bigger problem is that due to the gaussian elimination the matrix is no longer sparse. Thus the matrix multiplication will result in a complexity of $\mathcal{O}(n^2)$ [2].

Approximate Lower Triangular Form

4. Field Programmable Gate Array (FPGA)

write
some ba-
sics about
FPGA

5. Approach

6. Implementation

7. Results

A. Appendix

Bibliography

- [1] Robert R. Gallager. “Low-Density Parity-Check Codes”. In: (1963).
- [2] Hanghang Qi and Norbert Goertz. “Low-Complexity Encoding of LDPC Codes: A New Algorithm and its Performance”. In: ().
- [3] Thomas J. Richardson and Rüdiger L. Urbanke. *Efficient Encoding of Low-Density Parity-Check Codes*. 2001. DOI: 10.1109/18.910579.
- [4] Bashar Tahir, Stefan Schwarz, and Markus Rupp. “BER comparison between Convolutional, Turbo, LDPC, and Polar codes”. In: (2017). DOI: 10.1109/ICT.2017.7998249.
- [5] M. Tanner. “A recursive approach to low complexity codes”. In: (1981). DOI: 10.1109/TIT.1981.1056404.