


BILL OF MATERIAL							
LINE #	QTY	PC MARK	DESCRIPTION	LENGTH	REMARKS	WEIGHT TOTAL	ADVANCE MILL #
	ONE	F-08.03M1	BENT PLATE			53	
	1	F-08.03M1	PL 1/2x15 1/16	2 0	BENT A36	53	
			FIELD BOLTS				
	3		3/4 Dia HILTI HAS V-36	0 8	(6" EMBED)		
			THREADED ROD				
			w/HILTI HY-200				
	3	F-08.03M2	BENT PLATE			196	
	3	F-08.03M2	PL 1/2x19 3/16	2 0	BENT A36	196	
			FIELD BOLTS				
	9		3/4 Dia HILTI HAS V-36	0 8	6" EMBED		
			THREADED ROD				
			w/HILTI HY-200				
	3	F-08.03M3	HSS			29	
	3	F-08.03M3	HSS 3/4x3 1/2x9 3/16	0 7 1/2	A500C	24	
	6	p3257	PL 1/4x3 1/2	0 3 1/2	A36	5	
	4	F-08.03M4	HSS			431	
	4	F-08.03M4	HSS 5/8x3 1/8	4 2	A500C	373	
	4	a154	LS 5/8x3 1/8	0 10	A36	34	
	8	p3256	PL 1/4x5	0 5	A36	14	
	8		3/4 Dia A325N	0 6 1/2	+1HD WASH	10	
			FIELD BOLTS				
	8		1/2 Dia HILTI KB-T22	0 7			
			EXPANSION ANCHOR		(5 1/2" EMBEDMENT)		
	ONE	F-08.03M5	ANGLE			2	
	1	F-08.03M5	L4x4x1/4	0 4	A36	2	
	ONE	F-08.03M6	PLATE			7	
	1	F-08.03M6	PL 1/4x7	1 1 1/2	A36	7	
	ONE	F-08.03EP1	EMBED PLATE			440	
	1	F-08.03EP1	PL 3/4x15	11 6	A36	440	
	ONE	F-08.03EP2	EMBED PLATE			177	
	1	F-08.03EP2	PL 5/8x20	4 2	A36	177	
			FIELD BOLTS				
	8		3/4 Dia HILTI HAS V-36	0 8	(5" EMBEDMENT)		
			w/ HILTI HY-200 EPOXY				

Total weight : 1336



PAINT	:NO PAINT
PREPARATION	:SSPC-SP3

- *Structural steel shall conform to ASTM-A992.
- *Structural SQR/RND.tubing conform to ASTM A500 Grade C
- *Pipe shall conform to ASTM A53, Grade B.
- *Channels, Angles and plates shall conform to A36.
- *All bolts shall be $\frac{3}{4}$ " High strength in accordance with ASTM A325 (UNO)
- *Welding Electrodes for Carbon steel :E70xx

IRON FABRICATION SERVICES, LLC

Location: **1250 MARYLAND AVENUE SW**
WASHINGTON, DC 20024

Contractor:

BALFOUR BEATTY

--	--

Drawing # 1-00.00	
Contract Item: PLATE & ANGLE DETAIL	

Ref:

Date:	Drawing Title:
-------	----------------

01/ 23/ 2025	MISCELLANEOUS DETAIL
Scale	

--	--