




ONE HSS6x6x $\frac{5}{16}$ x3-6 $\frac{3}{4}$ hss3790

GRADE: A500C

General Notes

*Structural steel shall conform to ASTM-A992.
 *Structural SQR/RND tubing conform to ASTM A500 Grade C
 *Pipe shall conform to ASTM A53, Grade B.
 *Channels, Angles and plates shall conform to A36.
 *All bolts shall be $\frac{3}{4}$ " High strength in accordance with ASTM A325 (UNO)
 *Welding Electrodes for Carbon steel :E70xx
 *Structural members are to be shop primer (U.N.O).
 *Surface Preparation-SSPC-SP3 UNO.
 *If welds exposed to view, should be ground smooth.

1	0	FOR FABRICATION	11-14-2025
# of Copies	Revision/Issue	Destination	Date

IRON FABRICATION SERVICES, LLC.

3029 M. Street, NW, Suite 202
 Washington, DC 20007
 Tel: 202-800-5599
 Fax: 202-478-0303

Project Name and Address

MARYLAND AVENUE

Location: **1250 MARYLAND AVENUE SW
 WASHINGTON, DC 20024**

Contractor:

BALFOUR BEATTY

Approved for Fabrication by:

Signature

Contract # **224009**

Drawing # **hss3790**

Contract Item: **HSS**

Ref:

SOW -10:F-10.00-F-10.05

Date
01/23/2025

Drawing Title:
HSS

Scale
VARIES

HOLE: $\frac{13}{16}$ Ø (U.N.O)