Caleb Logemann MATH 517 Finite Difference Methods Homework 2

1. Consider the 2-pt boundary value problem:

$$-u'' = f(x) \text{ on } 0 < x < L$$

$$u(0) = \alpha, \quad u'(L) = \sigma.$$

Discretize this problem using the $O(h^2)$ central finite differences and a ghost point near x = L to handle the Neumann boundary condition. Write out the resulting linear system.

To discretize this problem let $x_i = ih$ where $h = \frac{L}{N+1}$ and N is the number of points in the discretization. Thus the solution to this BVP will be approximated on these grid points. Let U_i be the approximate value of $u(x_i)$. Thus an approximate solution to this BVP will be the values of U_i for $0 \le i \le N+1$. From the boundary conditions, it can be noted that $U_0 = \alpha$. The other boundary condition can be handled by introducing a ghost point U_{N+2} with the following two conditions

$$\frac{1}{h^2}(-U_N + 2U_{N+1} - U_{N+2}) = f(x_{N+1}) = f(L)\frac{1}{2h}(U_{N+2} - U_N) = \sigma$$

In other words the central finite difference for the second derivative must hold on U_N , 2_{N+1} , and U_{N+2} , and the central difference for the first derivative must equal σ when centered on U_{N+1} . These two equations can be combined so that the ghost point U_{N+2} no longer appears in our finite difference method.

$$\frac{1}{h^2}(-2U_N + 2U_{N+1}) = f(x_{N+1}) + \frac{2\sigma}{h}$$

Now instead of a system of N equations for $i=1,2,\ldots,N$, we have a system of N+1 equations for $i=1,2,\ldots,N+1$. For $i=2,\ldots,N$, the central finite difference can be applied directly to the PDE to result in the following N-1 equations.

$$\frac{1}{h^2}(-U_{i-1} + 2U_i - U_{i+1}) = f(x_i)$$

For i = 1, we simply replace U_0 with α and simplify to

$$\frac{1}{h^2}(2U_1 - U_2) = f(x_1) + \frac{\alpha}{h^2}$$

For i = N + 1, we use the equation we found before after removing the ghost point.

$$\frac{1}{h^2}(-2U_N + 2U_{N+1}) = f(x_{N+1}) + \frac{2\sigma}{h}$$

Then this system of equations cen be written as a matrix equation as follows

$$A\mathbf{U} = \mathbf{f}$$

where

$$\mathbf{U} = [U_1, U_2, \cdots, U_{N+1}]^T$$

$$\mathbf{f} = \left[f(x_1) + \frac{\alpha}{h^2}, f(x_2), \cdots, f(x_N), f(x_{N+1}) + \frac{2\sigma}{h} \right]^T$$

$$A = \frac{1}{h^2} \begin{bmatrix} 2 & -1 & & \\ -1 & 2 & -1 & & \\ & \ddots & \ddots & \ddots & \\ & & -1 & 2 & -1 \\ & & & -2 & 2 \end{bmatrix}$$

2. Find the Green's function that satisfies:

$$-G'' = \delta(x - \xi), \quad G(0; \xi) = 0, \quad G'(L; \xi) = 0.$$

- 3. Use the result from Problem 2 to write out the exact solution to the boundary value problem with general f(x), α , and σ .
- 4. Use the results from Problems 2 and 3 to find the exact inverse to the finite difference matrix found in Problem 1.
- 5. Use the result in Problem 4 to prove that the finite difference method in Problem 1 is L_{∞} -stable.
- 6. Consider the uniform mesh $x_i = jh$ and let

$$U_j = u(x_j)$$
 and $W_j \approx u'(x_j)$.

In standard finite differences, we typically find linear combinations of U_j to define the approximation W_i to $u'(x_j)$:

$$W_i = \sum_j \beta_j U_j$$

In compact finite differences we are allowed to generalize this to

$$\sum_{j} \alpha_{j} W_{j} = \sum_{j} \beta_{j} U_{j}$$

Find the compact finite difference with the optimal local truncation error that has the following form:

$$\alpha W_{j-1} + W_j + \alpha W_{j+1} = \beta \left(\frac{U_{j+1} - U_{j-1}}{2h} \right).$$

We can find the local truncation error by inserting the exact solution into the finite difference equation and using Taylor series.

$$\tau_{j} = -\alpha u'(x_{j-1}) - u'(x_{j}) - \alpha u'(x_{j+1}) + \beta \left(\frac{u(x_{j+1}) - u(x_{j-1})}{2h}\right)$$

$$u(x_{j-1}) = u(x_{j}) - hu'(x_{j}) + \frac{h^{2}}{2}u''(x_{j}) - \frac{h^{3}}{6}u'''(x_{j}) + \frac{h^{4}}{24}u^{(4)}(x_{j}) - \frac{h^{5}}{120}u^{(5)}(x_{j}) + O(h^{6})$$

$$u(x_{j+1}) = u(x_{j}) + hu'(x_{j}) + \frac{h^{2}}{2}u''(x_{j}) + \frac{h^{3}}{6}u'''(x_{j}) + \frac{h^{4}}{24}u^{(4)}(x_{j}) + \frac{h^{5}}{120}u^{(5)}(x_{j}) + O(h^{6})$$

$$u'(x_{j-1}) = u'(x_{j}) - hu''(x_{j}) + \frac{h^{2}}{2}u'''(x_{j}) - \frac{h^{3}}{6}u^{(4)}(x_{j}) + \frac{h^{4}}{24}u^{(5)}(x_{j}) - \frac{h^{5}}{120}u^{(6)}(x_{j}) + O(h^{6})$$

$$u'(x_{j+1}) = u'(x_{j}) + hu''(x_{j}) + \frac{h^{2}}{2}u'''(x_{j}) + \frac{h^{3}}{6}u^{(4)}(x_{j}) + \frac{h^{4}}{24}u^{(5)}(x_{j}) + \frac{h^{5}}{120}u^{(6)}(x_{j}) + O(h^{6})$$

Substituting in these Taylor series and simplifying results in

$$\tau_j = (-1 - 2\alpha + \beta)u'(x_j) + \frac{h^2}{6}(-6\alpha + \beta)u^{(3)}(x_j) + \frac{h^4}{120}(-10\alpha + \beta)u^{(5)}(x_j) + O(h^6)$$

To make the local truncation error as small as possible, we must choose α and β such that the following two equations are satisfied.

$$0 = -1 - 2\alpha + \beta$$
$$0 = -6\alpha + \beta$$

If both of these equations are satisfied then this finite difference will be a fourth order approximation. These two equations can be solved as follows.

$$\beta = 6\alpha$$

$$0 = -1 - 2\alpha + 6\alpha$$

$$1 = 4\alpha$$

$$\alpha = \frac{1}{4}$$

$$\beta = \frac{3}{2}$$

If α and β are set to these values, then the local truncation error becomes

$$\tau_j = \frac{h^4}{120}(-10\alpha + \beta)u^{(5)}(x_j) + O(h^6)$$

Thus the compact finite difference operator will be

$$\frac{1}{4}W_{j-1} + W_j + \frac{1}{4}W_{j+1} = 3\left(\frac{U_{j+1} - U_{j-1}}{4h}\right).$$

which is 4th order accurate, because the local truncation error is $\tau = O(h^4)$.

7. Consider Poisson's equation in 2D:

$$-u_{xx} - u_{yy} = f(x, y)$$
 in $\Omega = [0, 1] \times [0, 1],$
 $u = g(x, y)$ on $\partial \Omega$

Discretize this equation using the 5-point Laplacian on a uniform mesh $\Delta x = \Delta y = h$. Use the standard natural row-wise ordering.

First we need to specify the discretization of the space Ω . Let $x_i = ih$ for i = 0, 1, ..., N+1 and let $y_j = jh$ for j = 0, 1, ..., N+1, where $h = \frac{1}{N+1}$. Then the solution to this PDE can be described by approximating u on this mesh, that is $U_{i,j} \approx u(x_i, y_j)$ is an approximation to the exact solution.

Now we can apply finite differences to this PDE. The 5-point Laplacian on a uniform mesh is given by

$$\Delta u \approx \frac{1}{h^2} (U_{i-1,j} + U_{i+1,j} + U_{i,j-1} + U_{i,j+1} - 4U_{i,j}).$$

Using this finite difference in the PDE results in the following set of equations

$$\frac{1}{h^2}(4U_{i,j} - U_{i-1,j} - U_{i+1,j} - U_{i,j-1} - U_{i,j+1}) = f_{ij}$$

where $f_{ij} = f(x_i, y_j)$.

Now in order to turn this into a linear system, a new numbering scheme needs to be imposed. I will use the natural row-wise ordering where each point is numbered along the rows starting at $U_{1,1} = U_1$. In general $U_k = U_{i,j}$ when k = i + (j-1)N.

Using this numbering scheme

8. Write a MATLAB code that constructs the sparse coefficient matrix A and the appropriate right hand side vector \mathbf{F} .

The following function solves the 2D Poisson equations on $[0, L] \times [0, L]$, with source function f, Dirichlet boundary conditions g, and N points in the x and y discretization.

```
function [U, Ux, Uy] = Poisson2D(f, q, L, N)
   p = inputParser;
   p.addRequired('f', @Utils.isFunctionHandle);
   p.addRequired('g', @Utils.isFunctionHandle);
   p.addRequired('L', @(x) isnumeric(x) && x > 0);
   p.addRequired('N', @Utils.isInteger);
   p.parse(f, g, L, N);
   h = L/(N+1);
   x = 0:h:L;
   y = 0:h:L;
   % create functions to swap between row-wise ordering and i,j ordering
   %kFun = @(i, j) i + (j-1)*N;
   iFun = @(k) \mod(k-1,N)+1;
    jFun = @(k) floor((k-1)/N) + 1;
   k = 1:N^2;
   % create vectors for x and y positions for each entry in U
   Ux = x(iFun(k) + 1);
   Uy = y(jFun(k) + 1);
   % vector of forcing function values at each index k
   F = h^2 * f(Ux, Uy);
   \alpha(0(k) h^2*f(x(iFun(k) + 1), y(jFun(k) + 1)), k);
   % add on boundary conditions to F
   % add bottom boundary
   kBottom = 1:N;
   F(kBottom) = F(kBottom) + g(x(2:N+1),0);
   % add top boundary
   kTop = (N^2-N+1):N^2;
   F(kTop) = F(kTop) + g(x(2:N+1), L);
   % add left boundary
   kLeft = 1:N: (N^2-N)+1;
   F(kLeft) = F(kLeft) + g(0, y(2:N+1));
   % add right boundary
   kRight = N:N:N^2;
   F(kRight) = F(kRight) + g(L, y(2:N+1));
   % build sparse matrix A
   % build main diagonal
   iMain = k';
    jMain = k';
   sMain = 4 * ones(N^2, 1);
   % build upper main diagonal
   iUpper = k';
   iUpper(N:N:N^2) = [];
   jUpper = k';
   jUpper(1:N:N^2) = [];
   sUpper = -ones(size(iUpper));
   % build lower main diagonal
   iLower = jUpper;
   jLower = iUpper;
   sLower = sUpper;
   % build off upper diagonal
   iU = (1:(N^2-N))';
    jU = ((N+1):N^2)';
   sU = -ones(size(iU));
   % build off lower diagonal
   iL = jU;
   jL = iU;
```

```
sL = sU;

iA = [iMain; iUpper; iLower; iU; iL];
    jA = [jMain; jUpper; jLower; jU; jL];
    sA = [sMain; sUpper; sLower; sU; sL];
    A = sparse(iA, jA, sA);

U = A\F';

% change U from 1D vector to 2D matrix
%U = vec2mat(U, N);
end
```

9. Using your code, do a numerical convergence study for the following right-hand side forcing and exact solution:

$$f(x,y) = -1.25e^{x+.5y}$$
 and $u(x,y) = e^{x+.5y}$

The following code evaluates the function from the previous problem for the given BVP.

```
f = @(x,y) -1.25*exp(x + .5*y);
u = 0(x,y) \exp(x + .5*y);
Error = [];
for N = [10*2.^(0:5)]
    [U, Ux, Uy] = Poisson2D(f, u, 1, N);
   uExact = u(Ux, Uy);
     USquare = vec2mat(U,N);
     uExactSquare = vec2mat(uExact,N);
     figure;
     surf (USquare);
     hold on
     surf (uExactSquare);
     pause
    Error = [Error; Ux(2) - Ux(1), norm(U - uExact', 'inf')];
end
hRatios = Error(1:end-1,1)./Error(2:end,1);
errorRatios = Error(1:end-1,2)./Error(2:end,2);
order = log(errorRatios)./log(hRatios);
table (hRatios, errorRatios, order)
```

>> H02_9

ans =

hRatios	${\tt errorRatios}$	order
1.9091	3.6179	1.9886
1.9524	3.8055	1.9975
1.9756	3.9002	1.9989
1.9877	3.9498	1.9996
1.9938	3.975	1.9999