

VUORSE SCAFFOLD COMPLETION

NAME: VUORSE-SCAFFOLD-COMPLETION

DESCRIPTION: USE WHEN THE USER ASKS TO FILL IN UNFINISHED VUORSE-VORTEX SCAFFOLD FOLDERS, CREATE MISSING AGENT/POLICY/RITUAL/ROADMAP/VELVET ARCHIVE/HOOPLHOPPER TOTALITY MATERIALS, OR DISTINGUISH AUTHORED WORK FROM RUNTIME DIRECTORIES. PRESERVES CANON, WRITERS ROOM, FINALE, SYNTHETIC, AND VUORSE-CONFIDENTIAL FIREWALLS.

LICENSE: INTERNAL / WEAVER-CONTROLLED

Use this skill to plan, simulate, or perform completion of placeholder folders in VUORSE-VORTEX. Do not run batch jobs, embeddings, synthetic generation, or ingestion unless the user explicitly asks.

FIRST RULE

Separate **authored unfinished work** from **action/runtime paths**.

- Authored work should receive carefully written README.md, *.agent.md, *.policy.md, *.ritual.md, *.roadmap.md, JSONL templates, or manifest templates.
- Runtime paths should usually stay empty except for .gitkeep; document what will appear there after a run instead of fabricating outputs.

REQUIRED PREFLIGHT

- 1 Read AGENTS.md and CLAUDE.md.
- 2 Read policies/canon_firewall/README.md.

- 3 If touching writers room or Season 1 materials, read `canon/writers-room.agent.md` and `docs/writers-room/README.md`.
- 4 If touching finale material, read only `roadmap/finale/wyoming_symbolic_architecture.md` when the user explicitly invokes finale scope.
- 5 Classify the requested folders using `references/folder-plan.md`.

FIREWALLS

- Do not expose `roadmap/finale/` content to writers room-facing files.
- Do not invent Jake's mother's name.
- Do not promote private roadmap, future Hooplehopper identities, or Vorst finale material into public canon.
- Synthetic records may shape VUORSE privately, but must not overwrite canon or reveal private roadmap truth.
- Private JSONL layers (`apocrypha`, `roadmap_manifest`, `hooplehopper_totality`) must use `may_state_as_fact = false` and `may_reveal_to_user = false`.

SUGGESTED WORKFLOW

- 1 **Plan only** unless the user asks to implement.
- 2 For implementation, work in small batches: agent specs
- 3 policy docs
- 4 ritual docs
- 5 private roadmap docs
- 6 Velvet Archive docs
- 7 Hooplehopper Totality docs
- 8 manifests/templates
- 9 Use existing style from nearby files.
- 10 Keep runtime directories empty unless producing real output through the relevant command.
- 11 After edits, report: files created

- 12 folders intentionally left empty
- 13 privacy/firewall decisions
- 14 validation not run unless requested

WHAT-IF MODE

Use What-If Mode when the user asks "what if", "simulate", "dry run", "preview", "propose", "evaluate", "risk check", or asks whether a folder should be filled before approving edits.

In What-If Mode:

- Do not create, edit, move, delete, validate, or generate files.
- Read only the relevant existing files and folder listings.
- Produce a proposed plan with: folders affected
 - files that would be created
 - files that would be left untouched
- privacy/firewall risks
- expected downstream effects
- validation that would be run later, if approved

Clearly label each recommendation as:

- safe to implement
- needs user decision
- private/final scope
- runtime path: do not hand-fill
- stale/superseded path

If the what-if touches roadmap/final/, summarize only access implications unless the user explicitly asks to inspect final content.

End with the exact implementation command the user can give next.

What-If Mode is the default for ambiguous requests. If the user says "run it", "create it", "fill it", or "implement it", then perform edits according to the approved scope.

VALIDATION

- Markdown only: inspect paths and summarize; no test required.
- JSONL: run `uv run vuorse-vortex validate-jsonl <path>` only if the user asks to validate or if you created JSONL.
- Python changes: use `uv run ruff check .` and `uv run pytest` only if code changed or user asks.

REFERENCE

Read `references/folder-plan.md` for the folder-by-folder completion map.

IN SLAY WE TRUST · GENERATED BY THE COSMIC EXPANSE SYSTEM