



TDG Access API Documentation

Comprehensive guide for integrating with the Tire Discounter Group API

Revision: January 30th, 2026, Version 1.0.44



Confidentiality Notice: This document contains confidential information and is intended solely for authorized recipients. It may not be reproduced, distributed, or disclosed to any third party without prior written consent from Tire Discounter Group, Inc..

Introduction to the TDG Access API	4
Environments.....	4
1. Production Environment.....	4
2. Sandbox Environment.....	4
Authentication	5
Authentication Format	5
Example Request	6
Important Notes	6
Getting Started.....	7
Inventory Search Endpoint	8
Endpoint Description.....	8
Request.....	8
Response.....	9
Inventory All Endpoint.....	12
Endpoint Description.....	12
Request.....	12
Response.....	12
Product Search Endpoint	15
Endpoint Description	15
Request.....	15
Response	16
Product All Endpoint	18
Endpoint Description	18
Request.....	18
Response.....	18
Account ShippingAddresses Endpoint	20
Endpoint Description	20
Request.....	20
Response.....	20
Account ShippingMethods Endpoint.....	21
Endpoint Description	21

Request.....	21
Response.....	21
Account PickupLocations Endpoint	22
Endpoint Description	22
Request.....	22
Response.....	23
Account PaymentMethods Endpoint	23
Endpoint Description	23
Request.....	24
Response.....	24
Order Quote Endpoint.....	24
Endpoint Description	24
Request.....	25
Response.....	27
Order Create Endpoint.....	27
Endpoint Description	27
Request.....	27
Response.....	30
Order Status Endpoint.....	31
Endpoint Description	31
Request.....	31
Response.....	32

Introduction to the TDG Access API

Welcome to the Tire Discounter Group (TDG) Access API documentation. The TDG Access API provides a streamlined and secure way to access product data, inventory levels, pricing information, and order management capabilities. This API is designed to empower your integration efforts with reliable and scalable endpoints.

Environments

The TDG Access API supports two distinct environments to suit your development and production needs. Each environment requires a unique API key for access.

1. Production Environment

The production environment is intended for live applications and production-level integrations. Use this environment only when you are ready to work with real data and live transactions.

- **Base URL:** <https://www.tdgaccess.ca/api/>
- **API Key Prefix:** `rst`
- **Example API Key:**
`rst6hxlDnk1gU0ZE6ueSR2F1PrfEDzmvk1RgYD4JttN307JvpNjAzDcq38CrBT92X5o`

2. Sandbox Environment

The sandbox environment is designed for testing and development purposes. It provides the same functionality as the production environment but uses test data to ensure safe integration.

Confidentiality Notice: This document contains confidential information and is intended solely for authorized recipients. It may not be reproduced, distributed, or disclosed to any third party without prior written consent from Tire Discounter Group, Inc..

- **Base URL:** <https://sandbox.tdgaccess.ca/api/>
- **API Key Prefix:** `rstsb`
- **Example API Key:**
`rstsb7BV9W47iRgszokzi8zWJtEiaDi0WTbBc7aTA3531C5UDTiNR5BFURnBeKZU9TznvC`

Important Note: The API keys provided above are for example purposes only. You will need to obtain your own unique API keys from your TDG contact to access either environment.

Authentication

The TDG Access API uses an API key-based authentication mechanism. Clients must include their API key in the `Authorization` header of each request. This ensures secure and straightforward access to the API.

Authentication Format

Include your API key in the `Authorization` header using the following format:

```
Authorization: ApiKey <your_api_key>
```

Example Request

Here is an example of a request using the sandbox environment:

```
□POST /api/products HTTP/1.1
```

```
Host: sandbox.tdgaccess.ca
```

```
Authorization: ApiKey
```

```
rstsb7BV9W47iRgszokzi8zWJtEiaDi0WTbBc7aTA3531C5UDTiNR5BFURnBeKZU9Tznc
```

□Important Notes

1. Always use HTTPS to secure communication and protect your API key during transit.
2. Keep your API key confidential and avoid exposing it in client-side code or public repositories.
3. Use separate keys for your sandbox and production environments to maintain isolation.

Getting Started

To begin using the TDG Access API:

1. Request your API keys from your TDG contact.
2. Use the sandbox environment for development and testing.
3. Transition to the production environment once your integration is ready for live use.

Each endpoint within the TDG Access API is a subpath of the respective base URL for your chosen environment. All API endpoints return JSON-formatted responses unless otherwise specified. Detailed documentation for each endpoint will follow in the next sections.

Inventory Search Endpoint

Endpoint Description

The Inventory Search endpoint allows users to request product pricing and inventory information based on specific search criteria. It is designed to help clients locate products by providing part numbers or item numbers, returning detailed pricing and inventory availability across multiple locations.

Endpoint URL: `/api/inventory/search`

Request

The request to this endpoint should be a POST request with a JSON body containing the search parameters.

Request Parameters:

- `shippingAddress` (number, optional): The shipping address you wish to use for this inventory request. If omitted, the default shipping address will be used.
- `itemnumbers` (array of strings, optional): A list of item numbers to search for.
- `partnumbers` (array of strings, optional): A list of part numbers to search for.
- `brands` (array of strings, optional): A list of brand names to search for.
- `tireSizes` (array of strings, optional): A list of tire sizes to search for.
- `boltPatterns` (array of strings, optional): A list of bolt patterns to search for. ("6x135","6x139.7","5x114.3")
- `diameters` (array of strings, optional): A list of wheel diameters to search for.

("20","17")

- **widths**(array of strings, optional): A list of wheel width to search for. ("9","8")
- **serviceType** (string, optional): A service type to search for.
 - **P**: Limit results to **Passenger** tires
 - **LT**: Limit results to **Light Truck** tires.
- **tireSeason** (int, optional): A season name to search for.
 - **1**: Limit results to **Summer** tires
 - **2**: Limit results to **All Season** tires.
 - **3**: Limit results to **All Weather** tires.
 - **4**: Limit results to **Winter** tires.

Sample Request Payload:

```
{
  "itemnumbers": [ "AT-AH4126" ],
  "partnumbers": [ ]
}
```

Response

The response provides detailed information about the requested products, including pricing and availability across various locations.

Response Fields:

- **id** (integer): The unique identifier for the product.
- **brand** (string): The brand name of the product.

- **itemNumber** (string): The item number of the product.
- **gtin** (string): This is a GTIN for the product, most commonly the UPC.
- **partNumber** (string): The part number of the product.
- **pricing** (object):
 - **price** (number): The price of the product.
 - **msrp** (number): The manufacturer's suggested retail price.
 - **map** (number or null): The minimum advertised price, if applicable.
- **locations** (array of objects): A list of locations with inventory details:
 - **availability** (integer): Availability status of the product. Possible values:
 - **1**: Available at servicing branch
 - **2**: Available at hub branch
 - **3**: Available at a different TDG warehouse location
 - **4**: Available at a partner location (Possible fulfillment delays)
 - **100**: Location unavailable
 - **id** (integer): The unique identifier for the location.
 - **code** (string): The code of the location.
 - **name** (string): The name of the location.
 - **qtyAvailable** (integer): Quantity available at the location.
 - **qtyBackorder** (integer): Quantity on backorder at the location.
 - **qtyOnOrder** (integer): Quantity on order for the location.

Sample Response Payload:

```
{
  "id": 178706,
  "brand": "Antares",
  "itemNumber": "AT-AH4126",
```

```

"gtin": "849849045441",
"partNumber": "AH4126",
"pricing": {
  "price": 203.17,
  "msrp": 203.17,
  "map": null
},
"locations": [
  {
    "availability": 3,
    "id": 5,
    "code": "1",
    "name": "2-Orangeville DC",
    "qtyAvailable": 512,
    "qtyBackorder": 0,
    "qtyOnOrder": 0
  },
  {
    "availability": 2,
    "id": 6,
    "code": "7",
    "name": "8-Toronto DC",
    "qtyAvailable": 367,
    "qtyBackorder": 0,
    "qtyOnOrder": 0
  },
  ...
]
}
□

```

Inventory All Endpoint

Endpoint Description

The Inventory All endpoint provides a complete list of all available inventory. Users can optionally filter the results by specifying a product type. This endpoint is ideal for retrieving a comprehensive view of inventory across all or specific categories, such as wheels, tires, lug kits, or hub rings.

Endpoint URL: `/api/inventory/all`

Request

This endpoint does not require a request payload.

Response

The response provides detailed information about the requested products, including pricing and availability across various locations.

Response Fields:

- `id` (integer): The unique identifier for the product.
- `brand` (string): The brand name of the product.
- `itemNumber` (string): The item number of the product.
- `gtin` (string): A GTIN for the product, most commonly UPC.
- `partNumber` (string): The part number of the product.

- **pricing** (object):
 - **price** (number): The price of the product.
 - **msrp** (number): The manufacturer's suggested retail price.
 - **map** (number or null): The minimum advertised price, if applicable.
- **locations** (array of objects): A list of locations with inventory details:
 - **availability** (integer): Availability status of the product. Possible values:
 - **1**: Available at servicing branch
 - **2**: Available at hub branch
 - **3**: Available at a different TDG warehouse location
 - **4**: Available at a partner location (Possible fulfillment delays)
 - **100**: Location unavailable
 - **id** (integer): The unique identifier for the location.
 - **code** (string): The code of the location.
 - **name** (string): The name of the location.
 - **qtyAvailable** (integer): Quantity available at the location.
 - **qtyBackorder** (integer): Quantity on backorder at the location.
 - **qtyOnOrder** (integer): Quantity on order for the location.

Sample Response Payload:

```
{
  "id": 178706,
  "brand": "Antares",
  "itemNumber": "AT-AH4126",
  "gtin": "849849045441",
  "partNumber": "AH4126",
```

```

    "pricing": {
      "price": 203.17,
      "msrp": 203.17,
      "map": null
    },
    "locations": [
      {
        "availability": 3,
        "id": 5,
        "code": "1",
        "name": "2-Orangeville DC",
        "qtyAvailable": 512,
        "qtyBackorder": 0,
        "qtyOnOrder": 0
      },
      {
        "availability": 2,
        "id": 6,
        "code": "7",
        "name": "8-Toronto DC",
        "qtyAvailable": 367,
        "qtyBackorder": 0,
        "qtyOnOrder": 0
      },
      ...
    ]
  }

```

□ Product Search Endpoint

Endpoint Description

Confidentiality Notice: This document contains confidential information and is intended solely for authorized recipients. It may not be reproduced, distributed, or disclosed to any third party without prior written consent from Tire Discounter Group, Inc..

The Product Search endpoint allows users to search for products based on part numbers or item numbers. This endpoint provides detailed product information, including specifications that vary by product type.

Endpoint URL: `/api/product/search`

Request

The request to this endpoint should be a POST request with a JSON body containing the search parameters.

Request Parameters:

- `shippingAddress` (number, optional): If specified, inventory information will be included with the product information for the specified address.
- `itemnumbers` (array of strings, optional): A list of item numbers to search for.
- `gtin` (string): A GTIN for the product, most commonly UPC.
- `partnumbers` (array of strings, optional): A list of part numbers to search for.
- `brands` (array of strings, optional): A list of brand names to search for.
- `tireSizes` (array of strings, optional): A list of tire sizes to search for.
- `serviceType` (string, optional): A service type to search for.
 - a. `P`: Limit results to **Passenger** tires
 - b. `LT`: Limit results to **Light Truck** tires.
- `tireSeason` (int, optional): A season name to search for.
 - a. `1`: Limit results to **Summer** tires
 - b. `2`: Limit results to **All Season** tires.
 - c. `3`: Limit results to **All Weather** tires.

- d. 4: Limit results to **Winter** tires.

Sample Request Payload:

```
{
  "itemnumbers": [ "AT-AH4126" ],
  "partnumbers": [ ]
}
```

Response

The response is an array of objects, each containing detailed product information.

Sample Response Payload:

```
[
  {
    "brandId": 589,
    "brandName": "Antares",
    "productId": 18161,
    "productName": "Grip 20",
    "type": "Tire",
    "id": 217622,
    "itemNumber": "AT-AH4126",
    "gtin": "849849045441",
    "partNumber": "AH4126",
    "specifications": {
      "size": "225/55R17",
      "sidewall": "Black Sidewall",

```



```
        "outsideDiameter": "8.9",
        "loadIndex": "101",
        "speedRating": "T",
        "serviceDescription": "101T",
        "season": "Winter",
        "runFlat": "No",
        "eVCompatible": "No",
        "serviceType": "P-Passenger"
    },
    "productImageUrl": null
}
]
[]
```

Product All Endpoint

Endpoint Description

The Product All endpoint returns all available products in the system. This endpoint provides comprehensive product information without requiring any request parameters.

Endpoint URL: `/api/product/all`

Request

The request to this endpoint should be a POST request with a JSON body containing the search parameters.

Request Parameters:

- `shippingAddress` (number, optional): If specified, inventory information will be included in the product results.

Response

The response is an array of objects, each containing detailed product information.

Sample Response Payload:

```
[  
  {  
    "brandId": 589,  
    "brandName": "Antares",  
    "productId": 18161,  
  }  
]
```

```

    "productName": "Grip 20",
    "type": "Tire",
    "id": 217622,
    "itemNumber": "AT-AH4126",
    "partNumber": "AH4126",
    "gtin": "849849045441",
    "specifications": {
      "size": "225/55R17",
      "sidewall": "Black Sidewall",
      "outsideDiameter": "8.9",
      "loadIndex": "101",
      "speedRating": "T",
      "serviceDescription": "101T",
      "season": "Winter",
      "runFlat": "No",
      "eVCompatible": "No",
      "serviceType": "P-Passenger"
    },
    "productImageUrl": null
  }
]

```

Account ShippingAddresses Endpoint

Endpoint Description

The Account ShippingAddresses endpoint allows users to list all of the available shipping addresses for the current customer. This can be useful when placing an order or looking for inventory at a specific location.

Endpoint URL: `/api/account/shippingAddresses`

Request

This endpoint does not require a request payload.

Response

The response is an array of objects, each containing detailed address information.

Sample Response Payload:

```
[
  {
    "id": 13,
    "attention": null,
    "addressee": "CUSTOMER NAME",
    "address1": "1234 Main Street",
    "address2": null,
    "city": "Orangeville",
    "state": "ON",
    "zip": "L0N 1L0",
```

```

        "country": "CA"
    }
]

```

Account ShippingMethods Endpoint

Endpoint Description

The Account ShippingMethods endpoint allows users to list all of the available shipping methods for the current customer.

Endpoint URL: `/api/account/shippingMethods`

Request

This endpoint does not require a request payload.

Response

The response is an array of objects, each containing detailed shipment information.

The "isPickup" property of each delivery method indicates whether this is a pickup delivery method or not. Pickup delivery methods require a pickup location to be provided.

Sample Response Payload:

```

[] [
  {
    "id": "DD2E8AF3A33DA3421997C941EAB9D3A6|29667",

```

```
    "name": "TDG Delivery",
    "description": null,
    "isPickup": false
  }
]
```

Account PickupLocations Endpoint

Endpoint Description

The Pickup Locations endpoint returns a list of available pickup locations associated with the account. Each pickup location includes a unique ID, a reference code, name, and full address. The returned IDs can be used with order-related endpoints that support pickup-based delivery methods.

Endpoint URL: `/api/account/pickuplocations`

Request

This endpoint does not require a request payload.

Response

The response is an array of objects representing the available pickup locations.

Sample Response Payload:

```
[]
  {
```

```
    "id": 1,  
    "reference": "3",  
    "name": "4-Ottawa DC",  
    "address": "200-1101 Polytek St, Ottawa, ON K1J 0B3"  
  },  
  ...  
]
```

Account PaymentMethods Endpoint

Endpoint Description

The Account PaymentMethods endpoint allows users to list all of the available payment methods for the current customer.

Endpoint URL: `/api/account/paymentMethods`

Request

This endpoint does not require a request payload.

Response

The response is an array of objects, each containing detailed payment method information.

Sample Response Payload:

```
[
  {
    "id": "E1411CD381C5D70EC528A0D11AF7B9B8|TERM_STANDARD",
    "name": "PURCHASE WITH TERM ACCOUNT",
    "requirePo": false
  }
]
```

Order Quote Endpoint

Endpoint Description

The Order Create endpoint allows you to submit an order

Endpoint URL: </api/order/quote>

Request

The request to this endpoint should be a POST request with a JSON body containing the proposed order information.

Request Parameters:

- **shippingAddress** (number, optional): Shipping address to be used for the order. If not specified, the default shipping address will be used.
- **poNumber** (string, optional): If you have an internal PO number to link with this

order you can pass it via this field.

- **shippingMethod** (string): The shipping method to use for this order.
- **shipDate** (date, optional): A shipping date at least 1 day in the future. If specified, we will hold your order for shipment on this date.
- **shipComplete** (bool, optional): Indicates whether you want us to hold the item until all items can ship at the same time. Default is **true**.
- **paymentMethod** (number): The payment method to use for this order.
- **deliveryInstructions** (string, optional): Optional delivery instructions for our team.
- **products** (array of objects): A list of products to include on this order
 - a. **id** (integer): The internal id of the product to be ordered. This should have been received via a separate API request when looking up the item by either part number or item number.
 - b. **quantity** (integer): The quantity of this object to include on the order. Quantity must be between **1** and **50** for API based orders.

Sample Request Payload:

Confidentiality Notice: This document contains confidential information and is intended solely for authorized recipients. It may not be reproduced, distributed, or disclosed to any third party without prior written consent from Tire Discounter Group, Inc..

```
{
  "shippingAddress": 19,
  "poNumber": "P01234",
  "shippingMethod": "DD2E8AF3A33DA3421997C941EAB9D3A6|29667",
  "shipDate": "2025-04-24",
  "shipComplete": false,
  "paymentMethod": "E1411CD381C5D70EC528A0D11AF7B9B8|TERM_STANDARD",
  "deliveryInstructions": "Drop at front office",
  "products": [
    {
      "id": 217622,
      "quantity": 4,
      "services": [ "ST" ]
    }
  ]
}
```

Response

The response is an object which contains information about the quote.

Sample Response Payload:

```
{
  "quote": {
    "currency": "CAD",
    "subtotal": 670.00,
    "shipping": 18.00,
    "tax": 10.00,
    "total": 698.00
  }
}
```

Order Create Endpoint

Endpoint Description

The Order Create endpoint allows you to submit an order

Endpoint URL: `/api/order/create`

Request

The request to this endpoint should be a POST request with a JSON body containing the proposed order information.

- `shippingAddress` (number, optional): Shipping address to be used for the order. If not specified, the default shipping address will be used.
- `poNumber` (string, optional): If you have an internal PO number to link with this order you can pass it via this field.
- `shippingMethod` (string): The shipping method to use for this order.
- `pickupLocationId` (number, conditional): This Id must be included when requesting an order with a pickup shipping method.
- `shipDate` (date, optional): A shipping date at least 1 day in the future. If specified, we will hold your order for shipment on this date.
- `shipComplete` (bool, optional): Indicates whether you want us to hold the item until all items can ship at the same time. Default is **true**.

- **paymentMethod** (string): The payment method to use for this order.
- **deliveryInstructions** (string, optional): Optional delivery instructions for our team.
- **products** (array of objects): A list of products to include on this order
 - a. **id** (integer): The internal id of the product to be ordered. This should have been received via a separate API request when looking up the item by either part number or item number.
 - b. **quantity** (integer): The quantity of this object to include on the order. Quantity must be between **1** and **50** for API based orders.

Sample Request Payload:

```
{
  "orderHash": "baf62f829b6f04947fa6548385d9adf7",
  "shippingAddress": 19,
  "poNumber": "P01234",
  "shippingMethod": "DD2E8AF3A33DA3421997C941EAB9D3A6|29667",
  "shipDate": "2025-04-24",
  "shipComplete": false,
  "paymentMethod": "E1411CD381C5D70EC528A0D11AF7B9B8|TERM_STANDARD",
  "deliveryInstructions": "Drop at front office",
  "products": [
    {
      "id": 217622,
      "quantity": 4,
      "services": [ "ST" ]
    }
  ]
}
```

Response

The response is an object which contains information about the order that was created.

Sample Response Payload:

```
{
  "order": {
    "orderNumber": "20240412-65478984-22",
    "reference": "S0123",
    "currency": "CAD",
    "subtotal": 670.00,
    "shipping": 18.00,
    "tax": 10.00,
    "total": 698.00
  }
}
```

Order Status Endpoint

Endpoint Description

The Order Status endpoint provides real-time status information for a submitted order.

Endpoint URL: `/api/order/status`

Request

Confidentiality Notice: This document contains confidential information and is intended solely for authorized recipients. It may not be reproduced, distributed, or disclosed to any third party without prior written consent from Tire Discounter Group, Inc..

The request to this endpoint should be a POST request with a JSON body containing one of the supported identifiers.

Request Parameters:

- **orderNumber** (string, optional): The full TDG order number (e.g. 20250513-41967-1-1).
- **reference** (string, optional): A custom reference identifier for the order (e.g. SO530).

Sample Request Payload:

```
{  
  "reference": "SO530"  
}
```

Response

The response includes detailed order summary data along with a status field indicating the current state of the order.

Status Codes:

- **0**: Pending
- **1**: In Process
- **2**: Complete
- **10**: Cancelled

Sample Response Payload:

```
{  
  "status": 0,  
  "orderNumber": "20250513-41967-1-1",  
  "reference": "S0530",  
  "currency": "CAD",  
  "subtotal": 367.3600,  
  "shipping": 0.0000,  
  "tax": 47.7568,  
  "total": 433.1168  
}
```