2006-2009 Suzuki GSX-R600

Front	Rear	1st	2nd	3rd
11	44	22.00	16.21	13.53
11	45	22.50	16.58	13.84
11	46	23.00	16.95	14.15
11	47	23.50	17.32	14.46
11	48	24.00	17.68	14.76
11	49	24.50	18.05	15.07
11	50	25.00	18.42	15.38
11	51	25.50	18.79	15.69
11	52	26.00	19.16	15.99
11	53	26.50	19.53	16.30
11	54	27.00	19.89	16.61
11	55	27.50	20.26	16.92
12	44	20.17	14.86	12.41
12	45	20.62	15.20	12.69
12	46	21.08	15.54	12.97
12	47	21.54	15.87	13.25
12	48	22.00	16.21	13.53
12	49	22.46	16.55	13.82
12	50	22.91	16.89	14.10
12	51	23.37	17.22	14.38
12	52	23.83	17.56	14.66
12	53	24.29	17.90	14.94
12	54	24.75	18.24	15.23
12	55	25.21	18.57	15.51
13	44	18.61	13.72	11.45
13	45	19.04	14.03	11.71
13	46	19.46	14.34	11.97
13	47	19.88	14.65	12.23
13	48	20.31	14.96	12.49
13	49	20.73	15.28	12.75
13	50	21.15	15.59	13.01
13	51	21.58	15.90	13.27
13	52	22.00	16.21	13.53
13	53	22.42	16.52	13.79
13	54	22.84	16.83	14.05
13	55	23.27	17.15	14.31
14	44	17.28	12.74	10.63
14	45	17.68	13.03	10.88
14	46	18.07	13.32	11.12
14	47	18.46	13.61	11.36
14	48	18.86	13.89	11.60
14	49	19.25	14.18	11.84
14	50	19.64	14.47	12.08
14	51	20.03	14.76	12.33
14	52	20.43	15.05	12.57
14	53	20.82	15.34	12.81
14	54	21.21	15.63	13.05
14	55	21.61	15.92	13.29
15	44	16.13	11.89	9.92
15	45	16.50	12.16	10.15
15	46	16.87	12.43	10.38
15	47	17.23	12.70	10.60
15	48	17.60	12.97	10.83
15	49	17.97	13.24	11.05
15	50	18.33	13.51	11.28
15	51	18.70	13.78	11.50
15	52	19.07	14.05	11.73
15	53	19.43	14.32	11.95
15	54	19.80	14.59	12.18
15	55	20.17	14.86	12.41
16	44	15.47	11.40	9.52
16	45	15.81	11.65	9.73
16	46	16.15	11.90	9.94
16	47	16.49	12.16	10.15
16	48	16.84	12.41	10.36
16	49	17.18	12.66	10.57
16	50	17.53	12.92	10.78
16	51	17.87	13.17	10.99
16	52	18.22	13.42	11.21
16	53	18.56	13.68	11.42
16	54	18.90	13.93	11.63
16	55	19.25	14.18	11.84

ELITE ENGINE DEVELOPMENT

GEARING REFERENCE

HOW TO USE THIS CHART

The values shown represent the **final drive ratio output** based on front and rear sprocket combinations.

Final Drive Ratio = (Rear Sprocket ÷ Front Sprocket) × Primary × Transmission Gear

Use the table to compare gearing options and determine optimal acceleration vs. top speed balance for your track size.

- Lower ratio = **more top speed**
- Higher ratio = **more acceleration**

TRACK SIZE GUIDELINES

- ¼ Mile → Balanced accel & speed
- ⅕ Mile → Slightly more accel bias
- ⅙ Mile → Accel priority
- ⅛ Mile → Maximum accel focus

Adjust rear sprocket first when making small changes.

REV LIMIT NOTES

Final mph output is based on engine rev limit.

Common GSX-R600 limits:
- 15,500 rpm (stock)
- 16,500 rpm (Elite Engine)
- Custom builds may vary

Higher rev limit increases mph in each gear.

©2026 Elite Developments