Concurrency

COSC-361 Stephen Marz



1

Definitions

- <u>Parallel</u> two or more computational units capable of executing simultaneously.
- Concurrency ability of multiple parts of a program to be executed out of order and/or in parallel.
- <u>Critical section</u> instructions where preemption would cause failure.

TENNESSEE 1

2

Multi-user / Multi-process

- · Processes compete for limited resources.
- A process can be interrupted (preempted) at any moment.
- Sometimes, a request must be finished before another section can start.
 - This type of section is called a <u>critical section</u>

2/17/2019

ENNESSEE


3

Critical S	ections	
1. Guarantee m	nutual exclusion	
2. Prevent lock	out	
3. Prevent starv	/ation	
4. Prevent dead	dlock	
4 2/17/2019		TENNESSEE T

Naive Locking

- Big Kernel Lock (BKL)
 - Prevent any preemption at all
 - Very slow, things that have nothing to do with another can't run.
- Linux had BKL for quite a while.


5



6

A positive integer. When the integer reaches 0, it blocks until the integer is increased again. Functions Down: lock Decreases the integer. If integer is already 0, it waits. Up: unlock Increases the integer. Notifies that resources are again available.


7



2

Locking: Mutex • Mutual Exclusion (Mutex) • A binary semaphore • Integer is either 0 (locked) or 1 (unlocked) • Functions • Lock: sets the mutex to 0 • If lock is already set, it waits. • Unlock: sets the mutex to 1.

9




Locking: Barrier


- Barriers are a finish line for processes
- Processes wait at the end of the barrier until ALL processes make it to the barrier.


1 2/17/2019 COSC 381 TENNESSEE

11



12






14

Reader's/Writer's • Two types of processes • Readers - want to GET data • Writers - want to SET data • Critical Section • May have multiple readers • May have ONLY ONE writer • No readers allowed while a writer is in critical section.

15

R/W Rules 1. A reader may enter critical section if other readers are in it. a) when last reader exits, writers are allowed in. 2. All readers that arrive when a writer is in the critical section enter before the next writer.

16



17

Read-Copy-Update (RCU)

- · Primitive without need for locks.
- Locks have an acquire (lock) and release (unlock) cost.
- Typically implemented as a singly linked list

THE STATE STATE OF THE STATE S

18

