

Quick Sort


Instructor: Krishna Venkatasubramanian

CSC 212

Divide and Conquer Algorithms


- **Divide:** Break the larger problem into sub-problems that are smaller instances of the same problem
- **Conquer:** the sub-problems are solved *recursively*
 - If the sub-problem is really small, then solve in a straight-forward manner
- **Combine:** combine the solutions of the sub-problems to find the solution of the original problem!

Visually Speaking



Sorting: Problem Definition

- **Sorting takes an unordered collection and makes it an ordered one.**



How can we sort an array using divide and conquer approach?

Sorting Algorithms


- *Insertion Sort --- covered already*
- *Bubble Sort --- covered already*
- *Selection Sort --- covered already*
- *Merge Sort --- covered already*
- **Quick Sort**
- Linear-Time Sort
- Heap Sort
- ...

Quicksort Algorithm

```
QuickSort (A, left, right)
    if right-left +1 == 1
        return
    else
        pivot =
Partition (A, left, right)
        QuickSort (A, left, pivot)
        QuickSort (A, pivot+1, right)
```

How to Partition

- Given an array A
 - Pick one element to use as *pivot*.
 - Partition elements into two sub-arrays:
 - Elements **less than or equal to pivot**
 - Elements **greater than pivot**



Partition Example

We are given array of n integers to sort:


40	20	10	80	60	50	7	30	100
----	----	----	----	----	----	---	----	-----

Partition Example

There are a **number of ways to pick the pivot element**. In this example, we **will use the first element** in the array:

40	20	10	80	60	50	7	30	100
----	----	----	----	----	----	---	----	-----


Partition Example (Pseudocode)



Partition Example (Pseudocode)


→ 1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index

Note the pre-increment




Partition Example (Pseudocode)

→ 1. **while** data[too_big_index] <= data[pivot]
 too_big_index = too_big_index+1



Partition Example (Pseudocode)

→ 1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index




Partition Example (Pseudocode)

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index


→ 2. **while** data[too_small_index] > data[pivot]
 --too_small_index

Note the pre-decrement




Partition Example (Pseudocode)

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
- 2. **while** data[too_small_index] > data[pivot]
 --too_small_index




Partition Example (Pseudocode)

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
2. **while** data[too_small_index] > data[pivot]
 --too_small_index
- 3. **if** too_big_index < too_small_index
 swap data[too_big_index] and data[too_small_index]




Partition Example (Pseudocode)

1. **while** `data[too_big_index] <= data[pivot]`
 `++too_big_index`
2. **while** `data[too_small_index] > data[pivot]`
 `--too_small_index`
- 3. **if** `too_big_index < too_small_index`
 swap `data[too_big_index]` and `data[too_small_index]`




Partition Example (Pseudocode)

1. **while** `data[too_big_index] <= data[pivot]`
 `++too_big_index`
2. **while** `data[too_small_index] > data[pivot]`
 `--too_small_index`
3. **if** `too_big_index < too_small_index`
 swap `data[too_big_index]` and `data[too_small_index]`
- 4. **while** `too_small_index >= too_big_index`, go to Step 1.




Partition Example (Pseudocode)

- 1. **while** $\text{data}[\text{too_big_index}] \leq \text{data}[\text{pivot}]$
 ++too_big_index
- 2. **while** $\text{data}[\text{too_small_index}] > \text{data}[\text{pivot}]$
 --too_small_index
- 3. **if** $\text{too_big_index} < \text{too_small_index}$
 swap $\text{data}[\text{too_big_index}]$ and $\text{data}[\text{too_small_index}]$
- 4. **while** $\text{too_small_index} \geq \text{too_big_index}$, go to Step 1.




Partition Example (Pseudocode)

- 1. **while** $\text{data}[\text{too_big_index}] \leq \text{data}[\text{pivot}]$
 ++too_big_index
- 2. **while** $\text{data}[\text{too_small_index}] > \text{data}[\text{pivot}]$
 --too_small_index
- 3. **if** $\text{too_big_index} < \text{too_small_index}$
 swap $\text{data}[\text{too_big_index}]$ and $\text{data}[\text{too_small_index}]$
- 4. **while** $\text{too_small_index} \geq \text{too_big_index}$, go to Step 1.




Partition Example (Pseudocode)

1. **while** `data[too_big_index] <= data[pivot]`
 `++too_big_index`
- 2. **while** `data[too_small_index] > data[pivot]`
 `--too_small_index`
3. **if** `too_big_index < too_small_index`
 swap `data[too_big_index]` and `data[too_small_index]`
4. **while** `too_small_index >= too_big_index`, go to Step 1.




Partition Example

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
- 2. **while** data[too_small_index] > data[pivot]
 --too_small_index
3. **if** too_big_index < too_small_index
 swap data[too_big_index] and data[too_small_index]
4. **while** too_small_index >= too_big_index, go to Step 1.




Partition Example (Pseudocode)

1. **while** $\text{data}[\text{too_big_index}] \leq \text{data}[\text{pivot}]$
 ++too_big_index
2. **while** $\text{data}[\text{too_small_index}] > \text{data}[\text{pivot}]$
 --too_small_index
- 3. **if** $\text{too_big_index} < \text{too_small_index}$
 swap $\text{data}[\text{too_big_index}]$ and $\text{data}[\text{too_small_index}]$
4. **while** $\text{too_small_index} \geq \text{too_big_index}$, go to Step 1.




Partition Example

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
2. **while** data[too_small_index] > data[pivot]
 --too_small_index
- 3. **if** too_big_index < too_small_index
 swap data[too_big_index] and data[too_small_index]
4. **while** too_small_index >= too_big_index, go to Step 1.




Partition Example (Pseudocode)

1. **while** `data[too_big_index] <= data[pivot]`
 `++too_big_index`
2. **while** `data[too_small_index] > data[pivot]`
 `--too_small_index`
3. **if** `too_big_index < too_small_index`
 swap `data[too_big_index]` and `data[too_small_index]`
- 4. **while** `too_small_index >= too_big_index`, go to Step 1.




Partition Example (Pseudocode)

- 1. **while** $\text{data}[\text{too_big_index}] \leq \text{data}[\text{pivot}]$
 ++too_big_index
- 2. **while** $\text{data}[\text{too_small_index}] > \text{data}[\text{pivot}]$
 --too_small_index
- 3. **if** $\text{too_big_index} < \text{too_small_index}$
 swap $\text{data}[\text{too_big_index}]$ and $\text{data}[\text{too_small_index}]$
- 4. **while** $\text{too_small_index} \geq \text{too_big_index}$, go to Step 1.




Partition Example (Pseudocode)

- 1. **while** $\text{data}[\text{too_big_index}] \leq \text{data}[\text{pivot}]$
 ++too_big_index
- 2. **while** $\text{data}[\text{too_small_index}] > \text{data}[\text{pivot}]$
 --too_small_index
- 3. **if** $\text{too_big_index} < \text{too_small_index}$
 swap $\text{data}[\text{too_big_index}]$ and $\text{data}[\text{too_small_index}]$
- 4. **while** $\text{too_small_index} \geq \text{too_big_index}$, go to Step 1.




Partition Example (Pseudocode)

1. **while** `data[too_big_index] <= data[pivot]`
 `++too_big_index`
- 2. **while** `data[too_small_index] > data[pivot]`
 `--too_small_index`
3. **if** `too_big_index < too_small_index`
 swap `data[too_big_index]` and `data[too_small_index]`
4. **while** `too_small_index >= too_big_index`, go to Step 1.




Partition Example (Pseudocode)

1. **while** `data[too_big_index] <= data[pivot]`
 `++too_big_index`
- 2. **while** `data[too_small_index] > data[pivot]`
 `--too_small_index`
3. **if** `too_big_index < too_small_index`
 swap `data[too_big_index]` and `data[too_small_index]`
4. **while** `too_small_index >= too_big_index`, go to Step 1.




Partition Example

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
- 2. **while** data[too_small_index] > data[pivot]
 --too_small_index
3. **if** too_big_index < too_small_index
 swap data[too_big_index] and data[too_small_index]
4. **while** too_small_index >= too_big_index, go to Step 1.




Partition Example (Pseudocode)

1. **while** `data[too_big_index] <= data[pivot]`
 `++too_big_index`
2. **while** `data[too_small_index] > data[pivot]`
 `--too_small_index`
- 3. **if** `too_big_index < too_small_index`
 swap `data[too_big_index]` and `data[too_small_index]`
4. **while** `too_small_index >= too_big_index`, go to Step 1.




Partition Example (Pseudocode)

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
2. **while** data[too_small_index] > data[pivot]
 --too_small_index
3. **if** too_big_index < too_small_index
 swap data[too_big_index] and data[too_small_index]
- 4. **while** too_small_index >= too_big_index, go to Step 1.




Partition Example (Pseudocode)

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
2. **while** data[too_small_index] > data[pivot]
 --too_small_index
3. **if** too_big_index < too_small_index
 swap data[too_big_index] and data[too_small_index]
4. **while** too_small_index >= too_big_index, go to 1.
- 5. swap data[too_small_index] and data[pivot]




Partition Example (Pseudocode)

1. **while** data[too_big_index] <= data[pivot]
 ++too_big_index
2. **while** data[too_small_index] > data[pivot]
 --too_small_index
3. **if** too_big_index < too_small_index
 swap data[too_big_index] and data[too_small_index]
4. **while** too_small_index >= too_big_index, go to 1.
- 5. swap data[too_small_index] and data[pivot]




Partition Result



All this is done **in-place**, and does not require extra memory

Recursion: Quicksort Sub-arrays




Quicksort Analysis

- Assume that keys are random, uniformly distributed.
- What is **best case running time**?
 - Recursion:
 - Partition splits array in two sub-arrays of size $n/2$
 - Quicksort each sub-array
- Depth of recursion tree?
 - $O(\log_2 n)$
- Number of accesses in partition?
 - $O(n)$
- Best case running time: $O(n \log_2 n)$

**Worst case
running time?**

Depends on Balance of Partition





That's all Folks!
Any Question?