

# Quick Sort


Instructor: Krishna Venkatasubramanian

CSC 212

# Divide and Conquer Algorithms


- **Divide:** Break the larger problem into sub-problems that are smaller instances of the same problem
- **Conquer:** the sub-problems are solved *recursively*
  - If the sub-problem is really small, then solve in a straight-forward manner
- **Combine:** combine the solutions of the sub-problems to find the solution of the original problem!

# Visually Speaking



# Sorting: Problem Definition

- **Sorting takes an unordered collection and makes it an ordered one.**



**How can we sort an array using divide and conquer approach?**

# Sorting Algorithms


- *Insertion Sort --- covered already*
- *Bubble Sort --- covered already*
- *Selection Sort --- covered already*
- *Merge Sort --- covered already*
- **Quick Sort**
- Linear-Time Sort
- Heap Sort
- ...

# Quicksort Algorithm

```
QuickSort (A, left, right)
    if right-left +1 == 1
        return
    else
        pivot =
Partition (A, left, right)
        QuickSort (A, left, pivot)
        QuickSort (A, pivot+1, right)
```

# How to Partition

- Given an array A
  - Pick one element to use as *pivot*.
  - Partition elements into two sub-arrays:
    - Elements **less than or equal to pivot**
    - Elements **greater than pivot**



# Partition Example

We are given array of n integers to sort:

40	20	10	80	60	50	7	30	100
----	----	----	----	----	----	---	----	-----




# Partition Example

There are a **number of ways to pick the pivot element**. In this example, we **will use the first element** in the array:


40	20	10	80	60	50	7	30	100
----	----	----	----	----	----	---	----	-----

# Partition Example




# Partition Example

→ 1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1




# Partition Example

→ 1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1




# Partition Example

→ 1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1




# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
- 2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1




# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
- 2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1



# Partition Example


1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
- 3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]






# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
- 3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]




# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
- 4. **while** too\_small\_index > too\_big\_index, go to Step 1.




# Partition Example

- 1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
- 2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
- 3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
- 4. **while** too\_small\_index > too\_big\_index, go to Step 1.




# Partition Example

- 1. **while** `data[too_big_index] <= data[pivot]`  
    `too_big_index = too_big_index + 1`
- 2. **while** `data[too_small_index] > data[pivot]`  
    `too_small_index = too_small_index - 1`
- 3. **if** `too_big_index < too_small_index`  
    swap `data[too_big_index]` and `data[too_small_index]`
- 4. **while** `too_small_index > too_big_index`, go to Step 1.




# Partition Example

1. **while**  $\text{data}[\text{too\_big\_index}] \leq \text{data}[\text{pivot}]$   
     $\text{too\_big\_index} = \text{too\_big\_index} + 1$
- 2. **while**  $\text{data}[\text{too\_small\_index}] > \text{data}[\text{pivot}]$   
     $\text{too\_small\_index} = \text{too\_small\_index} - 1$
3. **if**  $\text{too\_big\_index} < \text{too\_small\_index}$   
    swap  $\text{data}[\text{too\_big\_index}]$  and  $\text{data}[\text{too\_small\_index}]$
4. **while**  $\text{too\_small\_index} > \text{too\_big\_index}$ , go to Step 1.




# Partition Example

1. **while** `data[too_big_index] <= data[pivot]`  
    `too_big_index = too_big_index + 1`
- 2. **while** `data[too_small_index] > data[pivot]`  
    `too_small_index = too_small_index - 1`
3. **if** `too_big_index < too_small_index`  
    swap `data[too_big_index]` and `data[too_small_index]`
4. **while** `too_small_index > too_big_index`, go to Step 1.




# Partition Example

1. **while**  $\text{data}[\text{too\_big\_index}] \leq \text{data}[\text{pivot}]$   
     $\text{too\_big\_index} = \text{too\_big\_index} + 1$
2. **while**  $\text{data}[\text{too\_small\_index}] > \text{data}[\text{pivot}]$   
     $\text{too\_small\_index} = \text{too\_small\_index} - 1$
- 3. **if**  $\text{too\_big\_index} < \text{too\_small\_index}$   
    swap  $\text{data}[\text{too\_big\_index}]$  and  $\text{data}[\text{too\_small\_index}]$
4. **while**  $\text{too\_small\_index} > \text{too\_big\_index}$ , go to Step 1.



# Partition Example


1. **while** `data[too_big_index] <= data[pivot]`  
    `too_big_index = too_big_index + 1`
2. **while** `data[too_small_index] > data[pivot]`  
    `too_small_index = too_small_index - 1`
- 3. **if** `too_big_index < too_small_index`  
    swap `data[too_big_index]` and `data[too_small_index]`
4. **while** `too_small_index > too_big_index`, go to Step 1.






# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
- 4. **while** too\_small\_index > too\_big\_index, go to Step 1.




# Partition Example

- 1. **while** `data[too_big_index] <= data[pivot]`  
    `too_big_index = too_big_index + 1`
- 2. **while** `data[too_small_index] > data[pivot]`  
    `too_small_index = too_small_index - 1`
- 3. **if** `too_big_index < too_small_index`  
    swap `data[too_big_index]` and `data[too_small_index]`
- 4. **while** `too_small_index > too_big_index`, go to Step 1.




# Partition Example

- 1. **while** `data[too_big_index] <= data[pivot]`  
    `too_big_index = too_big_index + 1`
- 2. **while** `data[too_small_index] > data[pivot]`  
    `too_small_index = too_small_index - 1`
- 3. **if** `too_big_index < too_small_index`  
    swap `data[too_big_index]` and `data[too_small_index]`
- 4. **while** `too_small_index > too_big_index`, go to Step 1.




# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
- 2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
4. **while** too\_small\_index > too\_big\_index, go to Step 1.




# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
- 2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
4. **while** too\_small\_index > too\_big\_index, go to Step 1.




# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
- 2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
4. **while** too\_small\_index > too\_big\_index, go to Step 1.




# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
- 3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
4. **while** too\_small\_index > too\_big\_index, go to Step 1.



# Partition Example


1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
- 4. **while** too\_small\_index > too\_big\_index, go to Step 1.






# Partition Example

1. **while** data[too\_big\_index] <= data[pivot]  
    too\_big\_index = too\_big\_index+1
2. **while** data[too\_small\_index] > data[pivot]  
    too\_small\_index = too\_small\_index-1
3. **if** too\_big\_index < too\_small\_index  
    swap data[too\_big\_index] and data[too\_small\_index]
4. **while** too\_small\_index > too\_big\_index, go to 1.
- 5. swap data[too\_small\_index] and data[pivot]




# Partition Example

1. **while** `data[too_big_index] <= data[pivot]`  
    `too_big_index = too_big_index + 1`
2. **while** `data[too_small_index] > data[pivot]`  
    `too_small_index = too_small_index - 1`
3. **if** `too_big_index < too_small_index`  
    swap `data[too_big_index]` and `data[too_small_index]`
4. **while** `too_small_index > too_big_index`, go to 1.
- 5. swap `data[too_small_index]` and `data[pivot]`




# Partition Result



All this is done **in-place**, and does not require extra memory

# Recursion: Quicksort Sub-arrays




# Quicksort Analysis

- Assume that keys are random, uniformly distributed.
- What is **best case running time**?
  - Recursion:
    - Partition splits array in two sub-arrays of size  $n/2$
    - Quicksort each sub-array
- Depth of recursion tree?
  - $O(\log_2 n)$
- Number of accesses in partition?
  - $O(n)$
- Best case running time:  $O(n \log_2 n)$

**Worst case  
running time?**

# Depends on Balance of Partition





*That's all Folks!*  
*Any Question?*