

Basic Sorting Algorithms (2)


Instructor: Krishna Venkatasubramanian

CSC 212

Announcement


- Don't forget the office hours poll on Piazza.
 - Last day to do it today.
 - We will make our decision (to change or not to change) tomorrow.
- Who is Ming?
- Grade for Quiz 1 will be out soon.

Clarification: Asymptotic Growth Rates



Sorting: Problem Definition

- **Sorting takes an unordered collection and makes it an ordered one.**



Sorting Algorithms

- *Insertion Sort --- covered already*
- *Bubble Sort --- covered already*
- **Selection Sort**
- Heap Sort
- Merge Sort
- Quick Sort
- ...

Selection Sort


- Simple Algorithm --- has similarities to both Insertion-Sort and Bubble-Sort
 - Array divided into two parts – sorted and unsorted (like Insertion-Sort)
 - Stack the array from smallest to the largest (inverse of Bubble-Sort)
- **Invariants**
 - Elements in the sorted array are fixed
 - No element in the sorted array is greater than element in the unsorted array

1	2	4	5	18	9	10	7
---	---	---	---	----	---	----	---

SORTED ARRAY

UNSORTED ARRAY

Example (of basic steps)




i = denotes position which is to be brought into the sorted array (initially the first element, as the entire array is unsorted)



The first element is in it's correct spot

Next Step



The first two element is in it's correct spot

Continuing On...



Green = already sorted (numbers in correct position)

Blue = i^{th} position

Red = smallest element, which swaps with the i^{th} position element

The Selection Sort Algorithm

Selection Sort(A):

for i in range(len(A)-1):

Why len(A) - 1?

Find the minimum element in remaining unsorted array

min_id = i

for j in range(i+1, len(A)):

if A[min_id] > A[j]:

min_id = j

Why len(A) here ?

Swap the found minimum element with the first element
A[i], A[min_id] = A[min_id], A[i]

Selection Sort Time Complexity

- **Best-Case Time Complexity**

- The scenario under which the algorithm will do the least amount of work (finish the fastest)

- **Worst-Case Time Complexity**

- The scenario under which the algorithm will do the largest amount of work (finish the slowest)

Selection Sort Time Complexity

- **Best-Case Time Complexity**

- Array is already sorted
- Need N-1 iterations
- $(N-1) + (N-2) + \dots + 1 = (N-1) * N / 2$
comparisons

Called Quadratic Time
 $O(N^2)$
Order-of-N-square

- **Worst-Case Time Complexity**


- Array reverse sorted
- Still need N-1 iterations
- $(N-1) + (N-2) + \dots + 1 = (N-1) * N / 2$

Called Quadratic Time
 $O(N^2)$
Order-of-N-square


Sorting Algorithm Additional Properties

- Memory Requirement:
 - **Denotes the amount of auxiliary storage** needed beyond that used by the list itself, under the same assumption.
 - No extra storage required. **Sorting in place.**
- Stability:
 - **Stable sorting algorithms sort repeated elements in the same order that they appear** in the **input**.
 - When sorting some kinds of data, only part of the data is examined when determining the sort order.
 - If two items compare as equal if one came before the other in the input, it will also come before the other in the output.


Stability Example



Insertion Sort



Bubble Sort



Selection Sort

Memory Use and Stability of Basic Sorting Algorithms

- Insertion Sort
 - Memory = $O(1)$ *# in place sorting (small amount of auxiliary space allowed, like to temp swap a variable)*
 - Stability = Yes
 - Best-case Running Time = $O(n)$
 - Worst-case Running Time = $O(n^2)$
- Bubble Sort
 - Memory = $O(1)$ *# in place sorting*
 - Stability = Yes
 - Best-case Running Time = $O(n^2)$
 - Worst-case Running Time = $O(n^2)$
- Selection Sort
 - Memory = $O(1)$ *# in place sorting*
 - Stability = Yes
 - Best-case Running Time = $O(n^2)$
 - Worst-case Running Time = $O(n^2)$

Exchange Sorts

- All three sorting algorithms seen thus far are examples of **Exchange sorting** algorithms
 - They swap (exchange) elements to sort
- Other algorithms exist that are faster than these for typical conditions
- So why are these algorithms slow?

General Slowness of Exchange Sort

- The crucial bottleneck is that only *adjacent* records are compared.
 - Thus, comparisons and moves (for Insertion and Bubble Sort) are by single steps.
- The cost of any exchange sort can be *at best* **the total number of inversions**
 - The number of elements with key value greater than the current record's key value appears before it that need to be moved.

Quiz

- How many **inversions** are in the following array?

14	5	81	92	101	7
----	---	----	----	-----	---

5 inversions

4	5	1	9	11	12
---	---	---	---	----	----

2 inversions

63	-51	-9	17	1	0
----	-----	----	----	---	---

8 inversions

Worst Case

N elements				
X_n	X_{n-1}	X_{n-2}	1

$$1+2+3\ldots+n-1 = \frac{n(n-1)}{2} \\ = O(n^2) \text{ inversions}$$

$$X_n > X_{n-1} > X_{n-2} \ldots > 1$$

Basic Sorting algorithms

- Insertion, selection and bubble sort have quadratic worst-case performance
 - That is $O(n^2)$
- The faster comparison based algorithm ?
 - $O(n \cdot \log_2 n)$ or $O(n \lg n)$ complexity
 - REMEMBER: $O(n \lg n)$ more efficient than $O(n^2)$
- Examples Mergesort and Quicksort



That's all Folks!
Any Question?