ILAC-MRA certificate — Service description

SERVICE DESCRIPTION Rev A · 2026-10-24

What you get

A calibration certificate for your specific target, issued by an accredited third-party laboratory whose accreditation body is a signatory to the ILAC MRA (in Germany: DAkkS; recognised worldwide). The certificate states measured feature positions, flatness, measurement uncertainty and traceability to national standards. It is the document auditors ask for under ISO 9001 / IATF 16949 / ISO 17025 quality systems.

This is different from the inspection report included with every target: the inspection report is issued by Calib.Tools from our own measurements; the certificate is independent and accredited.

Scope

Applies to	Any Calib.Tools planar target; recommended for ceramic and glass, available for composite
Measured	Pattern feature positions (all corners, or a defined subset for large boards), flatness, overall dimensions
Uncertainty (typical)	Ceramic/glass: U = 1–2 µm (k = 2) · Composite: U = 10–20 µm (k = 2); stated per certificate
Reference temperature	20 °C
Deliverable	PDF certificate with laboratory accreditation mark; measured coordinates CSV; our cover note CT-CC-<serial> linking certifica
Lead time	Adds 1–3 weeks to delivery (board is measured before shipping)
Validity	Certificates carry no expiry; recommended recalibration interval is stated (typically 24 months for composite, 36–60 months f

How to order

Add the ILAC-MRA certificate on the product page when buying a target, or order SVC-X-CERT-ILAC separately for a target you already own (return shipping both ways is on you; we handle the laboratory).

Recalibration

SVC-X-RECAL: the same measurement on a target you already have, with a new certificate. Ask for a quote with the serial number.

Notes

- Laboratory and accreditation body are named on the certificate. Calib.Tools does not issue accredited certificates itself.
- Certificates are issued to the serial number, not to the buyer; they stay with the board if it changes hands.
- Price shown on the product page covers one target up to 400 × 300 mm; larger boards are quoted.

Revision history

Rev	Date	Change
A	2026-10	First issue