Checkerboard composite calibration target

DATASHEET Rev A · 2026-10-24

Overview

The checkerboard composite calibration target provides a classic black-and-white grid pattern on a rigid aluminium composite substrate. Ideal for OpenCV camera calibration with findChessboardCorners().

Available sizes

Part number	Board size	Grid	Square	Inner corners	Tolerance
CHT-P-7x10-200x150-25	200 x 150 mm	7 x 10	25 mm	54	+/-0.3 mm
CHT-P-7x10-300x200-25	300 x 200 mm	7 x 10	25 mm	54	+/-0.3 mm
CHT-P-9x6-400x300-30	400 x 300 mm	9 x 6	30 mm	40	+/-0.3 mm
CHT-P-5x8-600x400-40	600 x 400 mm	5 x 8	40 mm	28	+/-0.3 mm

Substrate

- Material: aluminium / LDPE composite (Dibond-type), 6 mm thick
- Surface: UV-printed, matte finish, scratch-resistant
- CTE: approximately 24 um/(m.K)
- Operating temperature: -50 to +80 C

Feature accuracy

- Feature tolerance: +/-0.3 mm + 0.2 mm/m
- Flatness: <= 0.5 mm/m
- Corner radius: 6 mm

Deliverables

Each target ships with:

- Dimensional inspection report (included)
- Datasheet PDF
- DXF board outline
- OpenCV JSON configuration

Storage and handling

Store flat, away from direct sunlight and moisture. Clean with a soft, dry cloth.