DATASHEET

# Mounting fixture, ¼″-20

Edge clamp that holds any Calib.Tools target on a tripod, light stand or arm with a standard ¼″-20 thread. Soft jaws protect ceramic and glass; the clamp spans the full jaw width so composite boards are not point-loaded.

## 1 Specifications

| FEATURE | SPECIFICATION |
|---|---|
| Part number | CT-ACC-A-FIX-14 (Shopify SKU ACC-A-FIX-14) |
| Material | Anodised aluminium 6061, black; TPU soft jaws (Shore 70A) |
| Jaw opening | 2 – 16 mm (covers 3 mm ceramic to 15 mm honeycomb) |
| Jaw width | 120 mm |
| Thread | ¼″-20 UNC, 7 mm deep; 3/8″-16 adapter bushing included |
| Max board | 800 × 600 mm composite (3.2 kg) when clamped on the long edge; 400 × 300 mm hand-held |
| Load rating | 5 kg static, vertical |
| Weight | 180 g |
| Operating temperature | –20 to +60 °C |
| Included | fixture, 3/8″ bushing, 3 mm hex key |

## 2 Instructions

- Open the jaws with the thumb screw; insert the board edge fully to the stop (≥ 15 mm engagement).
- Tighten until the soft jaws compress slightly — hand-tight. Do not use tools on the thumb screw with ceramic or glass.
- Mount to the tripod head via ¼″-20; use the bushing for 3/8″ heads. Lock the head before releasing the board.
- Centre the clamp on the edge. For boards ≥ 600 mm, use two fixtures on a cross-bar or support the lower edge.
- Check: push the board top gently — no rotation in the jaws. If it rotates, re-seat deeper, do not over-tighten.
- Do not clamp across the pattern face. Do not use as a carrying handle for ceramic or glass. Replacement jaws: ACC-A-FIX-14-JAW.

## 3 Compliance & customs

| TOPIC | STATEMENT |
|---|---|
| RoHS | RoHS-compliant. |
| HS code | 9031 90 |

## 4 Revision history

| REV | DATE | CHANGE |
|---|---|---|
| A | 2026-10 | First issue |

Specifications subject to change.

calib.tools/files/CT-DS-ACC-A-FIX-14