

**SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS****CERTIFICATE OF COMPLIANCE****Note:** This table completed by **HERSECC** Registry.

Project Name:	Enforcement Agency:
Dwelling Address:	Permit Number:
City and Zip Code:	Permit Application Date:

A. Product Information

01	02	03	04	05	06	07
Tag/ Identification	Orientation	Fenestration has a Temporary or Site-Built NFRC Label Certificate	SHGC Value from NFRC Label	Non-NFRC Labeled SHGC Information	Exterior Shading Device Type	Exterior Shading SHGC

B. Default Solar Heat Gain Coefficient Using Table 110.6-B

01	02	03	04	05	06	07
Tag/ Identification	Orientation	Frame Type	Product	Glazing	Number of Panels	Default Fenestration SHGC

C. Non-Rated Site-built Solar Heat Gain Coefficient Calculation Using Equation NA6-2 from Reference Appendices, Nonresidential Appendix NA6.3

01	Conditioned Floor Area					
02	5% of the Condition Floor Area					
03	Total Allowed Non-Rated Site-Built Fenestration Area					
04	Proposed Area of Site-Built Fenestration					
05	06	07			08	
Tag/ Identification	Glass Area	Center of Glass (COG) Solar Heat Gain Coefficient			Total Allowed SHGC of the Non- Rated Site-Built Fenestration	

D. Combined Solar Heat Gain Coefficient Calculation and Shading Device Calculation

01	02	03	04
Tag/ Identification	$SHGC_{max} =$	$SHGC_{min} =$	Total Combined Adjusted SHGC with Exterior Shading Device ($SHGC_{total}$)

**SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS****DOCUMENTATION AUTHOR'S DECLARATION STATEMENT**

1. I certify that this Certificate of Compliance documentation is accurate and complete.

Documentation Author Name:	Documentation Author Signature:
Company:	Signature Date:
Address:	CEA/AEA/ HERSECC Certification Identification (if applicable):
City/State/Zip:	Phone:

RESPONSIBLE PERSON'S DECLARATION STATEMENT

I certify the following under penalty of perjury, under the laws of the State of California:

1. The information provided on this Certificate of Compliance is true and correct.
2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer).
3. The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations.
4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application.
5. I understand that a registered copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections, and I will take the necessary steps to accomplish this requirement.
6. I understand that a registered copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy, and I will take the necessary steps to accomplish these requirements.

Responsible Designer Name:	Responsible Designer Signature:
Company:	Date Signed:
Address:	License:
City/State/Zip:	Phone:

For assistance or questions regarding the Energy Standards, contact the Energy Hotline at: 1-800-772-3300

CF1R-ENV-03-E Instructions

This worksheet is to be used to determine the total Solar Heat Gain Coefficient (SHGC) value of fenestration in combination with an exterior shading device. This worksheet is to be completed for each different fenestration and exterior shading combination. Total SHGC_{total} value in subsection D4 is calculated by choosing the larger of A4, A7, B7 or C7 for SHGC_{max} and the smaller of A4, A7, B7 or C7 for SHGC_{min}.

The following rules apply when selecting exterior shading devices:

1. If using this worksheet, a standard bug screen must be assumed for all vertical fenestration unless replaced by another exterior shading device as listed in A6 (and Table S-1 below); only one exterior shading device may be applied to a vertical window.
2. The listed SHGC for bug screens is an area-weighted value that assumes that the screens are only on operable windows. If no exterior shade is selected, then assume a SHGC of 0.76 for standard bug screens for all windows.
3. This requirement does not apply to skylights. For skylights the exterior shading SHGC is assumed to be 1.00.
4. When exterior shading devices are applied and the combined total SHGC values do not meet the prescriptive efficiencies for windows or skylights then these windows and skylight must be area-weighted using the CF1R-ENV-02-E. Different shading conditions may also be modeled explicitly using the computer performance method.

The target value for Total SHGC_{total} is 0.23 for Climate Zones 2, 4 and 6-~~15~~14 and 0.20 for Climate Zones 15. However, not being able to meet the target value will require calculating the area weighted average (CF1R-ENV-02-E compliance document) with other more efficient windows and skylights.

The resultant Total SHGC_{total} value shall be documented prescriptively on the CF1R-NCB-01-E, CF1R-ADD-01-E or CF1R-ALT-01-E in the Fenestration section—attach a completed CF1R-ENV-03-E with submittal. When using the Performance Approach, the program will generate its own CF1R and will include the Total SHGC_{total} values.

A. Product Information

1. Tag/Identification: User entered value which should equal data given on the other CF1Rs for the same fenestration; provides an identification name or tag name that uniquely identifies the window system. If there is a window schedule the tag name may be given on the plans.
2. Orientation: The direction the fenestration faces.
3. Fenestration has a Temporary or Site-Built NFRC Label Certificate: Indicate Yes or No.
4. SHGC value from NFRC label: Provide the SHGC from the NFRC Label.
5. User selects from list: Table 110.6-B of the Energy Standards if default SHGC are specified; Reference Appendices, Nonresidential Appendix NA6, Equation NA6-2 if site-built center of glass SHGC are specified.
6. User selects from list: Standard Bug Screens, Exterior Sunscreens with Weave 53 x 16/inch, Sunscreens w/Louvers as Wide as Window Openings, Low Sun Angle Louvered Sunscreens, Vertical Roller Shades or Retractable Drop Arm/Combination/Marquisolette and Operable Awnings, Roll Down Blinds or Slats or None (for skylights only).

Note: Default is Standard Bug Screens.

7. Exterior Shade SHGC: This value is auto filled based on the selection in A06 and the referenced value found in Table S-1.

B. Default Solar Heat Gain Coefficient Using Table 110.6-B

1. Tag/Identification: Auto-filled from Section A.
2. Orientation: User selects orientation from list: North, East, South or West.
3. Frame Type: User selects fenestration frame type from list: Metal, Non-metal (such as wood or vinyl), or Metal w/Thermal Break.
4. Product: User selects from list: Fixed or Operable.
5. Glazing: User selects from list: Clear (not visibly tinted) or Tinted (visibly tinted).
6. Number of Panes: User selects from list: Single, Double or Glass Block.
7. Default Fenestration SHGC: This value is auto filled based on the selections in B03, B04, B05 and B06 and the referenced values found in Table 110.6-B. of the Energy Standards

C. Non-Rated Site-Built Solar Heat Gain Coefficient Calculation Using Equation NA6-2 from Reference Appendices, Nonresidential Appendix NA6.3

1. Conditioned Floor Area: User entered Conditioned Floor Area: Indicate the Conditioned Floor Area of the building. This should be the same value found on the CF1R-NCB-01-E, CF1R-ADD-01-E or CF1R-ALT-01-E.
2. 5% of the Condition Floor Area: This value is auto filled based on a calculated value.
3. Total Allowed Non-Rated Site-Built Fenestration Area: This value is auto filled based on a calculated value.
4. Proposed Area of Site-Built Fenestration: User entered value equal to the total area of the site-built fenestration; Note: must be 250 square feet (ft²) or less.
5. Tag/Identification: Auto-filled from Section A.
6. Glass Area: User entered Fenestration Area.
7. Center of Glass Solar Heat Gain Coefficient: User entered Center of Glass (COG) Solar Heat Gain Coefficient: Indicate the SHGC_c value calculated in accordance with NFRC 200, Section 4.5.1.1 <https://cmast.nfrc.org/?Aspx>.
8. Total Allowed SHGC of the Non-Rated Site-Built Fenestration: This value is auto filled based on the equation ((Center of glass SHGC x 0.86) + 0.08).

D. Combined Solar Heat Gain Coefficient Calculation and Shading Device Calculation

1. Tag/Identification: Auto-filled from Section A.
2. SHGC_{max}: This value is auto filled based on the maximum SHGC listed in A04, A07, B07 or C07.
3. SHGC_{min}: This value is auto filled based on the minimum SHGC listed in A04, A07, B07 or C07.
4. Total Combined Adjusted SHGC with Exterior Shading Device: This value is auto filled based on the equation (((SHGC_{max} x 0.2875) + 0.75) x SHGC_{min})

Documentation Declaration Statements

1. The person who prepared the CF1R will sign and complete the fields for their name, company (if applicable), address, phone number, certification information (if applicable), date and signature (may be electronic).

2. The person who is assuming responsibility for the project being built to comply with Title 24, Part 6, will complete the fields for their name, company (if applicable), address, phone number, license number (if applicable), date and signature (may be electronic).

For information and data collection
only. Not valid until registered with an
ECC provider

TABLE 110.6-B DEFAULT SOLAR HEAT GAIN COEFFICIENT (SHGC)

FRAME TYPE	PRODUCT	GLAZING	FENESTRATION PRODUCT SHGC		
			Single Pane SHGC	Double Pane SHGC	Glass Block SHGC
Metal	Operable	Clear	0.80	0.70	0.70
	Fixed	Clear	0.83	0.73	0.73
	Operable	Tinted	0.67	0.59	N.A.
	Fixed	Tinted	0.68	0.60	N.A.
Metal, Thermal Break	Operable	Clear	N.A.	0.63	N.A.
	Fixed	Clear	N.A.	0.69	N.A.
	Operable	Tinted	N.A.	0.53	N.A.
	Fixed	Tinted	N.A.	0.57	N.A.
Nonmetal	Operable	Clear	0.74	0.65	0.70
	Fixed	Clear	0.76	0.67	0.67
	Operable	Tinted	0.60	0.53	N.A.
	Fixed	Tinted	0.63	0.55	N.A.

TABLE S-1

Exterior Shading Device		SHGC _{Exterior Shade}
1	Standard Bug Screens	0.76
2	Exterior Sunscreens with Weave 53 x 16/inch	0.30
3	Louvered Sunscreens w/Louvers as Wide as Openings	0.27
4	Low Sun Angle (LSA) Louvered Sunscreens	0.13
5	Vertical Roller or Shades or Retractable or Drop Arm/Marquisolette or Operable Awnings	0.13
6	Roll Down Blinds or Slats	0.13
7	None (for skylights only)	1.00

A. Product Information

01	02	03	04	05	06	07
Tag/ Identification	Orientation	Fenestration has a temporary or Site-built NFRC label certificate	SHGC value from NFRC label	Non-NFRC labeled SHGC information	Exterior Shading Device Type	Exterior Shading SHGC
<<User entry >>	<<User entry >>	<<User select from following: Yes or No>>	<<if cell A03 = yes, then user inputs value. Allow A04 nonnegative decimal value. If cell A03 = no then A04 = N/A>>	<<if cell A03 = Yes then A05 = N/A, else user selects Table 110.6-B or Calculated Using Equation NA6-2 >>	<<User selects from the following list: Standard Bug Screens, Exterior Sunscreens with Weave 53 x 16/inch, Louvered Sunscreens w/Louvers as Wide as Openings, Low Sun Angle (LSA) Louvered Sunscreens, Vertical Roller or Shades or Retractable or Drop Arm/Marquisolet te or Operable Awnings Roll Down Blinds or Slats, None (for skylights only)>>	<< value depends on what is selected in cell A06. If A06 = Standard Bug Screens, SHGC = 0.76. If A06 = Exterior Sunscreens with Weave 53 x 16/inch, SHGC = 0.30. If A06 = Louvered Sunscreens w/Louvers as Wide as Openings, SHGC = 0.27. If A06 = Low Sun Angle (LSA) Louvered Sunscreens, SHGC = 0.13. If A06 = Vertical Roller or Shades or Retractable or Drop Arm/Marquisolet te or Operable Awnings, SHGC = 0.13. If A06 = Roll Down Blinds or Slats, SHGC = 0.13. If A06 = None (for skylights only), SHGC = 1.00>>

B. Default Solar Heat Gain Coefficient Using Table 110.6-B

<<If Column A05 contains entry = Table 110.6-B then display this section; else display section header and standard section does not apply message>>

01	02	03	04	05	06	07
Tag/ Identification	Orientation	Frame Type	Product	Glazing	Number of Panels	Default Fenestration SHGC
<<values should come from Section A for fenestration that has Table 110.6-B in A05>>	<<User selects N, E, S, or W>>	<<user selects from the following list: Metal, Non-metal, or Metal w/Thermal Break>>	<<User selects from following: Fixed or Operable>>	<< User selects from following: Clear or Tinted>>	<<User selects from the following list: Single Pane, Double Pane, Glass Block>>	<< calculated value from Table 110.6-B of the standards based on information provided in cells B03, B04, B05, B06>>

C. Non-Rated Site-built Solar Heat Gain Coefficient Calculation Using Equation NA6-2 from Reference Appendices, Nonresidential Appendix NA6.3

<<If Column A05 contains entry = Equation NA6-2 then display this section; else display section header and standard section does not apply message>>

01	Conditioned Floor Area				<< User entry >>	
02	5% of the Condition Floor Area				<<=(Cell C01 x 0.05)>>	
03	Total Allowed Non-rated site-built Fenestration Area				<< min of C02 or 250>>	
04	Proposed Area of site-built Fenestration				<<user input, nonnegative decimal <= C03; if greater than C03, display message "Proposed site-built Fenestration exceeds allowable area" do not proceed>>	
05	06		07		08	
Tag/ Identification	Glass Area		Center of Glass (COG) Solar Heat Gain Coefficient		Total Allowed SHGC of the Non-Rated Site-Built Fenestration	
<<values should come from Section A for fenestration that has Calculated Using Equation NA6-2 in A05>>	<<User entry, nonnegative decimal >>		<<User entry, non-negative decimal>>		<< = ((C07 x 0.86)+0.08) >>	

D. Combined Solar Heat Gain Coefficient Calculation and Shading Device Calculation

01	02	03	04
Tag/ Identification	$SHGC_{max} =$	$SHGC_{min} =$	total combined adjusted SHGC with exterior shading device ($SHGC_{total}$)
<<should match what was entered in Section A>>	<< =max of cell A04, A07, B07, C08>>	<< = min of A04, A07, B07, C08>>	<<-= (((0.2875 x D02)+0.75)x D03)