



Incident report analysis

Summary	Earlier today, our organization experienced a DoS attack that lasted for two hours. A flood of ICMP packets overloaded the network servers, and internal network services became unresponsive. The ICMP packets entered the network through an unconfigured firewall. We have already responded by blocking incoming ICMP traffic and restoring network services.
Identify	Our analysis of the incident revealed that the attacker took advantage of the unconfigured firewall, which allowed the ICMP flood attack. This took down internal network servers and halted normal business operations.
Protect	To prevent future attacks, we have already implemented new configurations for the firewall, including limiting the rate of incoming ICMP packets and checking for spoofed IP addresses. We will also invest in an IDS/IPS system.
Detect	We have installed network-monitoring software and an IDS/IPS system to detect abnormal traffic patterns and filter out suspicious ICMP traffic.
Respond	In the event of future attacks, we will isolate any affected systems as quickly as possible. We will restore critical systems in a safe manner, and we will analyze network and security logs to understand the progression and range of the incident. We will also report all incidents to upper management and to any legal authorities, as required by law.
Recover	To recover from a DoS ICMP flood attack, the first step is to block all ICMP traffic at the firewall. Then all non-essential network services should be stopped to reduce internal network traffic. Finally, critical network services should be restored, followed by the non-essential services.

Reflections/Notes: