

# Installing WebCenter Content

Windows 7 and MS SQL Server

*A Green Field Installation Guide*

**Andy Little**

Technical Director

Oracle Financial Services Global Business Unit

Rev 1.1, 17 Sep 2017

This guide assumes you are installing Oracle WebCenter Content 12.2.1.3 on Windows 7 SP1 x64 using SQL Server as your target database. Some portions of the installation process may be applicable to other databases as well.

## Prerequisites

1. Database - SQL Server 2012 Express, using defaults with the following exceptions:
  1. Use Mixed Mode authentication; provide a strong password for *sa* user.
  2. Default instance `MSSQLSERVER` rather than named instance).
  3. Using the `Latin1_General_CS_AS_WS` collation (case-sensitive with Unicode support).
  4. Install the SQL Server Management Studio (SSMS) from [here](#).
  5. Create a database using SSMS; name the database something appropriate; referred to hereafter as `<WCC_DB>`. Note: you must enable Read Committed Snapshot or else the RCU will fail. You can turn this on during the creation of the database setting appropriate option, or you can do this after the fact with SSMS (Database > Properties > Options > Miscellaneous > Is Read Committed Snapshot On = True).
  6. Ensure the database owner account is enabled and you know the password. This document assumes the *sa* user.
2. Java Development Kit 1.8.x
  1. Download and install latest JDK 1.8 from [here](#). Must be 64-bit version of JDK.
  2. Set `JAVA_HOME` environment variable
    1. Start -> Computer -> Right Click -> Properties -> Advanced System Settings -> Environment Variables -> System Variables
    2. Locate `JAVA_HOME`. If not available, click New -> Variable Name and enter `JAVA_HOME`
    3. Set Variable Value as the path to JDK installation folder, e.g. `c:\proga~1\Java\JDK1.8.0_144`
3. Windows Configuration
  1. Disable 8.3 file naming by opening Windows Registry Editor.
    1. Locate `HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\FileSystem`
    2. Set `NtfsDisable8dot3NameCreation = 1`

3. Reboot.
2. Refer to product documentation on acquiring and installing the **Visual C++ 2005 Redistributable** package. If this is not installed, the product may fail to start.

## Installation

1. Navigate to here. Accept the license agreement.
2. Download **either** *Quick Installer for Mac OSX, Windows and Linux (209 MB)* or *Generic Installer for Oracle WebLogic Server and Coherence (800 MB)*. This document assumes use of the Generic installer, but either will work.
  1. The Generic installer allows you to customize the installation, selecting an Oracle Home directory, JDK location, and more.
  2. The Quick Installer uses built-in defaults.
3. Download *Fusion Middleware Infrastructure Installer (1.5 GB)*.
4. Navigate to here. Accept the license agreement.
5. Download the *Release 12c 12.2.1.3.0 Generic (1.6 GB)*.
6. Unzip all zip archives into a directory, referenced as <INSTALL\_DIR>
7. Open a command window as Administrator (Start -> Command Window -> Right-Click -> Run as Administrator)
8. Execute the following in <INSTALL\_DIR>

```
C:\> %JAVA_HOME%\bin\java -jar fmw_12.2.1.3.0_wls.jar
```

  1. [ Welcome ] Click Next.
  2. [ Auto Updates ] Select Skip Auto Updates, click Next.
  3. [ Installation Location ] Select desired Oracle Home directory, referred to hereafter as <ORACLE\_HOME>. Click Next.
  4. [ Installation Type ] Select WebLogic Server, click Next
  5. [ Prerequisite Checks ] Click Next. Note: if you have problems, resolve them.
  6. [ Installation Summary ] Click Install. Click Next.
  7. [ Installation Complete ] Uncheck Automatically Launch Configuration Wizard. Click Finish.
9. Execute the following in <INSTALL\_DIR>:

```
C:\> %JAVA_HOME%\bin\java -jar fmw_12.2.1.3.0_infrastructure.jar
```

  1. [ Welcome ] Click Next.
  2. [ Auto Updates ] Select *Skip Auto Updates*, click Next.

3. [ Installation Location ] Select <ORACLE\_HOME> from the dropdown. Click Next.
  4. [ Installation Type ] Select *Fusion Middleware Infrastructure*, click Next
  5. [ Prerequisite Checks ] Click Next. Note: if you have problems, resolve them.
  6. [ Installation Summary ] Click Install. Click Next.
  7. [ Installation Complete ] Click Finish.
10. Execute the following in <INSTALL\_DIR>:
- ```
c:\> %JAVA_HOME%\bin\java -jar fmw_12.2.1.3.0_wcccontent.jar
```
1. [ Welcome ] Click Next.
  2. [ Auto Updates ] Select *Skip Auto Updates*, click Next.
  3. [ Installation Location ] Select <ORACLE\_HOME> from the dropdown. Click Next.
  4. [ Prerequisite Checks ] Click Next. Note: if you have problems, resolve them.
  5. [ Installation Summary ] Click Install. Click Next.
  6. [ Installation Complete ] Click Finish.
11. Run the *Repository Creation Utility (RCU)* in:
- ```
<ORACLE_HOME>/oracle_common/bin/rcu.bat
```
1. [ Welcome ] Click Next.
  2. [ Create Repository ] Select *Create Repository* and *System Load and Product Load*. Click Next.
  3. [ Database Connection Details ] Select *Microsoft SQL Server*, *Unicode Support = Yes*, and *Connection Parameters*. Enter the following as your connection parameters<sup>1</sup>, then click Next. Click OK on the prerequisite check dialog.
    1. *Server Name* = localhost
    2. *Port* = 1433
    3. *Database Name* = <WCC\_DB>
    4. *Username* = sa
    5. *Password* = <sa password>
  4. [ Select Components ] Use the DEV schema prefix, Select *WebCenter Content* which will check other components as well. Click Next. Click OK to dismiss the prerequisite check dialog. Note: if you experience any errors, note the location of the error log and review for remediation.

---

<sup>1</sup> If you chose a named instance other than the default you may need to use Connection String instead.

5. [ Schema Passwords ] Enter passwords for schema(s) as desired. Note this password as you will be required to enter it in the next section. Click Next.
6. [ Summary ] Review summary and click Create. Watch the system load progress, click Close when completed.

## Configuration

1. Run the *Configuration Wizard* in:  
    <ORACLE\_HOME>/oracle\_common/common/bin/config.cmd
2. [ Create Domain ] Select *Create a new domain*. Optionally, select the domain location (hereafter referenced as <DOMAIN\_HOME>). Click Next.
3. [ Templates ] Select the following templates (note that this will , then click Next
  1. Oracle Universal Content Management - Inbound Refinery
  2. Oracle Universal Content Management - Content Server
  3. Oracle Universal Content Management - Web UI
  4. Oracle WebCenter Enterprise Capture
4. [ High Availability Options ] Accept defaults and click Next.
5. [ Application Location ] Accept defaults and click Next.
6. [ Administrator Account ] Enter a password for the weblogic user and click Next.
7. [ Domain Mode and JDK ] Select development mode and specify the JDK (it should be set to the JDK you use to execute the installer JAR. Click Next.
8. [ Datasources ] Check the box for the given datasource(s) and then update the settings as shown below, then click Next.
  1. Vendor : MS SQL Server
  2. Driver : Oracle's MS SQL Server Driver (Type 4) Versions: Any<sup>2</sup>
  3. Hostname : localhost
  4. DBMS/Service : WCC
  5. Port : 1433
  6. Username : DEV\_MDS
  7. Password : <password entered in Schema Passwords step>
9. [ JDBC DS Test ] All tests should complete ok, Click Next.

---

<sup>2</sup> Do NOT choose the Type 4:XA driver!

10. [ Database Configuration Type ] Select *RCU Data*, then use the same settings as shown Datasources (exception is that Username : DEV\_STB. Click *Get RCU Configuration*. Click Next.
11. [ Component Datasources ] Click Next.
12. [ JDBC Test ] All tests should complete ok, Click Next.
13. [ Credentials ] Enter a username and password, then click Next. Note: MOS note suggests this username should be set to *sysadmin*.
14. [ Advanced Configuration ] Select *Administration Server*, *Topology*, and *Deployments and Services*<sup>3</sup>. Click Next.
15. [ Administration Server ] Choose a *single* Listen Address (specifically an IP address, not localhost and not All Local Addresses). Leave Server Groups as Unspecified. You may enable SSL and optionally change all Listen Ports (although for this guide I will leave as default 7001/7002). Click Next.
16. [ Managed Servers ] Choose a *single* Listen Address for each Managed Server. *If you don't choose the actual IP address, the installer may complain later*. Note: the names for the managed servers may be slightly different, but the names aren't important. Do not enable SSL until you have a functional SSL certificate. Recommended settings are shown below; do not change the group names. Click Next<sup>4</sup>.

1. WCC User Interface

1. Server Name=wccui\_server\_1 (may show as wccadf\_server1)
2. Listen address=<IP\_ADDRESS>
3. Listen port=16225
4. Enable SSL on SSL Listen port 16227
5. Server Group is UCM-ADF-MGD-SVR
6. Click add and repeat above, incrementing the server name by 1, Listen Port = 7003, and SSL Port 16227.

2. Capture Server

1. Server Name=capture\_server1 (may show as cpt\_server1)
2. Listen address=<IP\_ADDRESS>

---

<sup>3</sup> You may add Node Manager, but for a development server this is probably not required. If so, follow the product installation documentation for specifics.

<sup>4</sup> The product installation documentation suggests creating additional managed servers for high availability but this step is not required for a development environment.

3. Listen port=16400
4. Server Group is CAPTURE-MGD-SVR
5. Click add and repeat above, incrementing the server name by 1, Listen Port = 7004. No SSL.
3. WCC Server
  1. Server Name=wcc\_server\_1 (may show as UCM\_server1)
  2. Listen address=<IP\_ADDRESS>
  3. Listen port=16200
  4. Enable SSL on SSL Listen Port 16201.
  5. Server Group is UCM-MGD-SVR
4. IBR Server
  1. Server Name=ibr\_server\_1
  2. Listen address=<IP\_ADDRESS>
  3. Listen port=16250
  4. Server Group is IBR-MGD-SVR
17. [ Clusters ] Name the default cluster wcc\_cluster\_1. Leave defaults. Click Add.
  1. Name the cluster cpt\_cluster\_1. Leave defaults. Click Add.
  2. Name the cluster ibr\_cluster\_1. Leave defaults. Click Add.
  3. Name the cluster wccui\_cluster\_1. Leave defaults. Click Next.
18. [ Server Templates ] Click Next. This is not needed for development environments.
19. [ Dynamic Servers ] Click Next.
20. [ Assign Servers to Clusters ] Select cpt\_server\_n in the Servers panel, select the cpt\_cluster\_1 in the Clusters panel. Click the Right arrow. Repeat for similarly-named servers and clusters. Click Next.
21. [ Coherence Clusters ] Click Next.
22. [ Machines ] Click Add and set the machine name to wcc\_machine\_1. Select a listen address that is *not localhost*. Click Next.
23. [ Assign Servers to Machines ] Move all servers to the machine wcc\_machine\_1. Click Next.
24. [ Virtual Targets ] Click Next. This is not needed for development environments.
25. [ Partitions ] Click Next. This is not needed for development environments.

26. [ Deployments Targeting ] Review the AppDeployment sections under each server, so you can see which applications are deployed to which managed server. Click Next.  
Example:
1. UCM\_server1 contains Oracle Universal Content Management - Content Server
  2. WCCADF\_Server1 contains Oracle WebCenter Content - Web UI
27. [ Services Targeting ] Click Next.
28. [ Configuration Summary ] If you see any warnings, correct them then come back to this screen. Click Create.
1. If you didn't pick IP addresses [here](#) or [here](#), you may see a complaint from Coherence clustering. To resolve, click the Administrator Server link on the left and select an IP address, and/or click Managed Servers on the left and select an IP address.
29. [ Configuration Progress ] Click Next when available.
30. [ End of Configuration ] Note the AdminServer URL that should look like *http://ipaddress:port/console*. Note the IP address and port as <ADMINSERVER>. Click Finish.
31. Install NodeManager as a Windows Service by executing <DOMAIN\_HOME>/bin/installNodeMgrSvc.cmd.
32. Optional: Using Notepad or similar text editing tool, open <DOMAIN\_HOME>/bin/startManagedWebLogic.cmd. Locate the following lines and add the credentials you configured in step 3.6. If you do not do this step, you will be prompted for the credentials any time you start a managed server. If you rerun the domain configuration tool, you will have to re-edit the cmd file.
33. Start NodeManager.
1. Start -> Run -> Services.msc
  2. Locate "Oracle WebLogic base\_domain NodeManager" service. Right click and select Start.
34. Start the AdminServer
1. Execute <DOMAIN\_HOME>/bin/startWebLogic.cmd
  2. A shell window will appear; when the system is ready you should see <Notice>  
<WebLogicServer> <BEA-000365> <Server state changed to RUNNING.>
35. Start Managed Servers. This can be done with either Enterprise Manager or WLS Console.



1. To use EM:
    1. Browse to <ADMINSERVER>/em (e.g. <http://localhost:7001/em>) and login with the credentials from Configuration Step 6.
    2. Select each desired server, and select Control > Start
  2. To use Console:
    1. Browse to <ADMINSERVER>/console and login with the credentials from Configuration Step 6.
    2. Select Environment > Servers from the Domain Structure.
    3. Select the Control tab in Summary of Servers
    4. Select the ibr\_server\_1 and wcc\_server\_1 servers using the checkbox.
    5. Click the Start button.
36. Configure Inbound Refinery (IBR)
1. Open a browser to <http://<server>:16250/ibr>, where server is the host where IBR is installed. Login the credentials from Configuration Step 6.
  2. You can review the default settings [here](#), the defaults should be sufficient.
  3. Click Submit. Restart the node as shown in step 35.
37. Configure Content Server (CS)
1. Open a browser to <http://<server>:16200/cs>, where server is the host where CS is installed. Login the credentials from Configuration Step 6.
  2. You can review the default settings [here](#), the defaults should be sufficient.
  3. Click Submit. Restart the node as shown in step 35.

## Exploration

Now you can proceed to explore the system and its configuration. Before beginning, you may wish to review the [Using WebCenter Content](#) documentation. This will allow you to become familiarized with concepts of working with and managing content, including general concepts of content management, document libraries, enterprise libraries, folders, and document workflows. This information is in Part I of the Using Oracle WebCenter Content document, available [here](#).

The Oracle WebCenter User Interface is a modern, intuitive interface that enables users to manage content in dynamic ways. Information on how to use this interface covers finding libraries, folders, and documents, viewing and annotating documents, check-in and check-

out of documents, how to work with libraries and content folders, and use of workflows. This information is in Part II of the Using Oracle WebCenter Content document, available [here](#).

## **Use Cases**

The list of use cases below is separated into non-functional and functional, where non-functional use cases are exemplary of system administration and configuration, and functional use cases are for end-users. The list of use case shows recommended application(s) and function(s) that will satisfy those use cases.

### Non-Functional Use Cases

1. To create highly-available service clusters, use the WebLogic Console.
2. To administer managed servers, use the WebLogic Console or WebLogic Enterprise Manager.
3. To administer clusters, use the WebLogic Enterprise Manager.
4. To administer the Content Server, use the WebLogic Content Server. This can include:
  1. Creating workflows
  2. Defining retention requirements
  3. Defining and administering scheduled jobs
  4. Configuring records settings
  5. Reviewing log files
  6. Refinery administration (the refinery is responsible for file format conversions).
  7. Security Configuration

### Functional Use Cases

1. To define Libraries, Workflows, Folders, use WebCenter Content Server.
2. To participate in Workflows, use WebCenter Content Server or WebCenter User Interface.

## **Application URLs**

Replace `localhost` with the hostname or IP address where you have installed the products using the steps above.

WebLogic Console	<a href="http://localhost:7001/console">http://localhost:7001/console</a>
WebLogic Enterprise Manager	<a href="http://localhost:7001/em">http://localhost:7001/em</a>
WebCenter Content Server	<a href="http://localhost:16200/cs">http://localhost:16200/cs</a>
WebCenter Content User Interface	<a href="http://localhost:16225/wcc">http://localhost:16225/wcc</a>
WebCenter Inbound Refinery	<a href="http://localhost:16250/ibr">http://localhost:16250/ibr</a>
WebCenter Capture	<a href="http://localhost:7004/cpt">http://localhost:7004/cpt</a>