

INDEX

ABOUT US	1						
PRODUCT RANGE	1						
American Tourer RP88	2						
American Tourer SA07	4						
American Tourer SV308	6						
American Tourer SL309 H/T	8						
American Tourer SU317 H/T	10						
American Tourer SL369 A/T	12						
LIMITED WARRANTY							



ABOUT US

American Tourer is the latest consumer tire brand from the house of Omni United. These tires have been engineered for the specific needs of the American driver and offer a wide variety of fitments that fit popular cars, CUVs, SUVs and light trucks.

The engineers at American Tourer are committed to attaining the highest performance, durability and manufacturing quality standards. Our Research and Development team implements its own stringent quality control processes that are audited both internally and externally. The manufacturing location is amongst the most sophisticated in the world and has been accredited with the following international quality standards: ISO 9001:2016, ISO 14001:2004 and DOT.

PRODUCT RANGE

American Tourer RP88
Touring I PCR



American Tourer SA07 Sport Touring I PCR/SUV



American Tourer SV308 Sport Touring I SUV



American Tourer SL309 H/T Highway I SUV/LT



American Tourer SU317 H/T Highway I CUV/SUV



American Tourer SL369 A/T All Terrain I SUV/LT



SUMMER I TOURING

American Tourer RP88 PCR

The American Tourer RP88 is a touring tire range that is designed for compact to large sedans. This range offers high driving stability, good traction on wet roads and a quiet ride.



Rim: 14 - 16 | **Width**: 175 - 235 | **Aspect Ratio**: 50 - 70 | **Speed Rating**: T, H, V

L.R.: SL | UTQG: 500AA | Marking: M+S

FEATURES

- · Variable pitch tread pattern
- · Continuous center rib
- Four grooves with open shoulder design

BENEFITS

- · Delivers a refined and quiet ride
- Provides improved handling and stability

03

Efficient water evacuation

SIZES AND SPECIFICATIONS

RIM	SIZE	L.I./S.R.	L.R.	SIDEWALL	STANDARD RIM	T.D. (1/32")	O.D. (IN)	SECTION WIDTH (IN)	UTQG	MAX. LOAD(LBS)	MAX. PRESSURE(PSI)
	175/65R14	82H		BSW	5.OJ	9.4	23.0	7.0	500AA	1047	44
	175/70R14	84T		BSW	5.OJ	9.4	23.7	7.0	500AA	1102	44
	185/60R14	82H		BSW	5.5)	9.4	22.8	7.4	500AA	1047	44
14	185/65R14	86H		BSW	5.5)	9.4	23.5	7.4	500AA	1168	44
14	185/70R14	88T		BSW	5.5)	9.4	24.3	7.4	500AA	1235	44
	195/60R14	86H		BSW	6.0J	9.8	23.2	7.9	500AA	1168	44
	195/70R14	91T		BSW	6.0J	9.8	24.8	7.9	500AA	1356	44
	205/70R14	95T		BSW	6.0J	9.8	25.4	8.2	500AA	1521	44
	185/60R15	84H		BSW	5.5J	9.4	23.7	7.4	500AA	1102	44
	185/65R15	88H		BSW	5.5J	9.4	24.4	7.4	500AA	1235	44
	195/60R15	88H		BSW	6.0J	9.8	24.2	7.9	500AA	1235	44
15	195/65R15	91H		BSW	6.0J	9.8	25.0	7.9	500AA	1356	44
15	205/60R15	91H		BSW	6.0J	9.8	24.7	8.2	500AA	1356	44
	205/65R15	94H		BSW	6.0J	9.8	25.5	8.2	500AA	1477	44
	205/70R15	96H		BSW	6.0J	9.8	26.3	8.2	500AA	1565	44
	215/70R15	98H		BSW	6.5J	9.8	26.9	8.7	500AA	1653	44
	205/50R16	87V		BSW	6.5J	9.8	24.1	8.4	500AA	1202	44
	205/55R16	91V		BSW	6.5J	9.8	24.9	8.4	500AA	1356	44
	205/60R16	92H		BSW	6.0J	9.8	25.7	8.2	500AA	1389	44
	205/65R16	95H		BSW	6.0J	9.8	26.5	8.2	500AA	1521	44
16	215/60R16	95H		BSW	6.5J	9.8	26.1	8.7	500AA	1521	44
16	215/65R16	98H		BSW	6.5J	9.8	27.0	8.7	500AA	1653	44
	225/60R16	98H		BSW	6.5J	9.8	26.6	9.0	500AA	1653	44
	225/65R16	100H		BSW	6.5J	9.8	27.5	9.0	500AA	1764	44
	235/60R16	100H		BSW	7.OJ	9.8	27.1	9.4	500AA	1764	44
	235/65R16	103H		BSW	7.OJ	9.8	28.0	9.4	500AA	1929	44

Speed Rating: T = 118mph;190km/h, H = 130mph;210km/h, V = 149mph;240km/h, L.R. = Load Range, SL = Standard Load, UTQG = Uniform Tire Quality Grading M+S = Mud and Snow, L.I. = Load Index, S.R. = Speed Rating, BSW = Black Side Wall, T.D. = Tread Depth, O.D. = Overall Diameter, IN. = Inches, LBS = Pounds PSI = Pounds per square inch

ALL SEASON I SPORT TOURING

American Tourer SA07 PCR/SUV

The American Tourer SA07 is an all-season sport touring tire range that is designed for high performance cars and SUVs. This premium range offers drivers confident and progressive handling, good hydroplaning resistance, enhanced wet and dry traction and low rolling resistance.



Rim: 16 - 20 | **Width**: 195 - 265 | **Aspect Ratio**: 35 - 55 | **Speed Rating**: V, W, Y

L.R.: SL, XL | UTQG: 460AA | Marking: M+S

FEATURES

- Asymmetric tread pattern with wide circumferential grooves
- · Silica tread compound technology
- Functional rim protectors

BENEFITS

- Offers quick and efficient water evacuation and enhanced wet handling
- Delivers low rolling resistance and good wet and dry traction

05

Protects rims against curbing damage

SIZES AND SPECIFICATIONS

RIM	SIZE	L.I./S.R.	L.R.	SIDEWALL	STANDARD RIM	T.D. (1/32")	O.D. (IN)	SECTION WIDTH (IN)	UTQG	MAX. LOAD(LBS)	MAX. PRESSURE(PSI)
16	195/45R16	84V	XL	BSW	6.5J	9.8	22.9	7.7	460AA	1102	51
	205/55R16	91V		BSW	6.5J	10.1	24.9	8.4	460AA	1356	44
16	215/55R16	93V		BSW	7.OJ	10.7	25.3	8.9	460AA	1433	44
	225/55R16	95W		BSW	7.OJ	10.7	25.7	9.2	460AA	1521	44
	205/40ZR17	84W	XL	BSW	7 . 5J	10.1	23.5	8.3	460AA	1102	51
	205/45ZR17	88W	XL	BSW	7.OJ	10.1	24.3	8.1	460AA	1235	51
	205/50R17	89W		BSW	6.5J	10.1	25.1	8.4	460AA	1279	44
	215/40ZR17	87W	XL	BSW	7 . 5J	10.1	23.8	8.6	460AA	1202	51
	215/45ZR17	91W	XL	BSW	7.OJ	10.1	24.6	8.4	460AA	1356	51
	215/50R17	91W		BSW	7.OJ	10.1	25.5	8.9	460AA	1356	44
	215/55R17	94V		BSW	7.OJ	10.7	26.3	8.9	460AA	1477	44
17	225/45ZR17	94W	XL	BSW	7.5J	10.1	25.0	8.9	460AA	1477	51
17	225/50R17	94W		BSW	7.OJ	10.7	25.9	9.2	460AA	1477	44
	225/55R17	97W		BSW	7.OJ	10.1	26.8	9.2	460AA	1609	44
	235/45ZR17	97W	XL	BSW	8.0J	10.1	25.4	9.3	460AA	1609	51
	235/50R17	100W	XL	BSW	7 . 5J	10.1	26.3	9.6	460AA	1764	51
	235/55R17	99W		BSW	7.5J	10.1	27.2	9.6	460AA	1709	44
	245/40ZR17	95W	XL	BSW	8.5J	10.1	24.7	9.8	460AA	1521	51
	245/45ZR17	95Y		BSW	8.0J	10.1	25.7	9.6	460AA	1521	44
	255/45ZR17	98W		BSW	8.5J	10.1	26.1	10.0	460AA	1653	44
	215/35ZR18	84W	XL	BSW	7.5J	10.1	23.9	8.6	460AA	1102	51
	215/40ZR18	89W	XL	BSW	7.5J	10.1	24.8	8.6	460AA	1279	51
	215/45ZR18	89W		BSW	7.OJ	10.1	25.6	8.4	460AA	1279	44
	225/40ZR18	92W	XL	BSW	8.0J	10.1	25.1	9.1	460AA	1389	51
	225/45ZR18	95W	XL	BSW	7.5J	10.1	25.9	8.9	460AA	1521	51
18	235/40ZR18	95W	XL	BSW	8.5J	10.1	25.4	9.5	460AA	1521	51
	235/45ZR18	94Y		BSW	8.0J	10.1	26.3	9.3	460AA	1477	44
	235/50R18	101W	XL	BSW	7.5J	10.1	27.3	9.6	460AA	1819	51
	245/40ZR18	97Y	XL	BSW	8.5J	10.1	25.7	9.8	460AA	1609	51
	245/45ZR18	96Y		BSW	8.0J	10.1	26.7	9.6	460AA	1565	44
	245/50R18	100Y		BSW	7.5J	10.1	27.7	10.0	460AA	1764	44
	225/40ZR19	93W	XL	BSW	8.0J	10.1	26.1	9.1	460AA	1433	51
10	245/40ZR19	94Y		BSW	8.5J	10.1	26.7	9.8	460AA	1477	44
19	255/35ZR19	96W	XL	BSW	9.0)	10.1	26.0	10.2	460AA	1565	51
	255/40ZR19	100W	XL	BSW	9.0J	10.1	27.0	10.2	460AA	1764	51
2.0	245/35ZR20	95W	XL	BSW	8.5)	10.1	26.8	9.8	460AA	1521	51
20	265/50R20	111V	XL	BSW	8.5J	10.1	30.5	10.9	460AA	2403	51

Speed Rating: V = 149mph;240km/h, W = 168mph;270 km/h, Y = 186 mph;300km/h, L.R. = Load Range, SL = Standard Load, XL = Extra Load, UTQG = Uniform Tire Quality Grading, M+S = Mud and Snow, L.I. = Load Index, S.R. = Speed Rating, BSW = Black Side Wall, T.D. = Tread Depth O.D. = Overall Diameter, IN. = Inches, LBS = Pounds, PSI = Pounds per square inch

* **American Tourer** *

ALL SEASON I SPORT TOURING

American Tourer SV308 SUV

The American Tourer SV308 is an all-season sport touring tire range that is designed for high performance SUVs. This tire range offers precise and predictable handling, great traction on wet and dry highways, efficient water clearance and outstanding cornering grip.



Rim: 20 - 24 | **Width**: 265 - 305 | **Aspect Ratio**: 35 - 55 | **Speed Rating**: H

L.R.: SL, XL | UTQG: 460AA | Marking: M+S

FEATURES

- · Silica-based tread compound
- Functional Rim Protectors
- Circumferential V-shaped grooves
- Solid center rib

BENEFITS

- Provides good traction on wet and dry highways
- Protects the wheel rim from damage

07

- · Promotes efficient water drainage
- Delivers stable center feel and outstanding wet traction when cornering

SIZES AND SPECIFICATIONS

RIM	SIZE	L.I./S.R.	L.R.	SIDEWALL	STANDARD RIM	T.D. (1/32")	O.D. (IN)	SECTION WIDTH (IN)	UTQG	MAX. LOAD(LBS)	MAX. PRESSURE(PSI)
	275/45R2O	110H	XL	BSW	9.0J	11.7	29.8	10.7	460AA	2337	44
20	275/55R2O	117H	XL	BSW	8.5J	11.7	31.9	11.2	460AA	2833	44
	285/50R20	112H		BSW	9.0J	11.9	31.3	11.7	460AA	2469	44
	265/35R22	98H		BSW	9.5J	11.7	29.3	10.7	460AA	1653	44
22	305/40R22	110H		BSW	11.0J	12.3	31.6	12.3	460AA	2337	44
	305/45R22	118H	XL	BSW	10.0J	12.3	32.8	11.9	460AA	2910	44
24	305/35R24	112H	XL	BSW	11.0J	12.3	32.4	12.3	460AA	2469	44

Speed Rating: H = 130mph;210km/h, L.R. = Load Range, SL = Standard Load, XL = Extra Load, UTQG = Uniform Tire Quality Grading, M+S = Mud and Snow L.I. = Load Index, S.R. = Speed Rating, BSW = Black Side Wall, T.D. = Tread Depth, O.D. = Overall Diameter, IN. = Inches, LBS = Pounds, PSI = Pounds per square inch



ALL SEASON I HIGHWAY

American Tourer SL309 H/T SUV/LT

The American Tourer SL309 H/T is an all-season highway terrain tire that is designed for SUVs and light trucks. This range offers confident and predictable handling, along with stability, exceptional durability and high load carrying capacity.



Rim: 15 - 18 | Width: 215 - 285, 10.50 | Aspect Ratio: 65 - 85 | Speed Rating: Q

L.R.: C, D, E | **UTQG**: - | **Marking**: M+S

FEATURES

- · Optimized all-season tread pattern design
- Two ply casing construction
- Heavy duty steel belt plies and two full joint-less nylon cap plies

BENEFITS

- Provides confidence in all-weather conditions
- Offers high load carrying capacity and delivers outstanding durability
- Delivers class beating handling, stability and durability

SIZES AND SPECIFICATIONS

RIM	SIZE	L.I./S.R.	L.R.	SIDEWALL	STANDARD RIM	T.D. (1/32")	O.D. (IN)	SECTION WIDTH (IN)	UTQG	MAX. LOAD(LBS)	MAX. PRESSURE(PSI)
	31×10.50R15LT	109 Q	С	BSW	8.5J	12.6	30.5	10.6	-	2271	51
15	LT215/75R15	100/97 Q	С	BSW	6.0J	11.3	27.7	8.5	-	1764/1609	51
	LT235/75R15	104/101 Q	С	BSW	6.5)	10.9	28.9	9.3	-	1984/1819	51
	LT215/85R16	115/112 Q	Е	BSW	6.0J	11.3	30.4	8.5	-	2679/2469	80
	LT225/75R16	115/112 Q	Е	BSW	6.0J	11.9	29.3	8.8	-	2679/2469	80
16	LT235/85R16	120/116 Q	Е	BSW	6.5J	13.2	31.7	9.3	-	3042/2778	80
10	LT245/75R16	120/116 Q	Е	BSW	7.OJ	13.2	30.5	9.8	-	3042/2778	80
	LT265/75R16	123/120 Q	E	BSW	7.5J	13.2	31.7	10.5	-	3417/3086	80
	LT285/75R16	122/119 Q	D	BSW	8.0J	13.2	32.8	11.3	-	3307/2998	65
	LT235/80R17	120/117Q	Е	BSW	6.5J	15.7	31.8	9.3	-	3086/2833	80
	LT245/70R17	119/116Q	Е	BSW	7.OJ	15.7	30.6	9.8	-	2998/2756	80
17	LT245/75R17	121/118Q	Е	BSW	7.OJ	15.7	31.5	9.8	-	3197/2910	80
	LT265/70R17	121/118Q	Е	BSW	8.0J	14.8	31.7	10.7	-	3197/2910	80
	LT285/70R17	121/118Q	D	BSW	8.5J	16.1	32.8	11.5	-	3197/2910	65
18	LT275/65R18	123/120Q	Е	BSW	8.0J	14.7	32.1	11.0	-	3417/3086	80

Speed Rating: Q = 99mph;160km/h, L.R. = Load Range, C = 6 Ply Rating, D = 8 Ply Rating, E = 10 Ply Rating, UTQG = Uniform Tire Quality Grading, M+S = Mud and Snow L.I. = Load Index, S.R. = Speed Rating, BSW = Black Side Wall, T.D. = Tread Depth, O.D. = Overall Diameter, IN. = Inches, LBS = Pounds, PSI = Pounds per square inch

omni-united.com 09 **American_Tourer*

ALL SEASON I HIGHWAY

American Tourer SU317 H/T CUV/SUV

The American Tourer SU317 H/T is a P-metric, all-season highway terrain tire that is designed to fit on CUVs & SUVs. This range offers good mileage and a quiet and comfortable ride.



Rim: 15 - 17 | **Width**: 215 - 265 | **Aspect Ratio**: 65 - 75 | **Speed Rating**: T, H

L.R.: SL | UTQG: 600AA | Marking: M+S

FEATURES

- · Wide shoulder block design
- Advanced tread compound technology
- · Asymmetric tread design

BENEFITS

- · Delivers stability and even wear
- Offers great control in wet and dry conditions
- Provides exceptional handling and good hydroplaning resistance

SIZES AND SPECIFICATIONS

RIM	SIZE	L.I./S.R.	L.R.	SIDEWALL	STANDARD RIM	T.D. (1/32")	O.D. (IN)	SECTION WIDTH (IN)	UTQG	MAX. LOAD(LBS)	MAX. PRESSURE(PSI)
15	P235/75R15	105H		BSW	6.5J	10.9	28.9	9.3	600AA	2039	44
	P215/65R16	98H		BSW	6.5J	10.7	27.0	8.7	600AA	1653	44
	P215/70R16	100T		BSW	6.5J	10.9	27.9	8.7	600AA	1764	44
	P225/70R16	103H		BSW	6.5J	10.9	28.4	9.0	600AA	1929	44
	P225/75R16	104H		BSW	6.0J	10.9	29.3	8.8	600AA	1984	44
16	P235/70R16	106H		BSW	7.OJ	11.3	29.0	9.4	600AA	2094	44
	P245/70R16	107T		BSW	7.OJ	11.9	29.5	9.8	600AA	2150	44
	P255/65R16	109H		BSW	7.5J	11.9	29.1	10.2	600AA	2271	44
	P255/70R16	111H		BSW	7 . 5J	11.9	30.1	10.2	600AA	2403	44
	P265/70R16	112T		BSW	8.0J	11.9	30.6	10.7	600AA	2469	44
	P225/65R17	102H		BSW	6.5J	10.7	28.5	9.0	600AA	1874	44
17	P235/65R17	104H		BSW	7.0J	11.3	29.1	9.4	600AA	1984	44
17	P245/65R17	107T		BSW	7.0J	11.9	29.5	9.8	600AA	2150	44
	P265/70R17	115H		BSW	8.0J	11.9	31.7	10.7	600AA	2679	44

Speed Rating: T = 118mph;190km/h, H = 130mph;210km/h, L.R. = Load Range, SL = Standard Load, UTQG = Uniform Tire Quality Grading, M+S = Mud and Snow L.I. = Load Index, S.R. = Speed Rating, BSW = Black Side Wall, T.D. = Tread Depth, O.D. = Overall Diameter, IN. = Inches, LBS = Pounds, PSI = Pounds per square inch

ALL SEASON I ALL TERRAIN

American Tourer SL369 A/T SUV/LT

The American Tourer SL369 A/T is an all-season, all-terrain tire that is designed for SUVs and light trucks. This tire range offers enhanced traction on both wet and dry roads as well as off road. This tires deliver assured performance on tracks and trails off the road without compromising comfort and handling on the road.



Rim: 15 - 20 | **Width**: 215-315, 10.50-12.50 | **Aspect Ratio**: 55 - 85

Speed Rating: Q, R, S, T | **L.R.**: SL, XL, C, D, E | **UTQG**: 500AA | **Marking:** M+S

FEATURES

- · Wide tread and multi-stepped grooves
- · Latest tread compound technology
- Aggressive sidewall protectors

BENEFITS

- Offers enhanced traction both on and off roads
- Delivers superb cut and chip resistance as well as good grip in all conditions on all surfaces
- Increases off-road bite and prevents damage to the sidewall from cuts and abrasions

SIZES AND SPECIFICATIONS

RIM	SIZE	L.I./S.R.	L.R.	SIDEWALL	STANDARD RIM	T.D. (1/32")	O.D. (IN)	SECTION WIDTH (IN)	UTQG	MAX. LOAD(LBS)	MAX. PRESSURE(PSI)
15	235/75R15	109S	XL	BSW	6.5J	11.9	28.9	9.3	500AA	2271	51
12	31×10.50R15LT	109Q	С	OWL	8.5J	15.7	30.5	10.6	-	2271	51
	215/70R16	1005		BSW	6.5J	11.9	27.9	8.7	500AA	1764	44
	LT215/85R16	115/112 Q	Е	BSW	6.0J	13.8	30.4	8.5	-	2679/2469	80
	225/70R16	103S		BSW	6.5J	11.9	28.4	9.0	500AA	1929	44
	225/75R16	1085	XL	BSW	6.0J	11.9	29.3	8.8	500AA	2205	51
	LT225/75R16	115/112 Q	Е	BSW	6.0J	13.8	29.3	8.8	-	2679/2469	80
	P235/70R16	106S		BSW	7.0J	11.9	29.0	9.4	500AA	2094	44
	235/75R16	112S	XL	BSW	6.5J	11.9	29.8	9.3	500AA	2469	51
	LT235/85R16	120/116 Q	Е	BSW	6.5J	15.7	31.7	9.3	-	3042/2778	80
16	245/70R16	1115	XL	BSW	7.0J	13.6	29.5	9.8	500AA	2403	51
16	245/75R16	111S		BSW	7.OJ	13.6	30.5	9.8	500AA	2403	44
	LT245/75R16	120/116 Q	Е	OWL	7.0J	15.7	30.5	9.8	-	3042/2778	80
	255/70R16	111T		BSW	7 . 5J	13.6	30.1	10.2	500AA	2403	44
	265/70R16	112S		BSW	8.0J	13.6	30.6	10.7	500AA	2469	44
	265/75R16	1165		BSW	7 . 5J	13.6	31.7	10.5	500AA	2756	44
	LT265/75R16	123/120 Q	Е	OWL	7 . 5J	15.7	31.7	10.5	-	3417/3086	80
	275/70R16	114S		BSW	8.0J	13.6	31.2	11.0	500AA	2601	44
	LT285/75R16	122/119Q	D	OWL	8.0J	16.1	32.8	11.3	-	3748/3417	80
	LT315/75R16	127/124R	Е	BSW	8.5J	16.1	34.6	12.3	-	3858/3527	65
	235/65R17	104S		BSW	7.0J	11.9	29.1	9.4	500AA	1984	44
	LT235/80R17	120/117Q	Е	BSW	6.5J	15.7	31.8	9.3	-	3086/2833	80
	245/65R17	1075		BSW	7.0J	13.6	29.5	9.8	500AA	2150	44
	245/70R17	110T		BSW	7.OJ	13.6	30.6	9.8	500AA	2205	44
	LT245/70R17	119/116Q	Е	BSW	7.OJ	15.7	30.6	9.8	-	2998/2756	80
	LT245/75R17	121/118Q	Е	BSW	7.OJ	15.7	31.5	9.8	-	3197/2910	80
17	265/65R17	112S		BSW	8.0J	13.6	30.6	10.7	500AA	2469	44
	265/70R17	115T		BSW	8.0J	13.6	31.7	10.7	500AA	2679	44
	LT265/70R17	121/118Q	Е	OWL	8.0J	15.7	31.7	10.7	-	3197/2910	80
	285/70R17	117T		BSW	8.5J	13.6	32.8	11.5	500AA	2833	44
	LT285/70R17	121/118Q	D	BSW	8.5J	16.1	32.8	11.5	-	3197/2910	65
	LT315/70R17	121/118R	Е	BSW	9.5J	16.1	34.4	12.7	-	3197/2910	65
	35×12.50R17LT	121Q	Е	BSW	10.0J	16.1	34.5	12.5	-	3197	65
18	275/65R18	116T		BSW	8.OJ	11.9	32.1	11.0	500AA	2756	44
10	LT275/65R18	123/120Q	Е	BSW	8.0J	16.1	32.1	11.0	-	3417/3086	80
	275/55R2O	1135		BSW	8.5J	11.9	31.9	11.2	500AA	2535	44
20	275/60R20	115T		BSW	8.0J	11.9	33.0	11.0	500AA	2679	44
20	LT275/65R20	126/1235	Е	BSW	8.OJ	16.1	34.1	11.0	-	3748/3417	80
	LT305/55R20	121/118R	Е	BSW	9.5J	16.1	33.2	12.4	_	3197/2910	65

Speed Rating: Q = 99mph;160km/h, R = 106mph;170km/h, S = 112mph;180km/h, T = 118mph; 190km/h, L.R. = Load Range, SL = Standard Load, XL = Extra Load C = 6 Ply Rating, D = 8 Ply Rating, E = 10 Ply Rating, UTQG = Uniform Tire Quality Grading, M+S = Mud and Snow, L.I. = Load Index, S.R. = Speed Rating BSW = Black Side Wall, OWL = Outline White Letters, T.D. = Tread Depth, O.D. = Overall Diameter, IN. = Inches, LBS = Pounds, PSI = Pounds per square inch



LIMITED WARRANTY

ELIGIBILITY

- This limited warranty applies to the original purchaser of a replacement American Tourer passenger or light truck tire bearing the DOT mark and is not transferable.
- Eligible tires must be purchased new and used on the vehicle that they were originally installed on.
- Proof of purchase is required for all warranty claims.
- The tires must be the size, load index, and speed rating equivalent or an acceptable alternative as specified by the vehicle manufacturer.
- · Applicable in the United States only.
- This warranty succeeds all previous warranties and applies to tires purchased after July 1st, 2017.

WORKMANSHIP AND MATERIALS WARRANTY

If a tire becomes unserviceable due to workmanship or material anomalies during the initial warranty period, which is one year from the date of original retail purchase of the replacement tires (purchase receipt required) or within the first 2/32" (1.6mm) of the original usable tread, whichever occurs first, the tire will be replaced to the owner free of charge. To receive consideration for warranty coverage, tires must be returned to an authorized American Tourer dealer. Technicians designated by American Tourer will make the final determination regarding qualification for Workmanship and Materials coverage on tires submitted to American Tourer via authorized channels. If the tire is presented for ride related anomalies the warranty period is one year from the date of original retail purchase of the vehicle or purchase of replacement tires (purchase receipt required) or within the first 2/32" (1.6mm) of the original usable tread, whichever occurs first. The owner must pay for any associated service charges, including costs associated with mounting and balancing in both the aforementioned cases.

WHAT IS NOT COVERED

All warranties will be null and void if any of the following conditions are found to exist:

- Tires transferred from the vehicle on which they were originally installed.
- Tires acquired as used (tires purchased used, equipped on a pre-owned vehicle etc.)
- · Tires used in any commercial application (i.e. tires used for taxi service, delivery etc.)
- · Misapplication (insufficient Speed Rating, Load Index, undersized or oversized tires, etc.)
- Tires damaged from improper mounting/dismounting.
- Tires damaged from dealer/retailer services: mounting, dismounting, balancing, studding, tire rotation or wheel alignment.
- · Passenger tires used on commercial vehicles or used in commercial applications.
- · Tires in which anything other than air or nitrogen has been used as the inflation medium.

- Tires injected with liquid balancer or sealant or any other balancing/sealing material or insert.
- Tires which have been modified by the addition or removal of material or any tire intentionally altered to change its appearance.
- Tires which become unserviceable because of tire operation in excess of tire/wheel manufacturers' specifications and recommendations, including spinning.
- Tires improperly repaired or with repairs not conforming to relevant Rubber Manufacturers Association standards, or with section repairs, or with a self-vulcanizing plug only or patch only.
- Tires which have been altered in any manner (recapped, re-treaded, regrooved, additional siping, buffing, stud pin holes etc.)
- Tires used in racing or other competitive events, or in off-road applications.
- · Multiple tires removed when only one tire can be claimed, or is suspect of a claim.
- Ride complaints after the first 1.6mm of tread wear.
- Tire complaints because of mechanical irregularities in the vehicle such as misalignment, defective brakes, defective shock absorbers or struts, or improper rims etc.
- Tires damaged by fire, chemical corrosion, vandalism, wrecks, chains, theft, run while flat, underinflated, overinflated or abused during servicing.
- Tires affected by flat spotting caused by improper transport or storage or hard braking/driving (showing as irregular wear).
- Tires which become unserviceable because of road hazard injuries (e.g., nails, glass, metal objects) or other penetrations or snags, bruises or impact damage.
- Tires with weather / ozone cracking over (4) four years from date of manufacture or date of purchase. Proof of purchase is required. Without proof of purchase the warranty will be four years from the manufactured date (DOT).
- · Summer tires which develop surface cracks due to use in low ambient temperatures.

WARRANTY PERIOD

This warranty policy shall not apply to tires five (5) years or older from the date of manufacture or three (3) years or older from the original date of purchase. Adjustments will be made on a pro rata basis determined on tread wear and tire age.

OWNER'S OBLIGATION

15

In order to be eligible for the limited warranty service, the owner must:

• Present the warrantable tire to an authorized American Tourer dealer ideally from whom the original purchase was made.



LIMITED WARRANTY

- Present proof of purchase in the form of the original purchase receipt.
- Present all receipts to the authorized American Tourer dealer reflecting all required services as recommended by the vehicle manufacturer. The costs related to mounting, balancing and any other service charges including applicable taxes are not covered under this warranty.

DISCLAIMER

This warranty or any warranty stated or referred to herein is exclusive and in lieu of any other warranty regarding the quality of the tires, whether expressed or implied and remedies for breach thereof shall be limited to those specifically provided herein.

HOW TO MAKE A CLAIM UNDER THIS WARRANTY

The owner, when making a claim under the terms of this warranty, must present the tire along with proof of purchase to any authorized American Tourer dealer. If further assistance or information is needed, please write to us on info@omni-united.com

For a detailed list of Terms and Conditions please visit our website http://omni-united.com/brands/terms-conditions/#usa

NOTES

•	

17



Omni United USA 5350 Birch Pointe Drive, Interlochen, Michigan 49643 omni-united.com | info@omni-united.com Toll Free: (1) 855-906-6646