

Hi,

We're integrating my website forms with Salesforce.

I will not share the production Client ID or Client Secret.

Please follow these instructions — you'll set everything up with placeholders and test using your own Salesforce Developer Edition org.

Once you're done, I'll insert the real credentials and run final live tests.

1 Get Your Free Salesforce Developer Edition (for testing)

This lets you build and test safely without accessing my real Salesforce.

1. Go to <https://developer.salesforce.com/signup>
2. Fill in your details (any company name is fine).
3. Salesforce will email you login details for your own free **Developer Edition org**.
4. Log in and go to **Setup → App Manager → New Connected App**
 - a. Create your own test app to get a **Client ID** and **Client Secret** for local testing.
5. Use that org for all development and testing.
6. When we're ready to go live, I'll insert my real credentials into production.

2 Environment / Configuration

Set these configuration variables (do not hardcode credentials):

```
SALESFORCE_TOKEN_URL=https://calvintranre.my.salesforce.com/services/oauth2/token  
SALESFORCE_CLIENT_ID=<CLIENT_ID_PLACEHOLDER>  
SALESFORCE_CLIENT_SECRET=<CLIENT_SECRET_PLACEHOLDER>  
SALESFORCE_API_VERSION=v61.0
```

I will provide and enter the actual Client ID and Secret myself in the production environment.

3 Authentication (OAuth 2.0 Client Credentials Flow)

Token Request

POST \${SALESFORCE_TOKEN_URL}
Content-Type: application/x-www-form-urlencoded

grant_type=client_credentials&
client_id=\${SALESFORCE_CLIENT_ID}&
client_secret=\${SALESFORCE_CLIENT_SECRET}

Response Example

```
{  
  "access_token": "00Dxx0000000abc!AQYAH...",  
  "instance_url": "https://calvintranre.my.salesforce.com",  
  "token_type": "Bearer"  
}
```

Use the access_token and instance_url for subsequent calls.

4 Lead Form → Salesforce Lead

Endpoint

POST {instance_url}/services/data/{SALESFORCE_API_VERSION}/subjects/Lead

Payload

```
{  
  "FirstName": "{firstName}",  
  "LastName": "{lastName}",  
  "Email": "{email}",  
}
```

```
"Phone": "{phone}",
"Company": "Website",
"LeadSource": "Web - Website Contact Form",
"Description": "{message}",
"Opportunity_Type__c": "{interestType}",    // Buyer, Seller, Renter, Landlord
"Has_Opted_In_Newsletter__c": {trueOrFalse}
}
```

5 Newsletter Form → Salesforce Contact (Upsert)

Endpoint

PATCH

{instance_url}/services/data/{SALESFORCE_API_VERSION}/subjects/Contact/Subscriber_Key__c/{lowercaseEmail}

Payload

```
{
  "FirstName": "{firstName}",
  "Email": "{email}",
  "Newsletter_Subscriber__c": true,
  "LeadSource": "Newsletter",
  "Subscriber_Key__c": "{lowercaseEmail}"
}
```

6 Add Contact to Campaign (Required)

Campaign Name: Real Estate Newsletter Subscribers

Campaign ID: 701Pg00001TaC81IAF

Step 1 – Get Contact Id

GET

```
{instance_url}/services/data/{SALESFORCE_API_VERSION}/query?q=SELECT+Id+FROM+Contact+WHERE+Subscriber_Key__c='{lowercaseEmail}'+LIMIT+1
```

Step 2 – Add to Campaign

POST

```
{instance_url}/services/data/{SALESFORCE_API_VERSION}/objects/CampaignMember
```

Payload

```
{
  "CampaignId": "701Pg00001TaC81IAF",
  "ContactId": "{003XXXXXXXXXXXXX}"
}
```

💡 Every newsletter subscriber must be added as a Campaign Member under the campaign above.

7 Error Handling

- Log both token and API responses (success/failure).
- Handle Salesforce validation and duplicate errors gracefully.
- Respect rate limits and use retries for 5xx errors.

8 Postman Test Collection (for verification)

To verify everything end-to-end, please create a Postman collection with the following requests:

S t	Request	Me	Endpoint
		th od	

e
p

1	Get Access Token	PO	https://calvintranre.my.salesforce.com/services/oauth2/token
2	Create Lead	ST	{{instance_url}}/services/data/v61.0/subjects/Lead
3	Upsert Contact	PA TC H	{{instance_url}}/services/data/v61.0/subjects/Contact/Subscriber_Key__c/{{email}}
4	Add Contact to Campaign	PO ST	{{instance_url}}/services/data/v61.0/subjects/CampaignMember

Headers

Authorization: Bearer {{access_token}}

Content-Type: application/json

Environment Variables

CLIENT_ID

CLIENT_SECRET

TOKEN_URL

INSTANCE_URL

ACCESS_TOKEN

API_VERSION

When done:

1. Share the Postman collection (.json export file) with me.
2. I'll import it into Postman, insert my real credentials, and test all four requests directly against my Salesforce org.
3. This confirms the integration works before connecting it to the live site.

9 Delivery Checklist

Please deliver:

- Code with credential placeholders (no hardcoded secrets).
- A working Postman collection for token + Lead + Contact + Campaign.
- A short README explaining:
 - Where to paste environment variables.
 - How to test each request.

I will then:

1. Paste my real Client ID and Secret into the production environment.
2. Run Postman to confirm everything connects.
3. Finalize the integration and test the live website forms.

1 Security Note

- Never request or store my production credentials.
- You can test freely in your own Developer Edition org.
- After the project, I'll rotate the secret to invalidate any old keys.

Thank you!

This process keeps my Salesforce data secure while allowing you to fully build and test the integration.