

MSL-5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024
Issue date: 7/20/2023 Supersedes: 7/20/2023 Version: 1.1

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : 5133-5 RESCUE HTF HD
Product code : JX5133-5

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Heavy-Duty Heat Transfer Cleaner Concentrate
Restrictions on use : Industrial use

1.4. Supplier's details

Supplier / Manufacturer

ISEL
5266 Highway Avenue
Jacksonville, FL 32254
USA
T 1.800.503.9533
www.iselinc.com

Distributor

DuBois Chemicals Canada, Inc.
1 First Canadian Place
100 King Street West, Suite 1600
Toronto, Ontario, M5X 1G5
Canada
T 1-866-861-3603

1.5. Emergency phone number

Emergency number : 1.904.378.3232

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 4	H227	Combustible liquid.
Acute toxicity (inhalation:dust,mist), Category 4	H332	Harmful if inhaled.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

Precautionary statements (GHS US)

- H319 - Causes serious eye irritation
- H332 - Harmful if inhaled
- H361 - Suspected of damaging fertility or the unborn child
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 - Avoid breathing mist, spray, vapors.
- P264 - Wash hands thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P280 - Wear protective gloves.
- P301+P310 - If swallowed: Immediately call a poison center or doctor.
- P302+P352 - If on skin: Wash with plenty of water.
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P312 - Call a poison center or doctor if you feel unwell.
- P331 - Do NOT induce vomiting.
- P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
- P337+P313 - If eye irritation persists: Get medical advice or attention.
- P362+P364 - Take off contaminated clothing and wash it before reuse.
- P370+P378 - In case of fire: Use appropriate media to extinguish.
- P403 - Store in a well-ventilated place.
- P405 - Store locked up.
- P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	wt% (% w/w)	GHS US classification
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	45 - 70*	Flam. Liq. 3, H226 Asp. Tox. 1, H304
2-Butoxyethanol	CAS-No.: 111-76-2	10 - 30*	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

Name	Product identifier	wt% (% w/w)	GHS US classification
Terpenes (hydrocarbon)	CAS-No.: 68956-56-9	3 - 7*	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Asp. Tox. 1, H304
Tricresyl Phosphate	CAS-No.: 1330-78-5	3 - 7*	Repr. 2, H361

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Harmful if inhaled.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung edema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing mist, spray, vapors. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing mist, spray, vapors. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up.
Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated light (64742-47-8)

USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	5 mg/m³ Mineral oil (Mist formation; ACGIH, 8 Hours)
-----------------	--

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

2-Butoxyethanol (111-76-2)

USA - ACGIH - Occupational Exposure Limits

Local name	2-Butoxyethanol (EGBE)
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024

USA - ACGIH - Biological Exposure Indices

Local name	2-Butoxyethanol
BEI (BLV)	200 mg/g Kreatinin Parameter: Butoxyacetic acid (BAA) (with hydrolysis) - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	2-Butoxyethanol
OSHA PEL TWA	240 mg/m ³ 50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous liquid.
Color	: colorless to slightly yellow
Odor	: citrus-like
Odor threshold	: No data available
pH	: Not applicable
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 87 °C (190 °F)
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.88
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 5 mm ² /s @ 40 °C (104 °F)
Explosion limits	: No data available
Particle characteristics	: No data available

Distillates (petroleum), hydrotreated light

Particle characteristics	No data available
--------------------------	-------------------

2-Butoxyethanol

Particle characteristics	No data available
--------------------------	-------------------

Terpenes (hydrocarbon)

Particle characteristics	No data available
--------------------------	-------------------

Tricresyl Phosphate

Particle characteristics	No data available
--------------------------	-------------------

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

5133-5 RESCUE HTF HD

ATE US (dust, mist)	4.921 mg/l/4h
---------------------	---------------

Distillates (petroleum), hydrotreated light (64742-47-8)

LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5.28 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID

2-Butoxyethanol (111-76-2)

LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 oral	470 mg/kg
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal	220 mg/kg
LC50 Inhalation - Rat (Vapors)	2.03 mg/l/4h
ATE US (oral)	1746 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	2.03 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Terpenes (hydrocarbon) (68956-56-9)

LD50 oral rat	> 2000 mg/kg Source: KOSHAMSDS
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	2000 mg/kg Source: KOSHAMSDS
ATE US (dermal)	2000 mg/kg body weight

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

Tricresyl Phosphate (1330-78-5)	
LD50 oral rat	3000 mg/kg
LD50 oral	3000 mg/kg
LD50 dermal	3700 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5.2 mg/l/4h
ATE US (oral)	3000 mg/kg body weight
ATE US (dust, mist)	5.2 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
pH: Not applicable

Serious eye damage/irritation : Causes serious eye irritation.
pH: Not applicable

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

2-Butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral,rat,90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Terpenes (hydrocarbon) (68956-56-9)	
NOAEL (oral,rat,90 days)	435.8 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Tricresyl Phosphate (1330-78-5)	
LOAEL (oral,rat,90 days)	50 mg/kg body weight Animal: rat

Aspiration hazard : May be fatal if swallowed and enters airways.

5133-5 RESCUE HTF HD	
Viscosity, kinematic	5 mm²/s @ 40 °C (104 °F)

Distillates (petroleum), hydrotreated light (64742-47-8)	
Hydrocarbon	Yes

Symptoms/effects after inhalation : Harmful if inhaled.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung edema.

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects

2-Butoxyethanol (111-76-2)	
LC50 - Fish [1]	≈ 1.474 g/l ECHA
EC50 - Crustacea [1]	≈ 1550 mg/l ECHA
EC50 72h - Algae [1]	911 mg/l Source: ECHA
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

Terpenes (hydrocarbon) (68956-56-9)

LC50 - Fish [1]	5.07 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	2.1 mg/l Test organisms (species): Daphnia magna

Tricresyl Phosphate (1330-78-5)

LC50 - Fish [1]	0.84 mg/l
EC50 - Crustacea [1]	0.25 mg/l
LC50 - Fish [2]	44.8 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	1.3 mg/l Source: ECOTOX
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	0.088 mg/l

12.2. Persistence and degradability

5133-5 RESCUE HTF HD

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Distillates (petroleum), hydrotreated light (64742-47-8)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

2-Butoxyethanol (111-76-2)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

Terpenes (hydrocarbon) (68956-56-9)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Tricresyl Phosphate (1330-78-5)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light (64742-47-8)

Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
---	------------------------

2-Butoxyethanol (111-76-2)

Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)
---	---

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

Terpenes (hydrocarbon) (68956-56-9)

Partition coefficient n-octanol/water (Log Pow)	≈ 4.46 @20°C
---	--------------

Tricresyl Phosphate (1330-78-5)

Partition coefficient n-octanol/water (Log Pow)	5.11 (Experimental value)
---	---------------------------

12.4. Mobility in soil

2-Butoxyethanol (111-76-2)

Surface tension	65.03 mN/m (20 °C, 2 g/l)
-----------------	---------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.5 – 0.9 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

Ecology - soil	Highly mobile in soil.
----------------	------------------------

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
NA1993	Not regulated	Not regulated
14.2. Proper Shipping Name		
Combustible liquid, n.o.s. (Distillates (petroleum), hydrotreated light ; Terpenes (hydrocarbon))	Not regulated	Not regulated
14.3. Transport hazard class(es)		
Combustible liquid	Not regulated	Not regulated

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

DOT	IMDG	IATA
14.4. Packing group		
III	Not regulated	Not regulated
14.5. Environmental hazards		
Dangerous for the environment: No	Not regulated	Not regulated
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

Special transport precautions : 49 CFR 173.150(f): A combustible liquid shipped in a non-bulk packaging (≤ 119 gallons) is excluded from regulation as a hazardous material, unless it is also a hazardous substance, hazardous waste, or marine pollutant.

DOT

UN-No. (DOT) : NA1993
DOT Special Provisions (49 CFR 172.102) : 148 - Except for transportation by aircraft, when transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

Not regulated

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Terpenes (hydrocarbon) (68956-56-9)

Listed on the Canadian DSL (Domestic Substances List)

Tricresyl Phosphate (1330-78-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2-Butoxyethanol (111-76-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Terpenes (hydrocarbon) (68956-56-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on Thailand Existing Chemicals Inventory (DIW)

2-Butoxyethanol (111-76-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on Thailand Existing Chemicals Inventory (DIW)

5133-5 RESCUE HTF HD

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

Terpenes (hydrocarbon) (68956-56-9)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on Thailand Existing Chemicals Inventory (DIW)

Tricresyl Phosphate (1330-78-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations



WARNING:

This product can expose you to chemicals including Formaldehyde (gas), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

Issue date : 7/20/2023

Full text of hazard classes and H-statements

H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H361	Suspected of damaging fertility or the unborn child

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.