



DOWNSVILLE, LA 71234- P: 318.614.7948- MIDSOUTHLUBE.COM

MSL-2185

Synthetic Food Grade Chain Lubricant with Tackifier

MSL-2185 is a high-temperature chain lubricant that meets H1 requirements for lubricants with incidental food contact (FDA 21 CFR 178.3570). It is designed to resist water washout, making it the ideal choice for applications where water exposure is likely.

Ideal for once through applications up to 500°F.

ATTRIBUTES

- Designed to resist water washout
- Meets H1 requirements for incidental food contact (FDA 21 CFR 178.3570)
- Long oil life
- Resists thermal and oxidative breakdown
- Controls carbon and varnish formation
- Excellent lubricity
- High film strength
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

MSL-2185 Grades	22	46	68	100
Viscosity cSt @ 40°C	20	47	69	102
Viscosity cSt @ 100°C	4.1	7.0	9.1	12.6
Viscosity Index	104	106	107	117
Flash Point °F (°C)	350 (177)	444 (229)	510 (266)	512 (267)
Pour Point °F (°C)	-50 (-46)	-38 (-39)	-31 (-35)	-20 (-29)
FZG Stage (1-12) (DIN 51354)	12+	12+	12+	12+
Timken OK Load, Kg	40	40	40	40
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 55°C, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0