



DOWNSVILLE, LA- PHONE: 318.614.7948-MIDSOUTHLUBE.COM

MSL-2245

Semi-Synthetic Food Grade AW Hydraulic

MSL-2245 is an inhibited formulation that has been developed with an advanced anti-wear package to meet the demands of today's modern hydraulic equipment. The addition of these state of the art additives will provide enhanced protection against wear, increased fluid life and improved energy efficiency. MSL-2245 has also been formulated to meet the requirements of major hydraulic pump manufacturers.

MSL-2245 is compliant with 21 CFR 178.3570 for lubricants with incidental food contact.

ATTRIBUTES

- Oxidative and thermal stability
- High Viscosity Index
- Carbon and varnish control
- High flash & auto-ignition points
- Zinc free
- Shear stable
- Compliant with 21 CFR 178.3570

TYPICAL LUBRICANT PROPERTIES

MSL-2245 Grades	32	46	68	100
Viscosity cSt @ 40°C	32.8	45.4	70.7	100.2
Viscosity cSt @ 100°C	5.7	6.8	9.6	11.8
Viscosity Index	113	102	116	107
Flash Point °F (°C)	435 (224)	442 (228)	456 (236)	503 (262)
Pour Point °F (°C)	-43 (-46)	-38 (-36)	-36 (-33)	-31 (-24)
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 54.4°C, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0
RPVOT, 25.4 PSI Drop, minutes				
Four-Ball Wear Test, Scar Diameter, mm	0.50	0.50	0.50	0.50