



DOWNSVILLE, LA 71234- P:318.614.7948- MIDSOUTHLUBE.COM

MSL-2284

Synthetic Biodegradable AW Hydraulic Fluid

MSL-2284 utilizes advanced synthetic base fluids and additives to provide biodegradability without sacrificing performance. This advanced-technology formulation has a long fluid life, even in severe operating conditions. It also offers excellent resistance against wear, corrosion and carbon deposits.

ATTRIBUTES

- Protects against wear, rust and corrosion
- Readily separates from water
- Oxidative stability
- Controls carbon and varnish to help reduce deposits
- Low volatility
- Zinc Free

TYPICAL LUBRICANT PROPERTIES

MSL-2284 Grades	32	46	68	100
Viscosity cSt @ 40°C	32	45.6	65.4	102
Viscosity cSt @ 100°C	6.2	8.0	10.5	14.4
Flash Point °F (°C)	425(218)	455(235)	480(248)	500 (260)
Pour Point °F (°C)	-49(-45)	-43(-42)	-38(-39)	-33 (-36)
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 54.4°C, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0
Rust Test	Pass	Pass	Pass	Pass
RPVOT, 25.4 PSI Drop, minutes	1,584	1,584	1,584	1,584
Four-Ball Wear Test, Scar Diameter, mm	0.45	0.45	0.45	0.45