



DOWNSVILLE, LA 71234- P:318.614.7948-MIDSOUTHLUBE.COM

MSL-C12

Food-Grade Low-Temperature Heat Transfer Fluid

MSL-C12 is formulated to meet HT-1 requirements for incidental food contact without comprising performance or fluid life. It utilizes clear base fluids that are free from impurities and aromatic compounds. MSL-C12 is ideal for low-temperature operations and rated for applications up to 450°F (232°C).

ATTRIBUTES

- NSF HT-1 registered Meets requirements for incidental food contact
- Low varnishing tendencies Allows for clean operation and greater thermal transfer efficiency
- Ideal for food-processing applications
- Minimal odor

TYPICAL LUBRICANT PROPERTIES

MSL-C12 Grades	MSL-C12
Minimum Temperature, °F (°C)	-37 (-38)
Maximum Bulk Temperature, °F (°C)	442 (227)
Pour Point, °F (°C)	-45 (-42)
Flash Point, °F (°C)	295 (146)
Fire Point, °F (°C)	320 (160)
Autoignition Point, °F (°C)	617 (325)
Thermal Expansion Coefficient, %/°C	0.0853
Thermal Conductivity @ 38°C, W/m-K	0.137
Heat Capacity @ 38°C, kJ/kg-K	2.122
Distillation Range (ASTM D2887), 10% °C	258
Distillation Range, 90%	502