

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024  
Issue date: 8/25/2025 Revision date: 9/16/2025 Supersedes: 8/25/2025 Version: 1.2

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT  
Product code : JX2082-220

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Lubricant  
Restrictions on use : Industrial use

#### 1.4. Supplier's details

##### Supplier / Manufacturer

ISEL  
5266 Highway Avenue  
Jacksonville, FL 32254  
USA  
T 1.800.503.9533  
[www.iselinc.com](http://www.iselinc.com)

##### Distributor

DuBois Chemicals Canada, Inc.  
1 First Canadian Place  
100 King Street West, Suite 1600  
Toronto, Ontario, M5X 1G5  
Canada  
T 1-866-861-3603

#### 1.5. Emergency phone number

Emergency number : 1.904.378.3232

### SECTION 2 Hazard Identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Reproductive toxicity, Category 2 H361 Suspected of damaging fertility or the unborn child.  
Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H361 - Suspected of damaging fertility or the unborn child  
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                                  | Product identifier  | wt%<br>(% w/w) | GHS US classification |
|-----------------------------------------------------------------------|---------------------|----------------|-----------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic                | CAS-No.: 64742-54-7 | 80 - 100*      | Not classified        |
| benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene | CAS-No.: 68411-46-1 | 0.5 - 1.5*     | Repr. 2, H361         |

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

|                                       |                                                                  |
|---------------------------------------|------------------------------------------------------------------|
| First-aid measures general            | : IF exposed or concerned: Get medical advice/attention.         |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water.                                |
| First-aid measures after eye contact  | : Rinse eyes with water as a precaution.                         |
| First-aid measures after ingestion    | : Call a poison center/doctor/physician if you feel unwell.      |

### 4.2. Most important symptoms/effects, acute and delayed

|                                     |                                 |
|-------------------------------------|---------------------------------|
| Symptoms/effects after inhalation   | : None under normal conditions. |
| Symptoms/effects after skin contact | : None under normal conditions. |
| Symptoms/effects after eye contact  | : None under normal conditions. |
| Symptoms/effects after ingestion    | : None under normal conditions. |

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

|                                   |                          |
|-----------------------------------|--------------------------|
| Other medical advice or treatment | : Treat symptomatically. |
|-----------------------------------|--------------------------|

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| Suitable extinguishing media   | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.               |

### 5.2. Specific hazards arising from the chemical

|             |                   |
|-------------|-------------------|
| Fire hazard | : No fire hazard. |
|-------------|-------------------|

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

|                                                  |                                |
|--------------------------------------------------|--------------------------------|
| Explosion hazard                                 | : No direct explosion hazard.  |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

### 5.3. Special protective equipment and precautions for fire-fighters

|                                |                                                                                                                                                       |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Firefighting instructions      | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.              |

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |                                                                                                                                         |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| General measures | : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage. |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------|

#### For non-emergency personnel

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Ventilate spillage area.                        |

#### For emergency responders

|                      |                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so.                                                                                               |

|                           |                                     |
|---------------------------|-------------------------------------|
| Environmental precautions | : Avoid release to the environment. |
|---------------------------|-------------------------------------|

### 6.2. Methods and materials for containment and cleaning up

|                         |                                                                                                                                                                                       |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For containment         | : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. |
| Methods for cleaning up | : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.                                                                         |
| Other information       | : Dispose of materials or solid residues at an authorized site.                                                                                                                       |

For further information refer to section 13

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

|                                   |                                                                                                                                                                                                      |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautions for safe handling     | : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. |
| Hygiene measures                  | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.                                                                                                  |
| Additional hazards when processed | : Not expected to present a significant hazard under anticipated conditions of normal use.                                                                                                           |

### 7.2. Conditions for safe storage, including incompatibilities

|                     |                                                                             |
|---------------------|-----------------------------------------------------------------------------|
| Technical measures  | : Keep in a cool, well-ventilated place away from heat.                     |
| Storage conditions  | : Store locked up.                                                          |
| Packaging materials | : Store always product in container of same material as original container. |

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

##### USA - ACGIH - Occupational Exposure Limits

|                 |                                                      |
|-----------------|------------------------------------------------------|
| ACGIH® TLV® TWA | 5 mg/m³ Mineral oil (Mist formation; ACGIH, 8 Hours) |
|-----------------|------------------------------------------------------|

#### 8.2. Appropriate engineering controls

|                                  |                                                |
|----------------------------------|------------------------------------------------|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Environmental exposure controls  | : Avoid release to the environment.            |

#### 8.3. Individual protection measures, such as personal protective equipment

##### Personal protective equipment:

Wear recommended personal protective equipment.

##### Hand protection:

Protective gloves

##### Eye protection:

Safety glasses

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

##### Personal protective equipment symbol(s):



### SECTION 9 Physical and chemical properties

#### 9.1. Basic physical and chemical properties

|                                                 |                       |
|-------------------------------------------------|-----------------------|
| Physical state                                  | : Liquid              |
| Appearance                                      | : Viscous liquid.     |
| Color                                           | : Colorless           |
| Odor                                            | : Mild odor           |
| Odor threshold                                  | : No data available   |
| pH                                              | : Not applicable      |
| Melting point                                   | : Not applicable      |
| Freezing point                                  | : No data available   |
| Boiling point                                   | : No data available   |
| Flash point                                     | : > 100 °C (212 °F)   |
| Flammability (solid, gas)                       | : Not applicable.     |
| Vapor pressure                                  | : No data available   |
| Relative vapor density at 20°C                  | : No data available   |
| Relative density                                | : 0.86                |
| Solubility                                      | : insoluble in water. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available   |

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

|                           |                              |
|---------------------------|------------------------------|
| Auto-ignition temperature | : No data available          |
| Decomposition temperature | : No data available          |
| Viscosity, kinematic      | : 220 mm²/s @ 40 °C (104 °F) |
| Explosion limits          | : No data available          |
| Particle characteristics  | : No data available          |

### Distillates (petroleum), hydrotreated heavy paraffinic

|                          |                   |
|--------------------------|-------------------|
| Particle characteristics | No data available |
|--------------------------|-------------------|

### benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

|                          |                   |
|--------------------------|-------------------|
| Particle characteristics | No data available |
|--------------------------|-------------------|

## 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

|                    |                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------|
| LD50 oral rat      | > 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rabbit | > 5000 mg/kg Source: IUCLID                                                               |

### benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

|               |                   |
|---------------|-------------------|
| LD50 oral rat | ≈ 5000 mg/kg ECHA |
|---------------|-------------------|

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

| benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1) |                                                                                                            |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| LD50 dermal rat                                                                    | > 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Skin) |

|                                   |                                                        |
|-----------------------------------|--------------------------------------------------------|
| Skin corrosion/irritation         | : Not classified<br>pH: Not applicable                 |
| Serious eye damage/irritation     | : Not classified<br>pH: Not applicable                 |
| Respiratory or skin sensitization | : Not classified                                       |
| Germ cell mutagenicity            | : Not classified                                       |
| Carcinogenicity                   | : Not classified                                       |
| Reproductive toxicity             | : Suspected of damaging fertility or the unborn child. |

| benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1) |                                                                                                                                         |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (animal/male, F1)                                                            | 54 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study) |

|                        |                  |
|------------------------|------------------|
| STOT-single exposure   | : Not classified |
| STOT-repeated exposure | : Not classified |

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) |                                                                                                                                          |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| LOAEL (oral,rat,90 days)                                            | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEC (inhalation,rat,dust/mist/fume,90 days)                       | > 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)                                  |

|                   |                  |
|-------------------|------------------|
| Aspiration hazard | : Not classified |
|-------------------|------------------|

| 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT |                            |
|----------------------------------------------|----------------------------|
| Viscosity, kinematic                         | 220 mm²/s @ 40 °C (104 °F) |

|                                     |                                 |
|-------------------------------------|---------------------------------|
| Symptoms/effects after inhalation   | : None under normal conditions. |
| Symptoms/effects after skin contact | : None under normal conditions. |
| Symptoms/effects after eye contact  | : None under normal conditions. |
| Symptoms/effects after ingestion    | : None under normal conditions. |

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

|                                                           |                                                                                                                        |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Ecology - general                                         | : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute)  | : Not classified                                                                                                       |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified                                                                                                       |

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) |                            |
|---------------------------------------------------------------------|----------------------------|
| LC50 - Fish [1]                                                     | > 5000 mg/l                |
| EC50 - Crustacea [1]                                                | > 1000 mg/l Source: IUCLID |
| EC50 96h - Algae [1]                                                | > 1000 mg/l Source: IUCLID |

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

| benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1) |                                                                                                                                            |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| LC50 - Fish [1]                                                                    | > 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Nominal concentration) |
| EC50 - Crustacea [1]                                                               | 733 mg/l Source: e-Chemportal                                                                                                              |
| EC50 72h - Algae [1]                                                               | > 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)                                      |
| ErC50 algae                                                                        | 600 mg/l Source: e-Chemportal                                                                                                              |

### 12.2. Persistence and degradability

| 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT                                       |                                     |
|------------------------------------------------------------------------------------|-------------------------------------|
| Persistence and degradability                                                      | Rapidly degradable                  |
| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)                |                                     |
| Persistence and degradability                                                      | Not rapidly degradable              |
| benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1) |                                     |
| Persistence and degradability                                                      | Not readily biodegradable in water. |

### 12.3. Bioaccumulative potential

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)                |                                                                                       |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Partition coefficient n-octanol/water (Log Pow)                                    | 3.9 – 6 Source: IUCLID                                                                |
| benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1) |                                                                                       |
| BCF - Fish [1]                                                                     | 1730 (42 day(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across, GLP) |
| Partition coefficient n-octanol/water (Log Pow)                                    | ≈ 6.7 @23°C ECHA                                                                      |
| Bioaccumulative potential                                                          | Potential for bioaccumulation (500 ≤ BCF ≤ 5000).                                     |

### 12.4. Mobility in soil

| benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1) |                                                  |
|------------------------------------------------------------------------------------|--------------------------------------------------|
| Mobility in soil                                                                   | 60460 Source: EPISUITE                           |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc)                         | 3.754 – 8.947 (log Koc, SRC PCKOCWIN v2.0, QSAR) |
| Ecology - soil                                                                     | Adsorbs into the soil.                           |

### 12.5. Other adverse effects

|                              |                  |
|------------------------------|------------------|
| Ozone                        | : Not classified |
| Fluorinated greenhouse gases | : No             |

## SECTION 13 Disposal considerations

|                                            |                                                                                               |
|--------------------------------------------|-----------------------------------------------------------------------------------------------|
| Regional waste regulation                  | : Disposal must be done according to official regulations.                                    |
| Waste treatment methods                    | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Sewage disposal recommendations            | : Disposal must be done according to official regulations.                                    |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations.                                    |
| Additional information                     | : Do not re-use empty containers.                                                             |

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

### SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

| DOT                                     | IMDG          | IATA          |
|-----------------------------------------|---------------|---------------|
| <b>14.1. UN number</b>                  |               |               |
| Not regulated for transport             |               |               |
| <b>14.2. Proper Shipping Name</b>       |               |               |
| Not regulated                           | Not regulated | Not regulated |
| <b>14.3. Transport hazard class(es)</b> |               |               |
| Not regulated                           | Not regulated | Not regulated |
| <b>14.4. Packing group</b>              |               |               |
| Not regulated                           | Not regulated | Not regulated |
| <b>14.5. Environmental hazards</b>      |               |               |
| Not regulated                           | Not regulated | Not regulated |
| No supplementary information available  |               |               |

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

**DOT**  
Not regulated

**IMDG**  
Not regulated

**IATA**  
Not regulated

### SECTION 15 Regulatory information

#### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### 15.2. International regulations

CANADA

**Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)**  
Listed on the Canadian DSL (Domestic Substances List)

**benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)**  
Listed on the Canadian DSL (Domestic Substances List)

# 2082-220 SYNTHETIC FOOD-GRADE GEAR LUBRICANT

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

### EU-Regulations

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### National regulations

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)  
Listed on Thailand Existing Chemicals Inventory (DIW)

#### benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on Thailand Existing Chemicals Inventory (DIW)  
Listed on the NCI (Vietnam - National Chemical Inventory)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### 15.3. State regulations



#### WARNING:

This product can expose you to chemicals including Formaldehyde (gas), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS) HazCom 2024

Revision date : 9/16/2025

Issue date : 8/25/2025

#### Full text of hazard classes and H-statements

|      |                                                     |
|------|-----------------------------------------------------|
| H361 | Suspected of damaging fertility or the unborn child |
|------|-----------------------------------------------------|

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.