



DOWNSVILLE, LA- P:318.614.7948- MIDSOUTHLUBE.COM

MSL-2015

Synthetic 8000 Hour Compressor Fluid

MSL-2015 utilizes the latest high-performance, full-synthetic base stocks and additives. This formulation offers an exceptional level of protection against wear, rust and corrosion, as well as outstanding resistance against oxidation and thermal breakdown.

MSL-2015 is designed to provide 8,000+ hours of service.

ATTRIBUTES

- 8,000-hour oil life at 100°C discharge temperature
- Excellent thermal stability
- Resists water contamination
- Saves energy
- High flash point
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

MSL-2015 Grades	32	46	68	100
Viscosity cSt @ 40°C	30.4	45	64	105
Viscosity cSt @ 100°C	5.3	6.5	8.57	12.33
Flash Point °F (°C)	430 (221)	445 (229)	451 (233)	503 (262)
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0