



DOWNSVILLE, LA- PHONE: 318.614.7948- MIDSOUTHLUBE.COM

MSL-2032

Synthetic EP Gear Fluid

MSL-2032, formulated with enhanced extreme-pressure (EP/AS) additives, designed for heavy-load and high-temperature applications such as heavily loaded gears, shock loading and frequent reversing action. This lubricant provides excellent protection and a long oil life — even in the most demanding applications and environments.

Applications: Enclosed Gear Systems, Differentials, Tow Motors, Industrial Gear Boxes

MSL-2032 meets or exceeds API GL5, API GL4, MTI and AIST 224 (formerly US Steel 224).

ATTRIBUTES

- Excellent lubricity
- Thermally and oxidatively stable
- Rust and oxidation inhibited
- Excellent wear protection (AS/EP)
- High film strength and sheer stability
- Excellent demulsibility
- Controls carbon and varnish to help reduce deposits
- Resists foaming

TYPICAL LUBRICANT PROPERTIES

MSL-2032 Grades	Test Method	150	220	320	460
Viscosity cSt @ 40°C	ASTM D7042	153	221	322	465
Viscosity cSt @ 100°C	ASTM D7042	15.7	22.5	29.8	38.7
Viscosity Index	ASTM D2270	105	124	127	128
Flash Point °F (°C)	ASTM D92	510(266)	515 (268)	517 (269)	527 (275)
Pour Point °F (°C)	ASTM D5949	-38(-38)	-35 (-37)	-20 (-29)	-15 (-26)
Rust Test	ASTM D665	Pass	Pass	Pass	Pass
Copper Corrosion, 24 Hr	ASTM D130	1a	1a	1a	1a
Demulsibility, 54.4°C, 30 Min	ASTM D1401	40/39/1	40/39/1	40/39/1	40/39/1
Four Ball Wear Diameter, mm	ASTM D4172	0.42	0.42	0.42	0.42
Weld Load kg	ASTM D2783	315	315	315	315
FZG	ASTM D5182	12+	12+	12+	12+