



DOWNSVILLE, LA- P: 318.614.7948- MIDSOUTHLUBE.COM

MSL-2243

Mineral Oil AW Hydraulic Fluid

MSL-2243 is an anti-wear hydraulic fluid designed for use in various hydraulic applications and provides good wear protection, oxidation and corrosion control, as well as foam suppression and demulsibility. MSL-2243 is non toxic to aquatic life and meets or exceeds the EPA LC 50 test.

ATTRIBUTES

- Anti-wear formulation
- High flash point
- Readily separates from water
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

MSL-2243 Grades	32	46	68	100
Viscosity cSt @ 40°C	32.8	47.2	62	104
Viscosity cSt @ 100	5.5	6.9	8.3	11.8
Viscosity Index	103	101	102	102
Flash Point °F (°C)	425 (218)	445 (229)	457 (236)	500 (260)
Pour Point °F (°C)	-16 (-27)	-13 (-25)	-8 (-22)	-5 (-21)
Copper Corrosion, 24 Hr	1b	1b	1b	1b
Demulsibility, 54.4°C, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Rust Test	Pass	Pass	Pass	Pass
RPVOT, 25.4 PSI Drop, minutes	219	219	219	219
Four-Ball Wear Test, Scar Diameter, mm	0.51	0.51	0.51	0.51