



DOWNSVILLE,LA- P: 318.614.7948- MIDSOUTHLUBE.COM

MSL-2244

Semi-Synthetic AW Hydraulic Fluid

MSL-2244 are anti-wear hydraulic fluids for use in normal to moderate hydraulic applications. MSL-2244 's enhanced additive package aids in protecting the system from wear, rust and corrosion.

ATTRIBUTES

- Long fluid life
- Enhanced additive package
- Resists water contamination
- Non-toxic/Non-hazardous

TYPICAL LUBRICANT PROPERTIES

MSL-2244 Grades	32	46	68	100
Viscosity Index	122	116	123	117
Viscosity cSt @ 40°C	32.5	42.6	64.6	99.0
Viscosity cSt @ 100°C	5.8	6.8	9.3	12.3
Flash Point °F(°C)	428 (220)	440 (227)	462 (239)	500 (260)
Pour Point °F(°C)	-20(-28)	-16(-26)	-12(-24)	0 (-18)
Rust Test	Pass	Pass	Pass	Pass
Copper Corrosion, 24 Hr.	1a	1a	1a	1a
Demulsibility, 54.4°C, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0
RPVOT, 25.4 Drop Time, Min	1,236	1,236	1,236	1,236
Four-Ball Wear Test, Scar Diameter, mm	0.47	0.47	0.47	0.47