



DOWNSVILLE, LA- PHONE: 318.614.7948- MIDSOUTHLUBE.COM

MSL-2384

Synthetic Multi-Viscosity AW Hydraulic Fluid

MSL2384 is designed to provide exceptional protection even in the most demanding applications. MSL-2384 provides excellent protection against wear, rust and copper corrosion. MSL-2384 is Non-toxic, non-hazardous.

ATTRIBUTES

- Maintains fluidity in cold temperatures
- Protects against wear, rust and corrosion
- Excellent demulsibility
- High viscosity index
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

MSL-2384 Grades	15	22	32	46
Viscosity cSt @ 40°C	15	22.4	31.1	47.6
Viscosity cSt @ 100	3.9	5.5	6.7	12.9
Viscosity Index	164	200	181	281
Flash Point °F (°C)	260 (126)	264 (129)	330 (165)	333 (167)
Pour Point °F (°C)	-75 (-59)	-65 (-53)	-60 (-51)	-57 (-49)
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 54.4°C, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Rust Test	Pass	Pass	Pass	Pass
RPVOT, 25.4 PSI Drop, minutes	1,857	1,857	1,857	1,857
Four-Ball Wear Test, Scar Diameter, mm	0.42	0.42	0.42	0.42