



DOWNSVILLE, LA- P: 318.614.7948- MIDSOUTHLUBE.COM

MSL-2585

FM Approved Fire Resistant EAL Hydraulic Fluid

MSL-2585 is an ester based, food grade, fire resistant hydraulic fluid designed for use in moderate to severe duty applications. MSL-2585 has enhanced oxidative stability to ensure long fluid life in the most extreme conditions. MSL-2585 complies with 21 CFR 178.3570 for lubricants with incidental food contact.

MSL-2585 is readily biodegradable according to the requirements of OECD 301B.

ATTRIBUTES

- Food Grade Formulation - Complies with 21 CFR 178.3570
- Long fluid life
- Excellent rust and corrosion protection
- Non-toxic/Non-hazardous
- >70% biodegradable (OECD 301B)

TYPICAL LUBRICANT PROPERTIES

MSL-2585 Grades	Test Method	68
Viscosity Index	ASTM D2270	200
Viscosity cSt @ 40°C	ASTM D7042	68
Viscosity cSt @ 100°C	ASTM D7042	13.3
Flash Point °F(°C)	ASTM D92	630 (332)
Pour Point °F(°C)	ASTM D5949	-35 (-37)
Four Ball Wear Diameter, mm	ASTM D4172	0.52