



DOWNSVILLE, LA 71234- P:318-614-7948- MIDSOUTHLUBE.COM

MSL-C5

High-Flash Food-Grade Heat Transfer Fluid

MSL-C5 is a high-flash food-grade heat transfer fluid designed for applications where exceptional performance is necessary in very high operating temperatures in both open and closed systems. MSL-C5 utilizes pure base fluids and a proprietary blend of advanced additives. This unique formulation increases fluid performance and lifespan by preventing fluid degradation, while offering the safety of a food-grade formulation. MSL-C5 has excellent oxidative resistance, making it ideal for systems with and without inert gas blanketing.

ATTRIBUTES

- Meets requirements for fluids with incidental food contact and Ideal for food-processing applications
- High flash point for added safety
- Resistant against fluid degradation
- Low varnishing tendencies
- Low volatility

TYPICAL LUBRICANT PROPERTIES

MSL-C5 Grades	MSL-C5
Minimum Temperature, °F (°C)	59 (15)
Maximum Bulk Temperature, °F (°C)	644 (340)
Flash Point °F (°C)	530 (276)
Pour Point°C(°F)	16 (-9)
Thermal Conductivity @ 38°C, W/m-K	0.149
Heat Capacity @ 38°C, kJ/kg-K	1.870
Distillation Range (ASTM D2887), 10% °C	445
Distillation Range, 90%	553