

The Observer Pattern



Gerald Britton

Pluralsight Author

@GeraldBritton www.linkedin.com/in/geraldbritton





Overview



Classification: Behavioral

One-to-many relationship between a set of objects

When the state of one changes its dependents are notified

Also known as

- Dependents pattern
- Publish-subscribe pattern



Demo



Dashboard for a tech support center

KPIs:


- Open tickets
- New tickets in last hour
- Closed tickets in last hour

Dashboard is the observer


KPI source is the subject or publisher



Observer Pattern



Observer Pattern UML









Separation of concerns

Single responsibility principle

Interface segregation principle

Open/Closed principle

Dependency inversion principle

Encapsulate what varies



Demo



Implement the classic pattern

Use ABCs for subject and observer

Build concrete classes using the ABCs

Rebuild the main program

Use two observers



What's Been Achieved?


**Implemented the observer
pattern**

**Separated the concerns of
subject and observer**

Easy to add new observers

One subtle bug





Python runs managed code

Uses reference counters for objects

Set of observers holds references

Need to detach each observer

Why?

If not detached, reference count > 0

Stops garbage collection

Dangling reference



Demo



Use a Python context manager

Change the main program to use “with”

Observers will detach themselves

Subjects will clean up observers

No more dangling references!



Summary



Define a one-to-many relationship

Notify the many when the one changes

Many applications, especially GUIs

MVC pattern:

- Model = Subject, View = Observer

One more thing:

- Extra logic in AbsSubject notify method
- Enables push notifications

