```
     41 4.911899              10.0.0.7                  128.119.245.12          TCP        78      63040→80
  [SYN] Seq=3807952962 Win=65535 Len=0 MSS=1460 WS=32 TSval=566756727 TSecr=0 SACK_PERM=1
  Frame 41: 78 bytes on wire (624 bits), 78 bytes captured (624 bits) on interface 0
  Ethernet II, Src: Apple_5f:04:7f (28:cf:e9:5f:04:7f), Dst: Netgear_88:93:60 (00:24:b2:88:93:60)
  Internet Protocol Version 4, Src: 10.0.0.7, Dst: 128.119.245.12
  Transmission Control Protocol, Src Port: 63040, Dst Port: 80, Seq: 3807952962, Len: 0
      Source Port: 63040
      Destination Port: 80
      [Stream index: 6]
      [TCP Segment Len: 0]
      Sequence number: 3807952962
      Acknowledgment number: 0
      Header Length: 44 bytes
      Flags: 0x002 (SYN)
          000. .... .... = Reserved: Not set
          ...0 .... .... = Nonce: Not set
          .... 0... .... = Congestion Window Reduced (CWR): Not set
          .... .0.. .... = ECN-Echo: Not set
          .... ..0. .... = Urgent: Not set
          .... ...0 .... = Acknowledgment: Not set
          .... .... 0... = Push: Not set
          .... .... .0.. = Reset: Not set
          .... .... ..1. = Syn: Set
          .... .... ...0 = Fin: Not set
          [TCP Flags: ·········S·]
      Window size value: 65535
      [Calculated window size: 65535]
      Checksum: 0xf666 [unverified]
      [Checksum Status: Unverified]
      Urgent pointer: 0
      Options: (24 bytes), Maximum segment size, No-Operation (NOP), Window scale, No-Operation
  (NOP), No-Operation (NOP), Timestamps, SACK permitted, End of Option List (EOL)
```