

Java Reference & Data Structures

Japjot Singh

October 21, 2018

1 A Brief Java Reference

1.1 Object-Oriented Mechanisms

1.1.1 Private/Final Class Structure

A class can't be marked as **private**, but a non-**public** class can be subclassed only by classes in the same package as the class, that is, classes within a different package will not be able to subclass. A **final** class means that it is the end of the inheritance. Furthermore, if a class has only **private** constructors, it cannot be subclassed. If a class is **private** then it cannot be subclassed, it marks the end of an inheritance. If a method is **private** then it cannot be overridden.

1.1.2 Overriding and Overloading

When you override a method from a superclass you must retain identical arguments (order matters), compatible return types, and the method itself cannot be less accessible. Method overloading, is nothing more than having two methods with identical names but different argument lists, Overloading allows for differing return types but requires a change to the argument list, and accommodates varying access in any direction.

1.1.3 The Stack and the Heap

There are two important areas of memory: The Stack and The Heap. The Stack is where all method invocations and local variables will reside, similar to how frames work, and that leaves The Heap to hold all objects and the instance variables within objects. An important note is that Object reference variables are still primitive variables and as such if they are declared as local variables, they belong on the stack. All objects, regardless of their reference being a local or instance variable, belong on The Heap.

Instance variables have a **default** value: 0/0.0/false/null

1.1.4 Constructors

It is a good idea to overload constructors in order to have a default no-arg constructor which will initialize the class object with default values. The compiler will only provide a no-arg constructor only if the user doesn't make any constructor at all. In order for a class to contain more than one constructor, the class **must** have **different** argument lists. Constructors can be **public**, **private**, or just default. Having private constructors will prevent anyone outside from the class from calling the constructor.

Constructor chaining is the phenomenon that occurs as a result of object creation. When an object is created on The Heap, all the constructor's in the object's inheritance lineage must also run first before the new object is made. If the user does not provide a call to **super()** inside the constructor of a subclass, the compiler will put a no-arg call to **super()** in each of the user's overloaded constructors and if the superclass has overloaded constructors, the one with no-arg will be called.

Making an analogy between inheritance and parenthood helps clarify the fact that the superclass parts of an object have to be fully-formed before the subclass parts can be constructed. The superclass constructor must finish before the subclass constructor. Thus the compiler will fail if **super()** is not the first statement in each constructor.

```

1 public abstract class Professional {
2     private String name;
3
4     public String getName() {
5         return name;
6     }
7
8     public Professional (String myName) {
9         name = myName;
10    }
11 }
12 public class Doctor extends Professional {
13
14     public Doctor (String name) {
15         super(name);
16     }
17 }
18 public class trainDoctor {
19     public static void main (String[] args) {
20         Doctor d = new Doctor("Phil");
21         System.out.println("d.getName()");
22     }
23 }

```

Listing 1.1: Will print out the name of the Doctor, Phil

Super class contains private instance variable and a public getter method for said instance variable and within constructor it sets that instance variable. Subclass is able to use `super(name)` to modify that private method within the superclass and then utilize the get method on its own object as the getter is inherited by the subclass.

Use `this()` to call a constructor from another overloaded constructor within in the same class. The call to `this()` can be used only within the the constructor and must be the first statement in the constructor, implying no constructor can contain both a call to `this()` and `super()`.

An object's eligibility for garbage collection:

- Object reference goes out of scope, permanently
- Object reference is assigned to another object
- Object reference is explicitly set to null

1.1.5 Autoboxing

Java will take care of wrapping primitives to their respectable object types and visa-versa, effectively letting the user specify either primitive or object while permitting both. This can be used in method arguments, return values, boolean expressions, operations on numbers, and assignments. Wrappers are particularly useful because of their static utility methods, allowing for easy conversion between a String and a primitive `Integer.parseInt(s)`, `Boolean("true").booleanValue()`.

1.2 Interfaces and Abstract Classes

Concrete classes are those which are specific enough to be instantiated, others whose sole purpose is to serve as a polymorphic argument or return type should be declared **abstract**.


1.2.1 Abstract Class and Abstract Methods

The compiler will not allow a user to instantiate an abstract class. An abstract class is virtually useless (unless it has **static** members), unless it is extended.

Methods can also be called abstract. The way an abstract class is written to be *extended*, an abstract method is written to be *overridden*. If the user declares an abstract method, the user **MUST** also mark the class as abstract. There cannot be an abstract method in a non-abstract class. The user **must** implement all abstract methods. Implementing an abstract method is similar to overriding a method. All the abstract methods of a lineage of abstract classes must be implemented by the *first* concrete class down the inheritance tree.

1.2.2 Object Reference and Compile Time

If a user makes an ArrayList of Object, when the user accesses the List they will in get type-Object in return.

The compiler decides whether the user can call a method based on the reference type, not the actual object type, once it finds the proper method signature and compiles the compiler will proceed to runtime where Java will look for the most specific dynamic type with the same signature as the reference signature and run that. 

In order to bypass the object reference issue the user can down cast the object to its specific type and then proceed to treat the object as if it was the specific type all along. If there is uncertainty behind the specific type, the **instanceof** operator allows for a quick check before casting `Dog d = (Dog) o`

At compile time the compiler check that the method being called on an object is defined in the reference type of the object. Java checks the class of the **reference** variable, not the class of the **object** (specific/dynamic type).

1.2.3 Interfaces

A Java Interface provides the polymorphic benefits of inheritance without the issues and complexities that comes with multiple inheritance. A Java interface is just a purely abstract class, where a subclass which **implements** the interface must implement all the abstract methods.

Important Remarks

- Extend only one abstract class, implement multiple interfaces
- Use an abstract class when describing an IS-A relationship, and you won't be instantiating the class, an abstract class can have both abstract and non-abstract methods
- Use an interface when the user wishes to define a role that the other classes can play, regardless of where they lie in an inheritance tree, must have all abstract methods
- (Insert interface use-case)
- To invoke the superclass version of a method from a subclass that's overriding the method, just use the **super** keyword

Algorithms

2 Introduction

Complexity is a means of measure how long it takes for some operation to complete, measure using O , Ω , Θ , signifying worst-case, best-case and the intersection of both, respectively.