

---

# **connectal Documentation**

***Release 14.12.6***

**Jamey Hicks, Myron King, John Ankcorn**

December 17, 2014



## CONTENTS

<b>1</b>	<b>Connectal BSV Libraries</b>	<b>3</b>
1.1	Address Generator . . . . .	3
1.2	Arith Package . . . . .	3
1.3	CtrlMux Package . . . . .	4
1.4	HostInterface Package . . . . .	4
1.5	Leds Package . . . . .	5
1.6	MemPortal Package . . . . .	5
1.7	MemreadEngine Package . . . . .	5
1.8	MemTypes Package . . . . .	5
1.9	MMU Package . . . . .	9
1.10	Pipe Package . . . . .	10
1.11	Portal Package . . . . .	14
<b>2</b>	<b>Connectal Examples</b>	<b>17</b>
2.1	Simple Example . . . . .	17
<b>3</b>	<b>Indices and tables</b>	<b>19</b>
	<b>Bsv Package Index</b>	<b>21</b>
	<b>Index</b>	<b>23</b>



Contents:



## CONNECTAL BSV LIBRARIES

## 1.1 Address Generator

One of the common patterns that leads to long critical paths in designs on the FPGA are counters and comparisons against counters. This package contains a module for generating the sequence of addresses used by a memory read or write burst, along with a field indicating the last beat of the burst.

```
struct AddressGenerator :: AddrBeat#(numeric type addrWidth)
```

```
  addr → Bit#(addrWidth)
```

The address for this beat of the request.

```
  bc → Bit#(BurstLenSize)
```

```
  tag → Bit#(MemTagSize)
```

```
  last → Bool
```

```
interface AddressGenerator :: AddressGenerator (numeric type addrWidth, numeric type dataWidth)
```

```
  request → Put#(PhysMemRequest#(addrWidth))
```

The interface for requesting a sequence of addresses.

```
  addrBeat → Get#(AddrBeat#(addrWidth))
```

The interface for getting the address beats of the burst. There is one pipeline cycle from the request to the first address beat.

```
module AddressGenerator :: mkAddressGenerator → (AddressGenerator#(addrWidth, dataWidth))
```

Instantiates an address generator.

## 1.2 Arith Package

The Arith package implements some functions that correspond to infix operators.

```
function Arith :: booland (Bool x1, Bool x2) → Bool
```

Returns logical “and” of inputs. Named to avoid conflict with the Verilog keyword “and”.

```
function Arith :: boolor (Bool x1, Bool x2) → Bool
```

Returns logical “or” of inputs. Named to avoid conflict with the Verilog keyword “or”.

```
function Arith :: eq (a x1, a x2) → Bool
```

```
function Arith :: add (a x1, a x2) → a
```

Returns sum of inputs. Requires Arith#(a).

**function** Arith: **mul** (*a x1, a x2*) → *a*  
Returns product of inputs. Requires Arith#(a).

**function** Arith: **rshift** (*Bit#(b) x1, Integer i*) → *Bit#(b)*  
Returns input right shifted by *i* bits.

**function** Arith: **a) vadd** (*Vector#(n, a) x1, Vector#(n, a) x2*) → *Vector#(n,*  
Returns sum of input vectors.

**function** Arith: **a) vmul** (*Vector#(n, a) x1, Vector#(n, a) x2*) → *Vector#(n,*  
Returns element-wise product of input vectors.

**function** Arith: **Bit# (b)) vrshift**(*Vector#(n, Bit#(b)) x1, Integer i*) → *Vector#(n,*  
Right shifts the elements of the input vector by *i* bits.

## 1.3 CtrlMux Package

**module** CtrlMux: **mkInterruptMux** (*Vector#(numPortals, MemPortal#(aw, dataWidth)) portals*) →  
(*ReadOnly#(Bool)*)  
Used by BsimTop, PcieTop, and ZynqTop. Takes a vector of MemPortals and returns a boolean indicating whether any of the portals has indication method data available.

**module** CtrlMux: **mkSlaveMux** (*Vector#(numPortals, MemPortal#(aw, dataWidth)) portals*) → (*Phys-*  
*MemSlave#(addrWidth,dataWidth)*)  
Takes a vector of MemPortals and returns a PhysMemSlave combining them.

## 1.4 HostInterface Package

The HostInterface package provides host-specific typedefs and interfaces.

### 1.4.1 Host-Specific Constants

**typedef** HostInterface: **DataBusWidth**  
Width in bits of the data bus connected to host shared memory.

**typedef** HostInterface: **PhysAddrWidth**  
Width in bits of physical addresses on the data bus connected to host shared memory.

**typedef** HostInterface: **NumberOfMasters**  
Number of memory interfaces used for connecting to host shared memory.

### 1.4.2 Host-Specific Interfaces

**interface** HostInterface: **BsimHost**  
Host interface for the bluesim platform

**interface** HostInterface: **PcieHost**  
Host interface for PCIe-attached FPGAs such as vc707 and kc705

**interface** HostInterface: **ZynqHost**  
Host interface for Zynq FPGAs such as zedboard, zc702, zc706, and zybo.  
The Zc706 is a ZynqHost even when it is plugged into a PCIe slot.



## 1.5 Leds Package

**interface** Leds : **Leds**

**typedef** Leds : **LedsWidth**

Defined to be the number of default LEDs on the FPGA board.

The Zedboard has 8, Zc706 has 4, ...

Leds : **leds** → Bit#(LedsWidth)

## 1.6 MemPortal Package

### 1.6.1 mkMemPortal Module

**module** MemPortal : **mkMemPortal** (*Bit#(slaveDataWidth) ifcId, PipePortal#(numRequests, numIndications, slaveDataWidth) portal*) → (MemPortal#(slaveAddrWidth, slaveDataWidth))

Takes an interface identifier and a PipePortal and returns a MemPortal.

## 1.7 MemreadEngine Package

**module** MemreadEngine : **mkMemreadEngine** (**MemreadEngineV** (*dataWidth, cmdQDepth, numServers*))

Creates a MemreadEngine with default 256 bytes of buffer per server.

**module** MemreadEngine : **mkMemreadEngineBuff** (*Integer bufferSizeBytes*) → (MemreadEngineV#(dataWidth, cmdQDepth, numServers))

Creates a MemreadEngine with the specified buffer size.

## 1.8 MemTypes Package

### 1.8.1 Constants

**typedef** MemTypes : **Bit#(32) SGLId**

**typedef** MemTypes : **44 MemOffsetSize**

**typedef** MemTypes : **6 MemTagSize**

**typedef** MemTypes : **8 BurstLenSize**

**typedef** MemTypes : **32 MemServerTags**

### 1.8.2 Data Types

**struct** MemTypes : **PhysMemRequest#(numeric type addrWidth)**

A memory request containing a physical memory address

**addr** → Bit#(addrWidth)

Physical address to read or write

**burstLen** → Bit#(BurstLenSize)

Length of read or write burst, in bytes. The number of beats of the request will be the burst length divided by the physical width of the memory interface.

**tag** → Bit#(MemTagSize)

**struct** MemTypes :: **MemRequest**

A logical memory read or write request. The linear offset of the request will be translated by an MMU according to the specified scatter-gather list.

**sglId** → SGLId

Indicates which scatter-gather list the MMU should use when translating the address

**offset** → Bit#(MemOffsetSize)

Linear byte offset to read or write.

**burstLen** → Bit#(BurstLenSize)

Length of read or write burst, in bytes. The number of beats of the request will be the burst length divided by the physical width of the memory interface.

**tag** → Bit#(MemTagSize)

**struct** MemTypes :: **MemData#(numeric type dsz)**

One beat of the payload of a physical or logical memory read or write request.

**data** → Bit#(dsz)

One data beat worth of data.

**tag** → Bit#(MemTagSize)

Indicates to which request this beat belongs.

**last** → Bool

Indicates that this is the last beat of a burst.

### 1.8.3 Physical Memory Clients and Servers

**interface** MemTypes :: **PhysMemSlave** (*numeric type addrWidth, numeric type dataWidth*)

**read\_server** → PhysMemReadServer#(addrWidth, dataWidth)

**write\_server** → PhysMemWriteServer#(addrWidth, dataWidth)

**interface** MemTypes :: **PhysMemMaster** (*numeric type addrWidth, numeric type dataWidth*)

**read\_client** → PhysMemReadClient#(addrWidth, dataWidth)

**write\_client** → PhysMemWriteClient#(addrWidth, dataWidth)

**interface** MemTypes :: **PhysMemReadClient** (*numeric type asz, numeric type dsz*)

**readReq** → Get#(PhysMemRequest#(asz))

**readData** → Put#(MemData#(dsz))

**interface** MemTypes :: **PhysMemWriteClient** (*numeric type asz, numeric type dsz*)

**writeReq** → Get#(PhysMemRequest#(asz))

**writeData** → Get#(MemData#(dsz))

```
writeDone → Put#(Bit#(MemTagSize))
```

```
interface MemTypes : :PhysMemReadServer (numeric type asz, numeric type dsz)
```

```
readReq → Put#(PhysMemRequest#(asz))
```

```
readData → Get#(MemData#(dsz))
```

```
interface MemTypes : :PhysMemWriteServer (numeric type asz, numeric type dsz)
```

```
writeReq → Put#(PhysMemRequest#(asz))
```

```
writeData → Put#(MemData#(dsz))
```

```
writeDone → Get#(Bit#(MemTagSize))
```

## 1.8.4 Memory Clients and Servers

```
interface MemTypes : :MemReadClient (numeric type dsz)
```

```
readReq → Get#(MemRequest)
```

```
readData → Put#(MemData#(dsz))
```

```
interface MemTypes : :MemWriteClient (numeric type dsz)
```

```
writeReq → Get#(MemRequest)
```

```
writeData → Get#(MemData#(dsz))
```

```
writeDone → Put#(Bit#(MemTagSize))
```

```
interface MemTypes : :MemReadServer (numeric type dsz)
```

```
readReq → Put#(MemRequest)
```

```
readData → Get#(MemData#(dsz))
```

```
interface MemTypes : :MemWriteServer (numeric type dsz)
```

```
writeReq → Put#(MemRequest)
```

```
writeData → Put#(MemData#(dsz))
```

```
writeDone → Get#(Bit#(MemTagSize))
```

## 1.8.5 Memory Engine Types

```
struct MemTypes : :MemengineCmd
```

A read or write request for a MemreadEngine or a MemwriteEngine. Memread and Memwrite engines will issue one or more burst requests to satisfy the overall length of the request.

```
sglId → SGLId
```

Which scatter gather list the MMU should use to translate the addresses

```
base → Bit#(MemOffsetSize)
```

Logical base address of the request, as a byte offset

**burstLen** → Bit#(BurstLenSize)  
Maximum burst length, in bytes.

**len** → Bit#(32)  
Number of bytes to transfer. Must be a multiple of the data bus width.

**tag** → Bit#(MemTagSize)  
Identifier for this request.

## 1.8.6 Memory Engine Interfaces

**interface** MemTypes :: **MemwriteServer** (*numeric type dataWidth*)

**cmdServer** → Server#(MemengineCmd, Bool)  
**dataPipe** → PipeIn#(Bit#(dataWidth))

**interface** MemTypes :: **MemwriteEngineV** (*numeric type dataWidth, numeric type cmdQDepth, numeric type numServers*)

**dmaClient** → MemWriteClient#(dataWidth)  
**writeServers** → Vector#(numServers, Server#(MemengineCmd, Bool))  
**dataPipes** → Vector#(numServers, PipeIn#(Bit#(dataWidth)))  
**write\_servers** → Vector#(numServers, MemwriteServer#(dataWidth))

**typedef** MemTypes :: **MemwriteEngineV#** (**dataWidth, cmdQDepth, 1**) **MemwriteEngine#** (*numeric type dataWidth*)

**interface** MemTypes :: **MemreadServer** (*numeric type dataWidth*)

**cmdServer** → Server#(MemengineCmd, Bool)  
**dataPipe** → PipeOut#(Bit#(dataWidth))

**interface** MemTypes :: **MemreadEngineV** (*numeric type dataWidth, numeric type cmdQDepth, numeric type numServers*)

**dmaClient** → MemReadClient#(dataWidth)  
**readServers** → Vector#(numServers, Server#(MemengineCmd, Bool))  
**dataPipes** → Vector#(numServers, PipeOut#(Bit#(dataWidth)))  
**read\_servers** → Vector#(numServers, MemreadServer#(dataWidth))

**typedef** MemTypes :: **MemreadEngineV#** (**dataWidth, cmdQDepth, 1**) **MemreadEngine#** (*numeric type dataWidth*)

## 1.8.7 Memory Traffic Interfaces

**interface** MemTypes :: **DmaDbg**

**getMemoryTraffic** → ActionValue#(Bit#(64))  
**dbg** → ActionValue#(DmaDbgRec)

### 1.8.8 Connectable Instances

```
instance MemTypes :: Connectable (MemReadClient#(dsz), MemReadServer#(dsz))
instance MemTypes :: Connectable (MemWriteClient#(dsz), MemWriteServer#(dsz))
instance MemTypes :: Connectable (PhysMemMaster#(addrWidth, busWidth), PhysMemSlave#(addrWidth, busWidth))
instance MemTypes :: Connectable (PhysMemMaster#(32, busWidth), PhysMemSlave#(40, busWidth))
```

## 1.9 MMU Package

```
typedef MMU :: 32 MaxNumSGLists
typedef MMU :: Bit# (TLog# (MaxNumSGLists)) SGListId
typedef MMU :: 12 SGListPageShift0
typedef MMU :: 16 SGListPageShift4
typedef MMU :: 20 SGListPageShift8
typedef MMU :: Bit# (TLog# (MaxNumSGLists)) RegionsIdx
typedef MMU :: 8 IndexWidth
```

### 1.9.1 Address Translation

```
struct MMU :: ReqTup
  Address translation request type

  id → SGListId
    Which SGList to use.

  off → Bit#(MemOffsetSize)
    The address to translate.

interface MMU :: MMU (numeric type addrWidth)
  An address translator

  request → MMURequest
    The interface of the MMU that is exposed to software as a portal.

  addr → Vector#(2, Server#(ReqTup, Bit#(addrWidth)))
    The address translation servers

module MMU :: mkMMU (Integer iid, Bool bsimMMap, MMUIndication mmuIndication) →
  (MMU#(addrWidth))
  Instantiates an address translator that stores a scatter-gather list to define the logical to physical address mapping.
  Parameter iid is the portal identifier of the MMURequest interface.
  Parameter bsimMMap ??
```

### 1.9.2 Multiple Address Translators

```
interface MMU :: MMUAddrServer (numeric type addrWidth, numeric type numServers)
  Used by mkMemServer to share an MMU among multiple memory interfaces.
```

**interface Vector** *((numServers, Server#(ReqTup, Bit#(addrWidth))) servers)*

The vector of address translators.

**module** MMU : **mkMMUAddrServer** *(Server#(ReqTup, Bit#(addrWidth)) server) → (MMUAddrServer#(addrWidth,numServers))*

Instantiates an MMUAddrServer that shares the input server among multiple clients.

## 1.10 Pipe Package

The Pipe package is modeled on Bluespec, Inc's PAClib package. It provides functions and modules for composing pipelines of operations.

### 1.10.1 Pipe Interfaces

**interface** Pipe : **PipeIn** *(type a)*

Corresponds to the input interface of a FIFO.

**enq** *(a v) → Action*

**notFull** → Bool

**interface** Pipe : **PipeOut** *(type a)*

Corresponds to the output interface of a FIFO.

**first** → a

**deq** → Action

**notEmpty** → Bool

**typeclass** Pipe : **ToPipeIn** *(type a, type b)*

**function** toPipeIn *(b in) → PipeIn#(a)*

Returns a PipeIn to the object "in" with no additional buffering.

**typeclass** Pipe : **ToPipeOut** *(type a, type b)*

**function** toPipeOut *(b in) → PipeOut#(a)*

Returns a PipeOut from the object "in" with no additional buffering.

**typeclass** Pipe : **MkPipeIn** *(type a, type b)*

**module** mkPipeIn *(b in) → (PipeIn#(a))*

Instantiates a module whose interface is a PipeIn to the input parameter "in". Includes a FIFO buffering stage.

**typeclass** Pipe : **MkPipeOut** *(type a, type b)*

**module** mkPipeOut *(b in) → (PipeOut#(a))*

Instantiates a module whose interface is PipeOut from the input parameter "in". Includes a FIFO buffering stage.

**instance** Pipe : **ToPipeIn** *(a, FIFO#(a))*

Converts a FIFO to a PipeIn.

**instance** `Pipe::ToPipeOut` (*a*, *function a pipefn()*)  
 Converts a function to a PipeOut.

**instance** `Pipe::ToPipeOut` (*a*, *Reg#(a)*)  
 Converts a register to a PipeOut.

**instance** `Pipe::ToPipeIn` (*Vector#(m, a)*, *Gearbox#(m, n, a)*)  
 Converts a Gearbox to a PipeOut.

**instance** `Pipe::ToPipeOut` (*a*, *FIFO#(a)*)  
 Converts a FIFO to a PipeOut.

**instance** `Pipe::ToPipeOut` (*Vector#(n, a)*, *MIMO#(k, n, sz, a)*)  
 Converts a MIMO to a PipeOut.

**instance** `Pipe::ToPipeOut` (*Vector#(n, a)*, *Gearbox#(m, n, a)*)  
 Converts a Gearbox to a PipeOut.

**instance** `Pipe::MkPipeOut` (*a*, *Get#(a)*)  
 Instantiates a pipelined PipeOut from a Get interface.

**instance** `Pipe::MkPipeIn` (*a*, *Put#(a)*)  
 Instantiates a pipelined PipeIn to a Put interface.

## 1.10.2 Get and Put Pipes

**instance** `Pipe::ToGet` (*PipeOut#(a)*, *a*)  
**instance** `Pipe::ToPut` (*PipeIn#(a)*, *a*)

## 1.10.3 Connectable Pipes

**instance** `Pipe::Connectable` (*PipeOut#(a)*, *Put#(a)*)  
**instance** `Pipe::Connectable` (*PipeOut#(a)*, *PipeIn#(a)*)

## 1.10.4 Mapping over Pipes

**function** `Pipe::toCountedPipeOut` (*Reg#(Bit#(n)) r*, *PipeOut#(a) pipe*) → *PipeOut#(a)*

**function** `Pipe::zipPipeOut` (*PipeOut#(a) ina*, *PipeOut#(b) inb*) → *PipeOut#(Tuple2#(a,b))*  
 Returns a PipeOut whose elements are 2-tuples of the elements of the input pipes.

**function** `Pipe::mapPipe` (*function b f(a av)*, *PipeOut#(a) apipe*) → *PipeOut#(b)*  
 Returns a PipeOut that maps the function *f* to each element of the input pipes with no buffering.

**module** `Pipe::mkMapPipe` (*function b f(a av)*, *PipeOut#(a) apipe*) → (*PipeOut#(b)*)  
 Instantiates a PipeOut that maps the function *f* to each element of the input pipes using a FIFO for buffering.

**function** `Pipe::mapPipeIn` (*function b f(a av)*, *PipeIn#(b) apipe*) → *PipeIn#(a)*  
 Returns a PipeIn applies the function *f* to each value that is enqueued.

## 1.10.5 Reducing Pipes

## 1.10.6 Functions on Pipes of Vectors

**function** `Pipe::unvectorPipeOut` (*PipeOut#(Vector#(l, a)) in*) → *PipeOut#(a)*

### 1.10.7 Funneling and Unfunneling

**module** `Pipe :: mkFunnel` (*PipeOut#(Vector#(mk, a)) in*)  $\rightarrow$  (*PipeOut#(Vector#(m, a))*)

Returns k Vectors of m elements for each Vector#(mk,a) element of the input pipe.

**module** `Pipe :: mkFunnel1` (*PipeOut#(Vector#(k, a)) in*)  $\rightarrow$  (*PipeOut#(a)*)

Sames as mkFunnel, but returns k singleton elements for each vector element of the input pipe.

**module** `Pipe :: mkFunnelGB1` (*Clock slowClock, Reset slowReset, Clock fastClock, Reset fastReset, PipeOut#(Vector#(k, a)) in*)  $\rightarrow$  (*PipeOut#(a)*)

Same as mkFunnel1, but uses a Gearbox with a 1 to k ratio.

**module** `Pipe :: mkUnfunnel` (*PipeOut#(Vector#(m, a)) in*)  $\rightarrow$  (*PipeOut#(Vector#(mk, a))*)

The dual of mkFunnel. Consumes k elements from the input pipe, each of which is an m-element vector, and returns an mk-element vector.

**module** `Pipe :: mkUnfunnelGB` (*Clock slowClock, Reset slowReset, Clock fastClock, Reset fastReset, PipeOut#(Vector#(l, a)) in*)  $\rightarrow$  (*PipeOut#(Vector#(k, a))*)

The same as mkUnfunnel, but uses a Gearbox with a 1-to-k.

**module** `Pipe :: mkRepeat` (*UInt#(n) repetitions, PipeOut#(a) inpipe*)  $\rightarrow$  (*PipeOut#(a)*)

Returns a PipeOut which repeats each element of the input pipe the specified number of times.

### 1.10.8 Fork and Join

Fork and Join with limited scalability

**module** `Pipe :: mkForkVector` (*PipeOut#(a) inpipe*)  $\rightarrow$  (*Vector#(n, PipeOut#(a))*)

Replicates each element of the input pipe to each of the output pipes. It uses a FIFO per output pipe.

**module** `Pipe :: mkSizedForkVector` (*Integer size, PipeOut#(a) inpipe*)  $\rightarrow$  (*Vector#(n, PipeOut#(a))*)

Used a SizedFIFO for each of the output pipes.

**module** `Pipe :: mkJoin` (*function c f(a av, b bv), PipeOut#(a) apipe, PipeOut#(b) bpipe*)  $\rightarrow$  (*PipeOut#(c)*)

Returns a PipeOut that applies the function f to the elements of the input pipes, with no buffering.

**module** `Pipe :: mkJoinBuffered` (*function c f(a av, b bv), PipeOut#(a) apipe, PipeOut#(b) bpipe*)  $\rightarrow$  (*PipeOut#(c)*)

Returns a PipeOut that applies the function f to the elements of the input pipes, using a FIFO to buffer the output.

**module** `Pipe :: mkJoinVector` (*function b f(Vector#(n, a) av), Vector#(n, PipeOut#(a)) apipes*)  $\rightarrow$  (*PipeOut#(b)*)

Same as mkJoin, but operates on a vector of PipeOut as input.

### 1.10.9 Funnel Pipes

Fork and Join with tree-based fanout and fanin for scalability.

These are used by MemreadEngine and MemwriteEngine.

**typedef** `Pipe :: Vector#(j, PipeOut#(a))`    **FunnelPipe#**(*numeric type j, numeric type k, type a, nu*)

**typedef** `Pipe :: Vector#(k, PipeOut#(a))`    **UnFunnelPipe#**(*numeric type j, numeric type k, type a, nu*)

**typeclass** `Pipe :: FunnelPipesPipelined` (*numeric type j, numeric type k, type a, numeric type bpc*)

**module** `mkFunnelPipesPipelined` (*Vector#(k, PipeOut#(a)) in*)  $\rightarrow$  (*FunnelPipe#(j,k,a,bpc)*)



```

module mkFunnelPipesPipelinedRR (Vector#(k, PipeOut#(a)) in, Integer c) → (Fun-
    nelPipe#(j,k,a,bpc)

module mkUnFunnelPipesPipelined (Vector#(j, PipeOut#(Tuple2#(Bit#(TLog#(k)), a))) in) →
    (UnFunnelPipe#(j,k,a,bpc)

module mkUnFunnelPipesPipelinedRR (Vector#(j, PipeOut#(a)) in, Integer c) → (UnFun-
    nelPipe#(j,k,a,bpc)

instance Pipe::FunnelPipesPipelined (l, l, a, bpc)
instance Pipe::FunnelPipesPipelined (l, k, a, bpc)
module Pipe::mkUnFunnelPipesPipelinedInternal (Vector#(l,
    Pipe-
    Out#(Tuple2#(Bit#(TLog#(k)), a))) in)
    → (UnFunnelPipe#(l,k,a,bpc)

module Pipe::mkFunnelPipes (Vector#(mk, PipeOut#(a)) ins) → (Vector#(m, PipeOut#(a))
module Pipe::mkFunnelPipes1 (Vector#(k, PipeOut#(a)) ins) → (PipeOut#(a))
module Pipe::mkUnfunnelPipes (Vector#(m, PipeOut#(a)) ins) → (Vector#(mk, PipeOut#(a))
module Pipe::mkPipelinedForkVector (PipeOut#(a) inpipe, Integer id) → (UnFun-
    nelPipe#(l,k,a,bpc)

```

### 1.10.10 Delimited Pipes

**interface** Pipe::FirstLastPipe (type a)

A pipe whose elements two-tuples of boolean values indicating first and last in a series. The ttype a indicates the type of the counter used.

**pipe** → PipeOut#(Tuple2#(Bool,Bool))  
The pipe of delimited elements

**start** (a count) → Action  
Starts the series of count elements

**module** Pipe::mkFirstLastPipe → (FirstLastPipe#(a))  
Creates a FirstLastPipe.

**struct** Pipe::RangeConfig#(type a)  
The base, limit and step for mkRangePipeOut.

**xbase** → a

**xlimit** → a

**xstep** → a

**interface** Pipe::RangePipeIfc (type a)

**pipe** → PipeOut#(a)

**isFirst** → Bool

**isLast** → Bool

**start** (RangeConfig#(a) cfg) → Action

**module** Pipe::mkRangePipeOut → (RangePipeIfc#(a))  
Creates a Pipe of values from xbase to xlimit by xstep. Used by Memread.

## 1.11 Portal Package

### 1.11.1 PipePortal Interface

**interface** Portal :: **PipePortal** (*numeric type numRequests, numeric type numIndications, numeric type slaveDataWidth*)

**messageSize** (*Bit#(16) methodNumber*) → Bit#(16)  
Returns the message size of the methodNumber method of the portal.

**requests** → Vector#(numRequests, PipeIn#(Bit#(slaveDataWidth)))

**indications** → Vector#(numIndications, PipeOut#(Bit#(slaveDataWidth)))

### 1.11.2 MemPortal Interface

**interface** Portal :: **MemPortal** (*numeric type slaveAddrWidth, numeric type slaveDataWidth*)

**slave** → PhysMemSlave#(slaveAddrWidth,slaveDataWidth)

**interrupt** → ReadOnly#(Bool)

**top** → WriteOnly#(Bool)

**function** Portal :: **getSlave** (*MemPortal#(\_a, \_d) p*) → PhysMemSlave(\_a,\_d)

**function** Portal :: **getInterrupt** (*MemPortal#(\_a, \_d) p*) → ReadOnly#(Bool)

**function** Portal :: **getInterruptVector** (*Vector#(numPortals, MemPortal#(\_a, \_d)) portals*) → Vector#(16,ReadOnly#(Bool))

### 1.11.3 ShareMemoryPortal Interface

**interface** Portal :: **SharedMemoryPortal** (*numeric type dataBusWidth*)  
Should be in SharedMemoryPortal.bsv

**readClient** → MemReadClient(dataBusWidth)

**writeClient** → MemWriteClient#(dataBusWidth)

**cfg** → SharedMemoryPortalConfig

**interrupt** → ReadOnly#(Bool)

### 1.11.4 ConnectalTop Interface

**interface** Portal :: **ConnectalTop** (*numeric type addrWidth, numeric type dataWidth, type pins, numeric type numMasters*)

Interface ConnectalTop is the interface exposed by the top module of a Connectal hardware design.

**slave** → PhysMemSlave#(32,32)

**masters** → Vector#(numMasters,PhysMemMaster#(addrWidth, dataWidth))

**interrupt** → Vector#(16,ReadOnly#(Bool))

**leds** → LEDS

**pins** → pins

### 1.11.5 StdConnectalTop Typedef

**typedef** Portal :: **StdConnectalTop** (numeric type addrWidth) → Connectal-  
Top##(addrWidth,64,Empty,0)

Type StdConnectalTop indicates a Connectal hardware design with no user defined pins and no user of host shared memory. The “pins” interface is Empty and the number of masters is 0.

**typedef** Portal :: **StdConnectalDmaTop** (numeric type addrWidth) → Connectal-  
Top##(addrWidth,64,Empty,1)

Type StdConnectalDmaTop indicates a Connectal hardware design with no user defined pins and a single client of host shared memory. The “pins” interface is Empty and the number of masters is 1.



## CONNECTAL EXAMPLES

### 2.1 Simple Example



## INDICES AND TABLES

- *genindex*
- *modindex*
- *search*





## a

AddressGenerator, 3  
Arith, 3

## c

CtrlMux, 4

## h

HostInterface, 4

## l

Leds, 5

## m

MemPortal, 5  
MemreadEngine, 5  
MemTypes, 5  
MMU, 9

## p

Pipe, 10  
Portal, 14



## Symbols

12 SGListPageShift0 (typedef in package MMU), 9  
 16 SGListPageShift4 (typedef in package MMU), 9  
 20 SGListPageShift8 (typedef in package MMU), 9  
 32 MaxNumSGLists (typedef in package MMU), 9  
 32 MemServerTags (typedef in package MemTypes), 5  
 44 MemOffsetSize (typedef in package MemTypes), 5  
 6 MemTagSize (typedef in package MemTypes), 5  
 8 BurstLenSize (typedef in package MemTypes), 5  
 8 IndexWidth (typedef in package MMU), 9

## A

a) vadd (function in package Arith), 4  
 a) vmul (function in package Arith), 4  
 add (function in package Arith), 3  
 AddrBeat#(numeric type addrWidth) (struct in package AddressGenerator), 3  
 AddressGenerator (interface in package AddressGenerator), 3  
 AddressGenerator (package), 3  
 Arith (package), 3

## B

Bit# (function in package Arith), 4  
 Bit#(32) SGLId (typedef in package MemTypes), 5  
 Bit#(TLog#(MaxNumSGLists)) RegionsIdx (typedef in package MMU), 9  
 Bit#(TLog#(MaxNumSGLists)) SGLId (typedef in package MMU), 9  
 booland (function in package Arith), 3  
 boolor (function in package Arith), 3  
 BsimHost (interface in package HostInterface), 4

## C

Connectable (instance in package MemTypes), 9  
 Connectable (instance in package Pipe), 11  
 ConnectalTop (interface in package Portal), 14  
 CtrlMux (package), 4

## D

DataBusWidth (typedef in package HostInterface), 4  
 dbg() (MemTypes::DmaDbg method), 8

deq() (Pipe::PipeOut method), 10  
 DmaDbg (interface in package MemTypes), 8

## E

enq() (Pipe::PipeIn method), 10  
 eq (function in package Arith), 3

## F

first() (Pipe::PipeOut method), 10  
 FirstLastPipe (interface in package Pipe), 13  
 FunnelPipesPipelined (instance in package Pipe), 13  
 FunnelPipesPipelined (typeclass in package Pipe), 12  
 FunnelPipesPipelined.mkFunnelPipesPipelined (module in package Pipe), 12  
 FunnelPipesPipelined.mkFunnelPipesPipelinedRR (module in package Pipe), 12  
 FunnelPipesPipelined.mkUnFunnelPipesPipelined (module in package Pipe), 13  
 FunnelPipesPipelined.mkUnFunnelPipesPipelinedRR (module in package Pipe), 13

## G

getInterrupt (function in package Portal), 14  
 getInterruptVector (function in package Portal), 14  
 getMemoryTraffic() (MemTypes::DmaDbg method), 8  
 getSlave (function in package Portal), 14

## H

HostInterface (package), 4

## I

isFirst() (Pipe::RangePipeIfc method), 13  
 isLast() (Pipe::RangePipeIfc method), 13

## L

LEDS (interface in package Leds), 5  
 Leds (package), 5  
 leds() (in package Leds), 5  
 LedsWidth (typedef in package Leds), 5

## M

mapPipe (function in package Pipe), 11

mapPipeIn (function in package Pipe), 11  
MemData#(numeric type dsz) (struct in package MemTypes), 6  
MemengineCmd (struct in package MemTypes), 7  
MemPortal (interface in package Portal), 14  
MemPortal (package), 5  
MemReadClient (interface in package MemTypes), 7  
MemreadEngine (package), 5  
MemreadEngineV (interface in package MemTypes), 8  
MemreadEngineV#(dataWidth,cmdQDepth,1) MemreadEngine#(numeric type dataWidth, numeric type cmdQDepth) (typedef in package MemTypes), 8  
MemReadServer (interface in package MemTypes), 7  
MemreadServer (interface in package MemTypes), 8  
MemRequest (struct in package MemTypes), 6  
MemTypes (package), 5  
MemWriteClient (interface in package MemTypes), 7  
MemwriteEngineV (interface in package MemTypes), 8  
MemwriteEngineV#(dataWidth,cmdQDepth,1) MemwriteEngine#(numeric type dataWidth, numeric type cmdQDepth) (typedef in package MemTypes), 8  
MemWriteServer (interface in package MemTypes), 7  
MemwriteServer (interface in package MemTypes), 8  
messageSize() (Portal::PipePortal method), 14  
mkAddressGenerator (module in package AddressGenerator), 3  
mkFirstLastPipe (module in package Pipe), 13  
mkForkVector (module in package Pipe), 12  
mkFunnel (module in package Pipe), 12  
mkFunnel1 (module in package Pipe), 12  
mkFunnelGB1 (module in package Pipe), 12  
mkFunnelPipes (module in package Pipe), 13  
mkFunnelPipes1 (module in package Pipe), 13  
mkInterruptMux (module in package CtrlMux), 4  
mkJoin (module in package Pipe), 12  
mkJoinBuffered (module in package Pipe), 12  
mkJoinVector (module in package Pipe), 12  
mkMapPipe (module in package Pipe), 11  
mkMemPortal (module in package MemPortal), 5  
mkMemreadEngine(MemreadEngineV (module in package MemreadEngine), 5  
mkMemreadEngineBuff (module in package MemreadEngine), 5  
mkMMU (module in package MMU), 9  
mkMMUAddrServer (module in package MMU), 10  
MkPipeIn (instance in package Pipe), 11  
MkPipeIn (typeclass in package Pipe), 10  
MkPipeIn.mkPipeIn (module in package Pipe), 10  
mkPipelinedForkVector (module in package Pipe), 13  
MkPipeOut (instance in package Pipe), 11  
MkPipeOut (typeclass in package Pipe), 10  
MkPipeOut.mkPipeOut (module in package Pipe), 10

mkRangePipeOut (module in package Pipe), 13  
mkRepeat (module in package Pipe), 12  
mkSizedForkVector (module in package Pipe), 12  
mkSlaveMux (module in package CtrlMux), 4  
mkUnfunnel (module in package Pipe), 12  
mkUnfunnelGB (module in package Pipe), 12  
mkUnfunnelPipes (module in package Pipe), 13  
mkUnFunnelPipesPipelinedInternal (module in package Pipe), 13  
MMU (interface in package MMU), 9  
MMU (package), 9  
MMUAddrServer (interface in package MMU), 9  
MMUAddrServer.Vector (interface in package MMU), 9  
mul (function in package Arith), 3

## N

notEmpty() (Pipe::PipeOut method), 10  
notFull() (Pipe::PipeIn method), 10  
NumberOfMasters (typedef in package HostInterface), 4

## P

PcieHost (interface in package HostInterface), 4  
PhysAddrWidth (typedef in package HostInterface), 4  
PhysMemMaster (interface in package MemTypes), 6  
PhysMemReadClient (interface in package MemTypes), 6  
PhysMemReadServer (interface in package MemTypes), 7  
PhysMemRequest#(numeric type addrWidth) (struct in package MemTypes), 5  
PhysMemSlave (interface in package MemTypes), 6  
PhysMemWriteClient (interface in package MemTypes), 6  
PhysMemWriteServer (interface in package MemTypes), 7  
Pipe (package), 10  
PipeIn (interface in package Pipe), 10  
PipeOut (interface in package Pipe), 10  
PipePortal (interface in package Portal), 14  
Portal (package), 14

## R

RangeConfig#(type a) (struct in package Pipe), 13  
RangePipeIfc (interface in package Pipe), 13  
ReqTup (struct in package MMU), 9  
rshift (function in package Arith), 4

## S

SharedMemoryPortal (interface in package Portal), 14  
start() (Pipe::FirstLastPipe method), 13  
start() (Pipe::RangePipeIfc method), 13  
StdConnectalDmaTop (typedef in package Portal), 15  
StdConnectalTop (typedef in package Portal), 15

## T

toCountedPipeOut (function in package Pipe), 11  
ToGet (instance in package Pipe), 11  
ToPipeIn (instance in package Pipe), 10, 11  
ToPipeIn (typeclass in package Pipe), 10  
ToPipeIn.toPipeIn (function in package Pipe), 10  
ToPipeOut (instance in package Pipe), 10, 11  
ToPipeOut (typeclass in package Pipe), 10  
ToPipeOut.toPipeOut (function in package Pipe), 10  
ToPut (instance in package Pipe), 11

## U

unvectorPipeOut (function in package Pipe), 11

## V

Vector#(j,PipeOut#(a)) FunnelPipe#(numeric type j, numeric type k, type a, numeric type bitsPerCycle) (typedef in package Pipe), 12  
Vector#(k,PipeOut#(a)) UnFunnelPipe#(numeric type j, numeric type k, type a, numeric type bitsPerCycle) (typedef in package Pipe), 12

## Z

zipPipeOut (function in package Pipe), 11  
ZynqHost (interface in package HostInterface), 4