

Unsupervised Learning

Christophe Ambroise

2021-2022

Section 1

Introduction

Types of machine learning

Machine learning is usually divided into two main types.

Predictive or supervised learning

- learn a mapping from inputs \mathbf{x} to outputs y ,
- given a training: set of input-output pairs $D = \{(\mathbf{x}_i, y - i)\}_{i=1}$.
- output (or response) variable may quantitative or qualitative

Reinforcement learning,

- less commonly used.
- useful for learning how to act or behave when given occasional reward or punishment signals.

Unsupervised learning

- Discover “interesting structure” in the data;
- Sometimes called knowledge discovery.

Data Analysis is a family of methods (sometimes statistical) allowing to explore data represented mostly in the form of

- array where each line describes an object (individual) and each column a variable:
- of similarity (or dissimilarity) pair between objects

(Exploratory) Data analysis

Certain methods, mainly geometric, make it possible to highlight the relations which can exist between the various data and to establish a summary (sometimes with statistic characteristic).

In French, the terminology “analyse de données” refers to a subset of what is more commonly called multivariate statistics.

The purpose of the data analysis is exploratory and aims to

- vizualise or
- summarize.

Both aspects are related. This course presents some of the most common methods.

Section 2

A few introductory examples

Image compression

- Data: $(X_i)_i$; the gray levels of an image
- Assumption there are $(Z)_i$; hidden label of the K gray levels classes




Figure 1: Famous Statistician R. Fisher

Clustering the nodes of a network I

Data

- V a set of given nodes $\in \{1, \dots, n\}$,
- E a set of edges $\in \{1, \dots, n\}^2$,
- $\mathbf{X} = (X_{ij})$ the adjacency matrix such that $\{X_{ij} = 1\} = \mathbb{I}\{i \leftrightarrow j\}$.
 - oriented : $X_{ij} \neq X_{ji}$,
 - valued : $X_{ij} \in \mathbb{R}$.

Assumption

hyp.: there exists a hidden structure into Q classes of connectivity,

- $\mathbf{Z} = (\mathbf{Z}_i)_i$, $Z_{iq} = \mathbb{I}\{i \in q\}$ are indep. hidden variables,
- $\boldsymbol{\alpha} = \{\alpha_q\}$, the *prior* proportions of groups,




Figure 2: Sample of 250 blogs (nodes) with their links (edges) of the French political Blogosphere




Figure 3: US political blog

Summarizing genetic information

In the Nature article "Gene Mirror Geography Within Europe", Novembre et al., 2008,

Data

- 3000 individuals
 - described by 500,000 SNP (Single Nucleotide Polymorphism)
- can be represented by a data table $\mathbf{X} = (X_{ij})$ with
- 3000 rows (if 1 meter high)
 - 50,000 columns colonnes (then 166 meters large !!!)

SNP

- 90 % of human genetic variation,
- SNP with allelic frequency greater than 1 % are present every 300 base pairs in average (in human genome)




Figure 4: SNP (wikipedia)

Data (continued)

Mother	Father	
	C	T
C	0	1
T	1	2

- How to summarize this table
- Each person is a vector in a 500,000 dimensional space

Solution: Principal component Analysis

Summarize 500,000 columns by 2 columns (linear combination of the original)





Figure 5: PCA of european population

Section 3

Outline and evaluation of the course

- ➊ Discrete latent factor
 - Hidden markov models (example in genetics)
 - Variational EM (example of Stochastic block model)
- ➋ Continuous Latent Variable
 - Independant Component Analysis



Reference document

The lecture closely follows and largely borrows material from “Machine Learning: A Probabilistic Perspective” (MLAPP) from Kevin P. Murphy, chapters:

- Chapter 17: Markov and hidden Markov models
- Chapter 21: Variational inference
- Chapter 12: Latent Linear Models
- Chapter 13: Sparse Linear Models

- ① R project (1/3)
- ② Final Exam (2/3)

Section 4

Markov and hidden Markov models

Models for sequences of observations, X_1, \dots, X_T , of arbitrary length T .

Such models have applications in - computational biology, - natural language processing, - time series forecasting, etc.

Focus

- Focus on the case where the observations occur at discrete “time steps”,
- “time” may also refer to locations within a sequence.

Markov chain assumes that X_t captures all the relevant information for predicting the future (i.e., we assume it is a sufficient statistic).

If we assume discrete time steps, the joint distribution is a **Markov chain** :

$$p(X_{1:T}) = p(X_1)p(X_2|X_1)p(X_3|X_2)\dots = p(X_1) \prod_{t=2}^T p(X_t|X_{t-1})$$

- X_t captures all relevant information for prediction the future
- X_t is a sufficient statistic

Homogeneous discrete Markov Chain

if $p(X_t|X_{t-1})$ is independent of time then the chain is called homogeneous, stationary or time invariant.

We assume in the following that the observed variables are discrete, so $X_t \in \{1, \dots, K\}$, this is called a finite-state Markov chain.

Transition matrix

When X_t is discrete $X_t \in \{1, \dots, K\}$, the conditional distribution $p(X_t|X_{t-1})$ can be written as a $K \times K$ matrix, known as the transition matrix A

where $A_{ij} = p(X_t = j|X_{t-1} = i)$ is the probability of going from state i to state j . $\forall j, \sum_i A_{ij} = 1$

Example 2 states Markov Chain

$$A = \begin{pmatrix} 1 - \alpha & \alpha \\ \beta & 1 - \beta \end{pmatrix}$$




Figure 6: 2 states Markov chain

Example of DNA mutation Markov Chain

$$A = \begin{bmatrix} & A & C & G & T \\ & \vdots & & & \\ P(X_t = G | X_{t-1} = C) & \dots & & & \end{bmatrix} \begin{matrix} A \\ C \\ G \\ T \end{matrix}$$




Figure 7: 4 states Markov chain

The n-step transition matrix $A(n)$

$$A_{ij} \triangleq p(X_{t+n} = j | X_t = i)$$

which is the probability of getting from i to j in exactly n steps.

$$A(1) = A$$

Chapman-Kolmogorov equations

$$A_{ij}(m+n) = \sum_k A_{ik}(m) A_{kj}(n)$$

We can write the above as a matrix multiplication

$$A(m+n) = A(m)A(n)$$

$$\text{And thus } A(n) = A^n$$

Language modeling

One important application of Markov models is to make statistical language models, which are probability distributions over sequences of words.

We define the state space to be all the words of some language.

n-gram models

- The marginal probabilities $p(X_t = k)$ are called unigram statistics.
- using first-order Markov model $p(X_t = k | X_{t-1} = j)$ is called a bigram model.
- using second-order Markov model $p(X_t = k | X_{t-1} = j, X_{t-2} = i)$ is called a trigram model.
- ...

Exercise

- Estimate unigram and bigram models for the letters $\{a, \dots, z, -\}$ from a set of Leonard Cohen songs

can be used for several things, such as the following:

- **Sentence completion** A language model can predict the next word given the previous words in a sentence. This can be used to reduce the amount of typing required, which is particularly important for disabled users or uses of mobile devices.
- **Data compression** Any density model can be used to define an encoding scheme, by assigning short codewords to more probable strings.
- **Text classification** Any density model can be used as a class-conditional density and hence turned into a (generative) classifier.
- **Automatic essay writing** One can sample from $p(x_{1:t})$ to generate artificial text.

MLE for Markov language models

The probability of any particular sequence of length T is given by

$$\begin{aligned} p(x_{1:T}|\theta) &= \pi(x_1)A(x_1, x_2)\dots A(x_{T-1}, x_T) \\ &= \prod_j \pi_j^{\mathbb{1}_{x_1=j}} \prod_{t=2}^T \prod_{jk} (A_{jk})^{\mathbb{1}_{(x_t=k, x_{t-1}=j)}} \end{aligned}$$

Hence the log-likelihood of a set of N sequences $\mathcal{D} = (x_1, \dots, x_N)$, where $x_i = (x_{i,1}, \dots, x_{i,T_i})$ is a sequence of length T_i , is given by

$$\log p(\mathcal{D}|\theta) = \log p(x_i|\theta) = N_j^1 \log \pi_j + N_{jk} \log A_{jk}$$

MLE estimates are normalized Counts

$$\begin{aligned} N_j^1 &\triangleq \sum_{i=1}^N \mathbb{1}_{(x_{i1}=j)}, \quad N_{jk} \triangleq \sum_{i=1}^N \sum_{t=1}^{T_i-1} \mathbb{1}_{(x_{it}=k, x_{i,t-1}=j)} \\ \hat{\pi}_j &= \frac{N_j^1}{\sum_j N_j^1}, \quad \hat{A}_{jk} = \frac{N_{jk}}{\sum_k N_{jk}} \end{aligned}$$

The problem of zero-counts

very acute whenever

- the number of states K ,
- and/or the order of the chain, n , is large.

A simple solution

use add-one smoothing, where we simply add one to all the empirical counts before normalizing (Bayesian interpretation. . .)

- However add-one smoothing assumes all n -grams are equally likely, which is not very realistic.

Empirical Bayes version of deleted interpolation

Deleted interpolation (Chen and Goodman 1996)

Defines the transition matrix as a convex combination of the bigram frequencies $f_{jk} = \frac{N_{jk}}{N_j}$ and the unigram frequencies $f_k = \frac{N_k}{N}$:

$$A_{jk} = (1 - \lambda)f_{jk} + \lambda f_k$$

The term λ is usually set by cross validation.

An equivalent simple hierarchical Bayesian model

Prior $A_j \sim \text{Dir}(\alpha_0 m_1, \dots, \alpha_0 m_K) = \text{Dir}(\alpha_0 m) = \text{Dir}(\alpha)$

- A_j is row j of the transition matrix,
- m is the prior mean (satisfying $\sum_k m_k = 1$) and
- α_0 is the prior strength.

Posterior $A_j \sim \text{Dir}(\alpha + N_j)$ where $N_j = (N_{j1}, \dots, N_{jK})$ is the vector that records the number of times we have transitioned out of state j to each of the other states.

Empirical Bayes version of deleted interpolation

the posterior predictive density is

$$p(X_{t+1} = k | X_t = j, \mathcal{D}) = \bar{A}_{jk} = \frac{N_{jk} + \alpha_0 m_k}{\sum_k N_{jk} + \alpha_0} = (1 - \lambda_j) f_{jk} + \lambda_j m_k \text{ where}$$
$$\bar{A}_{jk} = E[A_{jk} | \mathcal{D}, \alpha] \text{ and } \lambda_j = \frac{\alpha_j}{N_j + \alpha_0}$$

Remark

We have to choose α_0 and $m \dots$

Stationary distribution of a Markov chain

We are often interested in the long term distribution over states, which is known as the stationary distribution of the chain

Distribution over states

let $\pi_t(j) = p(X_t = j)$

- Assume that π_t is a row vector.
- If we have an initial distribution over states of π_0 , then at time 1 we have $\pi_1(j) = \sum_i \pi_0(i)A_{ij}$, which can be written as $\pi_1 = \pi_0 A$

Stationary distribution

If we ever reach a stage where

$$\pi = \pi A$$

then we say we have reached the stationary distribution (also called the invariant distribution or equilibrium distribution).

Computing the stationary distribution

Eigenvector associated with unit eigenvalue

To find the stationary distribution, we can just solve the eigenvector equation $A^T v = v$, and then to set $\pi = v^T$, where v is an eigenvector with eigenvalue 1.

Eigenvalues of A and A^T are the same.

A more general approach

We have K constraints from $\pi(I - A) = 0_{K \times 1}$ and 1 constraint from $\pi \mathbb{1}_{K \times 1} = 1$.

Since we only have K unknowns, this is overconstrained.

Let us replace any column (e.g., the last) of $I - A$ with 1, to get a new matrix, call it M . Next we define $r = [0, 0, \dots, 1]$, then solve

$$\pi M = r$$

.

Let

$$A^T = \begin{pmatrix} 0 & 1/2 & 1 \\ 1 & 0 & 0 \\ 0 & 1/2 & 0 \end{pmatrix}$$

be the transpose of a transition matrix. Compute the stationary distribution.

Exercise

Solution 1

```
A <- matrix(c(0, 1/2, 1, 1, 0, 0, 0, 1/2, 0), 3, 3)
eigen.res <- eigen(t(A))
pi <- eigen.res$vectors[, 1]
pi <- t(pi) %*% A
pi / sum(pi)
```

```
##           [,1]    [,2]    [,3]
## [1,] 0.4+0i 0.4+0i 0.2+0i
```

Solution 2

```
M <- diag(rep(1, 3)) - A
M[, 3] <- rep(1, 3)
solve(t(M), b = c(0, 0, 1))

## [1] 0.4 0.4 0.2
```

When does a stationary distribution exist?

Irreducible chain

A necessary condition to have a unique stationary distribution is that the state transition diagram be a singly connected component, i.e., we can get from any state to any other state. Such chains are called irreducible.

Aperiodic chain

Define the period of state i : $d(i) = \gcd\{t : A_{ii}(t) > 0\}$

We say a state i is aperiodic if $d(i) = 1$. (A sufficient condition to ensure this is if state i has a self-loop, but this is not a necessary condition.) A chain is aperiodic if all its states are aperiodic.

Irreducible, aperiodic finite state Markov chain

Every irreducible (singly connected), aperiodic finite state Markov chain has a limiting distribution, which is equal to π , its unique stationary distribution. Every regular finite state chain has a unique stationary distribution, where a regular chain is one whose transition matrix satisfies $A_{ij}^n > 0$ for n and all i, j . Consequently, after n steps, the chain could be in any state, no matter

Application: Google's PageRank algorithm for web page ranking

The web is a giant directed graph, where nodes represent web pages (documents) and edges represent links between them. We can get a refined search by storing the location of each word in each document.

For each word, we store a list of the documents where this word occurs.

Taking the web structure into account

But the link structure of the web provides an additional source of information.

Each incoming link is weighted by the source's authority. Thus we get the following recursive definition for the authoritativeness of page j , also called its **PageRank**:

$$\pi_j = \sum_i \pi_i A_{ij}$$

where A_{ij} is the probability of following a link from i to j . We recognize a stationary distribution of a Markov chain.

Mixture models and the EM algorithm

Latent variable models

Assume that the observed variables are correlated because they arise from a hidden common “cause”. Model with hidden variables are also known as latent variable models or LVMs.

Latent variables

In general there are L latent variables, z_{i1}, \dots, z_{iL} , and D visible variables, x_{i1}, \dots, x_{iD} , where usually $D \gg L$. If we have $L > 1$, there are many latent factors contributing to each observation, so we have a many-to-many mapping. If $L = 1$, we only have a single latent variable; in this case, z_i is usually discrete, and we have a one-to-many mapping.


Mixture models

The simplest form of LVM is when $z_i \in \{1, \dots, K\}$, representing a discrete latent state:

- $p(z_i) = \text{Cat}(\pi)$ (proportions)
- $p(x_i|z_i = k) = p_k(x_i)$ (class densities, components),

$$p(x_i|\theta) = \sum_k \pi_k p_k(x_i)$$

π_k satisfy $0 \leq \pi_k \leq 1$ and $\sum_k \pi_k = 1$.



In this model, each base distribution in the mixture is a multivariate Gaussian with mean μ_k and covariance matrix Σ_k :

$$p(x_i|\theta) = \sum_k \pi_k \mathcal{N}(x_i|\mu_k, \Sigma_k)$$

class- conditional density is a product of Bernoullis:

$$p(x_i|z_i = k, \theta) = \prod_j \text{Ber}(x_{ij}|\mu_{jk}).$$

Data

- Observed data : $\mathbf{x}_{1:n}$
- Missing (or hidden) data : $\mathbf{z}_{1:n}$

Principle

- Starting from θ^0
- At step q
 - E(xpectation) step: $Q(\theta, \theta^q) = E_{\mathbf{z}_{1:n}|\mathbf{x}_{1:n}}[\log P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta)]$
 - M(aximisation) step: $\theta^{q+1} = \operatorname{argmax}_{\theta} Q(\theta, \theta^q)$

EM algorithm

At each iteration the log-likelihood of the parameters increase

$$\begin{aligned} Q(\theta^{q+1}, \theta^q) &\geq Q(\theta^q, \theta^q) \\ 0 &\leq Q(\theta^{q+1}, \theta^q) - Q(\theta^q, \theta^q) \\ 0 &\leq E_{Z_{1:n}|\mathbf{x}_{1:n}} \left[\log \frac{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^{q+1})}{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^q)} \right] \\ E_{Z_{1:n}|\mathbf{x}_{1:n}} \left[\log \frac{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^{q+1})}{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^q)} \right] &\underset{\text{Jensen}}{\leq} \log E_{Z_{1:n}|\mathbf{x}_{1:n}} \left[\frac{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^{q+1})}{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^q)} \right] \\ 0 &\leq \log \int \frac{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^{q+1})}{P(\mathbf{x}_{1:n}, \mathbf{z}_{1:n}, \theta^q)} P(\mathbf{z}_{1:n}|\mathbf{x}_{1:n}) d\mathbf{z}_{1:n} \\ 0 &\leq \log \frac{P(\mathbf{x}_{1:n}, \theta^{q+1})}{P(\mathbf{x}_{1:n}, \theta^q)} \end{aligned}$$

Programmer un algorithme EM pour les mélange de Poisson univariés