proficiency-test-II

Cameron Flores

Task-1

```
for(i in 1:3){
print(mtcars$mpg[i])
}
```

```
[1] 21
[1] 21
[1] 22.8
```

Task-2

```
count_above <- function(x, c){ # creates count_above as a function, sets x as the vector and
  count <- 0 # sets the count to 0

for(i in 1:length(x)){ # for i is from 1 to the length of x
  if((1:length(x[i])) > c){ # if an index is greater than the cutoff
    count <- count + 1 #adds +1 to the counter
  }
}
  return(count) #returns count
}
```

```
count_aboveandequal <- function(x, c){ # creates count_above as a function, sets x as the ve
  count <- 0 # sets the count to 0

for(i in 1:length(x)){ # for i is from 1 to the length of x
  if(i >= c){ # if i is greater than or equal to c
```

```
    count <- count + 1 #adds +1 to the counter
  }
}
  return(count) #returns count
}
```

```
count_above(iris$Sepal.Length,6)
```

```
[1] 0
```

```
count_aboveandequal(mtcars$disp, 150)
```

```
[1] 0
```

Task 3

Masking functions is when you cover up a loaded in function that was installed, these laoded in functions usually override basic R studio functions.

Task 4

```
iris$Sepal.Length[1]
```

```
[1] 5.1
```

```
iris[1,1]
```

```
[1] 5.1
```

it returns the first value in the Sepal.Length column of iris