

# Machine Learning

A. G. Schwing & M. Telgarsky

University of Illinois at Urbana-Champaign, 2018

## L12: Structured Prediction (ILP, LP relaxation, message passing, graph cut)

## **Goals of this lecture**

## Goals of this lecture

- Getting to know structured inference algorithms

## **Goals of this lecture**

- Getting to know structured inference algorithms

## **Reading material:**

## **Goals of this lecture**

- Getting to know structured inference algorithms

## **Reading material:**

- D. Koller and N. Friedman; Probabilistic Graphical Models: Principles and Techniques;

## **Recap:** Inference Program

## **Recap:** Inference Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$



## **Recap:** Inference Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Algorithms:

## **Recap:** Inference Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Algorithms:

- Exhaustive search
- Dynamic programming

## **Recap:** Inference Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Algorithms:

- Exhaustive search
- Dynamic programming
- Integer linear program
- Linear programming relaxation
- Message passing
- Graph-cut

## Integer Linear Program


Example:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

## Integer Linear Program

Example:


$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$



## Integer Linear Program

Example:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$



Integer Linear Program (LP) equivalence: variables  $b_r(\mathbf{y}_r)$

## Integer Linear Program

Example:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

$\mathbf{y}_{1,2}$

$y_1$

$y_2$

Integer Linear Program (LP) equivalence: variables  $b_r(\mathbf{y}_r)$

$$\max_{b_1, b_2, b_{12}} \begin{bmatrix} b_1(1) \\ b_1(2) \\ b_2(1) \\ b_2(2) \\ b_{12}(1, 1) \\ b_{12}(2, 1) \\ b_{12}(1, 2) \\ b_{12}(2, 2) \end{bmatrix}^\top \begin{bmatrix} f_1(1) \\ f_1(2) \\ f_2(1) \\ f_2(2) \\ f_{12}(1, 1) \\ f_{12}(2, 1) \\ f_{12}(1, 2) \\ f_{12}(2, 2) \end{bmatrix}$$

## Integer Linear Program

Example:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

$\mathbf{y}_{1,2}$

$y_1$

$y_2$

Integer Linear Program (LP) equivalence: variables  $b_r(\mathbf{y}_r)$

$$\max_{b_1, b_2, b_{12}} \begin{bmatrix} b_1(1) \\ b_1(2) \\ b_2(1) \\ b_2(2) \\ b_{12}(1, 1) \\ b_{12}(2, 1) \\ b_{12}(1, 2) \\ b_{12}(2, 2) \end{bmatrix}^T \begin{bmatrix} f_1(1) \\ f_1(2) \\ f_2(1) \\ f_2(2) \\ f_{12}(1, 1) \\ f_{12}(2, 1) \\ f_{12}(1, 2) \\ f_{12}(2, 2) \end{bmatrix} \quad \text{s.t.}$$



# Integer Linear Program

Example:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

$\mathbf{y}_{1,2}$

$y_1$

$y_2$

Integer Linear Program (LP) equivalence: variables  $b_r(\mathbf{y}_r)$

$$\max_{b_1, b_2, b_{12}} \begin{bmatrix} b_1(1) \\ b_1(2) \\ b_2(1) \\ b_2(2) \\ b_{12}(1, 1) \\ b_{12}(2, 1) \\ b_{12}(1, 2) \\ b_{12}(2, 2) \end{bmatrix}^T \begin{bmatrix} f_1(1) \\ f_1(2) \\ f_2(1) \\ f_2(2) \\ f_{12}(1, 1) \\ f_{12}(2, 1) \\ f_{12}(1, 2) \\ f_{12}(2, 2) \end{bmatrix} \quad \text{s.t.} \quad b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r$$

## Integer Linear Program

Example:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

$\mathbf{y}_{1,2}$

$y_1$

$y_2$


Integer Linear Program (LP) equivalence: variables  $b_r(\mathbf{y}_r)$

$$\begin{aligned} \max_{b_1, b_2, b_{12}} & \begin{bmatrix} b_1(1) \\ b_1(2) \\ b_2(1) \\ b_2(2) \\ b_{12}(1,1) \\ b_{12}(2,1) \\ b_{12}(1,2) \\ b_{12}(2,2) \end{bmatrix}^T \begin{bmatrix} f_1(1) \\ f_1(2) \\ f_2(1) \\ f_2(2) \\ f_{12}(1,1) \\ f_{12}(2,1) \\ f_{12}(1,2) \\ f_{12}(2,2) \end{bmatrix} \\ \text{s.t.} & \quad b_r(\mathbf{y}_r) \in \{0, 1\} \\ & \quad \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 \end{aligned} \quad \begin{aligned} & \forall r, \mathbf{y}_r \\ & \forall r \end{aligned}$$

## Integer Linear Program

Example:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$



Integer Linear Program (LP) equivalence: variables  $b_r(\mathbf{y}_r)$

$$\begin{aligned} \max_{b_1, b_2, b_{12}} & \begin{bmatrix} b_1(1) \\ b_1(2) \\ b_2(1) \\ b_2(2) \\ b_{12}(1,1) \\ b_{12}(2,1) \\ b_{12}(1,2) \\ b_{12}(2,2) \end{bmatrix}^\top \begin{bmatrix} f_1(1) \\ f_1(2) \\ f_2(1) \\ f_2(2) \\ f_{12}(1,1) \\ f_{12}(2,1) \\ f_{12}(1,2) \\ f_{12}(2,2) \end{bmatrix} \\ \text{s.t.} & \quad b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r \\ & \quad \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 \quad \forall r \\ & \quad \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) \quad \forall r, \mathbf{y}_r, p \in P(r) \end{aligned}$$

# Integer Linear Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Integer linear program:

$$\begin{aligned} \max_{b_1, b_2, b_{12}} & \begin{bmatrix} b_1(1) \\ b_1(2) \\ b_2(1) \\ b_2(2) \\ b_{12}(1,1) \\ b_{12}(2,1) \\ b_{12}(1,2) \\ b_{12}(2,2) \end{bmatrix}^\top \begin{bmatrix} f_1(1) \\ f_1(2) \\ f_2(1) \\ f_2(2) \\ f_{12}(1,1) \\ f_{12}(2,1) \\ f_{12}(1,2) \\ f_{12}(2,2) \end{bmatrix} \\ \text{s.t.} & \quad b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r \\ & \quad b_r(\mathbf{y}_r) \geq 0 \quad \forall r, \mathbf{y}_r \\ & \quad \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 \quad \forall r \\ & \quad \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) \end{aligned}$$

# Integer Linear Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Integer linear program:

$$\begin{aligned} \max_{b_r} \quad & \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \\ \text{s.t.} \quad & b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r \\ & b_r(\mathbf{y}_r) \geq 0 \quad \forall r, \mathbf{y}_r \\ & \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 \quad \forall r \\ & \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) \end{aligned}$$

# Integer Linear Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Integer linear program:

$$\begin{array}{ll} \max_{b_r} & \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \\ \text{s.t.} & b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r \\ & b_r(\mathbf{y}_r) \geq 0 \quad \forall r, \mathbf{y}_r \\ & \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 \quad \forall r \end{array}$$

Marginalization

# Integer Linear Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Integer linear program:

$$b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r$$

$$\max_{b_r} \quad \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r)$$

s.t. Local probability  $b_r$

Marginalization

# Integer Linear Program

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

Integer linear program:

$$b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r$$

$$\max_{b_r} \quad \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \quad \text{s.t.} \quad \text{Local probability } b_r$$

Marginalization

- **Advantage:** global optimum, very good solvers available
- **Disadvantage:** very slow for larger problems



# Linear Programming Relaxation

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

LP relaxation:

~~$$b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r$$~~

$$\max_{b_r} \quad \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r)$$

s.t. Local probability  $b_r$

Marginalization

$$\underbrace{\hspace{10em}}_{\text{s.t. } b \in \mathcal{C}}$$

# Linear Programming Relaxation

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\hat{\mathbf{y}}_r)$$

LP relaxation:

$$b_r(\mathbf{y}_r) \in \{0, 1\} \quad \forall r, \mathbf{y}_r$$

$$\max_{b_r} \quad \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r)$$

s.t. Local probability  $b_r$

Marginalization

$$\underbrace{\hspace{10em}}_{\text{s.t. } b \in \mathcal{C}}$$

- **Advantage:** global optimum for LP, very good solvers available
- **Disadvantage:** no global optimum for ILP, slow for larger problems

## Message Passing ([Loopy] Belief Propagation)


Exploit:

## **Message Passing ([Loopy] Belief Propagation)**

Exploit: Graph structure defined via marginalization constraints


## Message Passing ([Loopy] Belief Propagation)

Exploit: Graph structure defined via marginalization constraints



## Message Passing ([Loopy] Belief Propagation)


Exploit: Graph structure defined via marginalization constraints



How:

## Message Passing ([Loopy] Belief Propagation)


Exploit: Graph structure defined via marginalization constraints



How: Compute the dual function

## Message Passing ([Loopy] Belief Propagation)

Exploit: Graph structure defined via marginalization constraints



How: Compute the dual function

### Message passing solvers:

- **Advantage:** Efficient due to analytically computable sub-problems
- **Disadvantage:** Special care required to find LP relaxation optimum



## Computing the dual of

$$\max_b \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \\ \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) & \forall r, p \in P(r), \mathbf{y}_r \end{cases}$$

Computing the dual of

$$\max_b \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \\ \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) & \forall r, p \in P(r), \mathbf{y}_r \end{cases}$$

Lagrangian:

## Computing the dual of

$$\max_b \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \\ \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) & \forall r, p \in P(r), \mathbf{y}_r \end{cases}$$

Lagrangian:

$$\begin{aligned} L() &= \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) + \sum_{r, p \in P(r), \mathbf{y}_r} \lambda_{r \rightarrow p}(\mathbf{y}_r) \left( \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) - b_r(\mathbf{y}_r) \right) \\ &= \end{aligned}$$

## Computing the dual of

$$\max_b \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \\ \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) & \forall r, p \in P(r), \mathbf{y}_r \end{cases}$$

Lagrangian:

$$\begin{aligned} L() &= \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) + \sum_{r, p \in P(r), \mathbf{y}_r} \lambda_{r \rightarrow p}(\mathbf{y}_r) \left( \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) - b_r(\mathbf{y}_r) \right) \\ &= \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right) \end{aligned}$$

Lagrangian:

$$L() = \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Lagrangian:

$$L() = \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Maximize Lagrangian w.r.t. primal variables subject to remaining constraints:

Lagrangian:

$$L() = \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Maximize Lagrangian w.r.t. primal variables subject to remaining constraints:

$$\max_b L() \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \end{cases}$$

Lagrangian:

$$L() = \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Maximize Lagrangian w.r.t. primal variables subject to remaining constraints:

$$\max_b L() \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \end{cases}$$

Dual function:



Lagrangian:

$$L() = \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Maximize Lagrangian w.r.t. primal variables subject to remaining constraints:

$$\max_b L() \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \end{cases}$$

Dual function:

$$g(\lambda) = \sum_r \max_{\mathbf{y}_r} \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Dual function:

$$g(\lambda) = \sum_r \max_{\mathbf{y}_r} \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Dual function:

$$g(\lambda) = \sum_r \max_{\mathbf{y}_r} \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Dual program:

Dual function:

$$g(\lambda) = \sum_r \max_{\mathbf{y}_r} \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Dual program:

$$\min_{\lambda} g(\lambda)$$

Dual function:

$$g(\lambda) = \sum_r \max_{\mathbf{y}_r} \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Dual program:

$$\min_{\lambda} g(\lambda)$$

Original primal:

Dual function:

$$g(\lambda) = \sum_r \max_{\mathbf{y}_r} \left( f_r(\mathbf{y}_r) - \sum_{p \in P(r)} \lambda_{r \rightarrow p}(\mathbf{y}_r) + \sum_{c \in C(r)} \lambda_{c \rightarrow r}(\mathbf{y}_c) \right)$$

Dual program:

$$\min_{\lambda} g(\lambda)$$

Original primal:

$$\max_b \sum_{r, \mathbf{y}_r} b_r(\mathbf{y}_r) f_r(\mathbf{y}_r) \quad \text{s.t.} \quad \begin{cases} b_r(\mathbf{y}_r) \geq 0 & \forall r, \mathbf{y}_r \\ \sum_{\mathbf{y}_r} b_r(\mathbf{y}_r) = 1 & \forall r \\ \sum_{\mathbf{y}_p \setminus \mathbf{y}_r} b_p(\mathbf{y}_p) = b_r(\mathbf{y}_r) & \forall r, p \in P(r), \mathbf{y}_r \end{cases}$$

Properties of dual program:

Properties of dual program:

- Convex program



Properties of dual program:

- Convex program
- Not strongly convex

## Properties of dual program:

- Convex program
- Not strongly convex
- Piecewise linear

Properties of dual program:

- Convex program
- Not strongly convex
- Piecewise linear
- **Unconstrained**

## Properties of dual program:

- Convex program
- Not strongly convex
- Piecewise linear
- **Unconstrained**
- Lagrange multipliers are messages

## Properties of dual program:

- Convex program
- Not strongly convex
- Piecewise linear
- **Unconstrained**
- Lagrange multipliers are messages

Lagrange multipliers are messages defined on edges of the graph. They shift 'energy' such that local maximization (dual) is identical to global maximization (primal).

# Graph-cut Solvers

## Graph-cut Solvers

- Efficient algorithms to compute the minimum cost cut in a weighted graph


## Graph-cut Solvers

- Efficient algorithms to compute the minimum cost cut in a weighted graph
- Efficient algorithms to compute the maximum flow through a weighted graph



## Graph-cut Solvers


- Efficient algorithms to compute the minimum cost cut in a weighted graph
- Efficient algorithms to compute the maximum flow through a weighted graph



## Graph-cut Solvers

For binary problems  $y_d \in \{1, 2\}$ :


- Convert scoring function  $F$  into auxiliary graph (not the same graph as before!)



## Graph-cut Solvers

For binary problems  $y_d \in \{1, 2\}$ :


- Convert scoring function  $F$  into auxiliary graph (not the same graph as before!)
- Compute a weighted cut cost corresponding to the labeling score



## Graph-cut Solvers

For binary problems  $y_d \in \{1, 2\}$ :


- Convert scoring function  $F$  into auxiliary graph (not the same graph as before!)
- Compute a weighted cut cost corresponding to the labeling score



What are the nodes and what are the weights on the edges in this auxiliary graph?


## Graph-cut Solvers

What are the nodes in the auxiliary graph?



## Graph-cut Solvers


What are the nodes in the auxiliary graph?



- Two special nodes called ‘source’ and ‘terminal’

## Graph-cut Solvers


What are the nodes in the auxiliary graph?



- Two special nodes called ‘source’ and ‘terminal’
- Variables  $y_d$  as nodes

## Graph-cut Solvers

What are the nodes in the auxiliary graph?



- Two special nodes called ‘source’ and ‘terminal’
- Variables  $y_d$  as nodes



What weights do we assign to edges?

## Graph-cut Solvers

What weights do we assign to edges?

Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_1(y_1 = 1) & f_1(y_1 = 2) \end{bmatrix}$$


## Graph-cut Solvers

What weights do we assign to edges?

Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_1(y_1 = 1) & f_1(y_1 = 2) \end{bmatrix}$$

Graph-cut solvers compute a min-cut:



## Graph-cut Solvers

What weights do we assign to edges?

Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_{12}(1, 1) & f_{12}(1, 2) \\ f_{12}(2, 1) & f_{12}(2, 2) \end{bmatrix} =$$

## Graph-cut Solvers

What weights do we assign to edges?

Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_{12}(1,1) & f_{12}(1,2) \\ f_{12}(2,1) & f_{12}(2,2) \end{bmatrix} = f(1,1) - f(2,1) + f(2,2) \\ + \begin{bmatrix} 0 & 0 \\ f(2,1) - f(1,1) & f(2,1) - f(1,1) \end{bmatrix} \\ + \begin{bmatrix} f(2,1) - f(2,2) & 0 \\ f(2,1) - f(2,2) & 0 \end{bmatrix} \\ + \begin{bmatrix} 0 & f(1,2) + f(2,1) - f(1,1) - f(2,2) \\ 0 & 0 \end{bmatrix}$$


## Graph-cut Solvers

What weights do we assign to edges?

Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_{12}(1,1) & f_{12}(1,2) \\ f_{12}(2,1) & f_{12}(2,2) \end{bmatrix} = f(1,1) - f(2,1) + f(2,2) \\ + \begin{bmatrix} 0 & 0 \\ f(2,1) - f(1,1) & f(2,1) - f(1,1) \end{bmatrix} \\ + \begin{bmatrix} f(2,1) - f(2,2) & 0 \\ f(2,1) - f(2,2) & 0 \end{bmatrix} \\ + \begin{bmatrix} 0 & f(1,2) + f(2,1) - f(1,1) - f(2,2) \\ 0 & 0 \end{bmatrix}$$

Graph-cut solvers compute a min-cut:




## Graph-cut Solvers

What weights do we assign to edges?

Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_{12}(1, 1) & f_{12}(1, 2) \\ f_{12}(2, 1) & f_{12}(2, 2) \end{bmatrix} = f(1, 1) - f(2, 1) + f(2, 2) \\ + \begin{bmatrix} 0 & 0 \\ f(2, 1) - f(1, 1) & f(2, 1) - f(1, 1) \end{bmatrix} \\ + \begin{bmatrix} f(2, 1) - f(2, 2) & 0 \\ f(2, 1) - f(2, 2) & 0 \end{bmatrix} \\ + \begin{bmatrix} 0 & f(1, 2) + f(2, 1) - f(1, 1) - f(2, 2) \\ 0 & 0 \end{bmatrix}$$

Graph-cut solvers compute a min-cut:




## Graph-cut Solvers

What weights do we assign to edges?

Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_{12}(1, 1) & f_{12}(1, 2) \\ f_{12}(2, 1) & f_{12}(2, 2) \end{bmatrix} = f(1, 1) - f(2, 1) + f(2, 2) \\ + \begin{bmatrix} 0 & 0 \\ f(2, 1) - f(1, 1) & f(2, 1) - f(1, 1) \end{bmatrix} \\ + \begin{bmatrix} f(2, 1) - f(2, 2) & 0 \\ f(2, 1) - f(2, 2) & 0 \end{bmatrix} \\ + \begin{bmatrix} 0 & f(1, 2) + f(2, 1) - f(1, 1) - f(2, 2) \\ 0 & 0 \end{bmatrix}$$

Graph-cut solvers compute a min-cut:






## Graph-cut Solvers

What weights do we assign to edges?


Recall that local scoring functions are arrays:

$$\begin{bmatrix} f_{12}(1, 1) & f_{12}(1, 2) \\ f_{12}(2, 1) & f_{12}(2, 2) \end{bmatrix} = f(1, 1) - f(2, 1) + f(2, 2) \\ + \begin{bmatrix} 0 & 0 \\ f(2, 1) - f(1, 1) & f(2, 1) - f(1, 1) \end{bmatrix} \\ + \begin{bmatrix} f(2, 1) - f(2, 2) & 0 \\ f(2, 1) - f(2, 2) & 0 \end{bmatrix} \\ + \begin{bmatrix} 0 & f(1, 2) + f(2, 1) - f(1, 1) - f(2, 2) \\ 0 & 0 \end{bmatrix}$$

Graph-cut solvers compute a min-cut:




## Graph-cut Solvers



Requirement for optimality:


## Graph-cut Solvers



Requirement for optimality: Pairwise edge weights are positive

$$f(1,1) + f(2,2) - f(1,2) - f(2,1) \geq 0 \quad \text{sub-modularity}$$

## Graph-cut Solvers




Requirement for optimality: Pairwise edge weights are positive

$$f(1,1) + f(2,2) - f(1,2) - f(2,1) \geq 0 \quad \text{sub-modularity}$$

For higher order functions?

## Graph-cut Solvers




Requirement for optimality: Pairwise edge weights are positive

$$f(1, 1) + f(2, 2) - f(1, 2) - f(2, 1) \geq 0 \quad \text{sub-modularity}$$

For higher order functions? More complicated graph constructions

## Graph-cut Solvers




Requirement for optimality: Pairwise edge weights are positive

$$f(1,1) + f(2,2) - f(1,2) - f(2,1) \geq 0 \quad \text{sub-modularity}$$

For higher order functions? More complicated graph constructions  
For more than two labels?

## Graph-cut Solvers



Requirement for optimality: Pairwise edge weights are positive

$$f(1,1) + f(2,2) - f(1,2) - f(2,1) \geq 0 \quad \text{sub-modularity}$$

For higher order functions? More complicated graph constructions  
For more than two labels? Move making algorithms

## Structured Prediction

Inference:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Efficiency and accuracy of inference algorithms is problem dependent:



## Structured Prediction

Inference:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Efficiency and accuracy of inference algorithms is problem dependent:

- Exhaustive search

## Structured Prediction

Inference:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Efficiency and accuracy of inference algorithms is problem dependent:

- Exhaustive search
- Dynamic programming

## Structured Prediction

Inference:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Efficiency and accuracy of inference algorithms is problem dependent:

- Exhaustive search
- Dynamic programming
- Integer linear program

## Structured Prediction

Inference:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Efficiency and accuracy of inference algorithms is problem dependent:

- Exhaustive search
- Dynamic programming
- Integer linear program
- Linear programming relaxation

## Structured Prediction

Inference:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Efficiency and accuracy of inference algorithms is problem dependent:

- Exhaustive search
- Dynamic programming
- Integer linear program
- Linear programming relaxation
- Message passing

## Structured Prediction

Inference:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Efficiency and accuracy of inference algorithms is problem dependent:

- Exhaustive search
- Dynamic programming
- Integer linear program
- Linear programming relaxation
- Message passing
- Graph-cut

## Quiz:

### **Quiz:**

- What is the advantage of ILP and LP relaxation compared to dynamic programming and exhaustive search?



### **Quiz:**

- What is the advantage of ILP and LP relaxation compared to dynamic programming and exhaustive search?
- When is a graph-cut algorithm optimal?

## **Important topics of this lecture**

- More inference algorithms for structured spaces

## **Up next:**

- Learning models for structured output spaces