

Codice dei Brush Shading Language

Questo documento riporta il codice di tutti (55) gli shader predefiniti in BlackInk 0.357.

Contents

Nothing	3
airbrush wisp	4
blur	6
blur Noise	8
box2.toUpperLeftNorm	11
Canvas noise	12
canvasSize	14
Cell Voronoi distruct gradient	15
Cell Voronoi Edge	17
Cell Voronoi gradient	20
Cell Voronoi trabeculum bicolor	22
Cell Voronoi trabeculum gradient	25
Charcoal dual texture	28
Charcoal dual texture background overlay	30
Charcoal dual texture background smudge	35
Charcoal dual texture multiply	40
gradient angular	45
gradient linear	47
hardness ctrl	49
Hardness dither ctrl	51
hardness noise blobby ctrl	53
Hardness noise ctrl	56
ink droplets	59
Perlin blobby noise	61
Perlin blobby noise_01	63
Perlin noise (error)	65
Perlin noise scatter	68
Perlin sin noise	71
pointShadow	73
prim texture alpha invy	75
prim texture alpha Luminance	76
prim texture alpha power	77
primBubbleNoise	78
primBlubbleNoiseSpread	81
primHardness	86

primsimplenoise (error)	87
primSimpleNoise_01	89
primSmoothNoise	91
radial gradient	92
rakeNoise	94
Smooth Voronoi gradient	97
Smudge	100
Smudge cloud noise	102
Smudge cloud noise_01	106
Smudge colored	110
Smudge expand colored	112
Smudge noise colored	115
Smudge Scatter perlin noise	119
Smudge scatter trabeculum	123
smudgeRake	127
subtle color shift	131
Texture Background pattern	135
Texture Voronoi Tiling	138
viewBox	141
viewZoom	144

Nothing



airbrush wisp



```
cfg{
    name="airbrush wisp";
    renderingTime = 20 ;
}

perPrim {
    float hardness = 0.5 ;
    {
        id = -1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "hardness" ;
    }
    float symetry = 0 ;
    {
        id = -1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "symetry" ;
    }
    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
}

float cptPrimAtt( idatas i, float2 dn, float attp, float sym )
{
    matrix2 tr = i.primBox.getToCenterTransfo();
    float2 p = tr.transform( i.pos+dn );
    float2 s = i.primBox.size ;
    float symf = lerp( 200, 1, pow(sym,0.01) );
    float y = (p.y < 0 ? -p.y*symf : p.y) / (s.y*0.5) ;
    float x = saturate( (abs(p.x)-s.x*0.05) / (s.x*0.5) ) ;

    return (1-x)*(1-pow(y,attp*0.5));
}

float2 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
```

```

    p3 += dot(p3, p3.yzx + 209.191349);
    return frac( float2( (p3.x + p3.y) * p3.z, (p3.x + p3.z) * p3.y ) );
}

// simple Value Noise
// the returned value is between [-1,1]
float2 noise( float3 x )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);
    float2 v1 = bilinearLerp( hash(p+float3(0,0,0)), hash(p+float3(1,0,0)),
                             hash(p+float3(0,1,0)), hash(p+float3(1,1,0)), u.xy );
    float2 v2 = bilinearLerp( hash(p+float3(0,0,1)), hash(p+float3(1,0,1)),
                             hash(p+float3(0,1,1)), hash(p+float3(1,1,1)), u.xy );

    return 2*lerp( v1, v2, u.z )-1;
}

float4 main( idatas i )
{
    // compute dithering noise
    float2 dn = i.noisePower * 10 * noise( float3( i.pos,i.nbUserStroke+i.dist*0.01) );
    float d = cptPrimAtt( i, dn, i.hardness, i.symetry );
    //d *= dn*0.5+0.5;
    float alpha = saturate(i.color.a*d) ;
    float3 col = i.color.xyz ;

    return float4( col, alpha ) ;
}

```

blur



```
cfg{
    name = "blur" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 7 ;
    renderingTime = 60 ;
}

perPrim{
    float blurStrength = 1 ;
    {
        uiFormat = percent ;
        uiMax = 1 ;
        uiTab = "Blur" ;
        uiName = "Strength" ;
    }

    float alphaHardness = 1 ;
    {
        uiName = "Hardness";
        uiMax = 1 ;
        uiFormat = percent ;
        uiTab = "Shape" ;
    }

    float overlayFactor = 0.1 ;
    {
        uiMax = 1 ;
        uiTab = "Color" ;
        uiFormat = percent ;
        uiName = "Color overlay" ;
    }
}

float hardnessCpt( idatas i, float h )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;
    float softness = pow( 1 - h,2) ;
    d /= sm*softness + 0.001 ;
    d = 1 - exp( -d );

    return i.primDistanceValid ? d : 1 ;
}

float4 blurBottom( idatas i, float s )
{
    int nbsample = 5 ;
    float4 noBlur = bottomLayer.pointSample( i, i.pos );
```

```

float maxdec = nbsample ;
float radius = pow( s, 2 ) * fromDrawSpace( maxdec ) ;
radius = min( radius, maxdec ) ;
float tot = 0 ;
float4 coltot = 0 ;
for( int y=0; y<nbsample; y++ )
    for( int x = 0; x<nbsample; x++ )
    {
        float2 d2 = 2*( ( float2( x, y ) + 0.5 ) / nbsample ) - 0.5 ) ;
        float d = length( d2 ) ;
        float att = exp( -d ) ;
        tot += att ;
        coltot += att * bottomLayer.bilinearSample( i, i.pos + d2*radius ) ;
    }
coltot /= tot ;

return smoothLerp( noBlur, coltot, saturate(radius) );
}

float4 main( idatas i )
{
    float4 noBlur = bottomLayer.pointSample( i, i.pos );
    float h = hardnessCpt( i, i.alphaHardness ) ;
    float bs = i.blurStrength * h ;
    float4 blurred = blurBottom( i, bs );
    float4 col = blurred ;
    // apply a color overlay
    float4 tmp = blendOverlay( blurred,
i.color*float4(1,1,1,i.overlayFactor*pow(h,1.95)) );
    col.xyz = tmp.xyz ;
    float alpha = i.color.a ;
    col = blendNormalAlpha( noBlur, col, alpha );
    // take care of the eraser state
    col = i.eraser ? float4( noBlur.xyz, noBlur.w * (1-alpha) ) : col ;

    return col ;
}

```

blur Noise



```
cfg{
  name = "blurNoise" ;
  blendEx = true ;
  blendDefault = replace ;
  samplingLayerMaxOffset = 7 ;
  renderingTime = 60 ;
}

globals{
  float noiseScale = 1 ;
  {
    uiTab = "Noise" ;
    uiName = "Scale" ;
    uiFormat = percent ;
    uiMax = 1 ;
  }
}

perPrim{
  float blurStrength = 1 ;
  {
    uiFormat = percent ;
    uiMax = 1 ;
    uiTab = "Blur" ;
    uiName = "Strength" ;
  }

  float alphaHardness = 1 ;
  {
    uiName = "Hardness";
    uiMax = 1 ;
    uiFormat = percent ;
    uiTab = "Shape" ;
  }

  float overlayFactor = 0.1 ;
  {
    uiMax = 1 ;
    uiTab = "blur" ;
    uiFormat = percent ;
    uiName = "color overlay" ;
  }

  float ndensity = 0.5 ;
  {
    uiTab = "Noise" ;
    uiName = "Density" ;
  }
}
```



```

        uiFormat = percent ;
        uiMax = 1 ;
    }

    float densityHardness = 0.15 ;
    {
        uiName = "Hardness";
        uiMax = 1 ;
        uiTab = "Noise" ;
    }
}

float hardnessCpt( idatas i, float h )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;
    float softness = pow( 1 - h,2) ;
    d /= sm*softness + 0.001 ;
    d = 1 - exp( -d );

    return i.primDistanceValid ? d : 1 ;
}

float hash( float3 p )
{
    float hscale = .1031 ;
    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);

    return frac( (p3.x + p3.y) * p3.z );
}

float adjustDensity( float r, float d )
{
    d = 1-d ;
    float a = clamp( (d-0.5)*2, 0, 1 );
    float b = clamp( d*2, 0, 1 );
    r = (r-a) / max( b-a, 0.001) ;
    r = saturate( r );

    return r ;
}

float hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

float cptPrimNoise( idatas i, float time, float density )
{
    float2 p = i.primBox.toUpperLeftNorm( i.pos ) * 2 - 1 ;
    p = floor( p*i.primBox.getSize()*noiseScale );

    return hashD( float3( p, time ), density );
}

float4 blurBottom( idatas i, float s )
{
    int nbsample = 5 ;

    float4 noBlur = bottomLayer.pointSample( i, i.pos );

```

```

float maxdec = nbsample ;
float radius = pow( s, 2 ) * fromDrawSpace( maxdec ) ;
radius = min( radius, maxdec ) ;

float tot = 0 ;
float4 coltot = 0 ;
for( int y=0; y<nbsample; y++ )
    for( int x = 0; x<nbsample; x++ )
    {
        float2 d2 = 2*( ( float2( x, y ) + 0.5 ) / nbsample ) - 0.5 ) ;
        float d = length( d2 ) ;
        float att = exp( -d ) ;
        tot += att ;
        coltot += att * bottomLayer.bilinearSample( i, i.pos + d2*radius ) ;
    }

coltot /= tot ;

return smoothLerp( noBlur, coltot, saturate(radius) );
}

float4 main( idatas i )
{
    float4 noBlur = bottomLayer.pointSample( i, i.pos );

    float density = i.ndensity * hardnessCpt( i, i.densityHardness );
    float n = cptPrimNoise( i, i.dist*0.001, density );
    float nover = cptPrimNoise( i, i.dist*0.0135, density );

    float h = hardnessCpt( i, i.alphaHardness ) ;
    float bs = i.blurStrength * h * n ;
    float4 blurred = blurBottom( i, bs );

    float4 col = blurred ;

    // apply a color overlay
    float4 tmp = blendOverlay( blurred,
i.color*float4(1,1,1,nover*i.overlayFactor*pow(h,1.95)) );
    col.xyz = tmp.xyz ;


    float alpha = i.color.a ;

    col = blendNormalAlpha( noBlur, col, alpha );

    return col ;
}

```

box2.toUpperLeftNorm



```
cfg{name="box2.toUpperLeftNorm";}
```

```
float4 main( idatas i )  
{  
    float2 p = i.primBox.toUpperLeftNorm( i.pos ) ;  
    return float4( p.x, p.y, 0, 1 ) ;  
}
```

Canvas noise



```
cfg{
    name = "canvas noise";
    renderingTime = 5 ;
}

globals{

    float noiseScale = 1 ;
    {
        uiTab = "Noise" ;
        uiName = "Scale" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }

}

perPrim{

    float ndensity = 0.5 ;
    {
        uiTab = "Noise" ;
        uiName = "Density" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }

}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return frac( (p3.x + p3.y) * p3.z );
}

float adjustDensity( float r, float d )
{
    d = 1-d ;
    float a = clamp( (d-0.5)*2, 0, 1 );
    float b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001 ) ;
    r = saturate( r );

    return r ;
}
```

```

}

float hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

float4 main( idatas i )
{
    float density = i.ndensity ;
    float2 p = floor( i.pos * noiseScale );
    float alpha = hashD( float3(p,i.nbUserStroke), density );
    alpha = (density>=1) ? 1 : alpha ;

    float4 col = i.color ;
    col.a *= alpha ;

    return col ;
}

```

canvasSize



```
cfg{name="canvasSize";}
```

```
float4 main( idatas i )  
{  
    float2 p = saturate( i.pos / canvasSize );  
    return float4( p.x, p.y, 0, 1 );  
}
```

Cell Voronoi destruct gradient



```
cfg{
  name="Cell Voronoi destruct gradient";
  renderingTime = 30 ;
}

globals{
  colorGradient grad ;
  {
    uiTab = "color" ;
    id = 1 ;
  }
}

float hash1( float2 p)
{
  float hscale = .1031 ;
  float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
  p3 += dot(p3, p3.yzx + 19.19);
  return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
  float3 hscale3 = float3( .1031, .1030, .0973 ) ;

  float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3) ;
  p3 += dot(p3, p3.yzx+19.19) ;
  return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y) );
}

float4 hash4( float2 p )
{
  float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

  float4 p4 = frac( float4(p.xyxy) * hscale4 );
  p4 += dot( p4, p4.wzxy+19.19) ;
  return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}

float4 voronoi( idatas i, float2 uv, float time )
{
  float2 f ;
  float2 n = decompose( uv, f ) ;

  float seed = i.nbUserStroke ;

  //-----
  // regular voronoi
```

```

//-----
float4 col = 0 ;
float3 lastd = 10 ;
for( int j=-1; j<=1; j++ )
{
    for( int i=-1; i<=1; i++ )
    {
        float2 g = float2( i, j );

        float2 ipos = n + g ;

        float2 o = hash2( ipos+seed );
        o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

        float2 r = g + o - f;
        float d = dot(r,r);

        // Get color and orderd 3 min distances
        if( d < lastd.x )
        {
            col = grad.sample( hash2( ipos+seed+5.4 ).x );
            lastd.yz = lastd.xy ;
            lastd.x = d ;
        }
        else if( d < lastd.y )
        {
            lastd.z = lastd.y ;
            lastd.y = d ;
        }
        else if( d < lastd.z )
        {
            lastd = d ;
        }
    }
}

return col ;
}

float4 main( idatas i )
{
    box2 b = box2FromCenterAxe( i.strokeStartPos, max( length(i.strokePos-
i.strokeStartPos), 2 ), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = 4*b.toCenter( i.pos ) / b.size ;
    float4 col = voronoi( i, p, i.dist*0.005 ) ;

    return col ;
}

```


Cell Voronoi Edge



```
cfg{
    name="Cell Voronoi Edge";
    renderingTime = 30 ;
}

globals{
    float distFromEdge = 0.1 ;
    {
        uiMax = 1 ;
        uiName = "Size";
        uiTab = "Edge" ;
        uiFormat = percent ;
    }
}

float hash1( float2 p)
{
    float hscale = .1031 ;
    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);

    return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;
    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3) ;
    p3 += dot(p3, p3.yzx+19.19) ;

    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y) );
}

float4 hash4( float2 p )
{
    float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

    float4 p4 = frac( float4(p.xyxy) * hscale4 );
    p4 += dot( p4, p4.wzxy+19.19) ;
    return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}

float voronoiEdge( idatas i, float2 uv, float time )
{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    float seed = i.nbUserStroke ;
```

```

//-----
// regular voronoi
//-----
float md = 10 ;
float2 mg;
float2 mr;
for( int j=-1; j<=1; j++ )
{
for( int i=-1; i<=1; i++ )
{
float2 g = float2( i, j );

float2 ipos = n + g ;

float2 o = hash2( ipos+seed );
o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

float2 r = g + o - f;
float d = dot(r,r);

if( d < md )
{
md = d ;
mr = r ;
mg = g ;
}
}
}

//-----
// second pass: distance to borders
//-----
md = 8.0;
float2 mr2 ;
for( int j=-2; j<=2; j++ )
{
for( int i=-2; i<=2; i++ )
{
float2 g = float2( i, j );

float2 ipos = n + g ;

float2 o = hash2( ipos+seed );
o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

float2 r = g + o - f;

if( dot(mr-r,mr-r)>0.00001 )
{
float dist = dot( 0.5*(mr+r), normalize(r-mr) ) ;
if( dist < md )
{
md = dist ;
mr2 = r ;
}
}
}
}

return 2*md ;

```

```

}

float4 main( idatas i )
{
    box2 b = box2FromCenterAxe( i.strokeStartPos, max( length(i.strokePos-
i.strokeStartPos), 2 ), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = 4*b.toCenter( i.pos ) / b.size ;
    float edgeD = voronoiEdge( i, p, i.dist*0.005 ) ;

    float alpha = 1 ;
    alpha *= edgeD < distFromEdge ? 1 : 0 ;
    float4 col = i.color ;
    col.a *= alpha;

    return col ;
}

```

Cell Voronoi gradient



```
cfg{
  name="Cell Voronoi gradient";
  renderingTime = 30 ;
}

globals{
  colorGradient grad ;
  {
    uiTab = "color" ;
    id = 1 ;
  }
}

float hash1( float2 p)
{
  float hscale = .1031 ;

  float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
  p3 += dot(p3, p3.yzx + 19.19);
  return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
  float3 hscale3 = float3( .1031, .1030, .0973 ) ;

  float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
  p3 += dot(p3, p3.yzx+19.19) ;
  return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y ) );
}

float4 hash4( float2 p )
{
  float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

  float4 p4 = frac( float4(p.xyxy) * hscale4 );
  p4 += dot( p4, p4.wzxy+19.19 ) ;
  return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}

float4 voronoi( idatas i, float2 uv, float time )
{
  float2 f ;
  float2 n = decompose( uv, f ) ;

  float seed = i.nbUserStroke ;

  //-----
  // regular voronoi
```

```

//-----
float4 col = 0 ;
float lastd = 10 ;
for( int j=-1; j<=1; j++ )
{
    for( int i=-1; i<=1; i++ )
    {
        float2 g = float2( i, j );

        float2 ipos = n + g ;

        float2 o = hash2( ipos+seed );
        o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

        float2 r = g + o - f;
        float d = dot(r,r);

        if( d < lastd )
        {
            col = grad.sample( hash2( ipos+seed+5.4 ).x );
            lastd = d ;
        }
    }
}

return col ;
}

float4 main( idatas i )
{
    box2 b = box2FromCenterAxe( i.strokeStartPos, max( length(i.strokePos-
i.strokeStartPos), 2 ), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = 4*b.toCenter( i.pos ) / b.size ;
    float4 col = voronoi( i, p, i.dist*0.005 ) ;

    return col ;
}

```

Cell Voronoi trabeculum bicolor



```
cfg{
    name="Cell Voronoi trabeculum bicolor";
    renderingTime = 30 ;
}

globals{
    float4 colA = 1 ;
    float4 colB = float4(0,0,0,1);
}

perPrim {
    float hardness = 0.5 ;
    {
        id = -1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "hardness" ;
    }
}

float hash1( float2 p)
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
    p3 += dot(p3, p3.yzx+19.19) ;
    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y ) );
}

float4 hash4( float2 p )
{
    float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

    float4 p4 = frac( float4(p.xyxy) * hscale4 );
    p4 += dot( p4, p4.wzxy+19.19 ) ;
    return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}
```

```

}

float4 voronoi( idatas i, float2 uv, float time )
{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    float seed = i.nbUserStroke ;

    //-----
    // regular voronoi
    //-----
    float3 lastd = 10 ;
    for( int j=-1; j<=1; j++ )
    {
        for( int i=-1; i<=1; i++ )
        {
            float2 g = float2( i, j );

            float2 ipos = n + g ;

            float2 o = hash2( ipos+seed );
            o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

            float2 r = g + o - f;
            float d = dot(r,r);

            // Get color and orderd 3 min distances
            if( d < lastd.x )
            {
                lastd.yz = lastd.xy ;
                lastd.x = d ;
            }
            else if( d < lastd.y )
            {
                lastd.z = lastd.y ;
                lastd.y = d ;
            }
            else if( d < lastd.z )
            {
                lastd.z = d ;
            }
        }
    }

    lastd = 5*sqrt(lastd);

    float alpha = 1./ ( 1./ (lastd.y-lastd.x)+1./ (lastd.z-lastd.x) ) ; // Formula (c)
    Fabrice NEYRET

    float hcut = lerp( 3, 0.05, i.hardness ) ;
    float4 col = alpha > hcut ? colA : colB ;

    return col ;
}

float4 main( idatas i )
{
    box2 b = box2FromCenterAxe( i.strokeStartPos, max( length(i.strokePos-
i.strokeStartPos), 2 ), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = 4*b.toCenter( i.pos ) / b.size ;

```

```
float4 col = voronoi( i, p, i.dist*0.005 ) ;  
return col ;  
}
```


Cell Voronoi trabeculum gradient



```
cfg{
    name="Cell Voronoi trabeculum gradient";
    renderingTime = 30 ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
}

perPrim {
    float hardness = 0.5 ;
    {
        id = -1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "hardness" ;
    }
}

float hash1( float2 p)
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
    p3 += dot(p3, p3.yzx+19.19) ;
    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y ) );
}

float4 hash4( float2 p )
{
    float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

    float4 p4 = frac( float4(p.xyxy) * hscale4 );
    p4 += dot( p4, p4.wzxy+19.19) ;
}
```

```

    return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}

float4 voronoi( idatas i, float2 uv, float time )
{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    float seed = i.nbUserStroke ;

    //-----
    // regular voronoi
    //-----
    float4 col = 0 ;
    float3 lastd = 10 ;
    for( int j=-1; j<=1; j++ )
    {
        for( int i=-1; i<=1; i++ )
        {
            float2 g = float2( i, j );

            float2 ipos = n + g ;

            float2 o = hash2( ipos+seed );
            o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

            float2 r = g + o - f;
            float d = dot(r,r);

            // Get color and orderd 3 min distances
            if( d < lastd.x )
            {
                col = grad.sample( hash2( ipos+seed+5.4 ).x );
                lastd.yz = lastd.xy ;
                lastd.x = d ;
            }
            else if( d < lastd.y )
            {
                lastd.z = lastd.y ;
                lastd.y = d ;
            }
            else if( d < lastd.z )
            {
                lastd.z = d ;
            }
        }
    }

    lastd = 5*sqrt(lastd);

    float alpha = 1./ ( 1./ (lastd.y-lastd.x)+1./(lastd.z-lastd.x) ) ; // Formula (c)
    Fabrice NEYRET

    float hcut = lerp( 3, 0.05, i.hardness ) ;
    col.a *= alpha > hcut ? 1 : 0 ;

    return col ;
}

float4 main( idatas i )

```

```

{
    box2 b = box2FromCenterAxe( i.strokeStartPos, max( length(i.strokePos-
i.strokeStartPos), 2 ), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = 4*b.toCenter( i.pos ) / b.size ;
    float4 col = voronoi( i, p, i.dist*0.005 ) ;

    return col ;
}

```

Charcoal dual texture



```
cfg{
    name="Charcoal dual texture";
    renderingTime = 30 ;

    samplerDefault ;
    {
        adressU = clamp;
        adressV = clamp;
    }
}

globals{
    uiTab "Texture" ;

    texture shape;
    {
        uiTab = "Texture" ;
    }
    texture splash;
    {
        uiTab = "Texture" ;
    }
}

float4 hash2( float2 p )
{
    float4 hscale = float4( .1031, 0.1059, -0.1087, -0.1029 ) ;

    float4 p4 = frac( p.xyxy * hscale ) ;
    p4 += dot(p4, p4.yzwx + 209.191349);
    return frac( float4( (p4.x + p4.y) * ( p4.z - p4.w ),
        (p4.y + p4.z) * ( p4.w - p4.x ),
        (p4.z + p4.w) * ( p4.x - p4.y ),
        (p4.w + p4.x) * ( p4.y - p4.z ) ) );
}

float4 cptSplash( float2 pos, float seed )
{
    float4 col = splash.sample( pos ) ; // first sampling

    float4 noise ;
    matrix2 b ;
    float maxmove = 0.10 ;
    float minSize = 0.795 ;
    float maxSize = 1.1 ;
    float2 texp ;

    // other sampling
    noise = hash2( float2(seed,0) ) ;
```

```

b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,1) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,2) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

return saturate( col );
}

float4 main( idatas i )
{
    float alpha = i.color.a ;

    // Get Shape
    {
        float2 pos = i.primBox.toUpperLeftNorm( i.pos ) ;
        float4 col = shape.sample( pos ) ;
        float a = col.a ;
        a = shape.isEmpty ? 1 : a ;
        alpha *= a ;
    }

    // Get Splash
    {
        float2 pos = i.primBox1.toUpperLeftNorm( i.pos ) ;
        float4 col = cptSplash( pos, i.primShapeId1+i.nbUserStroke ) ;

        float aover = i.primBox1Valid ? 1 : 0 ;
        float as = pow( i.color.a, 0.15 ) ;
        aover *= as ;

        // apply overlay blending
        alpha = blendOverlay( float4(alpha,alpha,alpha,1), float4(col.aaa,aover) ).x ;
    }

    return float4( i.color.xyz, alpha ) ;
}

```

Charcoal dual texture background overlay



```
cfg{
  name="Charcoal dual texture background overlay";
  renderingTime = 30 ;

  samplerDefault ;
  {
    adressU = clamp;
    adressV = clamp;
  }
}

globals{
  uiTab "Texture" ;

  uiTab roughness ;
  {
    row = 100 ;
  }

  uiTab stroke ;
  {
    row = 99 ;
  }

  texture shape;
  {
    id = -2 ;
    uiTab = "shape" ;
    uiName = "texture shape";
  }
  texture splash;
  {
    id = -1 ;
    uiTab = "shape" ;
    uiName = "texture splash";
  }

  sampler smplmat ;

  texture mat ;
  {
    uiTab = "roughness" ;
    uiName = "pattern" ;
  }

  float scalePattern ;
  {
    id = 100;
    uiMin = 0.25;
    uiMax = 10 ;
  }
}
```

```

        uiFormat = percent ;
        uiTab = "roughness" ;
    }
}

perPrim {

    // direction du tracé actuel
    float2 dir ;
    {
        uiEditor = angleDist ;
        raw = true ;
        uiTab = "stroke" ;
    }

    float pressure = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "pressure" ;
        uiTab = "stroke" ;
    }

    float directionality = 0.85 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "directionality" ;
        uiTab = "stroke" ;
    }
}

float4 hash2( float2 p )
{
    float4 hscale = float4( .1031, 0.1059, -0.1087, -0.1029 ) ;

    float4 p4 = frac( p.xyxy * hscale ) ;
    p4 += dot(p4, p4.yzwx + 209.191349);
    return frac( float4( (p4.x + p4.y) * ( p4.z - p4.w ),
        (p4.y + p4.z) * ( p4.w - p4.x ),
        (p4.z + p4.w) * ( p4.x - p4.y ),
        (p4.w + p4.x) * ( p4.y - p4.z ) ) ) );
}

float4 cptSplash( float2 pos, float seed )
{
    float4 col = splash.sample( pos ) ; // first sampling
    // col = 0 ;

    float4 noise ;
    matrix2 b ;
    float maxmove = 0.50 ;
    float minSize = 1. ;
    float maxSize = 4.5 ;
    float2 texp ;

    // other sampling
    noise = hash2( float2(seed,0) ) ;
}

```

```

b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,1) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,2) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,3) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

return saturate( col );
}

float surfaceHeight( float2 uv )
{
    return luminance( mat.sample( splmat, uv/scalePattern ) ) ;
}

float3 surfaceNormal( float2 pos, float h )
{
    float2 opa = 1/mat.size ;
    float2 uv = pos / mat.size ;

    // compute normal with a Sobel filter
    float s00 = surfaceHeight( uv + opa*float2(-1,-1) );
    float s10 = surfaceHeight( uv + opa*float2( 0,-1) );
    float s20 = surfaceHeight( uv + opa*float2( 1,-1) );
    float s01 = surfaceHeight( uv + opa*float2(-1, 0) );
    float s21 = surfaceHeight( uv + opa*float2( 1, 0) );
    float s02 = surfaceHeight( uv + opa*float2(-1, 1) );
    float s12 = surfaceHeight( uv + opa*float2( 0, 1) );
    float s22 = surfaceHeight( uv + opa*float2( 1, 1) );

    // Compute dx using Sobel:

```



```

//          -1 0 1
//          -2 0 2
//          -1 0 1
float dX = -s00 + s20 -2*s01 + 2*s21 -s02 + s22 ;

// Compute dy using Sobel:
//          -1 -2 -1
//           0  0  0
//           1  2  1
float dY = -s00 -2*s10 -s20 + s02 + 2*s12 + s22 ;

return normalizeSafe( float3( h*dX, h*dY, 1 ) );
}

float remap( in float a, float minv, float maxv )
{
    return saturate( (a-minv) / (maxv-minv) );
}

float cptBackMaterial( idatas i )
{
    float heightscale = 2 ;

    float2 dir = normalizeSafe( i.dir );

    float3 bn = normalizeSafe( float3(heightscale*dir,-1) );
    float3 cn = surfaceNormal( i.pos, heightscale );

    float ah = surfaceHeight( i.pos / mat.size ) ;
    float pressure = i.pressure ;
    float pmin;
    float pmax ;

    pmin = pressure < 0.5 ? (1-2*pressure) : -(pressure-0.49) ;
    pmax = pressure < 0.5 ? 1.01 : (1-2*(pressure-0.5)) ;
    ah = remap( ah, pmin, pmax );

    float a = saturate( -dot( bn, cn ) );
    a = lerp( 1-i.directionality, 1, lerp(a,1,pressure*pressure*pressure) );

    a *= ah ;
    return a ;
}

float4 main( idatas i )
{
    float alpha = i.color.a ;

    // Get Shape
    {
        float2 pos = i.primBox.toUpperLeftNorm( i.pos ) ;
        float4 col = shape.sample( pos ) ;
        float a = col.a ;
        a = shape.isEmpty ? 1 : a ;
        alpha *= a ;
    }

    // Get background
    alpha *= cptBackMaterial( i );
}

```

```

// Get Splash
{
    float2 pos = i.primBox1.toUpperLeftNorm( i.pos ) ;
    float4 col = cptSplash( pos, i.primShapeId1+i.nbUserStroke ) ;


    float aover = i.primBox1Valid ? 1 : 0 ;

    // apply overlay blending
    alpha = blendOverlay( float4(alpha,alpha,alpha,1), float4(col.aaa,aover) ).x ;
}

return float4( i.color.xyz, alpha ) ;
}

```

Charcoal dual texture background smudge



```
cfg{
  name="Charcoal dual texture background smudge";
  renderingTime = 40 ;
  blendEx = true ;
  blendDefault = replace ;
  samplingLayerMaxOffset = 64 ;

  samplerDefault ;
  {
    adressU = clamp;
    adressV = clamp;
  }
}

globals{
  uiTab "Texture" ;

  uiTab roughness ;
  {
    row = 100 ;
  }

  uiTab stroke ;
  {
    row = 99 ;
  }

  texture shape;
  {
    id = -2 ;
    uiTab = "shape" ;
    uiName = "texture shape";
  }
  texture splash;
  {
    id = -1 ;
    uiTab = "shape" ;
    uiName = "texture splash";
  }

  sampler smplmat ;

  texture mat ;
  {
    uiTab = "roughness" ;
    uiName = "pattern" ;
  }

  float scalePattern ;
  {
```

```

    id = 100;
    uiMin = 0.25;
    uiMax = 10 ;
    uiFormat = percent ;
    uiTab = "roughness" ;
}
}

perPrim {

    // direction du tracé actuel
    float2 dir ;
    {
        uiEditor = angleDist ;
        raw = true ;
        uiTab = "stroke" ;
    }

    float pressure = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "pressure" ;
        uiTab = "stroke" ;
    }

    float directionality = 0.85 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "directionality" ;
        uiTab = "stroke" ;
    }

    float load = 0.2 ;
    {
        uiMax = 1 ;
        uiFormat = percent ;
        uiTab = "color" ;
    }
}

float4 hash2( float2 p )
{
    float4 hscale = float4( .1031, 0.1059, -0.1087, -0.1029 ) ;

    float4 p4 = frac( p.xyxy * hscale ) ;
    p4 += dot(p4, p4.yzwx + 209.191349);
    return frac( float4( (p4.x + p4.y) * ( p4.z - p4.w ),
        (p4.y + p4.z) * ( p4.w - p4.x ),
        (p4.z + p4.w) * ( p4.x - p4.y ),
        (p4.w + p4.x) * ( p4.y - p4.z ) ) ) );
}

float4 cptSplash( float2 pos, float seed )
{
    float4 col = splash.sample( pos ) ; // first sampling
    // col = 0 ;

```

```

float4 noise ;
matrix2 b ;
float maxmove = 0.50 ;
float minSize = 1. ;
float maxSize = 4.5 ;
float2 texp ;

// other sampling
noise = hash2( float2(seed,0) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,1) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,2) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,3) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

return saturate( col );
}

float surfaceHeight( float2 uv )
{
    return luminance( mat.sample( splmat, uv/scalePattern ) ) ;
}

float3 surfaceNormal( float2 pos, float h )
{
    float2 opa = 1/mat.size ;
    float2 uv = pos / mat.size ;

    // compute normal with a Sobel filter

```

```

float s00 = surfaceHeight( uv + opa*float2(-1,-1) );
float s10 = surfaceHeight( uv + opa*float2( 0,-1) );
float s20 = surfaceHeight( uv + opa*float2( 1,-1) );
float s01 = surfaceHeight( uv + opa*float2(-1, 0) );
float s21 = surfaceHeight( uv + opa*float2( 1, 0) );
float s02 = surfaceHeight( uv + opa*float2(-1, 1) );
float s12 = surfaceHeight( uv + opa*float2( 0, 1) );
float s22 = surfaceHeight( uv + opa*float2( 1, 1) );

// Compute dx using Sobel:
//          -1 0 1
//          -2 0 2
//          -1 0 1
float dX = -s00 + s20 -2*s01 + 2*s21 -s02 + s22 ;

// Compute dy using Sobel:
//          -1 -2 -1
//           0  0  0
//           1  2  1
float dY = -s00 -2*s10 -s20 + s02 + 2*s12 + s22 ;

return normalizeSafe( float3( h*dX, h*dY, 1 ) );
}

float remap( in float a, float minv, float maxv )
{
    return saturate( (a-minv) / (maxv-minv) );
}

float cptBackMaterial( idatas i )
{
    float heightscale = 2 ;

    float2 dir = normalizeSafe( i.dir );

    float3 bn = normalizeSafe( float3(heightscale*dir,-1) );
    float3 cn = surfaceNormal( i.pos, heightscale );

    float ah = surfaceHeight( i.pos / mat.size ) ;
    float pressure = i.pressure ;
    float pmin;
    float pmax ;

    pmin = pressure < 0.5 ? (1-2*pressure) : -(pressure-0.49) ;
    pmax = pressure < 0.5 ? 1.01 : (1-2*(pressure-0.5)) ;
    ah = remap( ah, pmin, pmax );

    float a = saturate( -dot( bn, cn ) );
    a = lerp( 1-i.directionality, 1, lerp(a,1,pressure*pressure*pressure) );

    a *= ah ;
    return a ;
}

float4 Smudge( idatas i, float power )
{
    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    // compute displacement from the current position

```

```

float2 dir = i.strokePrecedPos - i.strokePos ;
dir *= power;
float mdisplace = length( dir ) ;

// Get the displaced color
float4 smpl = bottomLayer.pointSample( i, i.pos + dir );

return smpl ;
}

float4 main( idatas i )
{
    float alpha = i.color.a ;

    // Get Shape
    {
        float2 pos = i.primBox.toUpperLeftNorm( i.pos ) ;
        float4 col = shape.sample( pos ) ;
        float a = col.a ;
        a = shape.isEmpty ? 1 : a ;
        alpha *= a ;
    }

    // Get background
    alpha *= cptBackMaterial( i );

    // Get Splash
    {
        float2 pos = i.primBox1.toUpperLeftNorm( i.pos ) ;
        float4 col = cptSplash( pos, i.primShapeId1+i.nbUserStroke ) ;

        float aover = i.primBox1Valid ? 1 : 0 ;

        // apply overlay blending
        alpha = blendOverlay( float4(alpha,alpha,alpha,1), float4(col.aaa,aover) ).x ;
    }


    // final color blending
    float4 colS = Smudge( i, alpha ) ;
    float4 colI = float4( i.color.xyz, alpha*i.load ) ;
    float4 col = blendNormal( colS, colI );

    // take care of the eraser state
    col = i.eraser ? float4( colS.xyz, colS.w * (1-colI.w) ) : col ;

    return col ;
    //return float4( i.color.xyz, alpha ) ;
}

```

Charcoal dual texture multiply



```
cfg{
    name="Charcoal dual texture multiply";
    renderingTime = 30 ;

    samplerDefault ;
    {
        adressU = clamp;
        adressV = clamp;
    }
}

globals{
    uiTab "Texture" ;

    uiTab roughness ;
    {
        row = 100 ;
    }

    uiTab stroke ;
    {
        row = 99 ;
    }

    texture shape;
    {
        id = -2 ;
        uiTab = "shape" ;
        uiName = "texture shape";
    }
    texture splash;
    {
        id = -1 ;
        uiTab = "shape" ;
        uiName = "texture splash";
    }

    sampler smplmat ;

    texture mat ;
    {
        uiTab = "roughness" ;
        uiName = "pattern" ;
    }

    float scalePattern ;
    {
        id = 100;
        uiMin = 0.25;
        uiMax = 10 ;
    }
}
```



```

        uiFormat = percent ;
        uiTab = "roughness" ;
    }
}

perPrim {

    float pressure = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "pressure" ;
        uiTab = "stroke" ;
    }

    float directionality = 0.85 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "directionality" ;
        uiTab = "stroke" ;
    }

    float2 dir ;
    {
        uiEditor = angleDist ;
        raw = true ;
        uiTab = "stroke" ;
    }
}

float4 hash2( float2 p )
{
    float4 hscale = float4( .1031, 0.1059, -0.1087, -0.1029 ) ;

    float4 p4 = frac( p.xyxy * hscale ) ;
    p4 += dot(p4, p4.yzwx + 209.191349);
    return frac( float4( (p4.x + p4.y) * ( p4.z - p4.w ),
        (p4.y + p4.z) * ( p4.w - p4.x ),
        (p4.z + p4.w) * ( p4.x - p4.y ),
        (p4.w + p4.x) * ( p4.y - p4.z ) ) ) );
}

float4 cptSplash( float2 pos, float seed )
{
    float4 col = splash.sample( pos ) ; // first sampling

    float4 noise ;
    matrix2 b ;
    float maxmove = 0.40 ;
    float minSize = 0.5 ;
    float maxSize = 4.5 ;
    float2 texp ;

    // other sampling
    noise = hash2( float2(seed,0) ) ;
    b = matrix2FromPRS( maxmove*(noise.xy*2-1),

```

```

        TWOPI*noise.w,
        lerp( minSize, maxSize, noise.z ) ) ;

    texp = b.transform( pos-0.5 )+0.5;
    col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,1) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
        TWOPI*noise.w,
        lerp( minSize, maxSize, noise.z ) ) ;

    texp = b.transform( pos-0.5 )+0.5;
    col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,2) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
        TWOPI*noise.w,
        lerp( minSize, maxSize, noise.z ) ) ;

    texp = b.transform( pos-0.5 )+0.5;
    col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,3) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
        TWOPI*noise.w,
        lerp( minSize, maxSize, noise.z ) ) ;

    texp = b.transform( pos-0.5 )+0.5;
    col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,4) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
        TWOPI*noise.w,
        lerp( minSize, maxSize, noise.z ) ) ;

    texp = b.transform( pos-0.5 )+0.5;
    col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,5) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
        TWOPI*noise.w,
        lerp( minSize, maxSize, noise.z ) ) ;

    texp = b.transform( pos-0.5 )+0.5;
    col += splash.sample( texp ) ;

    return saturate( col );
}

float surfaceHeight( float2 uv )
{
    return luminance( mat.sample( splmat, uv/scalePattern ) ) ;
}

```

```

float3 surfaceNormal( float2 pos, float h )
{
    float2 opa = 1/mat.size ;
    float2 uv = pos / mat.size ;

    // compute normal with a Sobel filter
    float s00 = surfaceHeight( uv + opa*float2(-1,-1) );
    float s10 = surfaceHeight( uv + opa*float2( 0,-1) );
    float s20 = surfaceHeight( uv + opa*float2( 1,-1) );
    float s01 = surfaceHeight( uv + opa*float2(-1, 0) );
    float s21 = surfaceHeight( uv + opa*float2( 1, 0) );
    float s02 = surfaceHeight( uv + opa*float2(-1, 1) );
    float s12 = surfaceHeight( uv + opa*float2( 0, 1) );
    float s22 = surfaceHeight( uv + opa*float2( 1, 1) );

    // Compute dx using Sobel:
    //      -1 0 1
    //      -2 0 2
    //      -1 0 1
    float dX = -s00 + s20 -2*s01 + 2*s21 -s02 + s22 ;

    // Compute dy using Sobel:
    //      -1 -2 -1
    //      0  0  0
    //      1  2  1
    float dY = -s00 -2*s10 -s20 + s02 + 2*s12 + s22 ;

    return normalizeSafe( float3( h*dX, h*dY, 1 ) );
}

float remap( in float a, float minv, float maxv )
{
    return saturate( (a-minv) / (maxv-minv) );
}

float cptBackMaterial( idatas i )
{
    float heightscale = 2 ;

    float2 dir = normalizeSafe( i.dir );

    float3 bn = normalizeSafe( float3(heightscale*dir,-1) );
    float3 cn = surfaceNormal( i.pos, heightscale );

    float ah = surfaceHeight( i.pos / mat.size ) ;
    float pressure = i.pressure ;
    float pmin;
    float pmax ;

    pmin = pressure < 0.5 ? (1-2*pressure) : -(pressure-0.49) ;
    pmax = pressure < 0.5 ? 1.01 : (1-2*(pressure-0.5)) ;
    ah = remap( ah, pmin, pmax );

    float a = saturate( -dot( bn, cn ) );
    a = lerp( 1-i.directionality, 1, lerp(a,1,pressure*pressure*pressure) );

    a *= ah ;
    return a ;
}

```

```

float4 main( idatas i )
{
    float alpha = i.color.a ;

    // Get Shape
    {
        float2 pos = i.primBox.toUpperLeftNorm( i.pos ) ;
        float4 col = shape.sample( pos ) ;
        float a = col.a ;
        a = shape.isEmpty ? 1 : a ;
        alpha *= a ;
    }

    // Get background
    alpha *= cptBackMaterial( i );


    // Get Splash
    {
        float2 pos = i.primBox1.toUpperLeftNorm( i.pos ) ;
        float4 col = cptSplash( pos, i.primShapeId1+i.nbUserStroke ) ;

        alpha *= col.a ;
    }

    return float4( i.color.xyz, alpha ) ;
}

```

gradient angular



```
cfg{
    name = "gradient angular" ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
    uiTab CenterHide;
    {
        row = 3 ;
    }
}

perPrim{
    float opacity=1;
    {
        uiMax = 1 ;
        uiTab = "color" ;
        uiFormat = percent ;
        id = 0 ;
    }
    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
    float noiseScale=1;
    {
        uiMax = 1 ;
        uiName = "Scale";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
    float chide=0.06;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "CenterHide" ;
        uiFormat = percent ;
    }
    float cpos=0;
    {
        uiMax = 1 ;
        uiName = "Pos";
        uiTab = "CenterHide" ;
    }
}
```

```

        uiFormat = percent ;
    }
    float rotation=0;
    {
        uiMax = 1 ;
        uiName = "Rotation";
        uiTab = "Color" ;
        uiFormat = percent ;
    }
}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return frac( (p3.x + p3.y) * p3.z );
}

float noise( float3 x )
{
    return hash( floor(x) );
}

float4 main( idatas i )
{
    box2 b = box2FromCenterAxe( i.strokeStartPos, length(i.strokePos-
i.strokeStartPos), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = b.toCenter( i.pos ) ;
    float spp = mod( toSpherical( p ), TWOPI ) / TWOPI;

    // compute noise value
    float2 npos = i.noiseScale*i.pos ;
    float nv = 0.2*i.noisePower*(1-2*noise( float3(npos,i.nbUserStroke+i.dist*0.001)
));

    // hide centre discontinuity
    float l = length( i.strokeStartPos - i.pos ) ;
    float cphide = 1/(i.chide*500 + 1) ;
    float acenter = exp( -cphide*l );
    float4 ccenter = grad.sample( frac(saturate(i.cpos+nv)) );

    float4 col = grad.sample( frac(spp+nv+i.rotation) ) ;

    col = lerp( col, ccenter, acenter );

    col.a *= i.opacity ;

    return col ;
}

```

gradient linear



```
cfg{
    name = "gradient linear" ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
}

perPrim{
    float opacity=1;
    {
        uiMax = 1 ;
        uiTab = "color" ;
        uiFormat = percent ;
        id = 0 ;
    }
    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
    float noiseScale=1;
    {
        uiMax = 1 ;
        uiName = "Scale";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return frac( (p3.x + p3.y) * p3.z );
}

float noise( float3 x )
{
    return hash( floor(x) );
}
```

```

float4 main( idatas i )
{
    float2 dir = normalizeSafe( i.strokePos - i.strokeStartPos ) ;
    float l = length( i.strokeStartPos - i.strokePos );
    plane2 p = plane2FromNormPos( dir, i.strokeStartPos );
    plane2 p1 = plane2FromNormPos( perpendicular(dir), i.strokeStartPos );

    // compute noise value
    float2 npos = i.noiseScale*float2( p.getDistance(i.pos), p1.getDistance(i.pos) )
;
    float nv = i.noisePower*(1-2*noise( float3(npos,i.nbUserStroke+i.dist*0.001) ));

    float d = saturate( 0.2*nv + p.getDistance( i.pos ) / l );
    float4 col = grad.sample( d ) ;
    col.a *= i.opacity ;

    // output something only if with have more than 1 pixel to compute the plane
    col.a = (l>1) ? col.a : 0 ;

    return col ;
}

```


hardness ctrl



```
cfg{name="hardness ctrl";}

perPrim {
    float hardness = 0.5 ;
    {
        id = 1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ; // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );
```

```
float att = cptHardness( d, i.hardness, i.innerSize );
att = i.primDistanceValid ? att : 1 ;

float alpha = saturate(i.color.a*att) ;
float3 col = i.color.xyz ;

return float4( col, alpha ) ;
}
```

Hardness dither ctrl



```
cfg{
    name="Hardness dither ctrl";
    renderingTime = 20 ;
}

perPrim {
    float hardness = 0.5 ;
    {
        id = -1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }
    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ; // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
```

```

{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 9.191349);
    return frac((p3.x + p3.y) * p3.z) ;
}

// return noise value [-1,1]
float noise( float3 x )
{
    return 2*hash( floor(x) )-1;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // compute pure attenuation
    float att = cptHardness( d, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    // compute noise value
    float2 npos = i.pos ;
    float nv = (1-i.hardness)*(1-att)*i.noisePower*0.2*noise(
float3(npos,i.nbUserStroke+i.dist*0.0001) );
    float dn = saturate( d + nv );

    // compute perturbed attenuation
    float attn = cptHardness( dn, i.hardness, i.innerSize );
    attn = i.primDistanceValid ? attn : 1 ;

    float alpha = saturate(i.color.a*attn) ;
    float3 col = i.color.xyz ;

    return float4( col, alpha ) ;
}

```

hardness noise blobby ctrl



```
cfg{
  name="hardness noise blobby ctrl";
  renderingTime = 30 ;
}
```

```
perPrim {
  float hardness = 0.5 ;
  {
    id = -1 ;
    uiMin = 0 ;
    uiMax = 1 ;
    uiTab = "shape" ;
    uiFormat = percent ;
    uiName = "hardness" ;
  }
  float innerSize = 0.5 ;
  {
    id = 3 ;
    uiMin = 0 ;
    uiMax = 1 ;
    uiTab = "shape" ;
    uiFormat = percent ;
  }
  float noisePower=0.1;
  {
    uiMax = 1 ;
    uiName = "Power";
    uiTab = "Noise" ;
    uiFormat = percent ;
  }
  float noiseScale=1;
  {
    uiMin = 0.25 ;
    uiMax = 5 ;
    uiName = "Scale";
    uiTab = "Noise" ;
    uiFormat = percent ;
  }
  float ndensity = 0.5 ;
  {
    uiTab = "Noise" ;
    uiName = "Density" ;
    uiFormat = percent ;
    uiMax = 1 ;
  }
}
```

```
// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
```

```

{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
    size
    float d = max( -i.primDistance, 0 ) / sm ;    // compute normalized current
    distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
                             (p3.z + p3.y) * p3.x,
                             (p3.x + p3.z) * p3.y ) );
}

float3 adjustDensity( float3 rs, float d )
{
    float3 r = abs(rs);
    d = 1-d ;
    float3 a = clamp( (d-0.5)*2, 0, 1 );
    float3 b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001) ;
    r = saturate( r );

    return rs < 0 ? -r : r ;
}

float3 hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [0,1]
float noise( float3 x, float d )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hashD(p+float3(0,0,0),d), f-float3(0,0,0) ),
                             dot( hashD(p+float3(1,0,0),d), f-float3(1,0,0) ),

```

```

        dot( hashD(p+float3(0,1,0),d), f-float3(0,1,0) ), dot(
hashD(p+float3(1,1,0),d), f-float3(1,1,0) ), u.xy ) ;

    float v2 = bilinearLerp( dot( hashD(p+float3(0,0,1),d), f-float3(0,0,1) ),
dot( hashD(p+float3(1,0,1),d), f-float3(1,0,1) ),
        dot( hashD(p+float3(0,1,1),d), f-float3(0,1,1) ), dot(
hashD(p+float3(1,1,1),d), f-float3(1,1,1) ), u.xy ) ;

    float ret = lerp( v1, v2, u.z )/0.707; // normalize with the maxiumm slope
    return abs(ret);
}

// return a noise value between [-1,1]
float noiseFunction( float3 x, float d )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float ret = 0.5 * noise( x, d ) ; x = 2*m.transform(x);
    ret += 0.25 * noise(x, d); x = 2*m.transform(x);
    ret += 0.125 * noise(x, d); x = 2*m.transform(x);
    ret += 0.0625 * noise(x, d); x = 2*m.transform(x);
    return ret*2-1 ;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // compute noised distance
    float2 npos = toDrawSpace(i.pos)*.1/i.noiseScale ;
    float dn = d + i.noisePower*noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.0001), i.ndensity ) ;

    // compute attenuation

    float att = cptHardness( dn, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    float alpha = saturate(i.color.a*att) ;
    float3 col = i.color.xyz ;

    return float4( col, alpha ) ;
}

```

Hardness noise ctrl



```
cfg{
    name="Hardness noise ctrl";
    renderingTime = 30 ;
}
```

```
perPrim {
    float hardness = 0.5 ;
    {
        id = -1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }
    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float noiseScale=1;
    {
        uiMin = 0.25 ;
        uiMax = 5 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float ndensity = 0.5 ;
    {
        uiTab = "Noise" ;
        uiName = "Density" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }
}
```

```
// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
```



```

    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ;    // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

float3 adjustDensity( float3 rs, float d )
{
    float3 r = abs(rs);
    d = 1-d ;
    float3 a = clamp( (d-0.5)*2, 0, 1 );
    float3 b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001) ;
    r = saturate( r );

    return rs < 0 ? -r : r ;
}

float3 hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [0,1]
float noise( float3 x, float d )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hashD(p+float3(0,0,0),d), f-float3(0,0,0) ),
dot( hashD(p+float3(1,0,0),d), f-float3(1,0,0) ),
        dot( hashD(p+float3(0,1,0),d), f-float3(0,1,0) ), dot(
hashD(p+float3(1,1,0),d), f-float3(1,1,0) ), u.xy ) ;

```

```

float v2 = bilinearLerp( dot( hashD(p+float3(0,0,1),d), f-float3(0,0,1) ),
dot( hashD(p+float3(1,0,1),d), f-float3(1,0,1) ),
dot( hashD(p+float3(0,1,1),d), f-float3(0,1,1) ), dot(
hashD(p+float3(1,1,1),d), f-float3(1,1,1) ), u.xy ) ;

float ret = lerp( v1, v2, u.z )/0.707; // normalize with the maximum slope
return 0.5*ret+0.5;
}

// return a noise value between [-1,1]
float noiseFunction( float3 x, float d )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float ret = 0.5 * noise( x, d ) ; x = 2*m.transform(x);
    ret += 0.25 * noise(x, d); x = 2*m.transform(x);
    ret += 0.125 * noise(x, d); x = 2*m.transform(x);
    ret += 0.0625 * noise(x, d); x = 2*m.transform(x);
    return ret*2-1 ;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // compute noised distance
    float2 npos = toDrawSpace(i.pos)*.1/i.noiseScale ;
    float dn = d + i.noisePower*noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.0001), i.ndensity ) ;

    // compute attenuation

    float att = cptHardness( dn, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    float alpha = saturate(i.color.a*att) ;
    float3 col = i.color.xyz ;

    return float4( col, alpha ) ;
}

```

ink droplets



```
cfg{
    name="ink droplets";
    renderingTime = 30 ;
}

globals{
    float4 colA = 1 ;
    float4 colB = float4(0,0,0,1);
}

perPrim {
    float density = 0.5 ;
    {
        id = -1 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "density" ;
    }
    float hardness = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
        uiName = "hardness" ;
    }
}

float2 hash1( float3 p)
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return frac( float2( (p3.x + p3.y) * p3.z,
        (p3.x + p3.z) * p3.x ) ) ;
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
    p3 += dot(p3, p3.yzx+19.19) ;
    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y ) );
}

float voronoi( idatas i, float2 uv, float time )
```

```

{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    float seed = i.nbUserStroke ;

    //-----
    // regular voronoi
    //-----
    float ret = 0 ;
    for( int j=-3; j<=3; j++ )
    {
        for( int i=-3; i<=3; i++ )
        {
            float2 g = float2( i, j );

            float2 ipos = n + g ;

            float2 datas = hash1( float3(ipos,seed) );
            float att = lerp( 2.5, 10, pow(datas.x,1.5) );
            float move = lerp(0,1,datas.y );

            float2 o = hash2( ipos+seed );
            o = sin( time + 6.2831*o ); // animate the position

            float2 r = g + o - f;
            float d = dot(r,r);
            d = sqrt( d );

            ret += exp( -att*d ) ; // accumulate density
        }
    }

    return ret ;
}

float4 main( idatas i )
{
    box2 b = box2FromCenterAxe( i.strokeStartPos, max( length(i.strokePos-
i.strokeStartPos), 2 ), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = 4*b.toCenter( i.pos ) / b.size ;
    float density = voronoi( i, p, i.dist*0.02 ) ;

    // density = abs(density - 0.3) ;
    // density = frac( min( density*4, 40 ) );

    float cut = 1-i.density;


    float hscale = max( (1-cut) * (1-i.hardness), 0.001 );
    float smoothPos = density - cut ;
    smoothPos = saturate( smoothPos / hscale );

    // float4 col = density > (1-i.density) ? colA : colB ;
    float4 col = smoothLerp( colA, colB, smoothPos );

    return col ;
}

```

Perlin blobby noise



```
cfg{
    name = "Perlin blobby noise" ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
}

perPrim{
    float noiseScale=1;
    {
        uiMin = 0.5 ;
        uiMax = 10 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [0,1]
float noise( float3 x )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hash(p+float3(0,0,0)), f-float3(0,0,0) ), dot(
    hash(p+float3(1,0,0)), f-float3(1,0,0) ),
        dot( hash(p+float3(0,1,0)), f-float3(0,1,0) ), dot(
    hash(p+float3(1,1,0)), f-float3(1,1,0) ), u.xy ) ;

    float v2 = bilinearLerp( dot( hash(p+float3(0,0,1)), f-float3(0,0,1) ), dot(
    hash(p+float3(1,0,1)), f-float3(1,0,1) ),
```

```

        dot( hash(p+float3(0,1,1)), f-float3(0,1,1) ), dot(
hash(p+float3(1,1,1)), f-float3(1,1,1) ), u.xy ) ;

    float ret = lerp( v1, v2, u.z )/0.707; // normalize with the maximum slope
    return abs(ret);
}

// return a noise value between [0,1]
float noiseFunction( float3 x )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float ret = 0.5 * noise( x ) ; x = 2*m.transform(x);
    ret += 0.25 * noise(x); x = 2*m.transform(x);
    ret += 0.125 * noise(x); x = 2*m.transform(x);
    ret += 0.0625 * noise(x); x = 2*m.transform(x);
    return ret ;
}

float2 cpt2DPosFromMouse( idatas i )
{
    float2 dir = normalizeSafe( i.strokePos - i.strokeStartPos ) ;
    float l = max( length( i.strokeStartPos - i.strokePos ), 1 );
    plane2 p = plane2FromNormPos( dir, i.strokeStartPos );
    plane2 p1 = plane2FromNormPos( perpendicular(dir), i.strokeStartPos );

    return 15*float2( p.getDistance(i.pos), p1.getDistance(i.pos) )/l ;
}


float4 main( idatas i )
{
    // compute noise value
    float2 npos = 1/i.noiseScale*cpt2DPosFromMouse( i ) ;
    float nv = noiseFunction( float3(npos,i.nbUserStroke+i.dist*0.01) );

    float4 col = grad.sample(nv) ;

    return col ;
}

```

Perlin blobby noise_01



```
cfg{
    name = "Perlin blobby noise" ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
}

perPrim{
    float noiseScale=1;
    {
        uiMin = 0.5 ;
        uiMax = 10 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [0,1]
float noise( float3 x )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hash(p+float3(0,0,0)), f-float3(0,0,0) ), dot(
    hash(p+float3(1,0,0)), f-float3(1,0,0) ),
        dot( hash(p+float3(0,1,0)), f-float3(0,1,0) ), dot(
    hash(p+float3(1,1,0)), f-float3(1,1,0) ), u.xy ) ;
}
```

```

float v2 = bilinearLerp( dot( hash(p+float3(0,0,1)), f-float3(0,0,1) ), dot(
hash(p+float3(1,0,1)), f-float3(1,0,1) ),
dot( hash(p+float3(0,1,1)), f-float3(0,1,1) ), dot(
hash(p+float3(1,1,1)), f-float3(1,1,1) ), u.xy ) ;

float ret = lerp( v1, v2, u.z )/0.707; // normalize with the maximum slope
return abs(ret);
}

// return a noise value between [0,1]
float noiseFunction( float3 x )
{
matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
float ret = 0.5 * noise( x ) ; x = 2*m.transform(x);
ret += 0.25 * noise(x); x = 2*m.transform(x);
ret += 0.125 * noise(x); x = 2*m.transform(x);
ret += 0.0625 * noise(x); x = 2*m.transform(x);
return ret ;
}

float2 cpt2DPosFromMouse( idatas i )
{
float2 dir = normalizeSafe( i.strokePos - i.strokeStartPos ) ;
float l = max( length( i.strokeStartPos - i.strokePos ), 1 );
plane2 p = plane2FromNormPos( dir, i.strokeStartPos );
plane2 p1 = plane2FromNormPos( perpendicular(dir), i.strokeStartPos );

return 15*float2( p.getDistance(i.pos), p1.getDistance(i.pos) )/l ;
}

float4 main( idatas i )
{
// compute noise value
float2 npos = 1/i.noiseScale*cpt2DPosFromMouse( i ) ;
float nv = noiseFunction( float3(npos,i.nbUserStroke+i.dist*0.01) );

float4 col = grad.sample(nv) ;

return col ;
}

```


Perlin noise (error)



```
cfg{
    name = "Perlin noise" ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
    uiTab Dithering ;
    {
        row = 2 ;
    }
}

perPrim{
    float opacity=1;
    {
        uiMax = 1 ;
        uiTab = "color" ;
        uiFormat = percent ;
        id = 0 ;
    }
    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float noiseScale=1;
    {
        uiMax = 1 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float ditherPower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
    float ditherScale=1;
    {
        uiMax = 1 ;
        uiName = "Scale";
        uiTab = "Dithering" ;
    }
}
```

```

        uiFormat = percent ;
    }
}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return frac( (p3.x + p3.y) * p3.z );
}

float noise( float3 x )
{
    float3 f ;
    float3 p = decompose( x, f );
    f = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( hash(p+float3(0,0,0)), hash(p+float3(1,0,0)),
        hash(p+float3(0,1,0)), hash(p+float3(1,1,0)), f.xy );

    float v2 = bilinearLerp( hash(p+float3(0,0,1)), hash(p+float3(1,0,1)),
        hash(p+float3(0,1,1)), hash(p+float3(1,1,1)), f.xy );

    return lerp( v1, v2, f.z );
}

float noiseFunction( float3 x )
{
    return 0.5 * noise( x ) +
        0.25 * noise( x*2.02 ) +
        0.125 * noise( x*4.509 ) +
        0.0625* noise( x*8.1580 ) ;
}

float4 main( idatas i )
{
    float2 dir = normalizeSafe( i.strokePos - i.strokeStartPos ) ;
    float l = length( i.strokeStartPos - i.strokePos );
    plane2 p = plane2FromNormPos( dir, i.strokeStartPos );
    plane2 p1 = plane2FromNormPos( perpendicular(dir), i.strokeStartPos );

    // compute noise value
    float2 npos = i.noiseScale*20*float2( p.getDistance(i.pos),
p1.getDistance(i.pos) )/l ;
    float nv = i.noisePower*0.5*(1-2*noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.003) ));

    // compute dithering
    float2 nposDither = i.ditherScale*float2( p.getDistance(i.pos),
p1.getDistance(i.pos) ) ;
    float nvDither = i.ditherPower*(1-2*noiseDither(
float3(nposDither,i.nbUserStroke) ));

ERROR: Undeclared identifier 'noiseDither'

    float d = saturate( nvDither + nv + p.getDistance( i.pos ) / l );
    float4 col = grad.sample( d );
    col.a *= i.opacity ;
}

```

```
// output something only if with have more than 1 pixel to compute the plane
col.a = (l>1) ? col.a : 0 ;

return col ;
}
```

Perlin noise scatter



```
cfg{
    name = "Perlin noise scatter" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 64 ;
    renderingTime = 30 ;
}

globals{
    uiTab Noise ;
    {
        row = 3;
        id = 1;
    }
}

perPrim{
    float noiseScale=1;
    {
        uiMin = 0.01 ;
        uiMax = 2 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float scatterPower=0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
                            (p3.z + p3.y) * p3.x,
                            (p3.x + p3.z) * p3.y ) );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [-1,1]
float noise( float3 x )
{

```

```

float3 f = frac(x);
float3 p = decompose( x, f );
float3 u = f*f*(3.0-2.0*f);

float v1 = bilinearLerp( dot( hash(p+float3(0,0,0)), f-float3(0,0,0) ), dot(
hash(p+float3(1,0,0)), f-float3(1,0,0) ),
dot( hash(p+float3(0,1,0)), f-float3(0,1,0) ), dot(
hash(p+float3(1,1,0)), f-float3(1,1,0) ), u.xy );

float v2 = bilinearLerp( dot( hash(p+float3(0,0,1)), f-float3(0,0,1) ), dot(
hash(p+float3(1,0,1)), f-float3(1,0,1) ),
dot( hash(p+float3(0,1,1)), f-float3(0,1,1) ), dot(
hash(p+float3(1,1,1)), f-float3(1,1,1) ), u.xy );

return lerp( v1, v2, u.z )/0.707; // normalize with the maxiumm slope
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is 2D vector between [-1,1]
float2 noise2( float3 x )
{
return float2( noise(x), noise(-x.yzx+float3(10.321,10.8798,11.9842)) ) ;
}

// return a noise value between [-1,1]
float2 noiseFunction( float3 x )
{
matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
float2 ret = 0.5 * noise2( x ) ; x = 2*m.transform(x);
ret += 0.25 * noise2(x); x = 2*m.transform(x);
ret += 0.125 * noise2(x); x = 2*m.transform(x);
ret += 0.0625 * noise2(x); x = 2*m.transform(x);
return ret ;
}

float2 cpt2DPosFromMouse( idatas i )
{
float2 dir = normalizeSafe( i.strokePos - i.strokeStartPos ) ;
float l = max( length( i.strokeStartPos - i.strokePos ), 1 );
plane2 p = plane2FromNormPos( dir, i.strokeStartPos );
plane2 p1 = plane2FromNormPos( perpendicular(dir), i.strokeStartPos );

return 15*float2( p.getDistance(i.pos), p1.getDistance(i.pos) )/l ;
}

float4 main( idatas i )
{
// get the current background color
float4 colBack = bottomLayer.pointSample( i, i.pos );

// compute noise value
float2 npos = 1/i.noiseScale*cpt2DPosFromMouse( i ) ;
float2 nv = noiseFunction( float3(npos,i.nbUserStroke+i.dist*0.001) );

// compute the current pixel displacement
float mdisplace = i.scatterPower * samplingLayerMaxOffset;
float2 offset = nv*mdisplace ;

// Get the displaced color
float4 smpl = bottomLayer.bilinearSample( i, i.pos + offset );

```

```
    smpl = smoothLerp( colBack, smpl, saturate( mdisplace ) ); // reset to a
pointSampling for little displacement

    float4 col = smpl ;
    col.xy = smpl ;

    return col ;
}
```

Perlin sin noise



```
cfg{
    name = "Perlin sin noise" ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
}

perPrim{
    float noiseScale=1;
    {
        uiMin = 0.5 ;
        uiMax = 10 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float turbScale=0.5;
    {
        uiMax = 1 ;
        uiName = "Turbulence";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float freq=0.5;
    {
        uiMax = 4 ;
        uiName = "Freq";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [0,1]
```

```

float noise( float3 x )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hash(p+float3(0,0,0)), f-float3(0,0,0) ), dot(
hash(p+float3(1,0,0)), f-float3(1,0,0) ),
dot( hash(p+float3(0,1,0)), f-float3(0,1,0) ), dot(
hash(p+float3(1,1,0)), f-float3(1,1,0) ), u.xy ) ;

    float v2 = bilinearLerp( dot( hash(p+float3(0,0,1)), f-float3(0,0,1) ), dot(
hash(p+float3(1,0,1)), f-float3(1,0,1) ),
dot( hash(p+float3(0,1,1)), f-float3(0,1,1) ), dot(
hash(p+float3(1,1,1)), f-float3(1,1,1) ), u.xy ) ;

    float ret = lerp( v1, v2, u.z )/0.707; // normalize with the maxiumm slope
    return abs(ret);
}

// return a noise value between [0,1]
float noiseFunction( float3 x )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float ret = 0.5 * noise( x ) ; x = 2*m.transform(x);
    ret += 0.25 * noise(x); x = 2*m.transform(x);
    ret += 0.125 * noise(x); x = 2*m.transform(x);
    ret += 0.0625 * noise(x); x = 2*m.transform(x);
    return ret ;
}

float2 cpt2DPosFromMouse( idatas i )
{
    float2 dir = normalizeSafe( i.strokePos - i.strokeStartPos ) ;
    float l = max( length( i.strokeStartPos - i.strokePos ), 1 );
    plane2 p = plane2FromNormPos( dir, i.strokeStartPos );
    plane2 p1 = plane2FromNormPos( perpendicular(dir), i.strokeStartPos );

    return 15*float2( p.getDistance(i.pos), p1.getDistance(i.pos) )/l ;
}

float4 main( idatas i )
{
    // compute noise value
    float2 npos = 1/i.noiseScale*cpt2DPosFromMouse( i ) ;
    float nv = 0.5+0.5*sin( npos.x*i.freq + TWOPI*i.turbScale*noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.01) ) );

    float4 col = grad.sample(nv) ;

    return col ;
}

```


pointShadow



```
cfg{name="pointShadow";}
```

```
perPrim {  
  
    float size = 0.5 ;  
    {  
        uiMin = 0          ;  
        uiMax = 1          ;  
        uiTab = "shape"      ;  
        uiFormat = percent  ;  
        uiName = "inner size" ;  
    }  
  
    float hardness = 0.5 ;  
    {  
        uiMin = 0          ;  
        uiMax = 1          ;  
        uiTab = "shape"      ;  
        uiFormat = percent  ;  
    }  
  
    float salpha = 0.275 ;  
    {  
        uiMin = 0          ;  
        uiMax = 1          ;  
        uiTab = "shadow"    ;  
        uiFormat = percent  ;  
    }  
  
    float ssize = 0.39 ;  
    {  
        uiMin = 0          ;  
        uiMax = 1          ;  
        uiTab = "shadow"    ;  
        uiFormat = percent  ;  
    }  
  
    float shardness = 0.45 ;  
    {  
        uiMin = 0          ;  
        uiMax = 1          ;  
        uiTab = "shadow"    ;  
        uiFormat = percent  ;  
        uiName = "hardness" ;  
    }  
  
    float2 soffset = float2(-0.8,0.13) ;  
    {  
        uiTab = "shadow"      ;  
        uiName = "offset 2D"  ;  
    }  
}
```

```

    uiEditor = graph      ;
    uiYAxisInvert = true  ;
    power = 1             ;
}

}

float cirIceGauss( float2 p, float r, float hardness )
{
    float d = max( -(length( p ) - r), 0 );
    // return d;

    float softness = pow( 1 - hardness,2) ; // permet de donner un feedback plus
    lineaire sur ce paramètre
    d /= r*softness + 0.0001                ; // normalise la distance en fct de la taille
    de la primitive

    return 1 - exp( -d ); // courbe d'atténuation en fct de la distance
}

float4 main( idatas i )
{
    float2 uv = i.primBox.toUpperLeftNorm( i.pos ) * 2 - 1 ;

    float shadow = i.salpha * i.color.a * cirIceGauss( uv - i.soffset,
i.size*(1+i.ssize), i.hardness * i.shardness );
    float4 colShadow = float4(0,0,0,shadow );

    float calpha = cirIceGauss( uv, i.size, i.hardness );
    float4 col = i.color ;
    col *= calpha ;

    col = blendNormal( colShadow, col );

    return col ;
}

```

prim texture alpha invy



```
cfg{
  name="prim texture alpha invy";
  renderingTime = 20 ;
  samplerDefault ;
  {
    adressU = clamp;
    adressV = clamp;
  }
}

globals{
  texture mat;
  {
    uiTab = "Texture" ;
  }
}

float4 main( idatas i )
{
  float2 p = i.primBox.toUpperLeftNorm( i.pos ) ;

  // compute alpha from the Luminance of a Texture
  float4 cmat = mat.sample( float2( p.x, 1-p.y) ) ;
  cmat = mat.isEmpty ? 1 : cmat ;

  float alphaTex = cmat.a ;

  float4 col = i.color ;
  col.a *= alphaTex ;

  return col ;
}
```

prim texture alpha Luminance



```
cfg{
    name="prim texture alpha Luminance";
}

globals{
    texture mat;
}

float4 main( idatas i )
{
    float2 p = i.primBox.toUpperLeftNorm( i.pos ) ;

    float4 cmat = mat.sample( p ) ;
    cmat = mat.isEmpty ? 1 : cmat ;

    float4 col = i.color ;
    col.a *= luminance( cmat ) ;

    return col;
}
```

prim texture alpha power



```
cfg{
    name="prim texture alpha power";
    renderingTime = 10 ;
}

globals{
    uiTab "Texture" ;

    texture mat;
    {
        uiTab = "Texture" ;
    }
}

perPrim {
    float hardness = 0.5 ;
    {
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "Texture" ;
        uiFormat = percent ;
        uiName = "alphaPower" ;
    }
}

float4 main( idatas i )
{
    float2 p = i.primBox.toUpperLeftNorm( i.pos ) ;

    // compute alpha from the Luminance of a Texture
    float4 cmat = mat.sample( p ) ;
    cmat = mat.isEmpty ? 1 : cmat ;

    float alphaTex = cmat.a ;

    alphaTex = pow( alphaTex, lerp( 1, 8, i.hardness ) );

    float alpha = saturate(i.color.a*alphaTex) ;
    float3 col = i.color.xyz ;

    return float4( col, alpha ) ;
}
```

primBubbleNoise



```
cfg{name="primBubbleNoise";}
```

```
globals{
```

```
float fnbStep0 = 4 ;
{
  uiMin = 3          ;
  uiMax = 64         ;
  uiTab = "bubble 0"  ;
  uiFormat = integer ;
  uiName = "angular step" ;
  id = 2             ;
}
```

```
float fnbStep1 = 8 ;
{
  uiMin = 3          ;
  uiMax = 64         ;
  uiTab = "bubble 1"  ;
  uiFormat = integer ;
  uiName = "angular step" ;
  id = 2             ;
}
```

```
float tscale0 = 1 ;
{
  uiMin = 0          ;
  uiMax = 10         ;
  uiTab = "bubble 0"  ;
  uiName = "time scale" ;
  id = 120           ;
}
```

```
float tscale1 = 1 ;
{
  uiMin = 0          ;
  uiMax = 10         ;
  uiTab = "bubble 1"  ;
  uiName = "time scale" ;
  id = 120           ;
}
}
```

```
perPrim {
```

```
float ampl0 = 0.5 ;
{
  uiMin = 0          ;
  uiMax = 1          ;
  uiTab = "bubble 0" ;
}
```

```

    uiFormat = percent ;
    uiName = "noise amplitude" ;
    id = 0 ;
}

float ampl1 = 0.25 ;
{
    uiMin = 0 ;
    uiMax = 1 ;
    uiTab = "bubble 1" ;
    uiFormat = percent ;
    uiName = "noise amplitude" ;
    id = 0 ;
}

float aoff0 = 0.5 ;
{
    uiMin = 0 ;
    uiMax = 1 ;
    uiTab = "bubble 0" ;
    uiFormat = percent ;
    uiName = "radius" ;
    id = 1 ;
}

float aoff1 = 0.25 ;
{
    uiMin = 0 ;
    uiMax = 1 ;
    uiTab = "bubble 1" ;
    uiFormat = percent ;
    uiName = "radius" ;
    id = 1 ;
}

float2 coff0 = 0.5 ;
{
    uiTab = "bubble 0" ;
    uiName = "offset 2D" ;
    uiEditor = angleDist ;
    power = 0 ;
}

float2 coff1 = -0.5 ;
{
    uiTab = "bubble 1" ;
    uiName = "offset 2D" ;
    uiEditor = angleDist ;
    power = 0 ;
}

}

float hash1( float2 p)
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

```

```

}

float noise( float2 p, float t )
{
    float f ;
    float ip = decompose( p.x, f );
    float ip1 = mod( ip+1, p.y ) ; // fait boucler en fct du maxi passé en y

    float ft ;
    float it = decompose( t, ft );
    float it1 = it+1 ;

    float a0 = smoothLerp( hash1(float2(ip,it)), hash1(float2(ip1,it)), f );
    float a1 = smoothLerp( hash1(float2(ip,it1)), hash1(float2(ip1,it1)), f );

    return smoothLerp( a0, a1, ft );
}

// return 1 if we are in the AngleCurve shape
float AngleCurveShape( float2 pos, float2 offset, float ampl, float aoffset, float
time, float fnbStep, float seed )
{
    float2 sph = toSpherical( pos-offset );

    float angle = mod( sph.x + seed , TWOPI );
    float nbStep = floor(fnbStep) ;
    angle = nbStep * angle / TWOPI ;

    float displ = 0.5*noise( float2(angle, nbStep), time )
        + 0.25*noise( 2*float2(angle, nbStep), time )
        + 0.125*noise( 4*float2(angle, nbStep), time )
        + 0.0625*noise( 8*float2(angle, nbStep), time ) ;

    float p = aoffset + ampl*(2*displ-1) ;

    return sph.y > p ? 0 : 1 ;
}

float4 main( idatas i )
{
    float2 uv = i.primBox.toUpperLeftNorm( i.pos )*2-1 ;

    float seed = i.nbUserStroke * 2.23881;

    float shape0 = AngleCurveShape( uv, i.coff0, i.ampl0, i.aoff0, i.time*tscale0 +
seed, fnbStep0, seed );
    float shape1 = AngleCurveShape( uv, i.coff1, i.ampl1, i.aoff1, i.time*tscale1 +
seed*0.63798, fnbStep1, seed*1.205 );

    float gshape = shape0 + shape1 ;

    float alpha = gshape == 1 ? 1 : 0 ;

    float4 col = i.color ;
    col.a *= alpha ;

    return col ;
}

```


primBubblenNoiseSpread



```
cfg{
    name="primBubblenNoiseSpread";
    renderingTime = 10 ;
}

globals{

    float noiseScale = 1 ;
    {
        uiTab = "Noise" ;
        uiName = "Scale" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }

    float fnbStep0 = 4 ;
    {
        uiMin = 3 ;
        uiMax = 64 ;
        uiTab = "bubble 0" ;
        uiFormat = integer ;
        uiName = "angular step" ;
        id = 2 ;
    }

    float fnbStep1 = 8 ;
    {
        uiMin = 3 ;
        uiMax = 64 ;
        uiTab = "bubble 1" ;
        uiFormat = integer ;
        uiName = "angular step" ;
        id = 2 ;
    }

    float tscale0 = 1 ;
    {
        uiMin = 0 ;
        uiMax = 10 ;
        uiTab = "bubble 0" ;
        uiName = "time scale" ;
        id = 120 ;
    }

    float tscale1 = 1 ;
    {
        uiMin = 0 ;
        uiMax = 10 ;
        uiTab = "bubble 1" ;
        uiName = "time scale" ;
    }
}
```

```

        id = 120          ;
    }
}

perPrim
{
    float ndensity = 0.5 ;
    {
        uiTab = "Noise" ;
        uiName = "Density" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }

    float densityHardness = 0.15 ;
    {
        uiName = "Hardness";
        uiMax = 1 ;
        uiTab = "Noise" ;
    }
    float ampl0 = 0.5 ;
    {
        uiMin = 0          ;
        uiMax = 1          ;
        uiTab = "bubble 0" ;
        uiFormat = percent ;
        uiName = "noise amplitude" ;
        id = 0             ;
    }

    float ampl1 = 0.25 ;
    {
        uiMin = 0          ;
        uiMax = 1          ;
        uiTab = "bubble 1" ;
        uiFormat = percent ;
        uiName = "noise amplitude" ;
        id = 0             ;
    }

    float aoff0 = 0.5 ;
    {
        uiMin = 0          ;
        uiMax = 1          ;
        uiTab = "bubble 0" ;
        uiFormat = percent ;
        uiName = "radius" ;
        id = 1             ;
    }

    float aoff1 = 0.25 ;
    {
        uiMin = 0          ;
        uiMax = 1          ;
        uiTab = "bubble 1" ;
        uiFormat = percent ;
        uiName = "radius" ;
        id = 1             ;
    }

    float2 coff0 = 0.5 ;

```

```

{
    uiTab = "bubble 0"    ;
    uiName = "offset 2D"  ;
    uiEditor = angleDist  ;
    power = 0 ;
}

float2 coff1 = -0.5 ;
{
    uiTab = "bubble 1"    ;
    uiName = "offset 2D"  ;
    uiEditor = angleDist  ;
    power = 0 ;
}

}

float hash1( float2 p)
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float noise( float2 p, float t )
{
    float f ;
    float ip = decompose( p.x, f );
    float ip1 = mod( ip+1, p.y ) ; // fait boucler en fct du maxi passé en y

    float ft ;
    float it = decompose( t, ft );
    float it1 = it+1 ;

    float a0 = smoothLerp( hash1(float2(ip,it)), hash1(float2(ip1,it)), f );
    float a1 = smoothLerp( hash1(float2(ip,it1)), hash1(float2(ip1,it1)), f );

    return smoothLerp( a0, a1, ft );
}

// return 1 if we are in the AngleCurve shape
float AngleCurveShape( float2 pos, float2 offset, float ampl, float aoffset, float
time, float fnbStep, float seed )
{
    float2 sph = toSpherical( pos-offset );

    float angle = mod( sph.x + seed , TWOPI );
    float nbStep = floor(fnbStep) ;
    angle = nbStep * angle / TWOPI ;

    float displ = 0.5*noise( float2(angle, nbStep), time )
        + 0.25*noise( 2*float2(angle, nbStep), time )
        + 0.125*noise( 4*float2(angle, nbStep), time )
        + 0.0625*noise( 8*float2(angle, nbStep), time ) ;

    float p = aoffset + ampl*(2*displ-1) ;

    return sph.y > p ? 0 : 1 ;
}

```

```

}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float adjustDensity( float r, float d )
{
    d = 1-d ;
    float a = clamp( (d-0.5)*2, 0, 1 );
    float b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001 ) ;
    r = saturate( r );

    return r ;
}

float hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

float hardnessCpt( idatas i, float h )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;

    float softness = pow( 1 - h,2) ;
    d /= sm*softness + 0.001 ;

    d = 1 - exp( -d );

    return i.primDistanceValid ? d : 1 ;
}

float cptPrimNoise( idatas i, float time, float density )
{
    float2 p = i.primBox.toUpperLeftNorm( i.pos ) * 2 - 1 ;
    p = floor( p * i.primBox.getSize() * noiseScale );

    return hashD( float3( p, time ), density );
}

float4 main( idatas i )
{
    float2 uv = i.primBox.toUpperLeftNorm( i.pos ) * 2 - 1 ;

    float seed = i.nbUserStroke * 2.23881;

    float shape0 = AngleCurveShape( uv, i.coff0, i.ampl0, i.aoff0, i.time*tscale0 +
seed, fnbStep0, seed );
    float shape1 = AngleCurveShape( uv, i.coff1, i.ampl1, i.aoff1, i.time*tscale1 +
seed*0.63798, fnbStep1, seed*1.205 );

    float gshape = shape0 + shape1 ;

```

```
float alpha = gshape == 1 ? 1 : 0 ;

float density = i.ndensity * hardnessCpt( i, i.densityHardness );
alpha *= cptPrimNoise( i, i.dist*0.001, density );

float4 col = i.color ;
col.a *= alpha ;

return col ;
}
```

primHardness



```
cfg{name = "primHardness";
}

perPrim{
  float densityHardness = 0.15 ;
  {
    uiName = "Hardness";
    uiMax = 1 ;
    uiTab = "Shape" ;
  }
}

float hardnessCpt( idatas i, float h )
{
  float sm = vmin( i.primBox.getSize() ) ;
  float d = max( -i.primDistance, 0 ) ;

  float softness = pow( 1 - h,2) ;
  d /= sm*softness + 0.001 ;

  d = 1 - exp( -d );

  return i.primDistanceValid ? d : 1 ;
}

float4 main( idatas i )
{
  float alpha = hardnessCpt( i, i.densityHardness );

  float4 col = i.color ;
  col.a *= alpha ;

  return col ;
}
```

primsimplenoise (error)



```
cfg{
    name = "primSimpleNoise";
    renderingTime = 5 ;
}

globals{
    float noiseScale = 1 ;
    {
        uiTab = "Noise" ;
        uiName = "Scale" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }
}

perPrim{
    float ndensity = 0.5 ;
    {
        uiTab = "Noise" ;
        uiName = "Density" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }

    float densityHardness = 0.15 ;
    {
        uiName = "Hardness";
        uiMax = 1 ;
        uiTab = "Noise" ;
    }
}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float adjustDensity( float r, float d )
{
    d = 1-d ;
    float a = clamp( (d-0.5)*2, 0, 1 );
    float b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001) ;
    r = saturate( r );
}
```

```

    return r ;
}

float hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

float hardnessCpt( idatas i, float h )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;

    float softness = pow( 1 - h,2) ;
    d /= sm*softness + 0.001 ;

    d = 1 - exp( -d );

    return i.primDistanceValid ? d : 1 ;
}

float cptPrimNoise( idatas i, float time, float density )
{
    float2 p2 = i.primBox.toUpperLeftNorm( i.pos )*2 - 1 ;
    p2 = floor( p*i.primBox.getSize()*noiseScale );

ERROR: Undeclared identifier 'p'

    float3 x = float3( p2, time );
    float3 f ;
    float3 p = decompose( x, f );
    f = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( hashD(p+float3(0,0,0),d), hashD(p+float3(1,0,0),d),
        hashD(p+float3(0,1,0),d), hashD(p+float3(1,1,0),d), f.xy ) ;

    float v2 = bilinearLerp( hashD(p+float3(0,0,1),d), hashD(p+float3(1,0,1),d),
        hashD(p+float3(0,1,1),d), hashD(p+float3(1,1,1),d), f.xy ) ;

    return lerp( v1, v2, f.z );
}

float4 main( idatas i )
{
    float density = i.ndensity * hardnessCpt( i, i.densityHardness );
    float alpha = cptPrimNoise( i, i.dist*0.001, density );

    float4 col = i.color ;
    col.a *= alpha ;

    return col ;
}

```


primSimpleNoise_01



```
cfg{
    name = "primSimpleNoise";
    renderingTime = 5 ;
}

globals{

    float noiseScale = 1 ;
    {
        uiTab = "Noise" ;
        uiName = "Scale" ;
        uiFormat = percent ;
        uiMax = 1 ;
        id = 100 ;
    }

    texture mat ;
    {
        uiTab = "Noise" ;
        uiName = "Mat" ;
        id = -2 ;
    }
}

perPrim{
    float ndensity = 0.5 ;
    {
        uiTab = "Noise" ;
        uiName = "Density" ;
        uiFormat = percent ;
        uiMax = 1 ;
        id = -1 ;
    }

    float densityHardness = 0.15 ;
    {
        uiName = "Hardness";
        uiMax = 1 ;
        uiTab = "Noise" ;
    }
}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
```

```

    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float adjustDensity( float r, float d )
{
    d = 1-d ;
    float a = clamp( (d-0.5)*2, 0, 1 );
    float b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001 ) ;
    r = saturate( r );

    return r ;
}

float hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

float hardnessCpt( idatas i, float h )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;

    float softness = pow( 1 - h,2) ;
    d /= sm*softness + 0.001 ;

    d = 1 - exp( -d );

    return i.primDistanceValid ? d : 1 ;
}

float cptPrimNoise( idatas i, float time, float density )
{
    float2 p = i.primBox.toUpperLeftNorm( i.pos ) *2 - 1 ;
    p = floor( p*i.primBox.getSize()*noiseScale );

    return hashD( float3( p, time ), density );
}

float4 main( idatas i )
{
    float2 p = i.primBox.toUpperLeftNorm( i.pos ) ;

    float4 cmat = mat.sample( p ) ;
    cmat = mat.isEmpty ? 1 : cmat ;
    float dmat = luminance( cmat ) ;

    float density = i.ndensity * dmat * hardnessCpt( i, i.densityHardness );
    float alpha = cptPrimNoise( i, i.dist*0.001, density );

    float4 col = i.color ;
    col.a *= alpha ;

    return col ;
}

```

primSmoothNoise



```
cfg{
    name = "primSmoothNoise";
    renderingTime = 5 ;
}

globals{
    float noiseScale = 2 ;
    {
        uiName = "Scale";
        uiMin = 0.25 ;
        uiMax = 100 ;
        uiTab = "Noise" ;
    }

    float evoSpeed = 0.05 ;
    {
        uiName = "EvoSpeed";
        uiMax = 1 ;
        uiTab = "Noise" ;
    }
}
```

radial gradient



```
cfg{
    name = "radial gradient" ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
}

perPrim{
    float opacity=1;
    {
        uiMax = 1 ;
        uiTab = "color" ;
        uiFormat = percent ;
        id = 0 ;
    }
    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
    float noiseScale=1;
    {
        uiMax = 1 ;
        uiName = "Scale";
        uiTab = "Dithering" ;
        uiFormat = percent ;
    }
}

float hash( float3 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return frac( (p3.x + p3.y) * p3.z );
}

float noise( float3 x )
{
    return hash( floor(x) );
}
```

```

float4 main( idatas i )
{
    float l = max( length(i.strokePos - i.strokeStartPos ), EPSILON );
    float d = distance( i.pos, i.strokeStartPos ) / l;

    // compute noise value
    float2 npos = i.noiseScale*i.pos ;
    float nv = i.noisePower*(1-2*noise( float3(npos,i.nbUserStroke+i.dist*0.001) ));

    float4 col = grad.sample( saturate(d+0.2*nv) ) ;
    col.a *= i.opacity ;

    return col ;
}

```

rakeNoise



```
cfg{name="rakeNoise";}

globals{

  float evoSpeed = 0.5 ;
  {
    uiName = "EvoSpeed";
    uiMax = 4 ;
    uiTab = "Noise" ;
  }
}

perPrim {

  float noiseSize = 1 ;
  {
    uiMin = 0.0      ;
    uiMax = 2        ;
    uiTab = "Noise"   ;
    uiFormat = percent ;
  }

  float hardness = 0.5 ;
  {
    uiMin = 0        ;
    uiMax = 1        ;
    uiTab = "shape"   ;
    uiFormat = percent ;
    uiName = "hardness" ;
  }

  float hardRake = 0.5 ;
  {
    uiMin = 0        ;
    uiMax = 1        ;
    uiTab = "shape"   ;
    uiFormat = percent ;
    uiName = "hardness rake" ;
  }

  float ndensity = 0.5 ;
  {
    uiTab = "Noise" ;
    uiName = "Density" ;
    uiFormat = percent ;
    uiMax = 1 ;
  }
}
```

```

float hash( float2 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float adjustDensity( float r, float d )
{
    d = 1-d ;
    float a = clamp( (d-0.5)*2, 0, 1 );
    float b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001 ) ;
    r = saturate( r );

    return r ;
}

float hashD( float2 p, float d )
{
    return adjustDensity( hash(p), d );
}

float noiseEvo( idatas i )
{
    return i.nbUserStroke + toDrawSpace(i.dist)*evoSpeed*0.01;
}

float remap( float h, float a, float b )
{
    return saturate( (h-a) / (b-a+EPSILON) ) ;
}

float rakeNoise( idatas i, float density )
{
    float2 p = i.primBox.toCenter( i.pos );

    float rpf ;
    float rp = decompose( toDrawSpace(p.y) * i.noiseSize, rpf ) ;

    float f ;
    float dpos = decompose( noiseEvo(i), f );

    float n0 = smoothLerp( hashD(float2(rp,dpos),density),
hashD(float2(rp,dpos+1),density), f );
    float n1 = smoothLerp( hashD(float2(rp+1,dpos),density),
hashD(float2(rp+1,dpos+1),density), f );

    rpf = remap( rpf, 0.5*i.hardRake, 1-0.5*i.hardRake );

    return smoothLerp( n0, n1, rpf ) ;
}

float hardnessCpt( idatas i, float h )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;

```

```

float softness = pow( 1 - h,2) ;
d /= sm*softness + 0.001 ;

d = 1 - exp( -d );

return i.primDistanceValid ? d : 1 ;
}

float4 main( idatas i )
{
    float rnoise = rakeNoise( i, i.ndensity );

    float ha = hardnessCpt( i, i.hardness );

    float4 col = i.color ;
    col.a *= rnoise ;
    col.a *= ha ;

    return col ;
}

```


Smooth Voronoi gradient



```
cfg{
    name="Smooth Voronoi Gradient";
    renderingTime = 60 ;
}

globals{
    colorGradient grad ;
    {
        uiTab = "color" ;
        id = 1 ;
    }
}

perPrim{
    float voroSmooth=0.1;
    {
        uiMax = 1 ;
        uiName = "Smoothness";
        uiTab = "Voronoi" ;
        uiFormat = percent ;
    }

    float ditherPower=0.1;
    {
        uiMax = 1 ;
        uiName = "Dithering power";
        uiTab = "Voronoi" ;
        uiFormat = percent ;
    }
}

float hash1( float2 p)
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
    p3 += dot(p3, p3.yzx+19.19) ;
    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y ) );
}

float4 hash4( float2 p )
```

```

{
    float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

    float4 p4 = frac( float4(p.xyxy) * hscale4 );
    p4 += dot( p4, p4.wzxy+19.19 ) ;
    return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}

float4 voronoi( idatas i, float2 uv, float time )
{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    float seed = i.nbUserStroke ;
    float smoothness = lerp( 1, 50, pow(1-i.voroSmooth,4) );
    float2 ditherpos = i.pos ;
    float ditherPower = i.ditherPower ;

    //-----
    // regular voronoi
    //-----
    float tot = 0 ;
    float totAlph = 0 ;
    for( int j=-2; j<=2; j++ )
    {
        for( int i=-2; i<=2; i++ )
        {
            float2 g = float2( i, j );

            float2 ipos = n + g ;

            float2 o = hash2( ipos+seed );
            o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

            float2 r = g + o - f;
            float d = dot(r,r);

            // ad dithering
            d += 0.2*ditherPower*(2*hash1( ditherpos+g+seed+1.05)-1) ;

            float alpha = saturate(exp(-smoothness*d));

            float col = hash2( ipos+seed+5.4 ).x ;

            tot += alpha*col ;
            totAlph += alpha ;
        }
    }

    return grad.sample( tot / totAlph ) ;
}

float4 main( idatas i )
{
    box2 b = box2FromCenterAxe( i.strokeStartPos, length(i.strokePos-
i.strokeStartPos), normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = 4*b.toCenter( i.pos ) / b.size ;
    float4 col = voronoi( i, p, i.dist*0.005 ) ;

    return col ;
}

```

}

Smudge



```
cfg{
    name = "Smudge" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 32 ;
    renderingTime = 30 ;
}

perPrim {

    float hardness = 0.5 ;
    {
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "shape"  ;
        id = 0          ;
        uiFormat = percent ;
        uiName = "Hardness" ;
    }

    float maxDisplace = 1 ;
    {
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "smudge" ;
        uiFormat = percent ;
        uiName = "Power" ;
    }

    float overlayFactor = 0.1 ;
    {
        uiMax = 1      ;
        uiFormat = percent ;
        uiName = "Color overlay" ;
        uiTab = "color" ;
    }
}

float smudgeFactor( idatas i )
{
    float sm = vmin( i.primBox.getSize() ) ; // min axe size of the primitive
    float d = max( -i.primDistance, 0 ) ; // distance to the primitive
    d = i.primDistanceValid ? d : 0 ;

    float softness = pow( 1 - i.hardness,2 ) ; // more linear feedback from the
parameter
    d /= sm*softness + 0.0001 ; // normalize distance with the primitive
size
```

```

    return 1 - exp( -d ); // attenuation curve
}

float4 main( idatas i )
{
    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    // compute smudge factor
    float sfact = smudgeFactor( i );

    // compute displacement from the current position
    float2 dir = i.strokePrecedPos - i.strokePos ;
    float mdisplace = length( dir ) * sfact * i.maxDisplace ;
    dir *= sfact * i.maxDisplace ;

    // Get the displaced color
    float4 smpl = bottomLayer.bilinearSample( i, i.pos + dir );
    smpl = smoothLerp( colBack, smpl, saturate( mdisplace ) ); // reset to a
    pointSampling for little displacement

    // apply a color overlay
    float4 tmp = blendOverlay( smpl,
    i.color*float4(1,1,1,0.5*i.overlayFactor*pow(sfact,1.95)) );

    // Eraser smudge effect
    tmp.a *= i.eraser ? 0.95 : 1 ;

    /// blend
    float alpha = i.color.a*pow(sfact,0.75);
    float4 col = blendNormalAlpha( colBack, tmp, alpha );

    return col ;
}

```

Smudge cloud noise



```
cfg{
  name = "Smudge cloud noise" ;
  blendEx = true ;
  blendDefault = replace ;
  samplingLayerMaxOffset = 32 ;
  renderingTime = 50 ;
}

perPrim {
  float hardness = 0.5 ;
  {
    uiMin = 0      ;
    uiMax = 1      ;
    uiTab = "shape"  ;
    id = 0         ;
    uiFormat = percent ;
    uiName = "Hardness" ;
  }
  float innerSize = 0.5 ;
  {
    id = 3 ;
    uiMin = 0      ;
    uiMax = 1      ;
    uiTab = "shape" ;
    uiFormat = percent ;
  }

  float maxDisplace = 1 ;
  {
    uiMin = 0      ;
    uiMax = 1      ;
    uiTab = "smudge" ;
    uiFormat = percent ;
    uiName = "Power" ;
  }

  float colorAlpha = 0.1 ;
  {
    uiMax = 1      ;
    uiFormat = percent ;
    uiName = "Color alpha" ;
    uiTab = "color" ;
  }

  float noisePower=0.1;
  {
    uiMax = 1 ;
    uiName = "Power";
    uiTab = "Noise" ;
    uiFormat = percent ;
  }
}
```

```

    }
    float noiseScale=1;
    {
        uiMin = 0.25 ;
        uiMax = 5 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float ndensity = 0.5 ;
    {
        uiTab = "Noise" ;
        uiName = "Density" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ; // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

float3 adjustDensity( float3 rs, float d )
{
    float3 r = abs(rs);
    d = 1-d ;
    float3 a = clamp( (d-0.5)*2, 0, 1 );
    float3 b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001) ;
}

```

```

    r = saturate( r );

    return rs < 0 ? -r : r ;
}

float3 hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [0,1]
float noise( float3 x, float d )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hashD(p+float3(0,0,0),d), f-float3(0,0,0) ),
dot( hashD(p+float3(1,0,0),d), f-float3(1,0,0) ),
dot( hashD(p+float3(0,1,0),d), f-float3(0,1,0) ), dot(
hashD(p+float3(1,1,0),d), f-float3(1,1,0) ), u.xy ) ;

    float v2 = bilinearLerp( dot( hashD(p+float3(0,0,1),d), f-float3(0,0,1) ),
dot( hashD(p+float3(1,0,1),d), f-float3(1,0,1) ),
dot( hashD(p+float3(0,1,1),d), f-float3(0,1,1) ), dot(
hashD(p+float3(1,1,1),d), f-float3(1,1,1) ), u.xy ) ;

    float ret = lerp( v1, v2, u.z )/0.707; // normalize with the maximum slope
    return abs(ret);
}

// return a noise value between [-1,1]
float noiseFunction( float3 x, float d )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float ret = 0.5 * noise( x, d ) ; x = 2*m.transform(x);
    ret += 0.25 * noise(x, d); x = 2*m.transform(x);
    ret += 0.125 * noise(x, d); x = 2*m.transform(x);
    ret += 0.0625 * noise(x, d); x = 2*m.transform(x);
    return ret*2-1 ;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // compute noised distance
    float2 npos = toDrawSpace(i.pos)*.1/i.noiseScale ;
    float dn = d + i.noisePower*noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.0001), i.ndensity ) ;

    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    float att = cptHardness( dn, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    // compute smudge factor

```



```

float sfact = att;

// compute angle noise
float angle = (1-att)*HALFPI*noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.0001)+float3(-10.21,60.78,9780.7), i.ndensity
) ;

// compute displacement from the current position
float2 dir = i.strokePrecedPos - i.strokePos ;
float2 sphdir = toSpherical( dir+0.001 );
sphdir.x += angle ;
dir = sphdir.y*float2( cos(sphdir.x), sin(sphdir.x) );
float mdisplace = length( dir ) * sfact * i.maxDisplace ;
dir *= sfact * i.maxDisplace ;

// Get the displaced color
float4 smpl = bottomLayer.bilinearSample( i, i.pos + dir );
smpl = smoothLerp( colBack, smpl, saturate( mdisplace ) ); // reset to a
pointSampling for little displacement

// compute color noise
float acolor = abs(noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.0001)+float3(7.11221,-97.78,0.7), i.ndensity
)) ;

// apply a color on it
float4 tmp = blendNormal( smpl, i.color*float4(1,1,1,0.5*i.colorAlpha*acolor) );

/// blend
float4 col = blendNormalAlpha( colBack, tmp, i.color.a*pow(sfact,0.75) );

return col ;
}

```

Smudge cloud noise_01



```
cfg{
    name = "Smudge cloud noise" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 32 ;
    renderingTime = 40 ;
}

perPrim {
    float hardness = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        id = 0 ;
        uiFormat = percent ;
        uiName = "Hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }

    float maxDisplace = 1 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "smudge" ;
        uiFormat = percent ;
        uiName = "Power" ;
    }

    float colorAlpha = 0.1 ;
    {
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "Color alpha" ;
        uiTab = "color" ;
    }

    float noisePower=0.1;
    {
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}
```

```

    }
    float noiseScale=1;
    {
        uiMin = 0.25 ;
        uiMax = 5 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float ndensity = 0.5 ;
    {
        uiTab = "Noise" ;
        uiName = "Density" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ; // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

float3 adjustDensity( float3 rs, float d )
{
    float3 r = abs(rs);
    d = 1-d ;
    float3 a = clamp( (d-0.5)*2, 0, 1 );
    float3 b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001) ;
}

```

```

    r = saturate( r );

    return rs < 0 ? -r : r ;
}

float3 hashD( float3 p, float d )
{
    return adjustDensity( hash(p), d );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [0,1]
float noise( float3 x, float d )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hashD(p+float3(0,0,0),d), f-float3(0,0,0) ),
dot( hashD(p+float3(1,0,0),d), f-float3(1,0,0) ),
dot( hashD(p+float3(0,1,0),d), f-float3(0,1,0) ), dot(
hashD(p+float3(1,1,0),d), f-float3(1,1,0) ), u.xy ) ;

    float v2 = bilinearLerp( dot( hashD(p+float3(0,0,1),d), f-float3(0,0,1) ),
dot( hashD(p+float3(1,0,1),d), f-float3(1,0,1) ),
dot( hashD(p+float3(0,1,1),d), f-float3(0,1,1) ), dot(
hashD(p+float3(1,1,1),d), f-float3(1,1,1) ), u.xy ) ;

    float ret = lerp( v1, v2, u.z )/0.707; // normalize with the maximum slope
    return abs(ret);
}

// return a noise value between [-1,1]
float noiseFunction( float3 x, float d )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float ret = 0.5 * noise( x, d ) ; x = 2*m.transform(x);
    ret += 0.25 * noise(x, d); x = 2*m.transform(x);
    ret += 0.125 * noise(x, d); x = 2*m.transform(x);
    ret += 0.0625 * noise(x, d); x = 2*m.transform(x);
    return ret*2-1 ;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // compute noised distance
    float2 npos = toDrawSpace(i.pos)*.1/i.noiseScale ;
    float dn = d + i.noisePower*noiseFunction(
float3(npos,i.nbUserStroke+i.dist*0.0001), i.ndensity ) ;

    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    float att = cptHardness( dn, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    // compute smudge factor

```

```

float sfact = att;

// compute displacement from the current position
float2 dir = i.strokePrecedPos - i.strokePos ;
float mdisplace = length( dir ) * sfact * i.maxDisplace ;
dir *= sfact * i.maxDisplace ;

// Get the displaced color
float4 smpl = bottomLayer.bilinearSample( i, i.pos + dir );
smpl = smoothLerp( colBack, smpl, saturate( mdisplace ) ); // reset to a
pointSampling for little displacement

// apply a color on it
float4 tmp = blendNormal( smpl, i.color*float4(1,1,1,0.5*i.colorAlpha) );

/// blend
float alpha = i.color.a*pow(sfact,0.75);
float4 col = blendNormalAlpha( colBack, tmp, alpha );

// take care of the eraser state
col = i.eraser ? float4( colBack.xyz, colBack.w * (1-alpha) ) : col ;

return col ;
}

```

Smudge colored



```
cfg{
    name = "Smudge colored" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 32 ;
    renderingTime = 30 ;
}

perPrim {

    float hardness = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        id = 0 ;
        uiFormat = percent ;
        uiName = "Hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }

    float maxDisplace = 1 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "smudge" ;
        uiFormat = percent ;
        uiName = "Power" ;
    }

    float colorAlpha = 0.1 ;
    {
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "Color alpha" ;
        uiTab = "color" ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
```

```

    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ;    // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    float att = cptHardness( d, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    // compute smudge factor
    float sfact = att;

    // compute displacement from the current position
    float2 dir = i.strokePrecedPos - i.strokePos ;
    float mdisplace = length( dir ) * sfact * i.maxDisplace ;
    dir *= sfact * i.maxDisplace ;

    // Get the displaced color
    float4 smpl = bottomLayer.bilinearSample( i, i.pos + dir );
    smpl = smoothLerp( colBack, smpl, saturate( mdisplace ) ); // reset to a
pointSampling for little displacement

    // apply a color on it
    float4 acolor = i.color*float4(1,1,1,0.5*i.colorAlpha) ;
    acolor.a *= i.eraser ? 0 : 1 ; // disable the color when the eraser is enabled
    float4 tmp = blendNormal( smpl, acolor );

    // Eraser smudge effect
    tmp.a *= i.eraser ? 0.95 : 1 ;

    /// blend
    float alpha = i.color.a*pow(sfact,0.75);
    float4 col = blendNormalAlpha( colBack, tmp, alpha );

    return col ;
}

```

Smudge expand colored



```
cfg{
    name = "Smudge expand colored" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 32 ;
    renderingTime = 30 ;
}

perPrim {

    float hardness = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        id = 0 ;
        uiFormat = percent ;
        uiName = "Hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }

    float maxDisplace = 1 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "smudge" ;
        uiFormat = percent ;
        uiName = "Power" ;
    }

    float colorAlpha = 0.1 ;
    {
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "Color alpha" ;
        uiTab = "color" ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
```



```

    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ;    // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float4 sampleFire( idatas i, float2 pos, float dirN )
{
    float4 smpl = 0 ;
    smpl += bottomLayer.bilinearSample( i, pos + dirN*-1 );
    smpl += bottomLayer.bilinearSample( i, pos + dirN*0 );
    smpl += bottomLayer.bilinearSample( i, pos + dirN*1 );
    smpl += bottomLayer.bilinearSample( i, pos + dirN*2 );

    float2 pdir = perpendicular( dirN );
    smpl += bottomLayer.bilinearSample( i, pos + pdir*1 );
    smpl += bottomLayer.bilinearSample( i, pos + pdir*-1 );

    return smpl / 6. ;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    float att = cptHardness( d, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    // compute smudge factor
    float sfact = att;
    float alpha = i.color.a*pow(sfact,0.75);

    float2 dir = i.primBox.center - i.pos ;
    float ldir = max( length( dir )-10, 0 ) ;
    dir = normalizeSafe( dir );

    float smplPower = 1-d ;
    smplPower = pow( smplPower, 1. );
    float2 posStart = i.pos + dir*ldir*smplPower ;

    float4 smpl = sampleFire( i, posStart, dir*smplPower*alpha*8 );

    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    // apply a color on it

```

```

float4 acolor = i.color*float4(1,1,1,0.5*i.colorAlpha) ;
acolor.a *= i.eraser ? 0 : 1 ; // take into account eraser
float4 tmp = blendNormal( smpl, acolor );

// Eraser smudge effect
tmp.a *= i.eraser ? 0.95 : 1 ;

/// blend
float4 col = blendNormalAlpha( colBack, tmp, alpha );

return col ;
}

```

Smudge noise colored



```
cfg{
    name = "Smudge noise colored" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 64 ;
    renderingTime = 30 ;
}

globals{
    uiTab Noise ;
    {
        row = 3;
        id = 1;
    }
}

perPrim {

    float hardness = 0.5 ;
    {
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "shape" ;
        id = 0         ;
        uiFormat = percent ;
        uiName = "Hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }

    float maxDisplace = 1 ;
    {
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "smudge" ;
        uiFormat = percent ;
        uiName = "Power" ;
    }

    float colorAlpha = 0.1 ;
    {
        uiMax = 1      ;
        uiFormat = percent ;
        uiName = "Color alpha" ;
    }
}
```

```

        uiTab = "color"          ;
    }
    float noiseScale=1;
    {
        uiMin = 0.5 ;
        uiMax = 100 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float scatterPower=0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ;    // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [-1,1]
float noise( float3 x )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );

```

```

float3 u = f*f*(3.0-2.0*f);

float v1 = bilinearLerp( dot( hash(p+float3(0,0,0)), f-float3(0,0,0) ), dot(
hash(p+float3(1,0,0)), f-float3(1,0,0) ),
dot( hash(p+float3(0,1,0)), f-float3(0,1,0) ), dot(
hash(p+float3(1,1,0)), f-float3(1,1,0) ), u.xy );

float v2 = bilinearLerp( dot( hash(p+float3(0,0,1)), f-float3(0,0,1) ), dot(
hash(p+float3(1,0,1)), f-float3(1,0,1) ),
dot( hash(p+float3(0,1,1)), f-float3(0,1,1) ), dot(
hash(p+float3(1,1,1)), f-float3(1,1,1) ), u.xy );

return lerp( v1, v2, u.z )/0.707; // normalize with the maximum slope
}

// return a noise value between [-1,1]
float noiseFunction( float3 x )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float2 ret = 0.5 * noise( x ); x = 2*m.transform(x);
    ret += 0.25 * noise(x); x = 2*m.transform(x);
    ret += 0.125 * noise(x); x = 2*m.transform(x);
    ret += 0.0625 * noise(x); x = 2*m.transform(x);
    return ret ;
}

float2 noiseVecFunction( float3 x )
{
    return float2( noiseFunction( x + float3(EPSILON,0,0) ) - noiseFunction( x +
float3(-EPSILON,0,0) ),
noiseFunction( x + float3(0,EPSILON,0) ) - noiseFunction( x +
float3(0,-EPSILON,0) ) ) / EPSILON;
}

float2 cptNoiseDisplace( idatas i )
{
    // compute noise value
    float2 npos = i.pos/i.noiseScale;
    float2 nv = noiseVecFunction( float3(npos,i.nbUserStroke+i.dist*0.1) );

    // compute the current pixel displacement
    float mdisplace = i.scatterPower * samplingLayerMaxOffset;
    float2 offset = nv*mdisplace ;

    return offset ;
}

float cptAttNoise( idatas i )
{
    float d = length( i.pos - i.primBox.center ) / vmax( i.primBox.size );
    return pow( clamp( d-0.005, 0, 1 ), 1.5 );
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

```

```

float att = cptHardness( d, i.hardness, i.innerSize );
att = i.primDistanceValid ? att : 1 ;

// compute smudge factor
float sfact = att;

// compute displacement from the current position
float2 dir = i.strokePrecedPos - i.strokePos ;
float mdisplace = length( dir ) * sfact * i.maxDisplace ;
dir *= sfact * i.maxDisplace ;

// noise displacement
float nfact = sfact * cptAttNoise( i );
dir += cptNoiseDisplace( i )*nfact;

// Get the displaced color
float4 smpl = bottomLayer.bilinearSample( i, i.pos + dir );

// apply a color on it
float4 acolor = i.color*float4(1,1,1,0.5*i.colorAlpha) ;
acolor.a *= i.eraser ? 0 : 1 ;
float4 tmp = blendNormal( smpl, acolor );

// eraser
tmp.a *= i.eraser ? 0.95 : 1 ;

/// blend
float alpha = i.color.a*pow(sfact,0.75);
float4 col = blendNormalAlpha( colBack, tmp, alpha );

return col ;
}

```

Smudge Scatter perlin noise



```
cfg{
    name = "Smudge Scatter perlin noise" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 64 ;
    renderingTime = 40 ;
}

perPrim {

    float hardness = 0.5 ;
    {
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "shape"  ;
        id = 0          ;
        uiFormat = percent ;
        uiName = "Hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }
    float maxDisplace = 1 ;
    {
        uiMin = 0      ;
        uiMax = 1      ;
        uiTab = "Noise" ;
        uiFormat = percent ;
        uiName = "Smudge Power" ;
    }

    float colorAlpha = 0.1 ;
    {
        uiMax = 1      ;
        uiFormat = percent ;
        uiName = "Color alpha" ;
        uiTab = "color" ;
    }
    float scatterPower=0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}
```

```

    }
    float noiseScale=1;
    {
        uiMin = 0.01 ;
        uiMax = 2 ;
        uiName = "Scale";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ; // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float3 hash( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float3( (p3.x + p3.y) * p3.z,
        (p3.z + p3.y) * p3.x,
        (p3.x + p3.z) * p3.y ) );
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is between [-1,1]
float noise( float3 x )
{
    float3 f = frac(x);
    float3 p = decompose( x, f );
    float3 u = f*f*(3.0-2.0*f);

    float v1 = bilinearLerp( dot( hash(p+float3(0,0,0)), f-float3(0,0,0) ), dot(
hash(p+float3(1,0,0)), f-float3(1,0,0) ),
        dot( hash(p+float3(0,1,0)), f-float3(0,1,0) ), dot(
hash(p+float3(1,1,0)), f-float3(1,1,0) ), u.xy ) ;

    float v2 = bilinearLerp( dot( hash(p+float3(0,0,1)), f-float3(0,0,1) ), dot(
hash(p+float3(1,0,1)), f-float3(1,0,1) ),

```



```

        dot( hash(p+float3(0,1,1)), f-float3(0,1,1) ), dot(
hash(p+float3(1,1,1)), f-float3(1,1,1) ), u.xy ) ;

    return lerp( v1, v2, u.z )/0.707; // normalize with the maxiumm slope
}

// Gradient noise see https://www.shadertoy.com/view/XdXGW8
// the returned value is 2D vector between [-1,1]
float2 noise2( float3 x )
{
    return float2( noise(x), noise(-x.yzx+float3(10.321,10.8798,11.9842)) ) ;
}

// return a noise value between [-1,1]
float2 noiseFunction( float3 x )
{
    matrix3 m = matrix3FromPosAxes( float3(-0.8,0.63,1.03), float3(0.97,0.01,-
0.036), float3(-0.02,-.87,0.03), float3(0.04,0.024,1.01) );
    float2 ret = 0.5 * noise2( x ) ; x = 2*m.transform(x);
    ret += 0.25 * noise2(x); x = 2*m.transform(x);
    ret += 0.125 * noise2(x); x = 2*m.transform(x);
    ret += 0.0625 * noise2(x); x = 2*m.transform(x);
    return ret ;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    // compute hardness attenuation
    float att = cptHardness( d, i.hardness, i.innerSize );
    att = i.primDistanceValid ? att : 1 ;

    // compute noise value
    float2 npos = i.pos*0.1/i.noiseScale ;
    float2 nv = noiseFunction( float3(npos,i.nbUserStroke+i.dist*0.001) );

    // compute the noise displacement
    float mdisplace = att * i.scatterPower * samplingLayerMaxOffset ;
    float2 noffset = nv*mdisplace ;

    // compute smudge factor
    float sfact = att*att ;

    // compute displacement from the current position
    float2 soffset = i.strokePrecedPos - i.strokePos ;
    float sdisplace = sfact * i.maxDisplace * min( length( soffset ),
samplingLayerMaxOffset ) ;
    soffset = normalizeSafe(soffset) * sdisplace ;

    // compute final offset
    float2 offset = noffset + soffset ;

    // Get the displaced color
    float4 smpl = bottomLayer.bilinearSample( i, i.pos + offset );
    smpl = smoothLerp( colBack, smpl, saturate( length(offset) ) ); // reset to a
pointSampling for little displacement

```

```

// apply a color on it
float4 acolor = i.color*float4(1,1,1,0.15*i.colorAlpha*att) ;
acolor.a *= i.eraser ? 0 : 1 ;
float4 tmp = blendNormal( smpl, acolor );

// take care of the eraser state
tmp.a *= i.eraser ? 0.95 : 1 ;

/// blend
float alpha = i.color.a*pow(sfact,0.75);
float4 col = blendNormalAlpha( colBack, tmp, alpha );

return col ;
}

```

Smudge scatter trabeculum



```
cfg{
    name = "Smudge Scatter trabeculum" ;
    blendEx = true ;
    blendDefault = replace ;
    samplingLayerMaxOffset = 64 ;
    renderingTime = 40 ;
}

perPrim {
    float hardness = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        id = 0 ;
        uiFormat = percent ;
        uiName = "Hardness" ;
    }
    float innerSize = 0.5 ;
    {
        id = 3 ;
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "shape" ;
        uiFormat = percent ;
    }
    float maxDisplace = 1 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiTab = "Noise" ;
        uiFormat = percent ;
        uiName = "Smudge Power" ;
    }
    float colorAlpha = 0.1 ;
    {
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "Color alpha" ;
        uiTab = "color" ;
    }
    float scatterPower=0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiName = "Power";
        uiTab = "Noise" ;
        uiFormat = percent ;
    }
    float noiseScale=1;
```

```

{
    uiMin = 0.01 ;
    uiMax = 10 ;
    uiName = "Scale";
    uiTab = "Noise" ;
    uiFormat = percent ;
}
float TrabHardness = 0.5 ;
{
    id = -1 ;
    uiMin = 0 ;
    uiMax = 1 ;
    uiTab = "shape" ;
    uiFormat = percent ;
    uiName = "cell hardness" ;
}
}

// compute the normalized distance from the edge to the center of the primitive
float cptPrimNormDist( idatas i )
{
    float sm = 0.5*vmax( i.primBox.getSize() ) ; // retrieve maximum primitive axe
size
    float d = max( -i.primDistance, 0 ) / sm ; // compute normalized current
distance to the primitive edge

    return i.primDistanceValid ? d : 0 ;
}

// compute Hardness
// d - distance from primitive edge [0,1]
// h - hardness parameter [0,1]
// i - distance to the inner "safe" size [0,1]
//
float cptHardness( float d, float h, float i )
{
    float attsize = (1-i)*2*(1-h) ;
    float att = saturate( (d - (1-i - attsize*0.5) ) / max( attsize,0.0001) ) ;
    return smoothLerp(0,1,att);
}

float2 hash3( float3 p )
{
    float3 hscale = float3(.1031,-.1029,.1032) ;

    float3 p3 = frac( p * hscale ) ;
    p3 += dot(p3, p3.yzx + 209.191349);
    return -1+2*frac( float2( (p3.x + p3.y) * p3.z,
(p3.z + p3.y) * p3.x ) );
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
    p3 += dot(p3, p3.yzx+19.19) ;
    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y ) );
}

float2 voronoi( idatas i, float2 uv, float time )

```

```

{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    float seed = i.nbUserStroke ;

    //-----
    // regular voronoi
    //-----
    float3 lastd = 10 ;
    float2 off ;
    for( int j=-1; j<=1; j++ )
    {
        for( int i=-1; i<=1; i++ )
        {
            float2 g = float2( i, j );

            float2 ipos = n + g ;

            float2 o = hash2( ipos+seed );
            o = 0.5 + 0.5*sin( time + 6.2831*o );    // animate the position

            float2 r = g + o - f;
            float d = dot(r,r);

            // Get color and orderd 3 min distances
            if( d < lastd.x )
            {
                off = hash3( float3(ipos,time+seed) );
                lastd.yz = lastd.xy ;
                lastd.x = d ;
            }
            else if( d < lastd.y )
            {
                lastd.z = lastd.y ;
                lastd.y = d ;
            }
            else if( d < lastd.z )
            {
                lastd.z = d ;
            }
        }
    }

    lastd = 5*sqrt(lastd);

    float alpha = 1./ ( 1./ (lastd.y-lastd.x)+1./(lastd.z-lastd.x) ) ; // Formula
(c) Fabrice NEYRET

    float hcut = lerp( 3, 0.05, i.TrabHardness ) ;
    float2 ret = alpha > hcut ? off : 0 ;

    return ret ;
}

float4 main( idatas i )
{
    float d = cptPrimNormDist( i );

    // get the current background color

```

```

float4 colBack = bottomLayer.pointSample( i, i.pos );

// compute hardness attenuation
float att = cptHardness( d, i.hardness, i.innerSize );
att = i.primDistanceValid ? att : 1 ;

// compute noise value
float2 npos = i.pos*0.1/i.noiseScale ;
float2 nv = voronoi( i, npos, i.dist*0.01 );

// compute the noise displacement
float mdisplace = att * i.scatterPower * samplingLayerMaxOffset ;
float2 noffset = nv*mdisplace ;

// compute smudge factor
float sfact = att*att ;

// compute displacement from the current position
float2 soffset = i.strokePrecedPos - i.strokePos ;
float sdisplace = sfact * i.maxDisplace * min( length( soffset ),
samplingLayerMaxOffset ) ;
soffset = normalizeSafe(soffset) * sdisplace ;

// compute final offset
float2 offset = noffset + soffset ;

// Get the displaced color
float4 smpl = bottomLayer.bilinearSample( i, i.pos + offset );
smpl = smoothLerp( colBack, smpl, saturate( length(offset) ) ); // reset to a
pointSampling for little displacement

// apply a color on it
float4 acolor = i.color*float4(1,1,1,0.15*i.colorAlpha*att) ;
acolor.a *= i.eraser ? 0 : 1 ;
float4 tmp = blendNormal( smpl, acolor );

// take care of the eraser state
tmp.a *= i.eraser ? 0.95 : 1 ;

/// blend
float alpha = i.color.a*pow(sfact,0.75);
float4 col = blendNormalAlpha( colBack, tmp, alpha );

return col ;
}

```

smudgeRake



```
cfg{
  name = "smudgeRake";
  blendEx = true ;
  blendDefault = replace ;
  samplingLayerMaxOffset = 16 ;
  renderingTime = 30 ;
}

globals{

  uiTab smudge ;
  {
    row = 2;
    id = 3 ;
  }

  float evoSpeed = 0.5 ;
  {
    uiName = "EvoSpeed";
    uiMax = 4 ;
    uiTab = "smudge" ;
    id = 100 ;
  }

}

perPrim {

  float noiseSize = 1 ;
  {
    uiMin = 0.0      ;
    uiMax = 2        ;
    uiTab = "smudge" ;
    uiFormat = percent ;
    uiName = "Filament" ;
  }

  float hardness = 0.5 ;
  {
    uiMin = 0        ;
    uiMax = 1        ;
    uiTab = "shape" ;
    uiFormat = percent ;
    uiName = "hardness" ;
    id = -2 ;
  }

  float maxDisplace = 1 ;
  {
    uiMax = 1        ;
  }
}
```

```

    uiTab = "smudge" ;
    uiFormat = percent ;
    uiName = "Power" ;
    id = -1 ;
}

float overlayFactor = 0.1 ;
{
    uiMax = 1 ;
    uiTab = "color" ;
    uiFormat = percent ;
    uiName = "color overlay" ;
}

float hardRake = 0.5 ;
{
    uiMin = 0 ;
    uiMax = 1 ;
    uiTab = "shape" ;
    uiFormat = percent ;
    uiName = "hardness rake" ;
    id = -1 ;
}

float ndensity = 0.5 ;
{
    uiTab = "smudge" ;
    uiName = "Density" ;
    uiFormat = percent ;
    uiMax = 1 ;
}

}

float hash( float2 p )
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float adjustDensity( float r, float d )
{
    d = 1-d ;
    float a = clamp( (d-0.5)*2, 0, 1 );
    float b = clamp( d*2, 0, 1 );

    r = (r-a) / max( b-a, 0.001) ;
    r = saturate( r );

    return r ;
}

float hashD( float2 p, float d )
{
    return adjustDensity( hash(p), d );
}

float noiseEvo( idatas i )

```



```

{
    return i.nbUserStroke + toDrawSpace(i.dist)*evoSpeed*0.01;
}

float remap( float h, float a, float b )
{
    return saturate( (h-a) / (b-a+EPSILON) ) ;
}

float rakeNoise( idatas i, float density )
{
    float2 p = i.primBox.toCenter( i.pos );

    float rpf ;
    float rp = decompose( toDrawSpace(p.y) * i.noiseSize, rpf ) ;

    float f ;
    float dpos = decompose( noiseEvo(i), f );

    float n0 = smoothLerp( hashD(float2(rp,dpos),density),
hashD(float2(rp,dpos+1),density), f );
    float n1 = smoothLerp( hashD(float2(rp+1,dpos),density),
hashD(float2(rp+1,dpos+1),density), f );

    rpf = remap( rpf, 0.5*i.hardRake, 1-0.5*i.hardRake );

    return smoothLerp( n0, n1, rpf ) ;
}

float smudgeFactor( idatas i )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;
    d = i.primDistanceValid ? d : 0 ;

    float softness = pow( 1 - i.hardness,2) ;
    d /= sm*softness + 0.0001 ;

    return 1 - exp( -d ); // attenuation curve
}

float4 main( idatas i )
{
    float dirN = rakeNoise( i, i.ndensity ) ;

    // get the current background color
    float4 colBack = bottomLayer.pointSample( i, i.pos );

    // compute smudge factor
    float sfact = smudgeFactor( i );
    sfact *= dirN ;

    // compute displacement from the current position
    float2 dir = i.strokePrecedPos - i.strokePos ;
    float mdisplace = length( dir ) * sfact * i.maxDisplace ;
    dir *= sfact * i.maxDisplace ;

    // Get the displaced color
    float4 smpl = bottomLayer.bilinearSample( i, i.pos + dir );
    smpl = smoothLerp( colBack, smpl, saturate( mdisplace ) ); // reset to a
pointSampling for little displacement

```

```

// apply a color overlay
float4 acolor = i.color*float4(1,1,1,i.overlayFactor*pow(sfact,1.95)) ;
acolor.a *= i.eraser ? 0 : 1 ;
float4 tmp = blendOverlay( smpl, acolor );
smpl.xyz = tmp.xyz ;

// take care of the eraser state
smpl.a *= i.eraser ? 0.95 : 1 ;

/// blend
float alpha = i.color.a*pow(sfact,0.95);
float4 col = blendNormalAlpha( colBack, smpl, alpha );

return col ;
}

```

subtle color shift



```
cfg{
  name="subtle color shift";
  renderingTime = 30 ;
  blendEx = true ;
  blendDefault = replace ;

  samplerDefault ;
  {
    adressU = clamp;
    adressV = clamp;
  }
}

globals{
  uiTab "Texture" ;

  texture shape;
  {
    id = -2 ;
    uiTab = "shape" ;
    uiName = "texture shape";
  }
  texture splash;
  {
    id = -1 ;
    uiTab = "shape" ;
    uiName = "texture splash";
  }
  uiTab stroke ;
  {
    row = 99 ;
  }
  uiTab colorShifting ;
  {
    row = 100 ;
  }
}

perPrim {

  float pressure = 0.5 ;
  {
    uiMin = 0 ;
    uiMax = 1 ;
    uiFormat = percent ;
    uiName = "pressure" ;
    uiTab = "stroke" ;
  }

  float hshift = 0.5 ;
```

```

{
    uiMin = 0      ;
    uiMax = 1      ;
    uiFormat = percent ;
    uiName = "hue" ;
    uiTab = "colorShifting" ;
}

float sshift = 0.5 ;
{
    uiMin = 0      ;
    uiMax = 1      ;
    uiFormat = percent ;
    uiName = "saturation" ;
    uiTab = "colorShifting" ;
}

float vshift = 0.5 ;
{
    uiMin = 0      ;
    uiMax = 1      ;
    uiFormat = percent ;
    uiName = "brightness" ;
    uiTab = "colorShifting" ;
}
}

float4 hash2( float2 p )
{
    float4 hscale = float4( .1031, 0.1059, -0.1087, -0.1029 ) ;

    float4 p4 = frac( p.xyxy * hscale ) ;
    p4 += dot(p4, p4.yzwx + 209.191349);
    return frac( float4( (p4.x + p4.y) * ( p4.z - p4.w ),
                        (p4.y + p4.z) * ( p4.w - p4.x ),
                        (p4.z + p4.w) * ( p4.x - p4.y ),
                        (p4.w + p4.x) * ( p4.y - p4.z ) ) ) );
}

float4 cptSplash( float2 pos, float seed )
{
    float4 col = splash.sample( pos ) ; // first sampling
    col = 0 ;

    float4 noise ;
    matrix2 b ;
    float maxmove = 0.50 ;
    float minSize = 0.5 ;
    float maxSize = 2.5 ;
    float2 texp ;

    // other sampling
    noise = hash2( float2(seed,3) ) ;
    b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                      TWOPI*noise.w,
                      lerp( minSize, maxSize, noise.z ) ) ;

    texp = b.transform( pos-0.5 )+0.5;
}

```

```

col += splash.sample( texp ) ;

// other sampling
noise = hash2( float2(seed,3) ) ;
b = matrix2FromPRS( maxmove*(noise.xy*2-1),
                    TWOPI*noise.w,
                    lerp( minSize, maxSize, noise.z ) ) ;

texp = b.transform( pos-0.5 )+0.5;
col += splash.sample( texp ) ;

return saturate( col );
}

float remap( in float a, float minv, float maxv )
{
    return saturate( (a-minv) / (maxv-minv) );
}

float cptFromPressure( float a, float pressure )
{
    float pmin;
    float pmax ;

    pmin = pressure < 0.5 ? (1-2*pressure) : -(pressure-0.49) ;
    pmax = pressure < 0.5 ? 1.01 : (1-2*(pressure-0.5)) ;
    return remap( a, pmin, pmax );
}

float3 hash3( float2 p )
{
    float hscale = float3(.1031,0.1029,-0.1027) ;

    float3 p3 = frac( p.xy * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return float3( frac( (p3.x + p3.y) * p3.z ),
                  frac( (p3.z + p3.y) * p3.x ),
                  frac( (p3.z + p3.x) * p3.y ) ) ;
}

float4 main( idatas i )
{
    float alpha = i.color.a ;

    // Get Shape
    {
        float2 pos = i.primBox.toUpperLeftNorm( i.pos ) ;
        float4 col = shape.sample( pos ) ;
        float a = col.a ;
        a = shape.isEmpty ? 1 : a ;
        alpha *= a ;
    }

    // Get Splash
    {
        float2 pos = i.primBox1.toUpperLeftNorm( i.pos ) ;
        float4 col = cptSplash( pos, i.primShapeId1+i.nbUserStroke ) ;

        float aover = i.primBox1Valid ? col.a : 1 ;

        // apply overlay blending

```

```

    alpha *= cptFromPressure( aover, i.pressure );
}

// Compute Color shifting
float4 colBack = bottomLayer.pointSample( i, i.pos );

float4 hsv = fromRGBtoHSV( colBack );

float3 n = 2*hash3( float2(i.dist*0.1, i.nbUserStroke ) )-1;

hsv.xyz += n*(10./100.)*float3(i.hshift,i.sshift,i.vshift);
hsv.yz = saturate(hsv.yz);

float4 rgb = fromHSVtoRGB( hsv );

rgb.rgb = lerp( colBack.rgb, rgb.rgb, alpha ) ;

float4 col = float4( rgb.rgb, colBack.a ) ;

// take care of the eraser state
col = i.eraser ? float4( col.xyz, col.w * (1-alpha) ) : col ;

return col ;
}

```

Texture Background pattern



```
cfg{
    name="Texture Background pattern";
    renderingTime = 30 ;
}

globals{

    uiTab stroke ;
    {
        row = 99 ;
    }

    uiTab roughness ;
    {
        row = 100 ;
    }

    texture mat ;
    {
        uiTab = "roughness" ;
        uiName = "pattern" ;
    }

    float scalePattern ;
    {
        id = 100;
        uiMin = 0.25 ;
        uiMax = 10 ;
        uiFormat = percent ;
        uiTab = "roughness" ;
    }
}

perPrim {

    float pressure = 0.5 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
        uiName = "pressure" ;
        uiTab = "stroke" ;
    }

    float directionality = 0.85 ;
    {
        uiMin = 0 ;
        uiMax = 1 ;
        uiFormat = percent ;
    }
}
```

```

    uiName = "directionality" ;
    uiTab = "stroke" ;
}

float hardness = 1 ;
{
    uiTab = "Shape" ;
    id = -1 ;
    uiMax = 1 ;
    uiName = "Hardness" ;
}

// direction du tracé actuel
float2 dir ;
{
    uiEditor = angleDist ;
    raw = true ;
    uiTab = "stroke" ;
}
}

float surfaceHeight( float2 uv )
{
    return luminance( mat.sample( uv/scalePattern ) ) ;
}

float3 surfaceNormal( float2 pos, float h )
{
    float2 opa = 1/mat.size ;
    float2 uv = pos / mat.size ;

    // compute normal with a Sobel filter
    float s00 = surfaceHeight( uv + opa*float2(-1,-1) );
    float s10 = surfaceHeight( uv + opa*float2( 0,-1) );
    float s20 = surfaceHeight( uv + opa*float2( 1,-1) );
    float s01 = surfaceHeight( uv + opa*float2(-1, 0) );
    float s21 = surfaceHeight( uv + opa*float2( 1, 0) );
    float s02 = surfaceHeight( uv + opa*float2(-1, 1) );
    float s12 = surfaceHeight( uv + opa*float2( 0, 1) );
    float s22 = surfaceHeight( uv + opa*float2( 1, 1) );

    // Compute dx using Sobel:
    //      -1 0 1
    //      -2 0 2
    //      -1 0 1
    float dX = -s00 + s20 -2*s01 + 2*s21 -s02 + s22 ;

    // Compute dy using Sobel:
    //      -1 -2 -1
    //      0 0 0
    //      1 2 1
    float dY = -s00 -2*s10 -s20 + s02 + 2*s12 + s22 ;

    return normalizeSafe( float3( h*dX, h*dY, 1 ) );
}

float hardnessCpt( idatas i, float h )
{
    float sm = vmin( i.primBox.getSize() ) ;
    float d = max( -i.primDistance, 0 ) ;

```



```

float softness = pow( 1 - h,2) ;
d /= sm*softness + 0.001 ;
d = 1 - exp( -d );

d = i.primDistanceValid ? d : 1 ;
return d;
}

float remap( in float a, float minv, float maxv )
{
    return saturate( (a-minv) / (maxv-minv) );
}

float4 main( idatas i )
{
    float heightscale = 2 ;

    float2 dir = normalizeSafe( i.dir );

    float3 bn = normalizeSafe( float3(heightscale*dir,-1) );
    float3 cn = surfaceNormal( i.pos, heightscale );

    float ah = surfaceHeight( i.pos / mat.size ) ;
    float pressure = i.pressure ;
    float pmin;
    float pmax ;

    pmin = pressure < 0.5 ? (1-2*pressure) : -(pressure-0.49) ;
    pmax = pressure < 0.5 ? 1.01 : (1-2*(pressure-0.5)) ;
    ah = remap( ah, pmin, pmax );

    float a = saturate( -dot( bn, cn ) );
    a = lerp( 1-i.directionality, 1, lerp(a,1,pressure*pressure*pressure) );

    a *= ah ;


    a*= hardnessCpt( i, i.hardness );

    float4 col = i.color ;
    col.a *= a ;

    return col ;
}

```

Texture Voronoi Tiling



```
cfg{
    name="Texture Voronoi Tiling";
    renderingTime = 30 ;
}

globals{
    texture mat;
    {
        uiTab = "Texture" ;
    }
}

perPrim{
    float4 color1=1;
    {
        uiName = "Color";
        uiTab = "Color" ;
    }
    float overlay=0;
    {
        uiMax = 1 ;
        uiTab = "Color" ;
        uiFormat = percent ;
    }
    float matAlpha=1;
    {
        uiName = "alpha";
        uiTab = "Color" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }
}

float hash1( float2 p)
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
    p3 += dot(p3, p3.yzx+19.19) ;
    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y ) );
}
```

```

}

float4 hash4( float2 p )
{
    float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

    float4 p4 = frac( float4(p.xyxy) * hscale4 );
    p4 += dot( p4, p4.wzxy+19.19 ) ;
    return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}

float4 voronoiTex( texture tex, float2 uv, float seed, float time )
{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    // derivatives ( for correct mipmapping )
    float2 Dx = ddx(uv) ;
    float2 Dy = ddy(uv) ;

    //-----
    // regular voronoi
    //-----
    float4 tot = 0 ;
    float totAlph = 0 ;
    float totAlph2 = 0;
    for( int j=-1; j<=1; j++ )
    {
        for( int i=-1; i<=1; i++ )
        {
            float2 g = float2( i, j );

            float2 ipos = n + g ;

            float2 o = hash2( ipos+seed );
            o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

            float2 r = g + o - f;
            float d = dot(r,r);

            float alpha = exp(-5*d);

            // compute transform parameter for the texture
            float4 trans = hash4( ipos+seed );
            float2 dir = sign( trans.xy-0.5 );
            dir = dir==0 ? 1 : dir ; // fix the zero case

            float4 col = tex.sampleGrad( uv*dir + trans.zw, Dx, Dy );

            tot += alpha*col ;
            totAlph += alpha ;
            totAlph2 += alpha*alpha ;
        }
    }

    float4 mean = tex.sampleGrad( 0, 1000, 1000 );

    return mean + (tot-totAlph*mean) / sqrt(totAlph2) ; // contrast preserving
    blending
}

```

```

    return tot / totAlpha ; // normal blending
}

float4 main( idatas i )
{
    float2 ratio = mat.size / mat.size.x ;
    box2 b = box2FromCenterAxe( i.strokeStartPos, length(i.strokePos-
i.strokeStartPos)*ratio, normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = b.toCenter( i.pos ) / b.size ;
    float4 col = voronoiTex( mat, p, i.nbUserStroke, i.dist*0.005 ) ;
    col = mat.isEmpty ? 1 : col ;
    col.a *= i.matAlpha ;

    col.xyz = lerp( col.xyz, i.color1.xyz, i.overlay );

    return col ;
}

```

viewBox



```
cfg{
    name="Texture Voronoi Tiling";
    renderingTime = 30 ;
}

globals{
    texture mat;
    {
        uiTab = "Texture" ;
    }
}

perPrim{
    float4 color1=1;
    {
        uiName = "Color";
        uiTab = "Color" ;
    }
    float overlay=0;
    {
        uiMax = 1 ;
        uiTab = "Color" ;
        uiFormat = percent ;
    }
    float matAlpha=1;
    {
        uiName = "alpha";
        uiTab = "Color" ;
        uiFormat = percent ;
        uiMax = 1 ;
    }
}

float hash1( float2 p)
{
    float hscale = .1031 ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale ) ;
    p3 += dot(p3, p3.yzx + 19.19);
    return frac( (p3.x + p3.y) * p3.z );
}

float2 hash2( float2 p )
{
    float3 hscale3 = float3( .1031, .1030, .0973 ) ;

    float3 p3 = frac( float3(p.x,p.y,p.x) * hscale3 ) ;
    p3 += dot(p3, p3.yzx+19.19) ;
    return frac( float2( (p3.x + p3.y)*p3.z, (p3.x+p3.z)*p3.y) );
}
```

```

}

float4 hash4( float2 p )
{
    float4 hscale4 = float4( .1031, .1030, .0973, .1099 ) ;

    float4 p4 = frac( float4(p.xyxy) * hscale4 );
    p4 += dot( p4, p4.wzxy+19.19 ) ;
    return frac( float4((p4.x + p4.y)*p4.z, (p4.x + p4.z)*p4.y, (p4.y + p4.z)*p4.w,
(p4.z + p4.w)*p4.x));
}

float4 voronoiTex( texture tex, float2 uv, float seed, float time )
{
    float2 f ;
    float2 n = decompose( uv, f ) ;

    // derivatives ( for correct mipmapping )
    float2 Dx = ddx(uv) ;
    float2 Dy = ddy(uv) ;

    //-----
    // regular voronoi
    //-----
    float4 tot = 0 ;
    float totAlph = 0 ;
    float totAlph2 = 0;
    for( int j=-1; j<=1; j++ )
    {
        for( int i=-1; i<=1; i++ )
        {
            float2 g = float2( i, j );

            float2 ipos = n + g ;

            float2 o = hash2( ipos+seed );
            o = 0.5 + 0.5*sin( time + 6.2831*o ); // animate the position

            float2 r = g + o - f;
            float d = dot(r,r);

            float alpha = exp(-5*d);

            // compute transform parameter for the texture
            float4 trans = hash4( ipos+seed );
            float2 dir = sign( trans.xy-0.5 );
            dir = dir==0 ? 1 : dir ; // fix the zero case

            float4 col = tex.sampleGrad( uv*dir + trans.zw, Dx, Dy );

            tot += alpha*col ;
            totAlph += alpha ;
            totAlph2 += alpha*alpha ;
        }
    }

    float4 mean = tex.sampleGrad( 0, 1000, 1000 );

    return mean + (tot-totAlph*mean) / sqrt(totAlph2) ; // contrast preserving
    blending
}

```

```

    return tot / totAlpha ; // normal blending
}

float4 main( idatas i )
{
    float2 ratio = mat.size / mat.size.x ;
    box2 b = box2FromCenterAxe( i.strokeStartPos, length(i.strokePos-
i.strokeStartPos)*ratio, normalizeSafe(i.strokePos-i.strokeStartPos) );
    float2 p = b.toCenter( i.pos ) / b.size ;
    float4 col = voronoiTex( mat, p, i.nbUserStroke, i.dist*0.005 ) ;
    col = mat.isEmpty ? 1 : col ;
    col.a *= i.matAlpha ;

    col.xyz = lerp( col.xyz, i.color1.xyz, i.overlay );

    return col ;
}

```

viewZoom



```
cfg{name="viewZoom";}
```

```
// the brush color will change according the zoom value
```

```
float4 main( idatas i )
```

```
{
```

```
    float t = saturate( viewZoom ) ;
```

```
    float3 col = lerp( i.color.xyz, float3(1,0,0), t );
```

```
    return float4( col, i.color.a );
```

```
}
```