

Peer Observations of Observation Units

Camilla Stormoen

INF-3981 Master's Thesis in Computer Science ... May 2018



Abstract

What is wrong with the world? Motivation 1-3 sentences, Arch, Des, Imp, Exp
1,2-3 sentences, results and main conclusion.

Acknowledgements

Contents

Abstract	i
Acknowledgements	iii
List of Figures	vii
1 Introduction	1
1.1 Motivation	2
1.2 Contributions	2
1.3 Assumptions	2
1.4 Limitations	2
1.5 Outline	2
2 Routing Techniques in WSNs	5
2.1 Routing Protocols in WSNs	5
2.1.1 Hierarchical Routing	5
2.1.2 Location-based Routing	6
2.2 Routing Protocol Operations	6
3 Related Work	7
4 Idea	11
5 Architecture	13
5.1 Node Lookup Service	13
5.2 Discovery Of Other Nodes	13
5.3 Incoming Network Requests	15
5.3.1 Connect To Neighbours	15
5.3.2 Cluster Head Election Request	15
5.3.3 Data Transmission	16
5.4 Data Gathering?	16
6 Design	17
6.1 Discovery Of Other Nodes	17

6.1.1	Broadcasting	17
6.2	Cluster Head Election	19
6.2.1	New Node In Cluster Starts Election	19
6.2.2	Cluster Head Starts Election	19
6.3	Accumulate Data	22
7	Implementation	25
7.1	Distance To Other Nodes In The Network	25
7.2	Data Transmission	26
7.2.1	Cluster Head Election	26
7.3	Minimize Path To Leader	26
7.4	Data Accumulation	26
8	Evaluation	27
8.1	Experimental Setup	27
8.2	Experimental Design	28
8.2.1	CPU Measurements	28
8.2.2	Memory Measurements	28
8.2.3	Network (Socket) Usage	28
8.2.4	Network Lifetime?	28
8.3	Results	28
8.3.1	CPU Usage	28
8.3.2	Memory Usage	28
8.3.3	Network Usage	28
8.3.4	Network Lifetime?	28
9	Discussion	29
9.1	Availability of nodes in the system	29
9.2	Cluster Head Election	29
9.2.1	Cluster Head Calculation/Rating	29
9.3	Path To Leader	29
9.4	Data Transmission	29
9.4.1	Data Accumulation	29
9.5	Base Station Access	29
10	Conclusion	31
11	Future Work	33
12	Appendix	35
	Bibliography	37

List of Figures

5.1	Figure shows the architecture of the system.	14
6.1	Figure show design of the system.	18
6.2	Figure show broadcast range of a OU.	18
6.3	Figure show how a new node starts a leader election.	20
6.4	Figure show how a new node starts a leader election.	21
6.5	Figure show how nodes get an request for sending data to the leader.	22
6.6	Figure show how a node sends its data to the leader through the nodes the path.	23
7.1	Broadcast simulation	26

/ 1

Introduction

FRA CAPSTONE: *The Arctic tundra in the far northern hemisphere is challenged by climate changes in the world today and is one of the ecosystems that are most affected by these changes[10]. The Climate-ecological Observatory for Arctic Tundra (COAT) is a long-term research project developed by five Fram Center¹ institutions. Their goal is to create robust observation systems which enable documentation and understanding of climate change impacts on the Arctic tundra ecosystems. COAT was in autumn 2015 granted substantial funding to establish research infrastructure which allowed them to start up a research infrastructure during 2016-2020[10].*

Wireless Sensor Network (WSN) is a system that consists of hundreds or thousands of low-cost micro-sensor nodes. These nodes monitor and collect physical and environmental conditions. The various activities in the sensor nodes consume lots of energy and the battery of the sensor node is difficult to recharge in wireless scenarios and also because the sensor nodes are located at remote areas in the Arctic tundra.

This thesis presents the architecture, design and implementation of a peer observation that can observe and accumulate data from in-situ observation units.

¹. <http://www.framsenteret.no/english>

1.1 Motivation

The motivation behind this project is...

The purpose is to fetch and accumulate data observed by observation units for further use.

The observation units to be used for the prototype comprises Observation Unit Processes executing on PCs and/or Raspberry Pi.

1.2 Contributions

The dissertation makes the following contributions:

- A
- B

1.3 Assumptions

Avgrense viktig!

1.4 Limitations

Avgrense viktig!

1.5 Outline

This thesis is structured into X chapters including the introduction.

Chapter 2 describes ..

Chapter 3

Chapter 4

Chapter 5

Chapter 6

Chapter X

/2

Routing Techniques in WSNs

WSNs main task is to periodically collect information of the interested area and broadcast the information to a Base Station (BS). An easy approach to achieve this task is to make each sensor node transmit their data directly to the BS. But the problem is that the BS can be far away from the sensor node so a direct data transmission would not be possible, or if the routing path from the sensor node to the BS is long, the sensor node may/will die due to energy consumption. There are multiple hierarchical protocols that has been proposed as a solution to this problem.

2.1 Routing Protocols in WSNs

2.1.1 Hierarchical Routing

Hierarchical routing, also called cluster-based routing, is a well known technique for network routing with special advantages related to scalability, efficient communication and lower energy consumption in WSNs. Each cluster in the hierarchical routing protocol have a special node which is responsible for coordinating data transmission between all nodes in the cluster [1, 2, 4].

Two approaches based on hierarchical routing are Low-Energy Adaptive Clustering Hierarchy (LEACH)[1] and Power-efficient gathering in sensor information systems (PEGASIS)[5] which are described in Chapter 3.

2.1.2 Location-based Routing

In location-based routing, nodes are addressed based on their location. The distance between a node's and its neighbour can be estimated by incoming signal strengths, by GPS or via coordination among nodes [4]. Two approaches are Geographic Adaptive Fidelity (GAF)[17] and Geographic and Energy-Aware Routing (GEAR)[18].

2.2 Routing Protocol Operations

/3

Related Work

To improve the overall energy dissipaton of wsns, LEACH [1] introduce a hierarchical clustering algorithm for sensor networks. It is self-organized and use randomization to distribute the energy load evenly among the sensors in the network. The sensor nodes organize themselves into local clusters where one node is the local BS or Cluster Head (CH). The CH are not fixed to avoid nodes to drain their battery and to spread the energy usage over multiple nodes. The nodes self-elect a new CH depending on the amount of energy left at the nodes at different time-intervals. LEACH is divided into different rounds where each round include a setup phase and a steady-state phase [3]. In the setup phase will each node decide whether to become a CH or not. When a CH is chosen, each node will select its own CH based on the distance between the node and the CH and join the cluster. In the steady-state phase will the CH fuse the received data from the node members in the cluster and send it to BS.

In diversity, will nodes in our approach first connect to a cluster and then start a CH election rather than elect a CH first and then nodes joining the cluster. A resemblance between the two approaches is that neither of them consider a nodes energy level when calculating the CH.

LEACH do not consider a node's energy level when calculating the CH. It has therefor been a benchmark for improving algorithms such as the centralized clustering algorithm LEACH-C [9] and distributed clustering algorithm such as LEACH-E [11] and LEACH-B [12]. They concentrate on energy consumption

reducing a nodes residual energy and more relevant criterions [8].

Fuzzy-LEACH (**F**-LEACH) [6, 7] have three different fuzzy descriptors such as energy, concentration and centrality used to complement the cluster head selection process. The **BS** performs the **CH** election in each round by computing the chances of a node becoming a **CH** by calculating the three fuzzy descriptors. **F**-LEACH also assumes that the **BS** elects the appropriate **CH** because it has a complete information about the whole network.

In contrast to **F**-LEACH will our approach elect a **CH** by the nodes in the cluster and not in a **BS**. The **CH** election will not consider "variables" such as battery level or number of nodes in the cluster.

PEGASIS is a chain-based protocol with the idea to form a chain among the sensor nodes so each node will receive and transmit data to a close neighbor. The sensor nodes will also take turns on being the leader for transmitting data to the **BS** and therefor distribute the energy load evenly among the sensor nodes. The chain can be organized by the nodes themselves using a greedy algorithm starting from some node or the **BS** can compute the chain and broadcast it to all the nodes in the network [5].

To increase the robustness of devices and lower power consumptions, ZebraNet [13] provides a low-power wireless system for position tracking of wildlife by using peer-to-peer network techniques. This reduces the researchers effort to manage the sensors and collecting logged data for their research. The radios on their devices also operates on different frequencies and have different bandwidth, range and other characteristics.

A diversity to our approach is that ZebraNet stores multiple copies of the same data across multiple nodes while our approach forwards the data to a node

Gossip-based protocols, or epidemic protocols, are popular protocols due to their ability to reliably pass information among a large set on interconnected nodes. Jelassi et al. [14] provide a Gossip-based communication protocol (**GBCP**) where each node have peers to gossip with in a large-scale distributed system [10]. These nodes can quickly join and leave the network at any given point of time. The general principle of their framework is that every node (1) maintains a relatively small local membership table that provides a partial view of all nodes and (2) periodically refreshes the table using a gossiping procedure.

The difference between **GBCP** and our approach is that our approach does not use a gossip protocol to update its table of nodes, but instead relies on

the communication with other nodes to know about the election of a new CH, which of the node is the CH and when a node should accumulate data and send it to the CH.



4

Idea

Technical idea

/ 5

Architecture

This chapter describes the architecture of the system. The main functionality can be divided into 3 sub-sections: a nodes lookup service, discovery of other nodes and incoming network requests. The architecture of the system is presented in Figure 5.1.

5.1 Node Lookup Service

The lookup service is responsible for storing a list of all previous discovered nodes and their address.

5.2 Discovery Of Other Nodes

Each node can only discover nodes within a possible??? range. Figure 6.2 shows how a possible??? range of a node may be discovered. When a new node in the network has been discovered, meta-data about the node such as address be stored locally on the device in the cluster.




Figure 5.1: Figure shows the architecture of the system.

5.3 Incoming Network Requests

A node may receive incoming requests from other nodes in the network. The request handler will handle the request based on the type of request. The types of requests a node may receive are listed below.

5.3.1 Connect To Neighbours

When a node receives a list of neighbours in range from the lookup service, it will try to connect to the neighbours that are within the node's range. It will only connect to the neighbour node if it receives a OK-message.

Receive OK From Neighbours

When a node receives a OK-message it will connect itself to the neighbour. The neighbour will also then be connected to the new node.

5.3.2 Cluster Head Election Request

A node may receive a CH election request when a node has joined the cluster.

Cluster Head Election Request

When a node receives a CH election request it will perform a leader election and forward the result to its neighbours which will do a leader election as well.

Cluster Head Election Calculation Request

If there is a leader in the cluster already and a new election should be proposed, a CH election calculation request is sent from the leader. Nodes receiving this request will calculate their CH election number.

5.3.3 Data Transmission

Notify Neighbours About Sending Data To Leader

A node may receive a request that it should send its data to the leader. This request is forwarded to the nodes neighbour and so on.

Send Data To Leader

This request forwards a nodes data to the next node in the path to the leader. If the nodes data receiving this requests isn't sent to the leader of the cluster, will the data be accumulated with the received data and then forwarded to the next node.

5.4 Data Gathering?

/ 6

Design

In this chapter we will look at the design of the system and present the design of each component of the architecture. Figure 6.1 shows how the cluster network may appear (in the system). Nodes are connected to other nearby nodes represented by arrows and together they form a cluster network.

6.1 Discovery Of Other Nodes

6.1.1 Broadcasting

When a new node starts, it will contact the node lookup service to discover other nodes in the network. The node will then initiate a broadcast. Broadcast is limited due to a radio range limitations where only nodes that are within this range will receive the broadcast, shown in Figure 6.2. *Node 1* will only reach *node 5* and *node 7*.




Figure 6.1: Figure show design of the system.




Figure 6.2: Figure show broadcast range of a OU.

6.2 Cluster Head Election

A CH election may occur in two scenarios listed below.

6.2.1 New Node In Cluster Starts Election

When a new node has joined the cluster, it will start a new CH election. It will calculate its own CH-score and gossip the score to its neighbours. The neighbours will then start a CH election comparing the received CH-score against their own CH-score. The result of the CH election will then be gossiped to the node's neighbours with either the received CH-score or the nodes own CH-score. The gossiped message also contains a path to the leader. The node append its own address to the path if the received CH-score won the election, otherwise will the path to leader only contain the node itself. Eventually a new CH is elected and consistent in the whole cluster. A CH election is shown in Figure 6.3.

6.2.2 Cluster Head Starts Election

When a CH has accumulated data a certain times, it will start a new CH election. Initially, the CH will gossip a message to nodes the cluster to calculate a new CH-score. Then it will the CH start a new election and gossip this election to the other nodes. The nodes receiving this gossip message will start their leader-election as described in the section above. The election is illustrated in Figure 6.4.




Figure 6.3: Figure show how a new node starts a leader election.




Figure 6.4: Figure show how a new node starts a leader election.




Figure 6.5: Figure show how nodes get an request for sending data to the leader.

6.3 Accumulate Data

A CH will start a gathering of data by gossiping a message to nodes in the cluster, as seen in Figure 6.5. When a node receives this message it will send its data to the next node in the path to the CH as Figure 6.6 shows. When a node receive data from another node it will check if it's own data has been sent to the CH or not by a fingerprint and a status. If it hasn't been sent earlier, the node will accumulate the received data with the data on the current node, and then send the data to the next node in the path to CH. The CH will accumulate all received data and store it.




Figure 6.6: Figure show how a node sends its data to the leader through the nodes the path.

/ 7

Implementation

This chapter will elaborate on how we implemented the system, general implementation requirements, issues and choices.

The system is implemented in the open source programming language GO 1.9.3¹.

7.1 Distance To Other Nodes In The Network

The formula 7.1 is used to calculate the range between two points in a two-dimensional coordinate map and is used to see if a node is within a range or not, as seen in Figure 6.2.

$$d = \sqrt{(X_2 - X_1)^2 + (Y_2 - Y_1)^2} \quad (7.1)$$

Figure 7.1 shows how a node contact the lookup service where the nodes position is calculated and nodes in range is returned to the node. At last, the node will try to connect to the reachable nodes.

¹. <https://golang.org/>




Figure 7.1: Broadcast simulation

7.2 Data Transmission

7.2.1 Cluster Head Election

7.3 Minimize Path To Leader

7.4 Data Accumulation

The collected data is stored in a map and maps in Go are not safe for concurrent use. If a map is read from and wrote to from concurrent goroutines, the access must be compromised by a synchronization mechanism. One of the most common ways to protect maps is by using mutexes.

Listing 7.1: Small Go program showing how mutexes are used when updating a map

```

/*DBStation is a strucure that contains
a map that store data at leader*/
var DBStation struct {
    sync.Mutex
    BSdatamap map[uint32][]byte
}

func sendDataToLeaderHandler() {
    DBStation.Lock()
    defer DataBaseStation.Unlock()

    ...

    DBStation.BSdatamap[sData.FP] = receivedData
}

```



8

Evaluation

This chapter describes the experimental setup and metrics used to evaluate the implemented system.

8.1 Experimental Setup

All experiments were done on a Lenovo ThinkCenter with the following specifications:

- Intel® Core™ i5-6400T CPU @ 2.20GHz × 4
- Intel® HD Graphics 530 (Skylake GT2)
- 15,6 GiB memory and 503 GB disk
- Ubuntu 17.04 64-bit with gcc V6.3.0 compiler and GO 1.9.3

8.2 Experimental Design

8.2.1 CPU Measurements

8.2.2 Memory Measurements

8.2.3 Network (Socket) Usage

8.2.4 Network Lifetime?

8.3 Results

8.3.1 CPU Usage

8.3.2 Memory Usage

8.3.3 Network Usage

8.3.4 Network Lifetime?



9

Discussion

This chapter discusses our approach, experience, how we solved the problem and why we chose the solution we ended up with..

9.1 Availability of nodes in the system

9.2 Cluster Head Election

9.2.1 Cluster Head Calculation/Rating

9.3 Path To Leader

9.4 Data Transmission

9.4.1 Data Accumulation

9.5 Base Station Access



10

Conclusion

In this thesis, we have implemented a system/prototype...

Our experiments showed that the system ...



11

Future Work



12

Appendix

Bibliography

- [1] W. R. Heinzelman and A. Chandrakasan and H. Balakrishnan, *Energy-efficient communication protocol for wireless microsensor networks*, 2000, in *Proceedings of the 33rd Annual Hawaii International Conference on System Sciences*, 10 pp. vol.2-.
- [2] K. Latif and M. Jaffar and N. Javaid and M. N. Saqib and U. Qasim and Z. A. Khan, *Performance Analysis of Hierarchical Routing Protocols in Wireless Sensor Networks*, 2012, in *2012 Seventh International Conference on Broadband, Wireless Computing, Communication and Applications*, pp. 620-625.
- [3] Z. Han and J. Wu and J. Zhang and L. Liu and K. Tian, *A General Self-Organized Tree-Based Energy-Balance Routing Protocol for Wireless Sensor Network*, 2014, in *IEEE Transactions on Nuclear Science Vol.61, Nr.2*, pp. 732-740.
- [4] J. N. Al-Karaki and A. E. Kamal, *Routing techniques in wireless sensor networks: a survey*, 2004, in *IEEE Wireless Communications Vol.11, Nr.6*, pp. 6-28.
- [5] S. Lindsey and C. S. Raghavendra, *PEGASIS: Power-efficient gathering in sensor information systems*, 2002, in *Proceedings, IEEE Aerospace Conference Vol.3*, pp. 3-1125-3-1130.
- [6] A. K. Mishra and R. Kumar and J. Singh, *A review on fuzzy logic based clustering algorithms for wireless sensor networks*, 2015, in *2015 International Conference on Futuristic Trends on Computational Analysis and Knowledge Management (ABLAZE)*, pp. 489-494.
- [7] Indranil Gupta and D. Riordan and Srinivas Sampalli, *Cluster-head election using fuzzy logic for wireless sensor networks*, 2005, in *3rd Annual Communication Networks and Services Research Conference (CNSR'05)*, pp. 255-260.

- [8] Maryam Sabet and Hamid Reza Naji, *A decentralized energy efficient hierarchical cluster-based routing algorithm for wireless sensor networks*, 2015, in *AEU - International Journal of Electronics and Communications* Vol.69, Nr.5, pp. 790 - 799.
- [9] W. B. Heinzelman and A. P. Chandrakasan and H. Balakrishnan, *An application-specific protocol architecture for wireless microsensor networks*, in *IEEE Transactions on Wireless Communications* Vol.1, No.4, October 2002, pp. 660-670.
- [10] Demers, Alan and Greene, Dan and Hauser, Carl and Irish, Wes and Larson, John and Shenker, Scott and Sturgis, Howard and Swinehart, Dan and Terry, Doug, *Epidemic algorithms for replicated database maintenance*, in *ACM: Proceedings of the Sixth Annual ACM Symposium on Principles of Distributed Computing*, 1987, pp. 1-12.
- [11] Chen, Bai and Zhang, Yaxiao and Li, Yuxian and Hao, Xiao-Chen and Fang, Yan, *A Clustering Algorithm of Cluster-head Optimization for Wireless Sensor Networks Based on Energy*, in *Journal of Information and Computational Science*, Vol.8, 2011.
- [12] M. Tong and M. Tang, *LEACH-B: An Improved LEACH Protocol for Wireless Sensor Network*, in *J2010 6th International Conference on Wireless Communications Networking and Mobile Computing (WiCOM)*, 2010, pp. 1-4.
- [13] Juang, Philo and Oki, Hidekazu and Wang, Yong and Martonosi, Margaret and Peh, Li Shiuan and Rubenstein, Daniel, *Energy-efficient Computing for Wildlife Tracking: Design Tradeoffs and Early Experiences with ZebraNet*, in *ACM: SIGARCH Comput. Archit. News*, Vol.30, No.5, December 2002, pp. 96-107.
- [14] Jelasity, Márk and Voulgaris, Spyros and Guerraoui, Rachid and Kermarrec, Anne-Marie and van Steen, Maarten, *Gossip-based Peer Sampling*, in *ACM Trans. Comput. Syst.*, Vol.25, No.3, August 2007.
- [15] Draves, Richard and Padhye, Jitendra and Zill, Brian, *Routing in Multi-radio, Multi-hop Wireless Mesh Networks*, in *Proceedings of the 10th Annual International Conference on Mobile Computing and Networking*, 2004, pp. 114-128.
- [16] Holger Karl, Andreas Willig, *Protocols and Architectures for Wireless Sensor Networks*, John Wiley & Sons, Ltd, 2006.

- [17] Xu, Ya and Heidemann, John and Estrin, Deborah, *Geography-informed Energy Conservation for Ad Hoc Routing*, in *MobiCom '01: Proceedings of the 7th Annual International Conference on Mobile Computing and Networking, 2001*, pp.70–84.
- [18] Yu, Yan and Govindan, Ramesh and Estrin, Deborah, *Geographical and Energy Aware Routing: a recursive data dissemination protocol for wireless sensor networks*, in *UCLA Computer Science Department Technical Report, Vol.463, 2001*.