Notes on Dynamic Mode Decomposition (with some code)

camillejr.github.io/science-docs

1

3

3

Preface

Dynamic Mode Decomposition (DMD) is a data-driven method of finding low-rank structures in high-dimensional data sets.

These notes are taken from two lectures on Dynamic Mode Decomposition: [1] and [2] by Prof. Nathan Kutz from the University of Washington.

This document is still in preparation. Please feel free to contact me with any suggestions, corrections or comments

Contents

1	Description of the system		
2	Linear dynamical systems		
3	Dynamic Mode Decomposition theory		
	3.1	Exact DMD	
	3.2	Going low-rank	
	3.3	Eigendecomposition	
	3.4	Going back to the original dimensions	
	3.5	DMD solution	
4	A bı	A broader view on DMD	
	4.1	Optimized DMD	
	4.2	Robust DMD	
	4.3	Multi-diagnostics DMD	

5 Python example

- A Solution to linear dynamical systems
- **B** Moore-Penrose inverse
- C Singular Value Decomposition

1 Description of the system

We have a system described by a differential equation:

$$\frac{d\vec{x}}{dt} = f(\vec{x}, t, \mu) \tag{1}$$

The function $f(\vec{x}, t, \mu)$ is a way of *modeling* that system. We also have *measurements* of the system in different points in space at time k, in the form of a vector(s) \vec{y}_k :

$$\vec{y}_k = g(\vec{x}_k) \tag{2}$$

where \vec{x}_k is the quantity of interest that we are aiming at measuring. The fact that we might not be able to measure it directly is accounted for by some function g() (although it might happen that $\vec{y}_k = \vec{x}_k$, meaning that we are able to measure \vec{x}_k directly).

Notice, that for measurements at many moments in time, we may stack all the collected vectors \vec{y}_i for different times i to create a matrix whose columns represent time snapshots and whose rows represent position in space.




Figure 1: Data matrix with measurements of the system.

2 Linear dynamical systems

We are from now interested in systems where the governing equation from eq.(1) is not known (in other

- words, the function f is unknown) and we solely rely on measurements of the system which, in general, form
- 4 on measurements of the system which, in general, form a high-dimensional data set.
- In the Dynamic Mode Decomposition we approximate that data set by a linear dynamical system of the form:

$$\frac{d\vec{x}}{dt} = A\vec{x} \tag{3}$$

This is in fact a very handy approximation since we are able to write down exact solutions to linear systems. Once we assume that the general solution is of the form:

$$\vec{x} = \vec{v}e^{\lambda t} \tag{4}$$

to obtain the parameters we effectively solve the eigenvalue problem:

$$A\vec{v} = \lambda \vec{v} \tag{5}$$

The exact solution to the linear system from eq.(3) is:

$$x = \sum_{j=1}^{n} b_j \phi_j e^{\lambda_j t} \tag{6}$$

For a reader who is now shaky about how this solution was derived, more can be found in appendix A.

3 Dynamic Mode Decomposition theory

3.1 Exact DMD

For the moment, we assume that we can measure the system directly, that is we measure $\vec{y}_i = \vec{x}_i$. Moreover, we assume that our data is collected in equal¹ time steps Δt . The measurements are combined inside a large matrix \boldsymbol{X} where each of its columns represents one time snapshot:

$$\boldsymbol{X} = \begin{bmatrix} \vec{x}_1 & \vec{x}_2 & \vec{x}_3 & \dots & \vec{x}_m \end{bmatrix} \tag{7}$$

We split the large matrix X into two matrices X_1 and X_2 such that:

$$\boldsymbol{X_1} = \begin{bmatrix} \vec{x}_1 & \vec{x}_2 & \vec{x}_3 & \dots & \vec{x}_{m-1} \end{bmatrix} \tag{8}$$

$$\boldsymbol{X_2} = \begin{bmatrix} \vec{x}_2 & \vec{x}_3 & \vec{x}_4 & \dots & \vec{x}_m \end{bmatrix} \tag{9}$$

If we now assume that a linear operator will map the first element of X_1 with the first element of X_2 , second with the second, third with the third, and so on, matrix X_2 can be thought of as a matrix representing the *future state* of the matrix X_1 . That linear operator is assumed to be a matrix A.




Figure 2: Spliting the data matrix into *past* and *future* matrices X_1 and X_2 , linked by the linear operator A.

Note here, that for nonlinear systems, a matrix that transforms \vec{x}_1 to \vec{x}_2 is different from a matrix that transforms \vec{x}_2 to \vec{x}_3 and so on. DMD assumes, however, that there is one matrix A that does all these transformations at once, with the least amount of error. It finds the *best-fit* linear dynamical system for the non-linear data set. In mathematical terms, we are looking for such A that:

$$X_2 = AX_1 \tag{10}$$

To solve such system we multiply both sides by the *pseudo-inverse* of matrix X_1 which we denote by X_1^+ :

$$A = X_2 X_1^+ \tag{11}$$

The pseudo-inverse described here, also known as the Moore-Penrose inverse², is computed using the least squares method. There is therefore certain information lost when going from eq.(10) to eq.(11).

Once we have solved for matrix A, we can go back to eq.(5) and solve for eigenvalues and eigenvectors.

Up to this point, this is what the **exact DMD** computes. There is however a problem that the eq.(11) may pose when numerics are involved and this will be addressed in the next section.

3.2 Going low-rank

Matrices X_1^+ and X_2 typically represent huge spacial dimensionality³ which in turn means that the matrix A can become a square matrix of a massive size.

We are hence reluctant to perform the multiplication of matrices as is stated in eq.(11).

The hope comes from the Singular Value Decomposition (SVD). We belive that there are low-rank structures hidden in the data set and we are able to reduce the dimensionality of matrix *A* without significant loss of information⁴.

We perform the SVD on matrix X_1 :




Figure 3: Building the linear operator *A* in exact DMD

$$X_1 = U\Sigma V^T \tag{12}$$

Based on the rank structure of the matrix X_1 (one way to get information about the rank structure is to plot the

 $^{^{1}\}mathrm{Which}$ is indeed a special case for real life measurements. Check section 4 for more information.

 $^{^2 \}mbox{Check}$ appendix B for more information.

³This is often the case for data sets where we have very few snapshots in time but a large number of spacial points where the measurements were taken. Graphically, we might think of those matrices as being "tall" and this is illustrated in Figure 1.

⁴Professor Kutz said a very interesting sentence here, that the multiplication presented in Figure 3 completely ignores the fact that there might be low-rank structures in our data set.

elements from the diagonal of the matrix Σ) we perform a rank-r truncation on the SVD decomposition and approximate the matrix X_1 by its low-rank (rank-r) representation:

$$X_1 \approx X_{1r} = U_r \Sigma_r V_r^T \tag{13}$$

The pseudo-inverse of the truncated matrix is:

$$\boldsymbol{X}_{1r}^{+} = \boldsymbol{V_r} \boldsymbol{\Sigma}_r^{-1} \boldsymbol{U}_r^T \tag{14}$$

The usefulness of this decomposition might not yet be evident, since the matrix X_{1r} is of the same size as matrix X_1 , they only differ by rank. The idea is to nevertheless use the SVD decomposition but also, to generate a matrix similar to the matrix A (since similar matrices share eigenvalues and eigenvectors, among some other properties) but one that will have a smaller size (in fact, it will be size $(r \times r)$). This similar matrix will be denoted \underline{A} . Since it has a lower size than the original matrix A, we will only retrieve r eigenvectors and eigenvalues.

What will now follow are clever mathematical steps performed to avoid computation of the large matrix *A*.

We come back to the eq.(11) and

We perform a *similarity transform* of the matrix *A*:




Figure 4: Similarity transform of matrix *A* to reduce the size.

$$\underline{A} = U_r^T A U_r \tag{15}$$

Matrix *A* can be written as:

$$A = X_2 V_r \Sigma_r^{-1} U_r^T \tag{16}$$

The similar matrix A can be written as:

$$\underline{A} = U_r^T X_2 V_r \Sigma_r^{-1} \tag{17}$$

taking into account that $U_r^T U_r = I$.

We have thus chosen a low-dimensional subspace by performing rank-*r* truncation in which we now find the solution to the linear dynamical system presented initially. The model for the solution is built in this low-dimensional subspace.

3.3 Eigendecomposition

Now that we have computed the similar matrix \underline{A} , we move on to perform the eigendecomposition:

$$[\boldsymbol{W}, \boldsymbol{\Lambda}] = \operatorname{eig}(\boldsymbol{A}) \tag{18}$$

3.4 Going back to the original dimensions

Once the model has been built in the low-dimensional subspace, we want to move to the original dimensions. The DMD modes are obtained from:

$$\mathbf{\Phi} = \mathbf{X}_2 \mathbf{V} \mathbf{\Sigma}^{-1} \mathbf{W} \tag{19}$$

The above equation can be interpreted as transforming the eigenvectors matrix W to a new *basis vectors* matrix Φ where the linear transformation is given by the composition: $X_2V\Sigma^{-1}$.

What is worth mentioning here, is that DMD modes are not guaranteed to be orthogonal after such transformation. This creates a great capacity of DMD to be applicable to systems where data structure does not exhibit orthogonality.

3.5 DMD solution

The solution to the original dynamical system is finally computed:

$$\vec{x}(t) = \mathbf{\Phi}e^{\mathbf{\Omega}t}\vec{b} \tag{20}$$

the above equation is equivalent to:

$$\vec{x}(t) = \sum_{k=1}^{r} \phi_k e^{\omega_k t} b_k \tag{21}$$

The vector \vec{b} is a vector of initial amplitudes for each mode. It is computed by projecting the initial state of the data matrix (given by \vec{x}_1) onto the DMD modes. This is done in order for our initial condition to be formulated in the obtained DMD basis.

4 A broader view on DMD

What can go wrong with our data sets?

4.1 Optimized DMD

varying time steps
We mentioned earlier, that

4.2 Robust DMD

(18) Sparse Identification

4.3 Multi-diagnostics DMD

5 Python example

A Solution to linear dynamical systems

We first recall the general solution to the differential equation:

$$\frac{df(x)}{dt} = f(x) \tag{22}$$

to be the exponential function: $f(x) = a \cdot e^x$.

In an analogous way, the general solution to the linear dynamical system of the form:

$$\frac{d\vec{x}}{dt} = A\vec{x} \tag{23}$$

is:

$$\vec{x} = \vec{v}e^{\lambda t} \tag{24}$$

Computing the time derivative of the eq. 24 we get:

$$\frac{d\vec{x}}{dt} = \vec{v}\lambda e^{\lambda t} \tag{25}$$

And substituting the eq. 24 to eq. 23 we get:

$$\frac{d\vec{x}}{dt} = A\vec{v}e^{\lambda t} \tag{26}$$

The nontrivial solution for the equality of these two above equations is obtained when:

$$A\vec{v} = \lambda \vec{v} \tag{27}$$

which is the statement of eigenvalue problem.




Figure 5: Linear dynamical system.

B Moore-Penrose inverse

C Singular Value Decomposition




Figure 6: Sizes of component matrices in the Singular Value Decomposition and after rank truncation.

References

- [1] N. Kutz, *Dynamic Mode Decomposition Theory*, an online lecture: https://youtu.be/bYfGVQ1Sg98
- [2] N. Kutz, *Dynamic Mode Decomposition Code* , an online lecture: https://youtu.be/KAau5TBU0Sc
- [3] E. R. Scheinerman, Invitation to Dynamical Systems
- [4] G. Strang, Introduction to Linear Algebra, 5th edition
- [5] K. Zdybal, The von Karman Institute for Fluid Dynamics: *POD and DMD decomposition of numerical and experimental data*, stagiaire report