

Indexation de données biologiques : chaque mot compte

Camille Marchet

Univ. Lille, CNRS, CRISAL, France

camille.marchet@univ-lille.fr



@CamilleMrcht




Bioinformatics?



Sequence bioinformatics: allow the analysis of biological sequences (such as DNA), mostly through text and graph algorithms.


DNA, RNA, notions you need to brag about Covid-19




Texts, alphabet={A,C,G,T}

What does our data look like?

We get data through **sequencing**:



Indexing available raw sequences (reads) is a challenge



- Petabytes of reads stored on servers
- Hardly usable: no possible queries on this data
- Current state-of-the-art: index 10^3 to 10^6 datasets for specific queries

This talk's question: how to find a specific sequence in thousands of datasets or more?

- Different from document retrieval on the web:
 - We want exact matches
 - We want all hits
 - DNA has not a small lexicon such as human languages: many more search terms, the weight grows with each new dataset
- Data-bases, document indexing literature: often too costly, not specific enough to our query type

Query a sequence to a collection of datasets

a set of datasets $\{d_1, d_2, \dots d_n\}$
(reads multisets)

query sequence
...ATTACGTAGTA...



return all d_i 's where the query occurs

Use words: k -mers

Decompose sequence to k -mers

TGATGATTAGC

TGATG

GATGA

ATGAT

TGATT

...

k size order: 20-100

Main advantage:

- lower orders of magnitude to index
e.g.: 10^9 reads per dataset in 10^3 datasets becomes 10^9 k -mers in total
- the query remains quite specific with long enough k -mers

Use words: k -mers


same datasets, but seen as k -mer sets

same query, but converted
to a **set of k -mers**



report d_i 's containing sufficiently enough ($\geq t$)
 k -mers from the query [Solomon & Kingsford '16]

Summary


	Nature	Order of magnitude
Datasets	biological samples, made of text  d1 d2 d3	10^3 datasets, several Terabytes of input
Elements	subwords of fixed length e.g. "ATTGATCA"	$>10^9$ elements
Query	set of subwords of fixed length e.g. {"ATTGATCA", "TTTTTTTCA"}	$> 10^3$ queries, containing 10/100/1,000 subwords

State of the art


k -mer aggregative methods:



step 0: datasets
(called **colors**)



step 1: represent
each dataset




step 2: query the union

State of the art


color aggregative methods:



step 0: datasets
(called **colors**)



step 1: index
the intersection




step 2: associate
to colors


Bloom filters [Bloom '70]

$S_1 = \{a, b\}$, $x \notin S_1$


(1)



(2)




(3)




- Probabilistic way to represent a set
- Controlled false positive rate
- No false negative


K -mer aggregative method: the Sequence Bloom Tree (SBT)




Sequence Bloom Tree (SBT) construction




Sequence Bloom Tree (SBT) construction




Query the Sequence Bloom Tree (SBT)



Query the Sequence Bloom Tree (SBT)



Query the Sequence Bloom Tree (SBT)



Query the Sequence Bloom Tree (SBT)

- Repeat for each k -mer of the query
- If enough k -mers from the query fall in a dataset, report this dataset
- Hash-based: very quick response
- The false positive rate for a whole query decreases as the number of k -mers increases (see Solomon & Kingsford '16 for an analysis)

Sequence Bloom Tree (SBT)

Performances (example)

- Input: raw data is 5TB, 2,500 datasets with 3.7 billion k -mers
- Latest SBT index size in RAM: 200 GB

Improvements

- Clustering of the leaves [Sun et al. '18]
- Remove redundancy in internal nodes [Solomon and Kingsford '18, Sun et al. '18, Harris and Medvedev '19]
- Forest instead of a tree [Harris and Medvedev '19]
- Same paradigm but using matrix-like structures instead of trees [Bradley et al. '19, Bingman et al. '19]

Color aggregative methods




step 0: datasets
(called **colors**)



step 1: index
the intersection

efficient k-mer representation:
active research field
[Brinda et al. '20,
Rahman & Medvedev '20,
Marchet et al. '20]



step 2: associate
to colors

several hash-based solutions:

- Minimal perfect hashing [Marchet et al. '20, Almodaresi et al. '19, Holley and Melsted '19]
- Othello hashing [Yu et al. '18]
- Counting quotient filters [Pandey et al. '18]

Open problems

- Record other information than k -mer presence/absence in a dataset (quantification, read presence instead of word presence, ...)
- Represent efficiently a set of k -mers
- Plethora of propositions but can we find a "holy grail" data-structure?

→ Further questions in Antoine's talk

→ Feel free to write for internship inquiries:

camille.marchet@univ-lille.fr



@CamilleMrcht

Bibliography

About k -mer representation:

- Representation of k -mer sets using spectrum-preserving string sets, Rahman et al., '20
- <https://kamimrcht.github.io/webpage/tigs.html>

About SBT:

- Fast search of thousands of short-read sequencing experiments, Solomon and Kingsford, '16
- Improved representation of sequence bloom trees, Harris and Medvedev, '18

About hashing in color aggregative methods:

- Minimal Perfect hashing: Fast and scalable minimal perfect hashing for massive key sets, Limasset et al., '17
- Counting quotient filters: A General-Purpose Counting Filter: Making Every Bit Count, Pandey et al., '17
- Othello hashing: <https://kamimrcht.github.io/webpage/othello.html>

Recent survey:

- Data structures based on k -mers for querying large collections of sequencing datasets, Marchet et al., '20