Player joins the lobby

Player
Client UI (LoginView / TUI)
ClientController
ClientSideConnection (Socket / RMI)
Server connection (SocketServerConnection / RMIServerConnection)
MessageDispatcher
LobbyManager
GameController + LobbyState
ClientModel

Connection setup

The server creates a ServerSideConnection and registers it as pending before the player is authenticated.
Socket and RMI use different adapters, but then share the same flow.

Login request

1 choose nickname and totem
2 login(nickname, color)
3 send(LoginMessage)

alt [Socket client]
4 write/read LoginMessage DTO
[RMI client]
5 remote login(callback, nickname, color)
6 create LoginMessage DTO

7 dispatch(connection, LoginMessage)
8 handleLogin(connection, message)

alt [Login rejected]
9 LoginAckMessage(REJECTED, reason)
10 ServerMessage
11 onServerMessage(LoginAckMessage)
12 applyLoginAck(message)
13 onLoginResult()
14 show error

[Login accepted]
15 onMessageReceived(nickname, JoinGameAction)
16 validate nickname, totem and lobby size
17 addLobbyPlayer(player)
18 registerConnection(nickname, connection)
19 LoginAckMessage(LOGIN_OK)
20 LobbyUpdateMessage(players, expectedPlayers)
21 StateChangedMessage(currentState)

loop [for each server message]
22 ServerMessage DTO
23 onServerMessage(message)
24 apply message to local model
25 notify matching view event

26 show updated lobby

Player
Client UI (LoginView / TUI)
ClientController
ClientSideConnection (Socket / RMI)
Server connection (SocketServerConnection / RMIServerConnection)
MessageDispatcher
LobbyManager
GameController + LobbyState
ClientModel