

Pos. Tag - ID	Description	Quantity	Unit	Price (EUR)
				Total
10	7MF0340-1GL01-5AM2-Z A00+E01+H02+U03 1 PC SITRANS P320 Pressure transmitter 4 Differential pressure and flow PN160 0 HART (4...20 mA) 1 Measuring cell filling: Silicone oil G Maximum measuring span: 250 mbar (100.5 inH ² O) L Oval flange, fastening thread: 7/16-20 UNF (IEC 61518) 0 Diaphragm: Stainless steel 316L/1.4404, measuring cell: Stainless steel 316L/1.4404; Sensor Differential pressure: process flange: Stainless steel 316/1.4408 1 Die-cast aluminum housing 5 Dual chamber device A no Ex M 2 x 1/2-14 NPT 2 With display (lid with glass window) A00 Cable gland attached, plastic E01 General approval without Ex approval: World (CE, RCM, EAC, FM, CSA, KCC) H02 Mounting bracket, stainless steel 1.4301/304 U03 with mounted manifold (5-fold) 7MF9411-5CA, PTFE sealings, chrome-plated steel screws and pressure test, certified with a factory certificate (EN 10204-2.2) Netweight: 4.000 KG Delivery time (working days): 15 plus transportation time Price group: 8P1 LKZ: FR AL: N ECCN: 3A991X Commodity code: 90262020			on demand

Total Price

on demand
