

Pos. Tag - ID	Description	Quantity	Unit	Price (EUR)
				Total
10	7ML5883-0AE01-0AB1-Z A00+B00+C01+E01+L05+M03 SITRANS LG270 Guided radar level transmitter: continuous, contact, 60 m (197 ft) range. Monitors level and interface in liquids in extreme environments. 0A Approval: General Purpose (CSA, FM, CE) E Version / Material: Exchangeable rod diameter 16 mm (0.63 inch)/ 316L 01 Process fitting/Material: Thread 1 1/2" NPT (ASME B1.20.1) PN400/316L 0 Electronics: Two-wire 4...20mA/HART A Seal/Process temperature: Ceramic-graphite/ with / -196 ... +280 °C B Housing/Protection/Cable: Plastic IP66/IP67 1/2" NPT/blind stopper 1 Lengths: Rod diameter 16 mm/316L: 500 mm (19.69 inch) A00 Supplementary electronics: without B00 Dimensions centering weight (diameter/height): without C01 Rod mounted: mounted E01 Indicating/adjustment module: mounted L05 Language of Display: Spanish M03 Operating instructions: Spanish Netweight: 6.000 KG Delivery time (working days): 20 plus transportation time Price group: 8L4 LKZ: DE AL: N ECCN: EAR99I Commodity code: 90261029	1 PC	on demand	
Total Price				on demand